

RECEIVED  
AUG 2 2 03 PM '96

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division  
P.O. Box 1980  
Hobbs, NM 88241

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well

Oil Well     Gas Well     Other

2. Name of Operator

PLAINS PETROLEUM OPERATING COMPANY

3. Address and Telephone No.

415 W. Wall, Suite 1000 Midland, TX 79701 915/683-4434

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter G - 1400' FNL & 2280' FEL  
Sec. 34, T23S, R37E

5. Lease Designation and Serial No.  
NM LC064118

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.  
E. C. Hill "B" Federal #18

9. API Well No.  
30-025-33493

10. Field and Pool, or Exploratory Area  
TEAGUE BLINEBRY

11. County or Parish, State

LEA, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent  
 Subsequent Report  
 Final Abandonment Notice

TYPE OF ACTION

- Abandonment  
 Recompletion  
 Plugging Back  
 Casing Repair  
 Altering Casing  
 Other Spud, set surface csg  
 Change of Plans  
 New Construction  
 Non-Routine Fracturing  
 Water Shut-Off  
 Conversion to Injection  
 Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7-25-96 MI & RU Hondo Drilling Co. Spud 12-1/4" hole @ 6:30 PM

7-27-96 TD 12-1/4" hole @ 4:30 PM 7-26-96 Ran 28 jts (1142.53') 8-5/8" 24# J-55 ST&C csg, set @ 1145'KB. Cemented w/380 sx Premium Plus w/4% gel, 2% CaCl<sub>2</sub> & 1/4#/sk flocele (13.5 ppg & 1.74 ft<sup>3</sup>/sk) followed w/250 sx Premium Plus w/2% CaCl<sub>2</sub> & 1/8#/sk flocele (14.8 ppg & 1.32 ft<sup>3</sup>/sk). Circ 45 sx to pit. Ran 3 centralizers on middle of 1st jt & 2nd & 3rd collars. WOC 12 hours. PD @ 2:00 AM 7-27-96. Test BOP to 1500#, 1 hr, ok.

7-30-96 Drilling 7-7/8" hole at 3142' Dolomite

*Bonnie Husband*  
AUG 7 1996

14. I hereby certify that the foregoing is true and correct

Signed Bonnie Husband

Title Admin. Assist

Date 8-1-96

(This space for Federal or State office use)

Approved by \_\_\_\_\_

Title \_\_\_\_\_

Date \_\_\_\_\_

Conditions of approval, if any: