

DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Superseded by  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease  
State  Fee

5. State Oil & Gas Lease No.  
N/A

7. Unit Agreement Name

8. Form of Lease Name  
F. Hanagan

9. Well No.  
2

10. Field and Pool, or Wildcat  
Jalmat

12. County  
Lea

**SUNDRY NOTICES AND REPORTS ON WELLS**  
DO NOT USE THIS FORM FOR OPERATIONS TO BE PLUGGED OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT TO REFRIGERATE FOR SUCH OPERATIONS.

OIL WELL  GAS WELL  OTHER- P.A.

Name of Operator  
Maralo, Inc. (Atlantic) (Sinclair Repollo)

Address of Operator  
P. O. Box 832 Midland, Texas 79702

Location of Well  
UNIT LETTER K 2310 FEET FROM THE South LINE AND 2310 FEET FROM  
THE West LINE, SECTION 12 TOWNSHIP 25-S RANGE 36-E NMPM.

11. Elevation (Show whether DF, RT, CR, etc.)  
N/A

6. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> OTHER <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> CASING TEST AND CEMENT JOBS <input type="checkbox"/> OTHER <input type="checkbox"/>
Re-PLUG AND ABANDON <input checked="" type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Remove present surface plug.  
Remove present plug from 1370' to 1400'.  
Replug well as follows:

- 1) Tag cement plug @ 2900', if missing set 50 sx or 100' plug & tag. Cement should be 100' above perf @ 3135' to 3155'.
- 2) Displace hole with fresh water containing 5# gel per bbl.
- 3) 7" shot off @ 2190'; set 50 sx plug (100'), 50' in & out of 7".
- 4) 10 3/4" set @ 1450'; set 50 sx plug (100'), 50' below and 50' in 10 3/4".
- 5) Set 50 sx plug (100'), (T/Anhy) in 10 3/4" from 1150 to 1050'.
- 6) Set 50 sx plug from 100' to surface.

NO BE APPROVED

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: Jerry Denton TITLE: Drilling Superintendent DATE: Dec 15, 1979  
 APPROVED BY: Jerry Denton TITLE: Dist. I. Supv. DATE: DEC 13 1979  
 CONDITIONS OF APPROVAL, IF ANY: