

District I
 PO Box 1980, Hobbs, NM 88241-1980
 District II
 811 South First, Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
 2040 South Pacheco
 Santa Fe, NM 87505

Form C-101
 Revised October 18, 1994
 Instructions on back
 Submit to Appropriate District Office
 State Lease - 6 Copies
 Fee Lease - 5 Copies

AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address		² OGRID Number
Doyle Hartman 500 N. Main Street Midland, TX 79701		6473
		³ API Number
		30-025-91887
⁴ Property Code	⁵ Property Name	⁶ Well No.
5043	Dabbs	4*

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
E	34	25S	37E		1650'	FNL	660'	FWL	Lea

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1					¹⁰ Proposed Pool 2				
Jalmat (Gas) Tensilly-5R									

¹¹ Work Type Code	¹² Well Type Code	¹³ Cable/Rotary	¹⁴ Lease Type Code	¹⁵ Ground Level Elevation
E	G	R	P	3013.3'
¹⁶ Multiple	¹⁷ Proposed Depth	¹⁸ Formation	¹⁹ Contractor	²⁰ Spud Date
No	3620' PBTB	Yates	Lucky's Well Service	1-20-97

²¹ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
17 1/4"	13 3/8"	54.5#	567'	670 sx	Circ
12 1/4"	9 5/8"	36#	3708'	3350 sx	Circ

²² Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Permit Expires 1 Year From Approval
 Date Unless Drilling Underway
 Re-Entry

Propose to install casinghead and BOP, drill out 40-sx surface plug, and clean out to top of cement plug at 3620'. Upon reaching 3620', will pressure test casing, log well with Schlumberger CNL-DS-GR-CCL log, and complete well as infill Jalmat-Yates gas well at an approximate depth of 2700'-2950'.

²³ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.		OIL CONSERVATION DIVISION	
Signature: <i>Starla Snyder</i>	Printed name: STARLA SNYDER	Approved by: ORIGINAL SIGNED BY JERRY SEXTON	Title: DISTRICT I SUPERVISOR
Title: ENGINEERING TECH	Date: 1-20-97	Approval Date: JAN 30 1997	Expiration Date:
Phone: 915-684-4011	Conditions of Approval: Attached <input type="checkbox"/>		

*Formerly Western Natural Gas Co. "Dabbs No. 1"