

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

MISCELLANEOUS REPORTS ON WELLS

APR 10 1952

OIL CONSERVATION COMMISSION
HOBB'S OFFICE

Submit this report in triplicate to the Oil Conservation Commission District Office within ten days after the work specified is completed. It should be signed and filed as a report on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

April 8, 1952

Hobbs, New Mexico

Date

Place

Following is a report on the work done and the results obtained under the heading noted above at the.....

Stanolind Oil & Gas Co. State Y Well No. 1 in the
 Company or Operator NE/4 of Sec. 32, T. 24-S, R. 38-E, N. M. P. M.,
 Wildecat Pool Lea County.

The dates of this work were as follows: April 1-3, 1952

Notice of intention to do the work was (was not) submitted on Form C-102 on April 1, 1952 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

On April 3, 1952 at 3:20 a.m., 48 hours had elapsed since running 4264' of new 9-5/8" casing, landed at 4277' with staging collar set at 1223', and cementing in two stages as follows:

1st stage cemented with 300 sacks cement mixed 8% Jel plus 100 sacks neat cement.

2nd stage cemented through DV tool with 150 sacks of neat cement. Casing shut-off was tested to 1,000 psi for 30 minutes before and after drilling staging tool, as well as before and after drilling casing shoe. Since there was no drop in pressure, drilling operations were resumed.

Temperature survey indicated good cement at 900'.

Witnessed by J. T. Crawford Stanolind Oil & Gas Co. Head Houstabout
Name Company Title

APPROVED: OIL CONSERVATION COMMISSION

W. J. G. [Signature]
 Name
 Title
 Date

I hereby swear or affirm that the information given above is true and correct.

Name *Keith Hendricks*
 Position Field Superintendent
 Representing Stanolind Oil and Gas Company
 Company or Operator
 Address Box 68 Hobbs, New Mexico