

OWWO

COUNTY LEA FIELD Justis STATE NO. 20164
 OPR TEXACO INC. MAP
 3 New Mexico "BZ" State 101-1
 Sec 2, T-25-S, R-37-E CO-ORD
 1980' FSL, 989' FWL of Sec

Re-Cmp 9-24-71		CLASS		EL 3178'
FORMATION	DATUM	FORMATION	DATUM	
CSG & SX - TUBING				
11 3/4" at 249' w/350 sx				
8 5/8" at 3500' w/850 sx				
2 7/8" at 6243' w/900 sx				
2 7/8" at 6244'				
LOGS EL GR RA IND HC A				
	TD 6244'		PBD 6075'	

(Blinebry) Perfs 5192-5605'; NO NEW POTENTIAL
 (Drinkard) Perfs 6008-65'; NO CHANGE

Distribution limited and publication prohibited by subscribers' agreement.
 Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. PROP DEPTH 5605' TYPE WO
 DATE

10-5-71

F.R.C. 10-7-71; Opr's Elev. 3178' DF
 (Blinebry)
 (Orig. comp 8-14-63 dual thru (Blinebry)
 Perf 5644-91' & (Drinkard) Perfs 6087-6187',
 OTD 6244', OPB 6211'; OWWO & Re-Cmp 2-23-65
 dual thru (Blinebry) Perfs 5421-5605' &
 (Drinkard) Perfs 6087-6187', OPB 6211';
 OWWO & Re-Cmp 9-27-65 dual thru (Blinebry)
 Perfs 5421-5605' & (Drinkard) Perfs 6008-65', OPB
 OPB 6075'; OWWO & Re-Cmp 1-16-70 dual thru
 (Blinebry) Perfs 5273-5605' & (Drinkard)
 Perfs 6008-65', OPB 6075')
 TD 4244'; PBD 6075'; COMPLETE
 Perf (Blinebry) 5192-91', 5221', 5222', 5226',
 5229', 5231', 5234', 5236', 5239', 5249-52'
 w/1 SPF

TEXACO INC.

Justis NM
#3 New Mexico 620
State NCT-10

Sec 2, T25S, R37E
Page #2

10-5-71 Continued
Acid (5192-5605') 1100 gals
Frac (5192-5605') 20,000 gals jelled crude
+ 20,000# sd
10-7-71 COMPLETION REPORTED

MN 20164

COUNTY LEA FIELD Justis STATE NM OWWO

OPR TEXACO INC. MAP

3 New Mexico "BZ" State (NCT-10)

Sec 2, T-25-S, R-37-E CO-ORD

1980' FSL, 989' FWL of Sec.

CLASS OWWO EL 3178E

Re-Cmp 1-16-70 FORMATION DATUM FORMATION DATUM

CSG & SX TUBING

11 3/4" at 249' w/350 sx

8 5/8" at 3500' w/850 sx

2 7/8" at 6243'

2 7/8" at 6244' w/900 sx

LOGS EL GR RA IND HC A

TD 6244' PBD 6075'

(Blinebry) Perfs 5273-5605' NO NEW POTENTIAL.

(Drinkard) Perfs 6008-65' NO CHANGE.

Distribution limited and publication prohibited. All reproduction agreements. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT PROP OPEN 5605' TYPE WO

DATE

F.R.C. 7-9-70
PD 5605' - WO - Blinebry
(Orig. dually cmp 8-14-63 thru (Blinebry)
Perfs 5644-91' and (Drinkard) Perfs 6087-
6187', OTL 6244', OPB 6211'; OWWO and dually
re-cmp 2-23-65 thru (Blinebry) Perfs 5421-
5605' and (Drinkard) Perfs 6087-6137', OPB
6211'; OWWO and dually re-cmp 9-27-65 thru
(Blinebry) Perfs 5421-5605' and (Drinkard)
Perfs 6008-65', OPB 6075')
7-7-70 TD 6244', PBD 6075', COMPLETE
Perf 5273-79', 5281', 5282', 5308', 5312',
5321-24', 5352', 5398', 5399', 5416', 5418',
5483', 5484', 5488-90', 5523-25', 5555',
5559' w/1 SPF
Acid (5273-5605') 2000 gals
7-9-70 Frac (5273-5605') 2000 gals oil + 2000# sd
COMPLETION REPORTED

Dual COUNTY Lea FIELD Justis STATE N.M. NO.

OPR. Texaco Inc. MAP

NO. 3 LSE. State of New Mexico "BZ" (NCT-10)

SEC. 2 T. 25S BLK. 37E SUR. CO-ORD.

LOC. 1980' fr S Line & 989' fr W Line of Sec.

MI. FROM (Both Zones) CLASS. EL. 3728'

SPUD. 7-11-63 COMP. 8-17-63 FORMATION DATUM FORMATION DATUM

TRT. See below	LOG:			
	Yates 2440			
	Queen 3123			
CSG. & SX.				
11 3/4" 249' 350	SA 3708			
8 5/8" 3500 850	Glor 4833			
2 7/8" 6243', 2 7/8" 6244' /	Bli 5249			
TBG. DEPTH SIZE 900 SX	Tubb 5898			
LOGS EL GR RA IND HC A	Drkd 6085			
	TD 6244'		PB 6211'	

PROD INT.	(DAILY RATE)	BS&W	GH	GOR	GTY	C. P.	T. P.	HRS. TEST
5644-5691'	Flo. 205 BOPD + 51	22/64"	887	37.5			310#	8 hr
(Blinebry)		BWPD						test of 69 BO + 17 BW
6087-6187'	Flo. 124 BOPD + 36	18/64"	1134	36.7			285#	12 hr
(Drinkard)		BWPD						test of 62 BO + 18 BW

Distribution limited and publication prohibited by subscribers' agreement. Reproduction rights reserved by Williams & Lee Scouting Service, Inc.

CONT. DATE PROP DEPTH 6240' TYPE

7-15-63 F.R. 7-18-63, Blinebry & Drinkard. PD 6240'
 7-15-63 Drlg. 1874' anhy. & salt.
 7-22-63 Drlg. 3371' anhy & ls.
 7-29-63 TD 4533', fshg drill pipe.
 8-5-63 Drlg. 5934' ls.
 8-12-63 TD 6244', PB 6211', MO Rot.
 8-19-63 TD 6244', PB 6211', COMPLETED.
 Perf (Drinkard) 1 shot @ 6087', 6103', 6115', 6124', 6138', 6174' & 6187', treated 500 MA, Re-Tr. 3500 gals acid, SOF 10,000 gals + 10,000# sd.
 Perf (Blinebry) 1 shot @ 5644', 5666', 5678', & 5691 Tr 500 MA, re-treated 3500 gals regular acid. SOF 10,000 gals + 10,000# sand.