

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPT
(Other instructions
verse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

LC-032592 "b"

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NONE

7. UNIT AGREEMENT NAME

NONE

8. FARM OR LEASE NAME

C. C. Fristoe "b" NCT-1

9. WELL NO.

2

10. FIELD AND POOL, OR WILDCAT

Justis Blinebry &
Justis Tubb Drinkard

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 26, T-24-S, R-37-E

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR

TEXACO Inc.

3. ADDRESS OF OPERATOR

P. O. Box 728 - Hobbs, New Mexico

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

Well located 500' from the South Line, and 500' from the West
Line of Section 26, T-24-S, R-37-E, Lea County, New Mexico.

14. PERMIT NO.

Regular

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

Not Available

12. COUNTY OR PARISH

Lea

13. STATE

N. M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Total Depth - 1002'
Spudded 11" Hole At 4:00 P. M. January 6, 1966

Ran 988' of 8 5/8" O. D. Casing, 17.28 LB, Spiral Weld, NEW, and cemented at 1002' with 300 Sx. Trinity Lite Wate, plus 100 Sx. Class "C" neat with 1% CACL. Plug at 977'. Cement Circulated. Job complete 6:30 A. M. January 12, 1966.

Temperature of mixing slurry - 94°, 12 Hour Strength - 1050 P. S. I.
Bottom Hole Temperature - 70°- Job complete 6:30 A. M. January 12, 1966.

Tested 8 5/8" O. D. Casing for 30 minutes with 600 P. S. I. from 6:30 P. M. to 7:00 P. M. January 12, 1966. Tested O. K. Drilled cement plug and re-tested for 30 minutes with 600 P. S. I. from 8:00 P. M. to 8:30 P. M. January 12, 1966. Tested O. K. Job complete 8:30 P. M. January 12, 1966.

18. I hereby certify that the foregoing is true and correct

SIGNED

Dan Gillett
Dan Gillett

TITLE

Assistant District
Superintendent

DATE

January 12, 1966

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: