

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
N.M. Oil Cons. Division
P.O. Box 1980
Hobbs, NM 88241

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

5. Lease Designation and Serial No.

NM 92200

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Jamaica Olsen Federal #1

9. API Well No.

30025 27753

10. Field and Pool, or Exploratory Area

Undes Bone Spring/Wolfcamp

11. County or Parish, State

Lea County, NM

SUBMIT IN TRIPLICATE

1. Type of Well
 Oil Well Gas Well Other

2. Name of Operator
Enron Oil & Gas Company

3. Address and Telephone No.
P. O. Box 2267, Midland, Texas 79702 (915) 686-3714

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
1975' FSL & 1980' FEL
Sec 35, T25S, R34E

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- Notice of Intent
- Subsequent Report
- Final Abandonment Notice

TYPE OF ACTION

- Abandonment
- Recompletion
- Plugging Back
- Casing Repair
- Altering Casing
- Other: Csg test & cmt job
- Change of Plans
- New Construction
- Non-Routine Fracturing
- Water Shut-Off
- Conversion to Injection
- Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

9-26-96 - Re-Entry of Mobil's Olson Federal #1 P&A in 1991

Drilling plugs @ 60' (50')
472' (123')
1000' (210')

Top of 9-5/8" @ 4049'

9-27-96 - Drilling plugs @ 4425' to 4504'
@ 4787' to 4935'
@ 6960' to 7092'

9-29-96 - Drill on bridge plug @ 11,465'

9-30-96 - Drilling on bridge plug & push plug to top of cmt. Plug @ 12,390'
Drilling plug to top of 5-1/2" liner at 12,599'

(OVER)



14. I hereby certify that the foregoing is true and correct

Betty Gildon Betty Gildon

Title: Regulatory Analyst

Date: 10/7/96

(This space is for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

ACCEPTED FOR RECORD

OCT 11 1996

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

P. G. Lopez

10-1-96 - Ran 151 joints 5-1/2" 17# GR-95 LT&C and 145 joints 5-1/2" 17# P-110 LT&C casing set at 12609.
Cemented with 160 sacks Prem 50/50 Poz, 3# KCL, 5/10% Halad-322, 14.3 ppg, 1.27 cuft/sx, 36.19 blis slurry.
WOC - 12 hours. 30 minutes pressure tested to 2400#, OK.

