

Case No.

42

Large Exhibits

April 26, 1943

At a meeting of the Lea County Operators Committee called on April 12, 1943, and held in Santa Fe on April 26, 1943, representatives of twenty-three operators were present. Approximately ninety-eight operators who are members of the Lea County Operators Committee. The operators were polled and a majority of those present agreed that the following recommendations be presented to the Conservation Commission at its hearing called to consider "The application of the Lea County Operators Committee for a permanent gas-oil ratio order for the various fields located in Lea County, including a plan to permit the transfer of allowable from high gas-oil ratio wells to low gas-oil ratio wells, to prevent waste and to protect property rights", to be held at Santa Fe, April 27, 1943:

1. That a permanent gas-oil ratio order be promulgated.
2. That such permanent gas-oil ratio order provide for no exceptions without due notice and public hearing.
3. That no limiting gas-oil ratio be applied in Hardy, Penrose, Skelly, Matix, Langley, Rhodes, Lynn, Cooper and Jal fields, for the following reasons:
 - (a) Two types of waste must be considered -- subsurface and surface. All fields mentioned above are nearing depletion and surface. Adequate reservoir energy exists to produce the remaining recoverable oil without subsurface waste. (See Exhibit "A" attached).
 - (b) In the case of the sand belt fields, namely, Hardy, Penrose, Skelly, Matix, Langley and Rhodes, approximately 55% of the gas is being utilized at present, and plans are completed and priorities have been granted for the equipment to make possible the utilization of approximately 10% of the gas, which will bring the total to approximately 65%.
 - (c) The Lynn, Cooper and Jal fields have a very active water drive. There are several wells which have high gas-oil ratios, but when the volume of fluid lifted is considered, the ratios are quite low considering the existing conditions in the reservoir. Both from a geological study and results of remedial work, it can be stated that oil, gas and water are so closely associated within the reservoir that the segregation of one from the other two is very hazardous. Attempted remedial work in the three dolomite limestone fields has usually proven unsuccessful and ultimately led to the abandonment of the well.
4. That the following limiting ratios be set for the other fields in Lea County, to-wit:

POOL OR AREA

Armedwood	3500
Corbin	2000
Zaves	4000
Buile	5000
Halfway	2500
Rhodes	2000
Lynch	4000
Maljamar	4000
Monument	2000
North Lynch	2000
South Lynch	2000
South Buile	2000
South Lovington	2000
South Maljamar	2000
Faucus	2000
West Buile	2000
New and undesignated pools	2000

GAS-OIL RATIO LIMIT

Armedwood	3500
Corbin	2000
Zaves	4000
Buile	5000
Halfway	2500
Rhodes	2000
Lynch	4000
Maljamar	4000
Monument	2000
North Lynch	2000
South Lynch	2000
South Buile	2000
South Lovington	2000
South Maljamar	2000
Faucus	2000
West Buile	2000
New and undesignated pools	2000

Wells in newly discovered or undesignated pools shall be allowed to produce with a limiting gas-oil ratio of 2,000 cubic feet per barrel for purposes of allocation until a hearing shall have been held and testimony presented upon which a ratio can be set. Such hearing shall be held and rules issued within six months after the completion of the discovery well or upon the completion of test producing wells in the new pool, whichever occurs first.

No substantial subsurface waste exists in the fields listed above. In order to accomplish progress in the elimination of surface waste a mathematical approach was used in determining the limiting ratios. These limiting ratios were set so as to effect approximately the same percentage of units in each field.

5. That testing procedures for measuring gas-oil ratios, appended hereto as Exhibit "B", be adopted as Rules and Regulations of the Commission and not included as part of the gas-oil ratio order.

6. It is further recommended that in order to reduce the volume of gas produced, that the transfer of allowable from high to low gas-oil ratio units be permitted in all Lea County fields under the following provisions:

(a) Transfer of allowable will be permitted only after application to and approval by the Commission. The application shall show 48-hour individual tests of production of oil, gas and water of the well from which transfer is requested and the well or wells receiving the transferred allowable. Such tests shall have been made within 30 days of date of submitting request for transfer. A plot of the wells involved shall be attached and also a statement of the amount of allowable to be transferred

- to each such well. A copy of the application shall be furnished to all offset operators by the applicant at the time same is submitted to the Conservation Commission.
- (b) Permits to transfer shall be in force for a period of one year from date of approval, unless rescinded by the Commission. Renewals or changes may be obtained at the discretion of the Commission only upon submission of the information as shown in (a) above.
- (c) Transfer of oil from one unit to another or others will be permitted only within contiguous abutting portions of the same lease or unitized areas provided the areas involved shall not exceed 200 acres.
- (d) Transfer of allowable oil can be made only to a unit or units with a lower gas-oil ratio.
- (e) The amount of allowable transferred shall be the marginal or adjusted allowable for the unit, whichever is the smaller.
- (f) No unit shall be permitted to produce an allowable in excess of the allowable for two units.

Test data supporting the above recommendations are submitted as Exhibit "C".

DISCUSSION OF DATA RELATIVE TO REMEDIAL WORK IN FIELD DEVELOPMENT

Fields in Lea County New Mexico which are, within this report, considered to have made the nearest approach of any to depletion are:

1. Sand Pay types
 - a. Hardy
 - b. Matix
 - c. Penrose
 - d. Skelly
2. Dolomite limestone pay type
 - a. Cooper
 - b. Jal
 - c. Lynn

Monthly production decline curves which show the calculated average field decline for the Hardy Field (Graph A-1); the Matix Field (Graph A-2); the Penrose Field (Graph A-3) and the Skelly Field (Graph A-4) reflect the future recoverable oil (calculated at a weekly rate of 90 barrels) from these fields. The figures obtained are as follows:

FIELD	FUTURE RECOVERABLE OIL (90 BBL/WK)	FUTURE RECOVERABLE OIL PER ACRE
Hardy	165	5200 bbls.
Matix	271	8400
Penrose	158	4900
Skelly	340	10600

Average per acre recovery for each of the above listed fields, and its age as of July 1, 1942 is as follows:

FIELD	PER ACRE RECOVERY	AGE OF FIELD
Hardy	70.7-43	28 yr. 7-43
Matix	582 bbls.	61 yrs.
Penrose	1055 "	61 "
Skelly	674 "	61 "

The calculated ultimate recovery from these fields, based upon the foregoing tabulations is as follows:




FIELD	TOTAL PER ACRE RECOVERY
Hardy	147 bbls.
Matix	1271 "
Penrose	1132 "
Skelly	1229 "

Although reservoir pressure data on the above listed fields is not as complete as can be desired, that which is available shows an average decline of 90 pounds to date with an average reservoir pressure of 500 pounds remaining.

Reservoir conditions within the Matix Field are believed to be representative of those in the other three sand belt fields being considered. Therefore, a condition within the field can be accepted for the others.

Calculations show that within the Matix Field 83 percent of ultimate oil recovery has been obtained with 68 percent of the effective reservoir pressure drop.

Production - Gas-oil ratio curves of the Hardy Field (Graph C-1), the Matix Field (Graph C-2), the Penrose Field (Graph C-3) and the Skelly Field (Graph C-4) show, with exception of the Skelly Field, a definite downward trend in the total volume of gas being produced although gas-oil ratios are increasing. Such condition suggests a more rapid depletion of oil than gas and when considered in light of the fact that, as stated above, 83 percent of the ultimate oil recovery has been made with 68 percent of the effective reservoir pressure, it leads to the question as to whether or not the rate of gas production and corresponding reservoir pressure drop will materially affect ultimate recovery of oil.



NO.	WATER	NO.	WATER	NO.	WATER	NO.	WATER	NO.	WATER
1934	22	1935	82	1936	89	1937	86	1938	82
1939	83	1940	83	1941	87	1942	89	1943	89

Decline of water production in the Jal Field as shown on Graph D-3 coincides with abandonment of certain oil wells. Decline of oil production within the Jal and Cooper Fields, as shown on Graph D-1 and Graph D-2, coincides with a period of one year of curbing with the greatest yearly increase of water.

Attempted remedial work in the three dolomite limestone fields has often proven unsuccessful and ultimately led to complete abandonment. Both from a geological study and results of remedial work it can be stated that oil, gas and water are so closely associated within a common reservoir that the segregation of one from the other two is very difficult and certainly economically unjustified.

Appended hereto will be found a partial list of remedial work performed in sand and dolomite-limestone fields:

C.P. Miller
G.H. Gray
W.D. Little

Exhibit A 9

Exhibit A 11

DISCUSSION OF SAND AND LIME REMEDIAL WORK

Reclamation of remedial work aimed at reducing gas-oil ratios in the sand areas revealed that:

1. The close association of the gas with oil in the gas expansion type reservoir in narrow producing zones has offered little or no chance for the successful application of mechanical separation methods.
2. A large percentage of the wells were shut heavily on completion to obtain production from the light formation, therefore, mechanical control is impossible.
3. In general, the few jobs that have been effective or partially effective have only been temporary success.

TYPICAL REMEDIAL RESULTS DOLomite LIME FIELDS

COOPER
Phillips Pet. Co. D. Koolworth #12 26-24-36
1941 T.O. 325
Factor 331 - after GL above packer 30 bbl water/hr
Factor 334 - after GL above packer 54 bbl water/hr
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water







LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water

LYNN
Lynn Pet. Co. D. Ransy #2 2-25-36-5
1941 Completed 1200 sand below retainer C 311
Before GL 29 oil; 10000 water
After pumped 10 oil; 10 water
5000 acid; pumped 22 oil; 120 water



38

April 26, 1943

At a meeting of the Lee County Operators Committee held on April 12, 1943, and held in Santa Fe on April 26, 1943, representatives of twenty-three operators were present of approximately ninety-eight operators who are members of the Lee County Operators Committee. The operators were polled and a majority of those present agreed that the following recommendations be presented to the Conservation Commission at its next meeting for a permanent gas-oil ratio order for the various fields located in Lee County, including a plan to permit the transfer of allowable from high gas-oil ratio wells to low gas-oil ratio wells, to prevent waste and to protect property rights, to be held at Santa Fe, April 27, 1943:

1. That a permanent gas-oil ratio order be promulgated.
2. That such permanent gas-oil ratio order provide for no exceptions without due notice and public hearing.

3. That no limiting gas-oil ratio be applied in Hardy, Penrose, Shelly, Mattox, Langille, Rhodes, Lynn, Cooper and Jal fields, for the following reasons:

(a) Two types of waste must be considered -- subsurface and surface. All fields mentioned above are nearing depletion and adequate reservoir energy exists to produce the remaining recoverable oil without subsurface waste. (See Exhibit "A" attached).

(b) In the case of the sand belt fields, namely, Hardy, Penrose, Shelly, Mattox, Langille and Rhodes, approximately 55% of the gas is being utilized at present, and plans are completed and priorities have been granted for the equipment to make possible the utilization of approximately 10% of the gas, which will bring the total to approximately 65%.

(c) The Lynn, Cooper and Jal fields have a very active water drive. There are several wells which have high gas-oil ratios, but when the volume of fluid lifted is considered, the ratios are quite low considering the existing conditions in the reservoir. Both from a geological study and results of remedial work, it can be stated that oil, gas and water are so closely associated within the reservoir that the segregation of one from the other two is very hazy. Attempted remedial work in the three dolomite limestone fields has usually proven unsuccessful and ultimately led to the abandonment of the well.

4. That the following limiting ratios be set for the other fields in Lee County, to-wit:

POOL OR AREA

POOL OR AREA	GAS-OIL RATIO LIMIT
Arrowhead	3500
Gorbin	2000
Javes	4000
Rancho	5500
Halway	2500
Hobbs	2000
Lynch	2000
Malamar	4000
Monument	2000
North Lynch	2000
North Malamar	2000
Skaggs	7000
South Rancho	5000
South Lovington	2000
South Malamar	2000
Vacuum	2000
West Rancho	2000
New and undesignated pools	2000

Wells in newly discovered or undesignated pools shall be allowed to produce with a limiting gas-oil ratio of 2,000 cubic feet per barrel for purposes of allocation until a hearing shall have been held and testimony presented upon which a ratio can be set. Such hearing shall be called and rules issued within six months after the completion of the discovery well or upon the completion of ten producing wells in the new pool, whichever occurs first.

No substantial subsurface waste exists in the fields listed above. In order to accomplish progress in the elimination of surface waste a mathematical approach was used in determining the limiting ratios. These limiting ratios were set so as to effect approximately the same percentage of units in each field.

5. That testing procedure for measuring gas-oil ratios, appended hereto as Exhibit "B", be adopted as Rules and Regulations of the Commission and not included as part of the gas-oil ratio order.

6. It is further recommended that in order to reduce the volume of gas produced, that the transfer of allowable from high to low gas-oil ratio units be permitted in all Lee County fields under the following provisions:

(a) Transfer of allowable will be permitted only after application to and approval by the Commission. The application shall show (a) hour individual tests of production of oil, gas and water of the well from which transfer is requested and the well and water of the well to which transfer is requested. Such tests shall be made within 30 days of date of submitting request for transfer. A plot of the wells involved shall be attached and also a statement of the amount of allowable to be transferred

to each such well. A copy of the application shall be furnished all offset operators by the applicant at the time same is submitted to the Conservation Commission.

(b) Permits to transfer shall be in force for a period of one year from date of approval, unless renewed by the Commission. Renewals or changes may be obtained at the discretion of the Commission only upon submission of the information as shown in (a) above.

(c) Transfer of oil from one unit to another or others will be permitted only within contiguous abutting portions of the same basic lease or unitized area provided the areas involved shall not exceed 200 acres.

(d) Transfers of allowable oil can be made only to a unit or units with a lower gas-oil ratio.

(e) The amount of allowable transferred shall be the marginal or adjusted allowable for the unit, whichever is the smaller.

(f) No unit shall be permitted to produce an allowable in excess of the allowable for two units.

Test data supporting the above recommendations are submitted as Exhibit "C".

8

The ability of each field to produce is reflected graphically by allowable development curves on the Hardy Field (Graph B-1), Mattox Field (Graph B-2), Penrose Field (Graph B-3) and Shelly Field (Graph B-4). These curves show the continuous decline of the daily top allowable per well; the average daily allowable per marginal well and the rapidly approaching marginal condition of all the sand fields.

A tabulation is presented herewith to show the relationship of water to total fluid produced to date in each of the sand fields.

FIELD	TOTAL OIL	TOTAL WATER	TOTAL FLUID	% OF WATER TO TOTAL FLUID
Hardy	4,232,556	30,066	4,262,622	0.7
Mattox	6,281,969	137,487	6,419,456	1.7
Penrose	7,362,793	73,507	7,436,300	0.98
Shelly	2,895,123	45,104	2,940,227	1.52
Average				1.22

Estimated average field reservoir pressure drop = 900 pounds

The relationship of water produced to total fluid together with consideration of the reservoir pressure drop justifies the opinion that the sand fields are dominantly volumetric drive reservoirs.

An exact count of the number of sand field wells which have been shot is not readily available. However, it is believed that 75 percent of total completions is a conservative estimate.

In as much as calculations have shown that 17 percent of the future recoverable oil can be produced by 32 percent of the effective remaining reservoir energy, it is apparent that a surplus of flooding energy exists. However, it is also apparent that the future recoverable oil is so small that the expenditure necessary for remedial work in any section that has been shot is not economically justified.




If, as stated above, the relationship of water produced to total fluid together with consideration of reservoir pressure drop can be used as a means of identifying the type of reservoir drive within a field it is then evident, as shown by the following tabulation, that the Cooper, Jal and Lynn dolomite-limestone fields are dominantly hydrostatic drive reservoirs.

FIELD	TOTAL OIL	TOTAL WATER	TOTAL FLUID	% OF WATER TO TOTAL FLUID
Cooper	13,691,315	110,456,927	124,148,242	80.48
Jal	4,129,609	34,477,448	38,607,057	89.16
Lynn	1,943,448	3,124,300	5,067,748	61.16
Average				80.23

Estimated average field reservoir pressure drop = 129 pounds

Production-development curves on the Cooper Field (Graph D-1), the Lynn Field (Graph D-2) and the Jal Field (Graph D-3) show the rapid rate of increase of water during the early lives of the dolomite-limestone fields. Such an increase possibly reflects the inability of operators to segregate, by remedial work, water from the oil.

A tabulation is herewith presented to show water and oil production per well per year in the three dolomite-limestone fields.



19

TYPICAL REMEDIAL RESULTS-SAND FIELDS
Hardy
Hardy Oil Corp. No. 1 Western C 1B-235-372
1941 set packer & 3700 2300 acid below
Before gas-oil ratio 2350
After " " " 2798
Penrose
Continental Elliott Ref No. 1 9-223-372
1938 packer & 3500
Before gas-oil ratio 3545
After " " " 18231
1940
WEEK PERFORMED TEST APRI 21
Acid 1000 gal. (3540-3711) Oil 21 Gas 207 SGA
Shot 2 cts. (3711-3720) " 23 " 921
Set str. 13 times in zone " 12 " 971 best test
(3550-3600) " 4 " 648
1500 gal. formation plug " " 648
Shot well in account of high gas-oil ratio
Continental Elliott A-13 No. 2 15-228-372
1938 packer & 3500
Before gas-oil ratio 3500
After " " " 14000
Reset packer 3000
Before gas-oil ratio 14000
After " " " 14663
Present gas-oil ratio 24,200
Mattox
Regula Oil Co. Mosely #4 34-245-372
1940 shot 200 cts. 3355-3425 (lower pay)
solid stemming; packer & 3324
Before workover 33 oil; gas-oil ratio 44000
After workover 72 " " 19153
Present production 11 " " 59908
Anderson Frickard Oil Co. State A #1 32-243-372
1941 shot 90 cts. 3310-3540 solid stemming
Before 65 oil; gas-oil ratio 27000
After 61 " " 7885
Now " " 37364
Anderson Frickard State A No. 2 15-225-372
1941 set pack. 4 times with no beneficial results
Shot 120 cts. 3507-3610 solid stemming
Before 100 oil; gas-oil ratio 27000
After 108 " " 7350 gas-oil ratio
Now " " 31482
Shelly Oil & Gas Co. Myers 1-2 22-242-372
1941 treated with 1200 oil; formation plug
Before gas-oil ratio 27000
After " " " 16200
Since increased gas-oil ratio 34780 now
SEAL
Anderson Frickard Blinberry No. 1 29-238-372
March 1941 set packer & 3500 - no change in oil or gas production - no suitable packer seat was available below 3540, therefore, further attempts were not made.
Present gas-oil ratio 20799




12

Continental Penrose 4 No. 2 5-235-362
1941 before 13 oil; 7 water; 2316 gas-oil ratio
Packer set & 3704
Packer set 2 oil; 4 water; 186 WCF
Above packer 41 oil; 7 water; 3048 gas-oil ratio
Packer 3560
Below 0 oil; 12 water; 200 WCF
Above 38 oil; 17 water; 2420 gas-oil ratio
Now 12 oil; no water; 3875 gas-oil ratio




DISCUSSION OF REMEDIAL RESULTS IN THE COOPER, LYNN AND JAL FIELDS
The study of numerous remedial jobs performed in the dolomite lime fields in the southern portion of the county of which a few typical examples have been outlined above, brings forth the general conclusion:













1. The particular fields are characterized by early water invasion, control of which has been proven futile in the history of many wells. Water shut off has been accomplished almost universally at the cost of the entire oil production capacity of the well, resulting in many abandonments.

2. High gas-oil ratios in these fields are the necessary evil which must accompany natural flow of large fluid volumes only a small portion of which is oil.




39





40



TESTING PROCEDURE

All operating gas-oil ratio tests shall be taken by or under the supervision of the New Mexico Oil Conservation Commission hereinafter designated as "The Commission".

- Operator**
The operator shall: Upon request of the Deputy of the Commission, (a) supply each well to be tested with a gas-oil ratio test; (b) furnish the Deputy of the Commission a complete list of his wells showing the type and dimensions of measuring equipment used; (c) furnish sufficient and qualified labor to install and maintain all measuring equipment in preparation for and during gas-oil ratio tests conducted in accordance with this order.

- The Commission**
The Commission shall: (a) Assemble the information supplied by the operators as recommended above, and arrange test schedules; (b) assign engineers to make tests and act as official witnesses. Only in the event of an emergency shall company engineers be used as official witnesses. (c) Insure all personnel in the proper operation of measuring equipment and procedure in conducting the tests; (d) calculate all test results; (e) furnish, calculate, record and file all gas measurement sheets and records; (f) compute all gas-oil ratios.

- Official Witness**
The official witness shall take such action as may be necessary to accomplish the desired purpose.

- Manner of Testing**
(a) The flow period shall be 48 hours, except as hereinafter stated. The first 24 hours shall be the stabilization period and the last 24 hours shall be the period during which the well is tested. (b) Oil shall be pumped at the beginning and ending of each 24-hour period and gas shall be measured during the period wherein the well is tested. No change in the rate of flow shall be made during the last 24 hours of the 48-hour flow period and the rate of flow shall be as nearly as possible the unadjusted current allowable rate. (c) Should an operator desire to flow a well at a rate less than the unadjusted current allowable rate, and in that event, the rate of flow for production purposes shall be made. (d) In case of a jetted well, the oil and gas shall be measured for the time it is produced. (e) For gas lift or other wells the total volume of gas to be used in computing the operating gas/oil ratio is the total output volume minus the total input volume.

2. Fluid Measurements

- All tanks shall be gauged and total volume of fluids determined according to accepted oil field practice.
- The net volume of oil shall be the total volume of fluid less the volume of 2.5 degrees of water.
- Fluid level in the separator must be maintained relatively constant so that the oil dump valve is covered at all times by at least 12 inches of liquid.
- If it is necessary to use a flowline for the separation of water the water level must be the same at the beginning and end of the test.

3. Gas Measurement

- A pressure gauge shall be installed on each separator and readings taken periodically. In the event the operator chooses to conduct the test at a separator pressure in excess of 100 pounds a recording pressure gauge shall be installed on the separator and the measured gas shall be based on the measured or calculated volume going to the tanks. Calculated volume shall be based on the volume of gas at separator pressure minus the volume of gas at wellhead pressure. The gas volume shall be computed in cubic feet and gas-oil ratios in cubic feet per barrel of oil.
- Official well testers, official meters and side pressure test nipples are approved. Side pressure nipples shall be used only when it is necessary to measure volumes larger than can be measured by official meters. A standard set of tables for each device will be on file in the office of the Deputy of the Commission.

- Any well that cannot be tested under the preceding rules shall be referred to the Commission for special consideration and rules.

STANDARD (MCM/ST) - CONTD.

Wells with producing rates above 6000 cu ft/day

WELL	DATE	TEST DATE	PRODUCING RATE	ALLOWABLE RATE
W-1	1-1-35	1-1-35	12,000	12,000
W-2	1-1-35	1-1-35	12,000	12,000
W-3	1-1-35	1-1-35	12,000	12,000
W-4	1-1-35	1-1-35	12,000	12,000
W-5	1-1-35	1-1-35	12,000	12,000

Proposed allowable transfer plan

TRANSFER FROM	TRANSFER TO	TRANSFER TO	TRANSFER TO
W-1	W-2	W-3	W-4
W-5	W-6	W-7	W-8
W-9	W-10	W-11	W-12

FIELD OIL COMPANY

LEASE	DAILY AIL	G.O.A.	TOTAL GAS	DAILY AIL	G.O.A.	TOTAL GAS
St. James #1	10	370	11800	10	370	11800
St. James #2	10	370	11800	10	370	11800
St. James #3	10	370	11800	10	370	11800
Total gas			35400			35400

SUN OIL COMPANY

LEASE	DAILY AIL	G.O.A.	TOTAL GAS	DAILY AIL	G.O.A.	TOTAL GAS
St. James #1	10	370	11800	10	370	11800
St. James #2	10	370	11800	10	370	11800
St. James #3	10	370	11800	10	370	11800
Total gas			35400			35400

MARKET LEASE

LEASE	DAILY AIL	G.O.A.	TOTAL GAS	DAILY AIL	G.O.A.	TOTAL GAS
St. James #1	10	370	11800	10	370	11800
St. James #2	10	370	11800	10	370	11800
St. James #3	10	370	11800	10	370	11800
Total gas			35400			35400

MARKET LEASE

LEASE	DAILY AIL	G.O.A.	TOTAL GAS	DAILY AIL	G.O.A.	TOTAL GAS
St. James #1	10	370	11800	10	370	11800
St. James #2	10	370	11800	10	370	11800
St. James #3	10	370	11800	10	370	11800
Total gas			35400			35400

MARKET LEASE

LEASE	DAILY AIL	G.O.A.	TOTAL GAS	DAILY AIL	G.O.A.	TOTAL GAS
St. James #1	10	370	11800	10	370	11800
St. James #2	10	370	11800	10	370	11800
St. James #3	10	370	11800	10	370	11800
Total gas			35400			35400

The New Mexico Federal Unit (a unit used for convenience to describe an operation conducted by Continental Oil Company for itself and the other joint owners, Standard Oil and Gas Company, Standard Oil Company of Texas and Atlantic Refining Company, of certain Federal leases in Lea County) supervises the operation of 225 wells and considerable undeveloped acreage. The N. M. F. U. recommends the enactment and enforcement of stringent rules and regulations for the conservation of oil and gas in New Mexico and suggests the following procedure:

- The establishment of a reasonable gas-oil ratio limit for each pool.
- The permitting of the allowance of each well exceeding that limit so that no well be permitted to produce more gas than an amount equal to the normal oil allowable multiplied by such gas-oil ratio limit.
- That no exceptions from this procedure be granted, regardless of supposedly peculiar conditions affecting any particular well or operation.
- That accurate gas-oil ratio measurements be made at periodic intervals and that sworn reports be required from the operators through the U. S. mails.
- That state authorities test a sufficient number of wells to insure reasonably accurate reports and enable them to detect inequities.
- That consideration be given to a production unit plan in those cases where additional conservation may be achieved by the use of such a plan, but that the tentative or final application of such plan be not permitted to alter the procedure here suggested or delay putting it into effect.

The New Mexico Federal Unit (a unit used for convenience to describe an operation conducted by Continental Oil Company for itself and the other joint owners, Standard Oil and Gas Company, Standard Oil Company of Texas and Atlantic Refining Company, of certain Federal leases in Lea County) supervises the operation of 225 wells and considerable undeveloped acreage. The N. M. F. U. recommends the enactment and enforcement of stringent rules and regulations for the conservation of oil and gas in New Mexico and suggests the following procedure:

- The establishment of a reasonable gas-oil ratio limit for each pool.
- The permitting of the allowance of each well exceeding that limit so that no well be permitted to produce more gas than an amount equal to the normal oil allowable multiplied by such gas-oil ratio limit.
- That no exceptions from this procedure be granted, regardless of supposedly peculiar conditions affecting any particular well or operation.
- That accurate gas-oil ratio measurements be made at periodic intervals and that sworn reports be required from the operators through the U. S. mails.
- That state authorities test a sufficient number of wells to insure reasonably accurate reports and enable them to detect inequities.
- That consideration be given to a production unit plan in those cases where additional conservation may be achieved by the use of such a plan, but that the tentative or final application of such plan be not permitted to alter the procedure here suggested or delay putting it into effect.

TO ALL OPERATORS:

Attached to this report and made a part thereof will be found data in connection with the transfer of allowable from high gas-oil ratio wells to low gas-oil ratio wells on the same basic lease.

The data is necessarily incomplete, due to the lack of time allowed for the tests. It is felt, however, that the results herewith presented may be indicative of that which can be expected from more extensive tests.

Glenn Stanley

INDEX

PAGES 1-6 Report of Committee Number One: Adoption of a permanent gas-oil ratio order with changes after study of suggested limiting ratios for various fields.

PAGES 7-12 Report of Committee Number Two and Report of Committee No. 1 & No. 2 Combined: A presentation of data relative remedial work in fields near depletion in Lea County, New Mexico (Graphs opposite pages 8 and 12).

PAGES 13-18 Report of Committee Number Three: Studying and proposing a definite plan for transfer of allowable oil from high gas-oil units to units with low gas-oil ratios on the same basic lease.

MINUTES OF SUB-ADVISORY & ENGINEERING ADVISORY COMMITTEES

A special meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee was held in Midland, Texas, November 24 at the Sherburne Hotel at 10 A.M. The following persons were present:

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. E.A. Kahntrop of the Oklahoma Pool Engineering Committee explained in detail the "Midcontinent Plan" of transferring allowable from high gas-oil ratio wells to low gas-oil ratio wells. Mr. Kahntrop pointed out that the plan has worked very successfully; many more than a lot of repair jobs that were tried. This plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County. The committee was especially interested in the fact that the plan was discussed with the idea of trying it in some of the fields south of Hobbs in Lea County.

Mr. A.M. McMorris

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Mr. A.M. McMorris

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

















Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

Submitted herewith is a compilation of reports by the committee listed below which were appointed at a meeting of the Sub-Advisory and Engineering Advisory Committees of the Lea County Operators Committee at Midland, Texas, November 24. The committee was appointed to study a permanent gas-oil ratio order and give suggested limiting gas-oil ratios for the various fields of Lea County.

INDEX

PAGES 1-6 Report of Committee Number One: Adoption of a permanent gas-oil ratio order with changes after study of suggested limiting ratios for various fields.



COMPANY	WELL	UNIT	S.T.R.	ADJUSTED MONTHLY PRODUCTION	MONTHLY GAS	MONTHLY OIL	MONTHLY WATER	MONTHLY TOTAL	REMARKS
AMERICAN PET. CORP.	Wair A	L	25-19-36	120	324	36			Gas lift & flow
AMERICAN PET. CORP.	Wair B	L	25-19-36	23	690	17058	2570		Reoperation
CITIZEN SERVICE OIL CO.	Parsons	P	25-19-36	12	360	750	270	22	Gas lift
CONTINENTAL OIL CO.	State A	I	7-19-37	19	570	400	228		Gas lift
CHRYL OIL CO.	State A	I	26-19-36	25	750	3681	2901	25	Reoperation
Hatchett	1	L	13-19-37	33	990	2124	2103	46	
Smith	1	L	13-19-37	8	640	1400	58	7	Pump
Wair	1	L	25-19-36	14	400	2850	1200	35	Reoperation
Wair B	1	L	25-19-36	17	510	2790	292	39	Reoperation
Wair C	1	L	25-19-36	8	240	5270	268	229	
Wair D	1	L	25-19-36	8	240	5270	268	229	
Wair E	1	L	25-19-36	8	240	5270	268	229	
Wair F	1	L	25-19-36	8	240	5270	268	229	
Wair G	1	L	25-19-36	8	240	5270	268	229	
Wair H	1	L	25-19-36	8	240	5270	268	229	
Wair I	1	L	25-19-36	8	240	5270	268	229	
Wair J	1	L	25-19-36	8	240	5270	268	229	
Wair K	1	L	25-19-36	8	240	5270	268	229	
Wair L	1	L	25-19-36	8	240	5270	268	229	
Wair M	1	L	25-19-36	8	240	5270	268	229	
Wair N	1	L	25-19-36	8	240	5270	268	229	
Wair O	1	L	25-19-36	8	240	5270	268	229	
Wair P	1	L	25-19-36	8	240	5270	268	229	
Wair Q	1	L	25-19-36	8	240	5270	268	229	
Wair R	1	L	25-19-36	8	240	5270	268	229	
Wair S	1	L	25-19-36	8	240	5270	268	229	
Wair T	1	L	25-19-36	8	240	5270	268	229	
Wair U	1	L	25-19-36	8	240	5270	268	229	
Wair V	1	L	25-19-36	8	240	5270	268	229	
Wair W	1	L	25-19-36	8	240	5270	268	229	
Wair X	1	L	25-19-36	8	240	5270	268	229	
Wair Y	1	L	25-19-36	8	240	5270	268	229	
Wair Z	1	L	25-19-36	8	240	5270	268	229	
Wair AA	1	L	25-19-36	8	240	5270	268	229	
Wair AB	1	L	25-19-36	8	240	5270	268	229	
Wair AC	1	L	25-19-36	8	240	5270	268	229	
Wair AD	1	L	25-19-36	8	240	5270	268	229	
Wair AE	1	L	25-19-36	8	240	5270	268	229	
Wair AF	1	L	25-19-36	8	240	5270	268	229	
Wair AG	1	L	25-19-36	8	240	5270	268	229	
Wair AH	1	L	25-19-36	8	240	5270	268	229	
Wair AI	1	L	25-19-36	8	240	5270	268	229	
Wair AJ	1	L	25-19-36	8	240	5270	268	229	
Wair AK	1	L	25-19-36	8	240	5270	268	229	
Wair AL	1	L	25-19-36	8	240	5270	268	229	
Wair AM	1	L	25-19-36	8	240	5270	268	229	
Wair AN	1	L	25-19-36	8	240	5270	268	229	
Wair AO	1	L	25-19-36	8	240	5270	268	229	
Wair AP	1	L	25-19-36	8	240	5270	268	229	
Wair AQ	1	L	25-19-36	8	240	5270	268	229	
Wair AR	1	L	25-19-36	8	240	5270	268	229	
Wair AS	1	L	25-19-36	8	240	5270	268	229	
Wair AT	1	L	25-19-36	8	240	5270	268	229	
Wair AU	1	L	25-19-36	8	240	5270	268	229	
Wair AV	1	L	25-19-36	8	240	5270	268	229	
Wair AW	1	L	25-19-36	8	240	5270	268	229	
Wair AX	1	L	25-19-36	8	240	5270	268	229	
Wair AY	1	L	25-19-36	8	240	5270	268	229	
Wair AZ	1	L	25-19-36	8	240	5270	268	229	
Wair BA	1	L	25-19-36	8	240	5270	268	229	
Wair BB	1	L	25-19-36	8	240	5270	268	229	
Wair BC	1	L	25-19-36	8	240	5270	268	229	
Wair BD	1	L	25-19-36	8	240	5270	268	229	
Wair BE	1	L	25-19-36	8	240	5270	268	229	
Wair BF	1	L	25-19-36	8	240	5270	268	229	
Wair BG	1	L	25-19-36	8	240	5270	268	229	
Wair BH	1	L	25-19-36	8	240	5270	268	229	
Wair BI	1	L	25-19-36	8	240	5270	268	229	
Wair BJ	1	L	25-19-36	8	240	5270	268	229	
Wair BK	1	L	25-19-36	8	240	5270	268	229	
Wair BL	1	L	25-19-36	8	240	5270	268	229	
Wair BM	1	L	25-19-36	8	240	5270	268	229	
Wair BN	1	L	25-19-36	8	240	5270	268	229	
Wair BO	1	L	25-19-36	8	240	5270	268	229	
Wair BP	1	L	25-19-36	8	240	5270	268	229	
Wair BQ	1	L	25-19-36	8	240	5270	268	229	
Wair BR	1	L	25-19-36	8	240	5270	268	229	
Wair BS	1	L	25-19-36	8	240	5270	268	229	
Wair BT	1	L	25-19-36	8	240	5270	268	229	
Wair BU	1	L	25-19-36	8	240	5270	268	229	
Wair BV	1	L	25-19-36	8	240	5270	268	229	
Wair BW	1	L	25-19-36	8	240	5270	268	229	
Wair BX	1	L	25-19-36	8	240	5270	268	229	
Wair BY	1	L	25-19-36	8	240	5270	268	229	
Wair BZ	1	L	25-19-36	8	240	5270	268	229	
Wair CA	1	L	25-19-36	8	240	5270	268	229	
Wair CB	1	L	25-19-36	8	240	5270	268	229	
Wair CC	1	L	25-19-36	8	240	5270	268	229	
Wair CD	1	L	25-19-36	8	240	5270	268	229	
Wair CE	1	L	25-19-36	8	240	5270	268	229	
Wair CF	1	L	25-19-36	8	240	5270	268	229	
Wair CG	1	L	25-19-36	8	240	5270	268	229	
Wair CH	1	L	25-19-36	8	240	5270	268	229	
Wair CI	1	L	25-19-36	8	240	5270	268	229	
Wair CJ	1	L	25-19-36	8	240	5270	268	229	
Wair CK	1	L	25-19-36	8	240	5270	268	229	
Wair CL	1	L	25-19-36	8	240	5270	268	229	
Wair CM	1	L	25-19-36	8	240	5270	268	229	
Wair CN	1	L	25-19-36	8	240	5270	268	229	
Wair CO	1	L	25-19-36	8	240	5270	268	229	
Wair CP	1	L	25-19-36	8	240	5270	268	229	
Wair CQ	1	L	25-19-36	8	240	5270	268	229	
Wair CR	1	L	25-19-36	8	240	5270	268	229	
Wair CS	1	L	25-19-36	8	240	5270	268	229	
Wair CT	1	L	25-19-36	8	240	5270	268	229	
Wair CU	1	L	25-19-36	8	240	5270	268	229	
Wair CV	1	L	25-19-36	8	240	5270	268	229	
Wair CW	1	L	25-19-36	8	240	5270	268	229	
Wair CX	1	L	25-19-36	8	240	5270	268	229	
Wair CY	1	L	25-19-36	8	240	5270	268	229	
Wair CZ	1	L	25-19-36	8	240	5270	268	229	
Wair DA	1	L	25-19-36	8	240	5270	268	229	
Wair DB	1	L	25-19-36	8	240	5270	268	229	
Wair DC	1	L	25-19-36	8	240	5270	268	229	
Wair DD	1	L	25-19-36	8	240	5270	268	229	
Wair DE	1	L	25-19-36	8	240	5270	268	229	
Wair DF	1	L	25-19-36	8	240	5270	268	229	
Wair DG	1	L	25-19-36	8	240	5270	268	229	
Wair DH	1	L	25-19-36	8	240	5270	268	229	
Wair DI	1	L	25-19-36	8	240	5270	268	229	
Wair DJ	1	L	25-19-36	8	240	5270	268	229	
Wair DK	1	L	25-19-36	8	240	5270	268	229	
Wair DL	1	L	25-19-36	8	240	5270	268	229	
Wair DM	1	L	25-19-36	8	240	5270	268	229	
Wair DN	1	L	25-19-36	8	240	5270	268	229	
Wair DO	1	L	25-19-36	8	240	5270	268	229	
Wair DP	1	L	25-19-36	8	240	5270	268	229	
Wair DQ	1	L	25-19-36	8	240	5270	268	229	
Wair DR	1	L	25-19-36	8	240	5270	268	229	
Wair DS	1	L	25-19-36	8	240	5270	268	229	
Wair DT	1	L	25-19-36	8	240	5270	268	229	
Wair DU	1	L	25-19-36	8	240	5270	268	229	
Wair DV	1	L	25-19-36	8	240	5270	268	229	
Wair DW	1	L	25-19-36	8	240	5270	268	229	
Wair DX	1	L	25-19-36	8	240	5270	268	229	
Wair DY	1	L	25-19-36	8	240	5270	268	229	
Wair DZ	1	L	25-19-36	8	240	5270	268	229	
Wair EA	1	L	25-19-36	8	240	5270	268	229	
Wair EB	1	L	25-19-36	8	240	5270	268	229	
Wair EC	1	L	25-19-36	8	240	5270	268	229	
Wair ED	1	L	25-19-36	8	240	5270	268	229	
Wair EE	1	L	25-19-36	8	240	5270	268	229	
Wair EF	1	L	25-19-36	8	240	5270	268	229	
Wair EG	1	L	25-19-36	8	240	5270	268	229	
Wair EH	1	L	25-19-36	8	240	5270	268	229	
Wair EI	1	L	25-19-36	8	240	5270	268	229	
Wair EJ	1	L	25-19-36	8	240	5270	268	229	
Wair EK	1	L	25-19-36	8	240	5270	268	229	
Wair EL	1	L	25-19-36	8	240	5270	268	229	
Wair EM	1	L	25-19-36	8	240	5270	268	229	
Wair EN	1	L	25-19-36	8					

TABLE 4 COMPARISON BETWEEN OPERATORS AND GASOLINE PLANT GAS VOLUMES ON SINGLE WELL UNITS MINE'S FIELD											
COMPANY LEASE	WELL NO.	S.T.D.	NO. OPERATORS		GASOLINE PLANT		OPERATORS GAS OIL RATIO	MONTHLY CALC. WATER GAL. PROD.	METHOD PROD.	DAILY ALL MANG. WELLS	DAILY ALL PERMIZED WELL
			MONTHLY PROD.	REPORTED GAS VOL.	MONTHLY PROD.	REPORTED GAS VOL.					

[illegible]

TABLE NO. 6 - WELLS - COMHD											
COMPANY	WELL	JANUARY		FEBRUARY		MARCH		APRIL		MAY	
		NO.	W.T.	NO.	W.T.	NO.	W.T.	NO.	W.T.	NO.	W.T.
LOCKHART A	1	3	30-21-36	370							
	4	8		323	312H	400	3100			370	148
	5	8		312	312H	400	3100			370	212
	6	1	24-12-36	544	594	619	518	GL		512	88
	7	4		941	5302	2553				1387	640
	8	4		1025	826	6195				10641	6191
	9	1		610	628	613				6285	6135
	10	1	24-12-36	985	673	6832	210			1085	2345
	11	2		1009	3491	5630					
	12	1		1008	400	400	980		GL	1007	3312
MAYOR A	1	4		1008	400	400	980		GL	1007	400
	2	4	24-12-36	950	12721	14764	217			2015	807
	3	4		821	488	3707	248				
	4	0		829	3968	4271				1351	696
	5	4		1066	3510	4992	12400			1351	7620
	6	1		1065	3776	3627					
	7	1	17-21-36	1067	3458	3250			2182	8024	3767
	8	4		869	1196	1773				6289	3250
	9	4		671	699	1045	62			956	1185
	10	4		667	779	1510	620			1381	1045
MAYOR B	1	4		674	270	40					
	2	4		285	1211	1219			GL	674	270
	3	4	18-21-36	665	1211	1219					
	4	4		396	396	3731					
	5	2		428	400	2400			GL	2569	38
	6	4		1078	1069	1016	98			GL	2154
	7	4		1078	1069	1016	98			GL	2154
	8	4		1072	2336	2336	388			GL	1070
	9	4		1078	2336	2336	388			GL	1070
	10	4	6-21-36	1062	3663	6633				GL	1075
MAYOR C	1	4		1084	2776					GL	1084
	2	4		1080	2776					GL	1080
	3	4		1080	2776					GL	1080

[illegible][illegible]

TABLE NO. 6 - MONTHLY - MONUMENT												
COMPANY	WELL	DATE	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY
LEASE	NO.	S.T.R.	PROD.	GAS	G.O.R.	PROD.	USED	OIL	GAS	G.O.R.	PROD.	USED
Phillips A	1	11-18-37	1117	1139	1000			1101	1139	1000		
"	2	"	1109	866	781			1109	866	781		
"	3	"	854	721	756			854	721	756		
"	4	"	1139	849	745			1139	849	745		
Shell	1	4-20-37	1101	776	705			1101	776	705		
Cooper B	2	"	1101	558	480			1101	558	480		
"	3	"	1101	879	789			1101	879	789		
State B	1	2-18-36	1119	1445	1282			1119	1445	1282		
"	2	"	1120	1850	1625			1120	1850	1625		
"	3	"	1120	1114	995			1120	1114	995		
"	4	"	1120	6003	5580			1120	6003	5580		
State R	1	12-20-36	1085	309	341			1085	309	341		
"	2	"	1085	586	485	182		1085	586	485	182	
"	3	"	1085	532	430	244		1085	532	430	244	
"	4	"	1085	1268	1198			1085	1268	1198		
Kelly	1	9-20-37	1270	394	310			1270	394	310		
Van Ruten	2	"	1270	406	320			1270	406	320		
"	3	"	1270	441	347			1270	441	347		
"	4	"	1271	435	342			1271	435	342		
"	5	"	1270	470	370			1270	470	370		
"	6	"	1270	460	362			1270	460	362		
"	7	"	1270	438	341			1270	438	341		
"	8	"	1271	445	350			1271	445	350		
Stanley	1	2-18-36	1020	5270	5167			1020	5270	5167		
"	2	"	518	2887	2807			518	2887	2807		
"	3	"	518	4688	4685			518	4688	4685		
"	4	"	518	4688	4685			518	4688	4685		
"	5	"	518	4688	4685			518	4688	4685		
"	6	"	518	4688	4685			518	4688	4685		
"	7	"	518	4688	4685			518	4688	4685		
"	8	"	518	4688	4685			518	4688	4685		
"	9	"	518	4688	4685			518	4688	4685		
"	10	"	518	4688	4685			518	4688	4685		
"	11	"	518	4688	4685			518	4688	4685		
"	12	"	518	4688	4685			518	4688	4685		
"	13	"	518	4688	4685			518	4688	4685		
"	14	"	518	4688	4685			518	4688	4685		
"	15	"	518	4688	4685			518	4688	4685		
"	16	"	518	4688	4685			518	4688	4685		
"	17	"	518	4688	4685			518	4688	4685		
"	18	"	518	4688	4685			518	4688	4685		
"	19	"	518	4688	4685			518	4688	4685		
"	20	"	518	4688	4685			518	4688	4685		
"	21	"	518	4688	4685			518	4688	4685		
"	22	"	518	4688	4685			518	4688	4685		
"	23	"	518	4688	4685			518	4688	4685		
"	24	"	518	4688	4685			518	4688	4685		
"	25	"	518	4688	4685			518	4688	4685		
"	26	"	518	4688	4685			518	4688	4685		
"	27	"	518	4688	4685			518	4688	4685		
"	28	"	518	4688	4685			518	4688	4685		
"	29	"	518	4688	4685			518	4688	4685		
"	30	"	518	4688	4685			518	4688	4685		
"	31	"	518	4688	4685			518	4688	4685		
"	32	"	518	4688	4685			518	4688	4685		
"	33	"	518	4688	4685			518	4688	4685		
"	34	"	518	4688	4685			518	4688	4685		
"	35	"	518	4688	4685			518	4688	4685		
"	36	"	518	4688	4685			518	4688	4685		
"	37	"	518	4688	4685			518	4688	4685		
"	38	"	518	4688	4685			518	4688	4685		
"	39	"	518	4688	4685			518	4688	4685		
"	40	"	518	4688	4685			518	4688	4685		
"	41	"	518	4688	4685			518	4688	4685		
"	42	"	518	4688	4685			518	4688	4685		
"	43	"	518	4688	4685			518	4688	4685		
"	44	"	518	4688	4685			518	4688	4685		
"	45	"	518	4688	4685			518	4688	4685		
"	46	"	518	4688	4685			518	4688	4685		
"	47	"	518	4688	4685			518	4688	4685		
"	48	"	518	4688	4685			518	4688	4685		
"	49	"	518	4688	4685			518	4688	4685		
"	50	"	518	4688	4685			518	4688	4685		
"	51	"	518	4688	4685			518	4688	4685		
"	52	"	518	4688	4685			518	4688	4685		
"	53	"	518	4688	4685			518	4688	4685		
"	54	"	518	4688	4685			518	4688	4685		
"	55	"	518	4688	4685			518	4688	4685		
"	56	"	518	4688	4685			518	4688	4685		
"	57	"	518	4688	4685			518	4688	4685		
"	58	"	518	4688	4685			518	4688	4685		
"	59	"	518	4688	4685			518	4688	4685		
"	60	"	518	4688	4685			518	4688	4685		
"	61	"	518	4688	4685			518	4688	4685		
"	62	"	518	4688	4685			518	4688	4685		
"	63	"	518	4688	4685			518	4688	4685		
"	64	"	518	4688	4685			518	4688	4685		
"	65	"	518	4688	4685			518	4688	4685		
"	66	"	518	4688	4685			518	4688	4685		
"	67	"	518	4688	4685			518	4688	4685		
"	68	"	518	4688	4685			518	4688	4685		
"	69	"	518	4688	4685			518	4688	4685		
"	70	"	518	4688	4685			518	4688	4685		
"	71	"	518	4688	4685			518	4688	4685		
"	72	"	518	4688	4685			518	4688	4685		
"	73	"	518	4688	4685			518	4688	4685		
"	74	"	518	4688	4685			518	4688	4685		
"	75	"	518	4688	4685			518	4688	4685		
"	76	"	518	4688	4685			518	4688	4685		
"	77	"	518	4688	4685			518	4688	4685		
"	78	"	518	4688	4685			518	4688	4685		
"	79	"	518	4688	4685			518	4688	4685		
"	80	"	518	4688	4685			518	4688	4685		
"	81	"	518	4688	4685			518	4688	4685		
"	82	"	518	4688	4685			518	4688	4685		
"	83	"	518	4688	4685			518	4688	4685		
"	84	"	518	4688	4685			518	4688	4685		
"	85	"	518	4688	4685			518	4688	4685		
"	86	"	518	4688	4685			518	4688	4685		
"	87	"	518	4688	4685			518	4688	4685		
"	88	"	518	4688	4685			518	4688	4685		
"	89	"	518	4688	4685			518	4688	4685		
"	90	"	518	4688	4685			518	4688	4685		
"	91	"	518	4688	4685			518	4688	4685		
"	92	"	518	4688	4685			518	4688	4685		
"	93	"	518	4688	4685			518	4688	4685		
"	94	"	518	4688	4685			518	4688	4685		
"	95	"	518	4688	4685			518	4688	4685		
"	96	"	518	4688	4685			518	4688	4685		
"	97	"	518	4688	4685			518	4688	4685		
"	98	"	518	4688	4685			518	4688	4685		
"	99	"	518	4688	4685			518	4688	4685		
"	100	"	518	4688	4685			518	4688	4685		

TABLE NO. 6 - MONTHLY - MONUMENT - CONT'D												
COMPANY	WELL	DATE	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY	MONTHLY
LEASE	NO.	S.T.R.	PROD.	GAS	G.O.R.	PROD.	USED	OIL	GAS	G.O.R.	PROD.	USED
State J	1	17-10-37	859	948	869							
"	2	"	3508	3850	208							
"	3	"	32212	69187	18671							
"	4	"	47088									
Grand Total			171031	5517,000	5517,000							

GULF OIL CORPORATION		
----------------------	--	--

MONUMENT - TABLE NO. 6 CONT'D									
COMPANY	WELL	DATE	MOUST	MONTHLY	MONTHLY	MONTHLY	MONTHLY	TRANS.	ALL
LEASE	NO.	S.T.R.	PROD.	PROD.	PROD.	PROD.	PROD.	PROD.	PROD.
SHILCOFF	3 H	55-19-36	688	2890	3330	19	1427	474	330
"	4 J	"	988	2455	2475	61	1208	2920	2475
"	6 O	"	859	28785	30500				
"	6 B	"	214 M	1125	3250				
"	1 A	2-20-36	971	2541	2617				
"	2 B	"	1003	2618	2610				
"	3 E	"	2005	2618	2610				
"	4 O	"	971	2541	2617				
TEXAS	1 B	5-20-37	1296	1104	882				
"	2 A	"	1297	1087	846				
"	3 C	"	1298	1088	838				
"	14 H	"	1296	1115	841				
Mettern	1 L	20-12-37	952	932	948				
"	2 M	"	957	1107	1157				
"	3 N	"	959	1098	1133				
"	4 K	"	974	982	1008				
Phillips	1 D	6-20-37	1182	702	589	41	1192	702	589
"	2 C	"	1182	712	597		1182	712	597
"	3 E	"	1182	685	575		1182	685	575
"	4 Y	"	1182	770	651		1182	770	651
Sammons	1 M	12-13-37	1103	1219	1105		1103	1219	1105
"	2 O	"	1183	1269	1402		1183	1269	1402
"	3 J	"	1204	1356	1274		1204	1356	1274
"	4 K	"	1102	1181	1072		1102	1181	1072
"	1 H	1-20-36	1048	532	500		1048	532	500
"	2 L	"	1048	512	518	44	1048	512	518
"	3 W	"	1047	554	529		1047	554	529
"	4 X	"	1047	547	522		1047	547	522
State H	8 A	20-20-37	1222	1204	1132		1222	1204	1132
"	6 B	"	1222	1399	1141		1222	1399	1141
"	7 C	"	1219	1265	1080		1219	1265	1080
"	11 D	"	845	1389	1575				
TIDWATER	1 E	17-10-37	1116	1479	1325		2263	1706	754
State J	2 D	"	1147	865	754				
"	3 F	"	837	1272	1580	83			

TABLE NO. 7									
SUMMARY OF TABLES 4, 5 & 6									
NO.	NO.	NO.	NO.	NO.	NO.	NO.	NO.	NO.	NO.
LEASE	NO.	NO.	NO.	NO.	NO.	NO.	NO.	NO.	NO.
MONUMENT FIELD	54	54	5	5	14310	139436	3010	7774	46310
Single Unit Leases	136	10	12	128149	251177	5013	11421	25	128149
Two Unit Leases	66	312	13	17	321216	691967	2154	18871	59
Three or More Unit Leases	207	502	28	32	495475	1004580	38066	94	495475
TOTAL MONUMENT	207	502	28	32	495475	1004580	38066	94	495475
ENHANCE FIELD	43	43	18	9	30423	97965	3220	45426	30423
Single Unit Leases	44	86	16	10	75141	370378	4985	23872	19
Two Unit Leases	62	327	43	25	315695	1138635	3607	216452	104
Three or More Unit Leases	178	488	77	44	421259	1666978	285750	123	421259
TOTAL ENHANCE	178	488	77	44	421259	1666978	285750	123	421259
Summit & Monument	178	488	77	44	421259	1666978	285750	123	421259
Single Unit Leases	44	86	16	10	75141	370378	4985	23872	19
Two Unit Leases	62	327	43	25	315695	1138635	3607	216452	104
Three or More Unit Leases	178	488	77	44	421259	1666978	285750	123	421259

STANDARD (MONUMENT)-CONT'D.
Wells with producing ratios above 6000 cu/ft/bbl.

LEASE	WELL	DATE	TEST RATE	PRODUCED	PRODUCED
"	Gilluly A 4	24-30-36	12	24,335	24,335
"	" B 4	21-20-36	53	8655	8655
"	" B 4	22-20-37	50	33647	33647
"	" B 5	17	17	37061	37061

Proposed allowable transfer plan

Transfer from	Transfer to	cu/ft. gas conserved
Gilluly A 4	Gilluly A 9	215,388
Gilluly B 4	Gilluly B 2	175,436
Gilluly B 5	Gilluly B 2	170,856

OHIO OIL COMPANY
STATE HANSEN LEASE

LEASE	DAILY ALL.	G.O.P.	TOTAL GAS	DAILY ALL.	G.O.P.	TOTAL GAS
St. Hansen #1	10	370	11600	10	370	11600
St. Hansen #2	44	370	15170	44	370	15170
St. Hansen #3	24	455	22040	24	455	22040
Total gas	78	1195	48810	78	1195	48810

Total saving of gas/day by trans. 221,170 cu/ft.

SUN OIL COMPANY
MAVERICK LEASE

MAVERICK #5 daily allowable 23 bbl. Gas oil ratio October, 1942 = 50,900

LEASE	DAILY ALLOW.	TOTAL GAS	DAILY ALLOW.	TOTAL GAS
MAVERICK #3	30	385	118,243	385
MAVERICK #4	31	418	121,272	418
MAVERICK #5	23	30,900	1,004,200	30,900
Daily total gas from 3, 4 & 5	84	1,035,823	1,035,823	1,035,823

Total daily gas savings 338,500 cu/ft.
12 bbl. per day transferred from #5 to #4
11 bbl. per day transferred from #5 to #3

49