State of New Mexico Oil Conservation Division

Closure Report Attachment Checklist: Each of the following items must be included in the closure report.

A scaled site and sampling diagram as described in 19.15.29.11 NMAC

Incident ID	nPAC0605450765
District RP	1RP-731
Facility ID	3002503091
Application ID	pPACO605450923

Released to Imaging: 8/26/2021 9:46:17 AM

Closure

The responsible party must attach information demonstrating they have complied with all applicable closure requirements and any conditions or directives of the OCD. This demonstration should be in the form of a comprehensive report (electronic submittals in .pdf format are preferred) including a scaled site map, sampling diagrams, relevant field notes, photographs of any excavation prior to backfilling, laboratory data including chain of custody documents of final sampling, and a narrative of the remedial activities. Refer to 19.15.29.12 NMAC.

Photographs of the remediated site prior to backfill or photos of the liner integrity if applicable (Note: appropriate OCD District office

must be notified 2 days prior to liner inspection). Laboratory analyses of final sampling (Note: appropriate OD Description of remediation activities	C District office must be notified 2 days prior to final sampling)				
and regulations all operators are required to report and/or file certa may endanger public health or the environment. The acceptance o should their operations have failed to adequately investigate and re human health or the environment. In addition, OCD acceptance of	ations. The responsible party acknowledges they must substantially onditions that existed prior to the release or their final land use in				
Printed Name: Amy Barnhill	Title: Waste and Water Specialist				
Signature:	Date: <u>2-27-2020</u>				
email: ABarnhill@chevron.com	Telephone: <u>432-687-7108</u>				
OCD Only					
Received by:	Date:				
Closure approval by the OCD does not relieve the responsible party of liability should their operations have failed to adequately investigate and remediate contamination that poses a threat to groundwater, surface water, human health, or the environment nor does not relieve the responsible party of compliance with any other federal, state, or local laws and/or regulations.					
Closure Approved by: Bradford Billin	gs Date: 08/26/2021				
Printed Name: Bradford Billings	Title: Envi.Spec.A				

REMEDIATION DOCUMENTATION AND CLOSURE REPORT

FOR THE
PRODUCTION FLUID RELEASE
ASSOCIATED WITH THE

VACUUM UNIT WELL #103

New Mexico Oil Conservation Division Case #

UL-F SE¼ OF THE NW¼ SECTION 6, T18S, R35E

-1.5 mile south of Buckeye

Lea County, New Mexico

Latitude 32°46'43.9"N Longitude 103°29'42.3"W

SEPTEMBER 2002

Prepared by

Environmental Plus, Inc.
2100 Avenue O
P.O. Box 1558
Eunice, New Mexico 88231
Tele 505•394•3481 FAX 505•394•2601



Table of Contents

Table of Contents	
Executive Summary	
1 Vacuum Unit Well #103 Remediation Work Plan	
1.1 Remediation Strategy and Objective	
1.2 Occurrence	
1.3 Site Description	. 2
1.3.1 Historical Use	. 2
1.3.2 Legal Description	. 2
1.3.3 Photographic documentation	
1.3.4 Ecological Description	. 2
1.3.5 Environmental Media Characterization	
1.3.6 NMOCD Site Ranking and Remedial Goals	. 4
1.4 Data Quality	
1.5 Project Safety	
1.6 Process/Procedure	. 4
2 Work Plan Implementation and Closure	. 6
2.1 Excavation and Composite Sampling	. 6
2.2 Discussion of Data	
2.3 Soil Disposal and Backfilling	
2.4 Conclusion	. 9
2.5 Follow Up	. 9
Attachment I: Site Maps	
Attachment II: Photographs	1 4
Attachment III: Analyses	
Attachment IV: New Mexico Office of the State Engineer Well Reports	
Attachment V: Site Metrics and Information Form	
Attachment VI: Chevron Digging Permit	

EXECUTIVE SUMMARY

On June 17,2002, a production fluid leak consisting of an undetermined volume of crude oil, natural gas, and formation water occurred at the ChevronTexaco Vacuum Unit Well #103. The leak resulted from the failure of the polish rod stuffing box packing and oversprayed the caliche well pad and a vegetated area to the southwest encompassing approximately 16,612 ft². The fluid impact was restricted to the compacted caliche well pad and flowed west and south from the well head. Only minor overspray impact was observed beyond the well pad. The ground water is estimated to occur at 89 feet below ground surface and is based on water level information obtained from the New Mexico Office of the State Engineer and the New Mexico Tech Internet Mapping System. Below are the acceptable remedial goals for the Constituents of Concern (CoCs), i.e., Total Petroleum Hydrocarbon EPA method 8015M (TPH^{8015m}), Benzene, and BTEX (the sum of Benzene, Toluene, Ethyl Benzene, and Xylene). There are no surface water bodies within 1000 horizontal feet of the site.

	Total Site Ranking S	core and Acceptable Concentration	18
Parameter	>19 (surface to 89'bgs)	10-19 (NA)	0-9 (NA)
Benzene ¹	10 ppm	10 ppm	10 ppm
BTEX1	50 ppm	50 ppm	50 ppm
TPH	100 ppm	1000 ppm	5000 ppm

A windmill and livestock watering tub are located ~203 feet west of the leak origin and approximately 130' from the affected area perimeter and was not observed to be impacted by the overspray but was nonetheless sampled and tested for Benzene, BTEX, Chloride, and Total Dissolved Solids (TDS). BTEX was not detected above the instrument detection limits for the specific parameter and the Chloride and TDS were within background levels, i.e., TDS = 343 mg/L and Chloride = 44 mg/L. On September 30, 2002, the windmill production flow stream was sampled for BTEX, Chloride, and TDS with no BTEX detected above the instrument detection limits and Chloride and TDS within background levels, i.e., 160 and 367 mg/L, respectively. The land is owned by the New Mexico State Land Office and leased for livestock grazing purposes to Giles Lee. At ChevronTexaco's request Environmental Plus, Inc. (EPI) of Eunice, New Mexico mitigated the spill. Mitigation activities involved treating the affected surface and vegetation with MicroBlaze Spill Control (a non-hazardous phosphate based detergent inoculated with petrophilic microbes to promote bio-attenuation) and spreading and blending clean soil into the affected near surface soil. Composite near surface (0-6"below ground surface (bgs)) samples were collected from each quadrant on June 18, 2002 and the Headspace Volatile Organic Constituent (VOC) surveyed using a calibrated Photoionization Detector (PID). Readings were all less than 50 ppm and were therefore sent to Cardinal Laboratories in Hobbs, New Mexico for analysis. Analytical results indicated the Total Petroleum Hydrocarbon EPA method 8015m (TPH^{8015m}) in the north, west, and south quadrants to be in excess of the New Mexico Oil Conservation Division (NMOCD) guideline threshold of 100 mg/Kg, consequently, approximately 60 cubic yards (yd³) of impacted near surface soil was disposed of in the New Mexico Oil Conservation Division (NMOCD) approved and permitted "Texaco Land Farm" (TLF). On June 25, 2002, soil borings were advanced to 15'bgs and sampled at 5' intervals in the north, west, and south quadrants pooling areas to determine vertical extent of contamination. BTEX was not detected above the instrument detection limit in any of the boring samples and TPH 8015m only nominally. Chloride levels in the south borehole (SBH) were < 250 mg/Kg for all but the 3'bgs and 15'bgs samples which were 300 and 480 mg/Kg, respectively. Chloride concentrations in all samples from the West Borehole (WBH) and the North Borehole (NBH) were less than 160 mg/Kg. Based on this information the excavated area was backfilled with clean soil and contoured. The information collected during the mitigation and remediation of the site indicate that the CoC remedial goals have been achieved and justifies the NMOCD requiring "no further action" at this site.

1 VACUUM UNIT WELL #103 REMEDIATION WORK PLAN

This plan restored the impacted surface area to acceptable levels by removing soil contaminated above New Mexico Oil Conservation Division (NMOCD) guidelines. The Constituents of Concern (CoCs) were Total Petroleum Hydrocarbon using EPA method 8015M (TPH^{8015m}), Benzene, BTEX, i.e., the sum of Benzene, Toluene, Ethyl Benzene, and m, p, & o Xylene, and soil Chloride.

1.1 Remediation Strategy and Objective

The site was delineated during excavation and by advancing vertical soil borings with soil disposal as the remediation strategy. The objectives of the plan were to;

- Document achievement of acceptable environmental thresholds established by the NMOCD and
- Restore the impacted surface area to pre-release status.

1.2 Occurrence

On June 17,2002, a production fluid leak consisting of an undetermined volume of crude oil, natural gas, and formation water occurred at the ChevronTexaco Vacuum Unit Well #103. The leak resulted from the failure of the polish rod stuffing box packing and oversprayed the caliche well pad and a vegetated area to the southwest encompassing approximately 16,612 ft². The fluid impact was restricted to the compacted caliche well pad and flowed west and south from the well head. Only minor overspray impact was observed beyond the well pad.

1.3 Site Description

The site is located ~1.5 miles south of Buckeye, New Mexico at Latitude 32°46'43.9"N Longitude 103°29'42.3"W and ~3,975 feet above mean sea level ('asml). A site map is included as Attachment I.

1.3.1 Historical Use

This land is owned by the State of New Mexico and leased to Giles Lee. The land is used for livestock grazing and oil and gas production facilities access.

1.3.2 Legal Description

The legal description is Unit Letter-F, in the SE¼ of the NW¼ of Section 6, Township 18 South, Range 35 East.

1.3.3 Photographic documentation

Photographs of the site are included as Attachment II.

1.3.4 Ecological Description

The area is an intergrade of the Lower Great Plains and the Upper Chihuahuan Desert Biomes consisting primarily of flat to hilly clay/loam/sand terrain dominated by typical desert grasses and weeds with interspersions of Harvard Shin Oak (Querqus harvardi) and Honey Mesquite (Prosopis glandulosa). Mammals present, include Orrd's and Merriam's Kangaroo Rat, Deer Mouse, White Throated Wood Rat, Cottontail Rabbit, Black Tailed Jackrabbit, and the Mule Deer. Reptiles, Amphibians, and Birds are numerous and typical of area. A survey of Listed, Threatened, or Endangered species has not been conducted.

1.3.5 Environmental Media Characterization

Chemical parameters of the soil were characterized consistent with the New Mexico Oil Conservation Division (NMOCD) guidelines published in the following documents;

• Guidelines for Remediation of Leaks, Spills and Releases (August 13, 1993)

• Unlined Surface Impoundment Closure Guidelines (February 1993)

Acceptable "Site Specific" thresholds for the CoCs, i.e., Benzene, Chloride, TPH 8015m, and BTEX, were determined based on the following;

- Depth to Ground water, i.e., distance from the lower most acceptable concentration to the ground water.
- Wellhead Protection Area, i.e., distance from fresh water supply wells.
- Distance to Surface Water Body, i.e., horizontal distance to all down gradient surface water bodies.

1.3.5.1 Ground Water Level

According to the Office of the New Mexico State Engineer ground water level database, the nearest water wells with known levels in section 6 of T18S R35E average to 89'bgs. The New Mexico Tech "geo-information" website, i.e., http://geoinfo.nmt.edu/.esrimap provided well data indicating consistent ground water depth. The windmill west of the site was not accessible for water level measurement. The wells are plotted on the topographical map in Attachment I and the well reports are included Attachment IV.

1.3.5.2 Depth to Ground Water Calculation

Depth to ground water, i.e., "the vertical distance from the lowermost contaminants to the seasonal high water elevation of the ground water." For the hydrocarbon source term, i.e., TPH^{8015m}, Benzene, and BTEX, this was determined to be 86'bgs.

1.3.5.3 Ground Water Gradient

According to the USGS (Nicholson & Clbesch), the gradient is to the southeast.

1.3.5.4 Wellhead Protection Area

A windmill well and drinking tub used by livestock are located approximately 200' west of the site and 130' from the affected area perimeter.

1.3.5.5 Distance to Nearest Surface Water Body

There are no naturally occurring surface water bodies located within a 1 mile radius of the site.

1.3.5.6 Soil Assessment

Composite near surface (0-6"below ground surface (bgs)) samples were collected from each quadrant on June 18, 2002 and the Headspace Volatile Organic Constituent (VOC) surveyed using a calibrated Photoionization Detector (PID). A site sampling map is included as Attachment I. Readings were all less than 50 ppm and were therefore sent to Cardinal Laboratories in Hobbs, New Mexico for analysis. Analytical results indicated the Total Petroleum Hydrocarbon EPA method 8015m (TPH^{8015m}) in the north, west, and south quadrants to be in excess of the New Mexico Oil Conservation Division (NMOCD) guideline threshold of 100 mg/Kg, consequently, approximately 60 cubic yards (yd³) of impacted near surface soil was disposed of in the New Mexico Oil Conservation Division (NMOCD) approved and permitted "Texaco Land Farm" (TLF). On June 25, 2002, soil borings were advanced to 15'bgs and sampled at 5' intervals in the north, west, and south quadrants pooling areas to determine vertical extent of contamination. BTEX was not detected above the instrument detection limit in any of the boring samples and TPH^{8015m} only nominally. Chloride levels in the south borehole (SBH) were < 250 mg/Kg for all but the 3'bgs and 15'bgs samples which were 300 and 480 mg/Kg, respectively. Chloride concentrations in all samples from the West Borehole (WBH) and the North Borehole (NBH) were less than 160 mg/Kg. Analytical reports are summarized and included in Attachment III.

1.3.5.7 Ground Water Assessment

The ground water level is conservatively estimated to occur at -89 feet bgs. The soil assessment did not indicate that the ground water had been impacted by the hydrocarbon source term. The water in the drinking tub at the windmill well west of the site was sampled on June 17, 2002 and tested for BTEX, Chloride, and TDS. BTEX was not detected above the instrument detection limit and the Chloride and TDS were monitored to be within background tolerances, i.e., Chloride = 44 mg/L and TDS = 343 mg/L. On September 30,

2002, the windmill production flow stream was sampled for BTEX, Chloride, and TDS with no BTEX detected above the instrument detection limits and Chloride and TDS within background levels, i.e., 160 and 367 mg/L, respectively. Analytical reports are summarized and included in Attachment III.

1.3.6 NMOCD Site Ranking and Remedial Goals

The Site information and Metrics form in Attachment V summarizes the information about the site, shows a site ranking of 30 points, and sets the following remedial goals for the CoCs.

1. G1	round Water	2. Wellhead Protection Area		3. Distance to Surface Water Body		
If Depth to GW	<50 feet: <i>20 points</i>	If < 10	000' from water source, or;<200' from	<200 horizontal feet: 20 points		
If Depth to GW	50 to 99 feet: <i>10 points</i>	priva	te domestic water source: 20 points	200-100 horizontal feet: 10 points		
If Depth to GW >100 feet: 0 points		If >1000' from water source, or; >200' from private domestic water source: <i>0 points</i>		>1000 horizontal feet: 0 points		
Ground water Score = 10		Wellh	head Protection Area Score= 20	Surface Water Score= 0		
Site Rank (1	(+2+3) = 30					
Total Site R	lanking Score and A	ссер	table Concentrations			
Parameter	>19 (surface to 89'bgs))	10-19 (NA)	0-9		
Benzene ¹	10 ppm		10 ppm	10 ppm		
BTEX ¹	50 ppm		50 ppm	50 ppm		
TPH	PH 100 ppm		1000 ppm	5000 ppm		
100 ppm field VOC headspace measurement may be substituted for lab analysis						

1.4 Data Quality

All laboratory analytical results were within the data quality objectives listed below.

- Laboratory data must have > 85% recovery for TPH and BTEX and >75% recovery for general chemistry parameters.
- Laboratory data must have <15% Relative Percent Difference
- Field headspace analyses must be supported with instrument calibration data and calibration gas certification.

Duplicates or blanks were not submitted to the laboratory.

1.5 Project Safety

Hazards encountered at this site include the following;

- Moving equipment
- Buried pipelines
- Highway ingress/egress
- Excavation
- Potential Hydrogen Sulfide Gas

Employees and subcontractors were required to confirm current training in these hazards. Standard personal protective equipment included;

- Personal H₂S Monitor
- Hard-hat
- Safety Glasses

- Excavation Safety
- Steel Toed Boots/Shoes

1.6 Process/Procedure

The following sequence was used to guide project implementation.

- 1. Site visit: Photograph and map
- 2. Issue "One Call" and notifying utilities
- 3. Complete the "ChevronTexaco Digging Permit" and signature approval process

- 4. Locate, hand spot, and mark buried lines or other structures
- 5. Overhead powerlines are not present and will not be a hazard.
- 6. Lockout/Tagout: Verify pumping unit is locked out and tagged and forms completed. Pipeline companies notified of activity but LO/TO unnecessary
- 7. Procedure: Equipment required will be: Backhoe, Excavator, Dump Trucks
 - Daily Tail gate safety meetings and PPE check
 - Excavation Safety Checklist Form
 - Excavate visibly contaminated soil and stockpile
 - Haul stockpiled soil to NMOCD approved facility
 - Conduct field VOC headspace analyses on selected samples
 - Collect Composite Samples of the selected areas for laboratory analysis
 - · Review data and calculate "Depth to Ground Water"
 - Backfill excavations with volume consistent with disposal volume
 - Photograph
 - Develop and issue site specific report
 - Contour and/or Reseed surface

2 WORK PLAN IMPLEMENTATION AND CLOSURE

The process of excavating and disposing of contaminated soil and field surveying began on June 17, 2002 with the disposal and backfilling phase completed on June 28, 2002.


2.1 Excavation and Composite Sampling

Composite near surface (0-6"below ground surface (bgs)) samples were collected from each quadrant on June 18, 2002 and the Headspace Volatile Organic Constituent (VOC) surveyed using a calibrated Photoionization Detector (PID). Readings were all less than 50 ppm and were therefore sent to Cardinal Laboratories in Hobbs, New Mexico for analysis. Analytical results indicated the TPH or the north, west, and south quadrants to be in excess of the New Mexico Oil Conservation Division (NMOCD) guideline threshold of 100 mg/Kg, consequently, approximately 60 cubic yards (yd³) of impacted near surface soil was disposed of in the New Mexico Oil Conservation Division (NMOCD) approved and permitted "Texaco Land Farm" (TLF). On June 25, 2002, soil borings were advanced to 15'bgs and sampled at 5' intervals in the north, west, and south quadrants pooling areas to determine vertical extent of contamination. BTEX was not detected above the instrument detection limit in any of the boring samples and TPH only nominally. Chloride levels in the south borehole (SBH) were < 250 mg/Kg for all but the 3'bgs and 15'bgs samples which were 300 and 480 mg/Kg, respectively. Chloride concentrations in all samples from the West Borehole (WBH) and the North Borehole (NBH) were less than 160 mg/Kg.

2.2 Discussion of Data

The NMOCD remedial goals have been achieved at this site. The Chloride concentrations in the South Borehole should not pose a threat to local ground water given that the surface is now covered with approximately 12" of compacted caliche. Application/treatment of the vegetated overspray area with MicroBlaze Spill Control will accelerate bio-attenuation and fertilize the area. ChevronTexaco personnel will monitor the status of the vegetation. The original laboratory analytical reports and data summary are included as Attachment III and the data is illustrated below.


CHEVRONTEXACO
VACUUM UNIT WELL #103
TOTAL PETROLEUM HYDROCARBON 8015M DELINEATION



TPH THRESHOLD 100 MG/KG

CHEVRONTEXACO VACUUM UNIT WELL #103 BTEX DELINEATION


TPH MG/KG



SAMPLE AREA AND DATE

BTEX MG/KG BTEX THRESHOLD MG/KG


CHEVRONTEXACO
VACUUM UNIT WELL #103
BENZENE DELINEATION



SAMPLE AREA AND DATE

BENZENE MG/KG BENZENE THRESHOLD MG/KG

CHEVRONTEXACO VACUUM UNIT WELL #103 CHLORIDE DELINEATION



■ CHLORIDE MG/KG

2.3 Soil Disposal and Backfilling

Under chain of custody, 60 yd³ was disposed of in the NMOCD approved and permitted Texaco Land Farm (TLF). A sufficient volume of clean backfill soil, i.e.60 yd³, was obtained from the TLF and used to bring the excavation to grade.


2.4 Conclusion


Production fluid contamination at this site resulted in soil contamination above the NMOCD remedial guidelines. The data support the conclusion that the site has been remediated to acceptable levels for the CoCs and as such justifies the NMOCD requiring "no further action" at this site.


2.5 Follow Up

The vegetated overspray area will be visually monitored by ChevronTexaco personnel.

Attachment I: Site Maps







Attachment II: Photographs

















Attachment III: Analyses

	Chevron-Texaco Vacuum Unit Well #103																
Sample Area	Sample Type	Sampling Interval (FT. BGS ¹)	SAMPLE ID#	Date	Lithology	HEADSPACE VOC² (ppm)	GRO ³ mg/Kg	DRO ⁴ mg/Kg	TPH ⁵ mg/Kg		Benzene mg/Kg		Ehtyl Benzene mg/Kg	m,p-o Xylene mg/Kg	Chloride mg/Kg	Total Dissolved Solids mg/Liter	mg/Liter
Windmill Drinking Tub	Grab	na	CTVUW10361702ST	6/17/2002	Ground Water	na	na	na	na	na	<0.010	<0.010	<0.010	<0.030	44	343	44
Puddle (hoof print) adjacent to the Drinking Tub	Grab	na	CTVUW10361702HP	6/17/2002	Ground Water	na	na	na	na	na	<0.002	<0.002	<0.002	<0.006	na	na	na
Windmill	Grab	na	WCTVU10393002	9/30/2002	Ground Water	na	na	na	na	na	< 0.002	< 0.002	< 0.002	< 0.006	na	367	160
North Quadrant	Comp	0-6"	CTVUW10361802N	6/18/2002	Caliche	38.2	366	2930	3296	4.304	0.031	0.223	1.010	3.040	1340	na	na
West Quadrant	Comp	0-6"	CTVUW10361802W	6/18/2002	Sand/Caliche	10.1	47.3	1460	1507.3	4.794	0.006	0.458	1.510	2.820	4960	na	na
South Quadrant	Comp	0-6"	CTVUW10361802S	6/18/2002	Sand/Caliche	17.9	59.1	2680	2739.1	2.719	0.005	0.401	0.903	1.410	1870	na	na
East Quadrant	Comp	0-6"	CTVUW10361802E	6/18/2002	Sand/Caliche	8.2	10	38.5	48.5	0.062	0.005	0.006	0.022	0.029	600	na	na
	Grab	3'	SCTV10362502SBH-3'	6/25/2002	Caliche	4.1	10	10	20	0.030	0.005	0.005	0.005	0.015	300	na	na
South Borehole	Grab	5'	SCTV10362502SBH-5'	6/25/2002	Sand/Caliche	2.7	10	10	20	0.030	0.005	0.005	0.005	0.015	96	na	na
South Borehole	Grab	10'	SCTV10362502SBH-10'	6/25/2002	Sand/Caliche	1.4	10	10	20	0.030	0.005	0.005	0.005	0.015	240	na	na
	Grab	15'	SCTV10362502SBH-15'	6/25/2002	Sand/Caliche	0.0	10	10	20	0.030	0.005	0.005	0.005	0.015	480	na	na
	Grab	3'	SCTV10362502WBH-3'	6/25/2002	Caliche	3.7	10	10	20	0.030	0.005	0.005	0.005	0.015	96	na	na
West Borehole	Grab	5'	SCTV10362502WBH-5'	6/25/2002	Sand/Caliche	0.9	10	10	20	0.030	0.005	0.005	0.005	0.015	96	na	na
West Barenare	Grab	10'	SCTV10362502WBH-10'	6/25/2002	Sand/Caliche	0.4	10	10	20	0.030	0.005	0.005	0.005	0.015	120	na	na
	Grab	15'	SCTV10362502WBH-15'	6/25/2002	Sand/Caliche	0.0	10	10	20	0.030	0.005	0.005	0.005	0.015	80	na	na
	Grab	3'	SCTV10362502NBH-3'	6/25/2002	Caliche	9.5	10	11.6	21.6	0.030	0.005	0.005	0.005	0.015	160	na	na
North Borehole	Grab	5'	SCTV10362502NBH-5'	6/25/2002	Sand/Caliche	0.4	10	10	20	0.030	0.005	0.005	0.005	0.015	80	na	na
	Grab	10'	SCTV10362502NBH-10'	6/25/2002	Sand/Caliche	0.2	10	10	20	0.030	0.005	0.005	0.005	0.015	80	na	na
These below ground surface	Grab	15'	SCTV10362502NBH-15'	6/25/2002	Brown Sand	0.0	10	10	20	0.030	0.005	0.005	0.005	0.015	112	na	na

1bgs - below ground surface

²VOC–Volatile Organic Contaminants/Constituents

GRO-Gasoline Range Organics C₆-C₁₀

⁴DRO-Diesel Range Organics C₁₀-C₂₈

TPH-Total Petroleum Hydrocarbon = GRO+DRO.

Bolded values are in excess of the New Mexico Oil Conservation Division guideline threshold for the parameter

Italicized values are < the instrument detection limit.

N/A Not Analyzed

Reported detection limits are considered "de minimus" values and are included in the GRO/DRO and BTEX summations.



PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2326 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 06/18/02 Reporting Date: 06/20/02 Project Owner: TEXACO

Project Name: TEXACO

Project Location: VACUUM UNIT WELL 103

Sampling Date: 06/17/02

Sample Type: GROUNDWATER Sample Condition: COOL & INTACT

Sample Received By: AH

Analyzed By: AH

LAB NUMBER SAMPLE ID

TDS (mg/L)

160.1

CI (mg/L)

ANALYSIS DATE:	06/19/02	06/18/02	
H6812-2 CTVUW10361702ST	343	44	
		.,.,.	
Quality Control	NR	1020	
True Value QC	NR	1000	
% Recovery	NR	102	
Relative Percent Difference	8.8	4.0	

*Std. Methods

METHODS: EPA 600/4-79-02

H6812

U-20-02
Date

4500-CIB*

PLEASE NOTE: Liability and Demages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tord, shall be limited to the amount paid by client for analyses.

All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In not event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, attlifiates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.



PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2326 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 08/18/02 Reporting Date: 06/20/02

Project Owner: TEXACO Project Name: TEXACO

Project Location: VACUUM UNIT WELL 103

Sampling Date: 06/17/02

Sample Type: GROUNDWATER Sample Condition: COOL & INTACT

Sample Received By: AH

Analyzed By: BC

BENZENE TOLUENE BENZENE XYLENES
LAB NUMBER SAMPLE ID (mg/L) (mg/L) (mg/L) (mg/L)

ANALYSIS I	DATE	06/18/02	06/18/02	06/18/02	06/18/02
H6812-1*	CTVUW10361702 HP	<0.010	< 0.010	< 0.010	< 0.030
H6812-2	CTVUW10361702 ST	<0.002	<0.002	<0.002	<0.006
Quality Cont	trol	0.102	0.108	0.107	0.316
True Value (20	0.100	0.100	0.100	0.300
% Recovery		102	108	107	105
Relative Per	cent Difference	4.1	6.7	2.9	4.8


METHOD: EPA SW-846 8260

us A. Cooke

*Dilution required due to pronounced odor and foaming during purge/trap.

Date

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim srising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, locusing those for negligence and any other cause whetever shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. The descriptions are consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its substituties, affiliates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.





PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (605) 393-2326 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 06/19/02 Reporting Date: 06/21/02 Project Number: NOT GIVEN

Project Name: CHEVRON TEXACO

Project Location: VACUUM UNIT WELL 103

Sampling Date: 06/18/02 Sample Type: SOIL

Sample Condition: COOL & INTACT

Sample Received By: BC

Analyzed By: BC

LAR NUMBI	ER SAMPLE ID	BENZENE	TOLUENE	BENZENE	TOTAL XYLENES
	IN OAKII EE ID	(mg/Kg)	(mg/Kg)	(mg/Kg)	(mg/Kg)
ANALYSIS	DATE	06/19/02	06/19/02	06/19/02	06/19/02
H6814-1	CTVI IW10361802NI	0.021	0.222	4.04	0.04

ANALYSIS	DATE	06/19/02	06/19/02	06/19/02	06/19/02
H6814-1	CTVUW10361802N	0.031	0.223	1.01	3.04
H6814-2	CTVUW10361802W	0,006	0.458	1.51	2.82
H6814-3	CTVUW10361802S	<0.005	0,401	0.903	1.41
H6814-4	CTVUW10361802E	<0.005	0.006	0.022	0.029
Quality Con	frol	0.107	0.102	0.101	0.290
True Value	QC	0.100	0,100	0.100	0.300
% Recovery		107	102	101	97.6
Relative Per	rcent Difference	5.0	6.1	5.7	8.9

METHOD: EPA SW-846 8260

6/21/02

Date

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All catings, including those for negligence and any other cause whatscaver shall be deemed walved unless made in writing and received by Cerdinal within thirty (30) days after completion of the applicable service for for the cause of the contract of the contract of the contract of the contract of the cause of the contract of the cause of the contract of the cause of the



PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2328 . 101 E. MARLAND . HOBBS, NM 88240

ANALYTICAL RESULTS FOR **CHEVRON TEXACO** ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 06/19/02

Reporting Date: 06/20/02

Project Number: NOT GIVEN Project Name: CHEVRON TEXACO

Project Location: VACUUM UNIT WELL 103

Sampling Date: 06/18/02

Sample Type: SOIL

Sample Condition: COOL & INTACT

Sample Received By: BC Analyzed By: BC/AH

GRO DRO CI* (>C10-C28) (C6-C10) (mg/Kg) (mg/Kg) (mg/Kg) LAB NUMBER SAMPLE ID

ANALYSIS	DATE	06/19/02	06/19/02	06/20/02
H6814-1	CTVUW10361802N	366	2930	1340
H6814-2	CTVUW10361802W	47.3	1460	4960
H6814-3	CTVUW10361802S	59.1	2680	1870
H6814-4	CTVUW10361802E	<10.0	38.5	600
Quality Con	itrol	764	818	1020
True Value		800	800	1000
% Recover		95.4	102	102
Relative Percent Difference		7.3	2.3	4.0


METHODS: TPH GRO & DRO: EPA SW-846 8015 M; CI: Std. Methods 4500-CIB *Analyses performed on 1:4 w:v aqueous extracts.

uggs JA Cooke

Date

H6814A.XLS

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in witting and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, total of use, or loss of profits incurred by client. Its subsidiaries, atfiliates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.





PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2326 . 101 E. MARLAND . HOBBS, NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 06/26/02 Reporting Date: 06/28/02

Project Owner: CHEVRON TEXACO
Project Name: VACUUM UNIT WELL 103

Project Location: NOT GIVEN

Sampling Date: 06/25/02 Sample Type: SOIL

Sample Condition: COOL & INTACT

Sample Received By: AH Analyzed By: BC/AH

LAB NUMBER SAMPLE ID	GRO (C ₆ -C ₁₀) (mg/Kg)	DRO (>C ₁₀ -C ₂₈) (mg/Kg)	CI* (mg/Kg)
ANALYSIS DATE	06/27/02	06/27/02	06/28/02
LIGHT 4 COT HEREFERDED LES		100	000

ANALYSIS [DATE	06/27/02	06/27/02	06/28/02
H6845-1	SCTV10362502SBH-3'	<10.0	<10.0	300
H6845-2	SCTV10362502SBH-5'	<10,0	<10.0	96
H6845-3	SCTV10362502SBH-10'	<10.0	<10.0	240
H6845-4	SCTV10362502SBH-15'	<10.0	<10.0	480
H6845-5	SCTV10362502WBH-3'	<10.0	<10.0	96
H6845-6	SCTV10362502WBH-5'	<10.0	<10.0	96
H6845-7	SCTV10362502WBH-10'	<10.0	<10,0	120
H6845-8	SCTV10362502WBH-15'	<10.0	<10.0	80
H6845-9	SCTV10362502NBH-3'	<10.0	11.6	160
H6845-10	SCTV10362502NBH-5'	<10.0	<10.0	80
H6845-11	SCTV10362502NBH-10'	<10.0	<10.0	80
H6845-12	SCTV10362502NBH-15'	<10.0	<10.0	112
Quality Cont	rol	718	766	1040
True Value 0	QC	800	800	1000
% Recovery	0 0	89.7	95.8	104
Relative Per	cent Difference	2.2	6.4	2.0

METHODS: TPH GRO & DRO: EPA SW-846 8015 M; CI: Std. Methods 4500-CIB *Analyses performed on 1:4 w:v aqueous extracts.

H6845A.XLS

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, including those for negligence and any other cause whateover shall be deemed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for including, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidieries, affiliates or auccessors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.



PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2326 • 101 E. MARLAND • HOBBS. NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 06/26/02 Reporting Date: 06/28/02

Project Owner: CHEVRON TEXACO

Project Name: VACUUM UNIT WELL 103

Project Location: NOT GIVEN

Sampling Date: 06/25/02

Sample Type: SOIL

Sample Condition: COOL & INTACT

Sample Received By: AH

Analyzed By: BC

LAB NO.	SAMPLE ID	BENZENE (mg/Kg)	TOLUENE (mg/Kg)	ETHYL BENZENE (mg/Kg)	TOTAL XYLENES (mg/Kg)
ANALYSIS	DATE	06/27/02	06/27/02	06/27/02	06/27/02
H6845-1	SCTV10362502SBH-31	< 0.005	<0.005	< 0.005	< 0.015
H6845-2	SCTV10362502SBH-5'	< 0.005	< 0.005	< 0.005	< 0.015
H6845-3	SCTV10362502SBH-10'	< 0.005	0.008	< 0.005	< 0.015
H6845-4	SCTV10362502SBH-15'	< 0.005	< 0.005	< 0.005	< 0.015
H6845-5	SCTV10362502WBH-3'	< 0.005	<0.005	< 0.005	< 0.015
H6845-6	SCTV10362502WBH-5'	< 0.005	< 0.005	< 0.005	<0.015
H6845-7	SCTV10362502WBH-10'	< 0.005	< 0.005	< 0.005	< 0.015
H6845-8	SCTV10362502WBH-151	< 0.005	< 0.005	< 0.005	< 0.015
H6845-9	SCTV10362502NBH-3'	< 0.005	< 0.005	< 0.005	< 0.015
H6845-10	SCTV10362502NBH-5'	< 0.005	< 0.005	< 0.005	< 0.015
H6845-11	SCTV10362502NBH-10'	< 0.005	<0.005	< 0.005	< 0.015
H6845-12	SCTV10362502NBH-15'	<0.005	<0.005	<0.005	<0.015
Quality Con	itrol	0.102	0.097	0.100	0.288
True Value	QC	0.100	0.100	0.100	0.300
% Recovery	/	102	97.0	99.7	95.9
Relative Pe	rcent Difference	0.3	5.1	4.3	3,9

METHOD: EPA SW-846 8260

Date

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses. All claims, (needing these for negligence and any other cause whatspewer shall be deemed waived unless made in writing and received by Cardinal within thin; (30) days after completion of the applicable sample. This event after Cardinal be liable for incidental or consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiarias, affiliate or successors arising out of or related to the performance of services harsunder by Cardinals, fograddes of whether such claim is based upon any of the above-stated reasons or otherwise.

PAGE Manager:			000	4		Com O	10 39	3:4	Cheu	P.O. &: Company: Cheu Teraco	0	_		
505,394,3981	Fax F. Sos	394	1-2401	0		Addr	8	# 6	JICY.	1 Saile	1.64		_	_
10:		Cheu	en l	10	1 Daco	0	3					_	_	
1 Harne: /	become duit with	103					素		Zipc			_	_	
1 Location:						3	Phone St	77					_	
or Harrie:	Fradly Shin					FR	Fax 8:					ı	6	
CHIC DIES			П	E	MATRIX		3384	RESERV		SAMPLING	ন	52	2/	
i 			ATER	ER				-				80%	800	,
INAL LAB	Sample LD.	(G)RAB OR (GROUNDWA	SOL	CRUDE OIL	OTHER:	ACID/BASE:	CE/COOL		DATE	TIME	TOH	BTOX	Chlor
STAN	SCTUIDS625005BH-3'	4		×				×		6-25-02	8.40	×	×	×l
-7 50	SCTUICH 25035AH-5'	0		X				X	6	6-25-02	8:55	×	×	× 1
13/2	SCTUIO3625025BH-10	0		×		H		×	6	6-250	9:15	×	×	\times
5.6-	SCHUIOSERASBIN-15"	1	Í	×		+	Ę	<u> ~</u>	5		9:35	×	×	X
5 5-	SCTU1036-350361811-3.	6		×		+	1	×	1	25:02	10:20	ĸ	×	×
20 5	SCTVIDSONSTHURH-S	20		×				X	6	62502	16:35	×	X	X
2	XIII/103434501/1111/10	2		2		H		Y	6	628-02	10:50	×	×	4
2	XTV10343603418H-115	C		-		+	\perp	7	1	6-25-02	11:30	X	×	1. 1
On his court dod Carded to least	espe. Ordad's hably and shoth unbales somely for any a fir majdymen and any other comes whethereses cheef in dea- to fable for haddenful or corresponded descriptor, habilitys will		iii	119	H	13				H	11177	1		
er Reunques	Dyta:		Received By:	*		Í		d i			Phone Res	O.		-1-1
May Bu	Tama:		>								REMARKS		77	7
Yell 0/A	000000	Reg	3	d By: (I	(Lab Sta	5		0				afe	as p	ar phace
belivered By: (Circle One)		-	-	2	V	7	_	×	_					

ariager: Par	70.0				Note to the state of the state
State: Jim Zip:	8823/ Man: Dar	Raflied Balley		_	
SAL 3481 Fax 8: 505: 594	261	100 m			
18: Project Owner: //cuema //cxaco				_	
* Name: Vacuus 103		: Zlpx		_	
	Phone St.	8.			_
har Harris Fendly Blerry	Fax 8:		ín	16	
	MATRIX	PRESERV SAMPLING	13.	. "	
Sample LD.	CONTAMERS ROUNDWATER ASTEWATER DE. RUDE OL. UDGE THER:	E/COOL THER:	TOH 80	BTex &	
	Х	x 6-25-02	12:45 ×		
8	×	1	X 00.	×	
-11 SCAVIO362608NBH - 10 G	×	x 6-25-01	1:30 X	×	
o'	×		2.com X	× ×	
Ardela lillig sel destremission or Agents tel sep des came victores d' in luisted a amount d'ampa, h	11	111	to ded is to		Terms and Conditions bound on its obtaged on all sensors. If dept paid don at the sole of 24% per sensors been the object and all make of sufficience, beduling stammer's from:
ahad: (Digita:	Received By:		Phone Result: Fax Result: REMARKS:	0700	CINO Addi Phone 8: CINO Addi Fax 8:
Inquished By: Date: Date:	Supple Condition Codd Interes	CHECKED BY:	21.		



PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2326 • 101 E. MARLAND • HOBBS. NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 09/30/02 Reporting Date: 10/03/02

Project Number: NOT GIVEN
Project Name: VACUUM UNIT #103

Project Location: BUCKEYE, NM

Sampling Date: 09/30/02

Sample Type: GROUNDWATER Sample Condition: COOL & INTACT

Sample Received By: BC

Analyzed By: AH

LAB NUMBER SAMPLE ID TDS CI (mg/L) (mg/L)

ANALYSIS DA	TE:	10/02/02	10/01/02
H7089-1	WCTVU10393002WM	367	160
Quality Control		NR	940
True Value QC		NR	1000
% Recovery		. NR	94.0
Relative Perce	nt Difference	8.8	6.0

*Std. Methods

METHODS: EPA 600/4-79-02

H7089

10-3-02 Date

4500-CIB*

160.1

PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analyses.

All claims, including those for negligence and any other cause whatsoever shall be deamed waived unless made in writing and received by Cardinal within thirty (30) days after completion of the applicable service. In no event shall Cardinal be liable for incidental or consequential damages, including without limitation, business interruptions, lose of use, or lose of profits incurred by client, its purplicable or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.



PHONE (915) 673-7001 • 2111 BEECHWOOD • ABILENE, TX 79603

PHONE (505) 393-2326 • 101 E. MARLAND • HOBBS, NM 88240

ANALYTICAL RESULTS FOR CHEVRON TEXACO ATTN: RODNEY BAILEY P.O. BOX 3109 MIDLAND, TX 79702 FAX TO:

Receiving Date: 09/30/02 Reporting Date: 10/03/02 Project Number: NOT GIVEN Project Name: VACUUM UNIT #103 Project Location: BUCKEYE

Sampling Date: 09/30/02 Sample Type: GROUNDWATER Sample Condition: COOL & INTACT Sample Received By: BC

Analyzed By: BC


ETHYL TOTAL BENZENE TOLUENE BENZENE **XYLENES** LAB NUMBER SAMPLE ID (mg/L) (mg/L) (mg/L) (mg/L)

ANALYSIS	DATE	09/30/02	09/30/02	09/30/02	09/30/02
H7089-1	WCTVU10393002WM	<0.002	<0.002	<0.002	<0.006
	•				
Quality Con	trol	0.103	0.103	0.108	0.310
True Value		0.100	0.100	0.100	0.300
% Recovery	,	103	103	108	103
Relative Pe	rcent Difference	0.3	0.2	0.7	0.8

METHOD: EPA SW-846 8260


PLEASE NOTE: Liability and Damages. Cardinal's liability and client's exclusive remedy for any claim arising, whether based in contract or tort, shall be limited to the amount paid by client for analysiss.

All claims, including those for negligence and any other cause whatsoever shall be deemed waived unless made in writing and received by Cardinal within thiny (30) days after completion of the applicable service. One consequential damages, including, without limitation, business interruptions, loss of use, or loss of profits incurred by client, its subsidiaries, affiliates or successors arising out of or related to the performance of services hereunder by Cardinal, regardless of whether such claim is based upon any of the above-stated reasons or otherwise.



Attachment IV: New Mexico Office of the State Engineer Well Reports

New Mexico Office of the State Engineer		Page 1 of
	fice of the State Er	
Township: 178 Range: 34E	Sections: 36	
NAD27 X: Y:	Zone:	Search Radius:
County: Basin:	Nun	nber: Suffix:
Owner Name: (First) (Las	(* All	C Non-Domestic C Domestic
Well / Surface Data Report	Avg Dep	oth to Water Report
	r Column Report	
Clear Form	WATERS Menu	Help
ttp://seowaters.ose.state.nm.us/awdProd/awd.h	ntml?email_address	=enviplus1@aol.com&t 9/28/200



New Mexico Office of the Sta	te Engineer					Page 1 of 1
		Office of the S				
Township: 17S	Range: 35E	Sections:	31	-		
NAD27 X:	Y:	Zone:	•	Search Ra	dius:	
County:	Basin:	<u>*</u>	Numl	per:	Suffix:	
Owner Name: (First)	(L	ast)		○ Non-Do	omestic C	Domestic
Well / Su	rface Data Repor	t A	Ava Dept	h to Water Re	eport	
		ater Column Rep				
	Clear Form	WATERS	Menu	Help		
Record Count: 2						
ttp://seowaters.ose.state.nm.						0.00

	te Engineer					Page 1 o
		Office of the Seports and Do				
Township: 18S	Range: 35E	Sections:	5,6,7,8			
NAD27 X:	Y:	Zone:	$\overline{}$	Search R	adius:	
County: B	asin:	_	Numb	er:	- Suffi	x:
Owner Name: (First)	(I	(• All		○ Non-D	omestic	C Domestic
Well / Surf	face Data Repor			to Water R	eport	
	Clear Form	eter Column Rep WATERS N		Help		
18S 35E 06 18S 35E 07 Record Count: 20		5 8	60 75	95	89 85	


Attachment V: Site Metrics and Information Form

ChevronTexaco Site Information and Metrics Incident Date and NMOCD Notified? June 17, 2002						
	ITE: Vacuum Unit Well #103 Assigned Site Reference #:					
Company:	ChevronTexaco					
Street Addre	ess: 15 Smith Roa	d 79705				
Mailing Add	Iress: P.O. Box 11	50				
City, State,	Zip: Midland,	Гехаѕ 7970	2			
	ive: Rodney Bailey					
Representati	ive Telephone: 9	15.238.427	74 FAX: 915.687.71	10		
Telephone:	Office 915.687.7	7251				
	e released (bbls):		Recovered (bbls): ?			
>25 bbls: N			m C-141 within 15 days. (Also applies to una			
T 1 0 111			s (Also applies to unauthorized releases of 50-5	500 mcf Natural Gas)		
Leak, Spill,	or Pit (LSP) Name:	Vacuu	m Unit Well #103			
Source of co	ontamination: Well	head stuff	ing box leak			
			New Mexico State Land (1	leased by Giles Lee)		
	ions ~180' x 12					
LSP Area:	16,612 ft					
	Reference Point (R					
	stance and direction					
Latitude:	32°46'43.967" 103°29'42.268"V	N				
Longitude:	103°29′42.268″V	<u>/</u>				
	ove mean sea level:	3975	amsl			
	outh Section Line					
	est Section Line					
Location- U		of the NW	1/4	Unit Letter: F		
Location- Se						
	ownship: 18S					
Location- R	ange: 35E					
G C	1 1 11 1000					
	er body within 1000					
	er body within 1000					
	ater wells within 10					
Domestic water wells within 1000' radius of site: Agricultural water wells within 1000' radius of site: Windmill 203' west						
				3' west		
	water wells within					
	r supply wells withi					
	r supply wells withi					
	land surface to gro		(DG) ~89'bgs			
Depth of co	ntamination (DC) -					
Depth to ground water (DG - DC = DtGW) -						
1. Ground Water 2. Wellhead Protection Area 3. Distance to Surface Water Body						
If Depth to GW	<50 feet: <i>20 points</i>	If <1000' from	n water source, or;<200' from	<200 horizontal feet: 20 points		
	50 to 99 feet: <i>10 points</i>		tic water source: 20 points	200-100 horizontal feet: <i>10 points</i>		
If \1000' from water source or \200' from						
If Depth to GW >100 feet: 0 points private domestic water source: 0 points >1000 horizontal feet: 0 points						
Ground water Score = 10 Wellhead Protection Area Score = 20 Surface Water Score = 0						
	$\frac{1}{(2+3)} = 30$		** ***	J		
Total Site Ranking Score and Acceptable Concentrations						
Parameter	>19 (surface to 89'bgs		10-19 (NA)	0-9		
Benzene ¹ 10 ppm 10 ppm						
BTEX ¹	50 ppm		50 ppm	50 ppm		
TPH						
		nav be substitut	**	, , , , , , , , , , , , , , , , , , ,		
¹ 100 ppm field VOC headspace measurement may be substituted for lab analysis						

Attachment VI: Chevron Digging Permit

CHEVRON U.S.A. INC.	
WEST ASSET TEAM / DIGGING PERMIT	
PERMIT FOR DIGGING, TRENCHING, OR EXCAVATING WITH ANY TYPE OF POWER	
TOOL OR MECHANIZED EQUIPMENT	ED
Supervisor: Radday Battey Eddie 5 Harpe Date Authorized: 6-17-02 Field Location: Vacuum unif well 103	
Type Work: Back dragging & Exchuating Contaminated soil	
Specific Restrictions:	
Mechanical digging equipment should not be used within 12" of an underground line.	-
PERMIT REQUIREMENTS:	
Basic Precautions:	
Has an underground line map been reviewed? Piping plan must be used when work is performed within a facility. Yes No N/A Piping plan must be used when work is performed within a facility.	
2. Has the person operating the digging equipment isolated the energy source	
and performed LOTO?	-
3. Have digging operations been discussed w/ an employee familiar with the area?	
4. Has a metal detecting line finder been used in the area to be excavated?	11 23
5. Are there any line markers near the excavation area?	
6. Is there a visible right-of-way where the digging will be done?	
7. Are there special concerns with any equipment, i.e., tank batteries, satellites, wells, buildings, power poles, etc., within 150' of the excavation area?	
8. Are there special concerns with overhead power lines within 100' of the excavation?	2
9. Will digging exceed 16" in depth? If yes, see Special Precaution below.	
10. Have you discussed the importance of not creating a spill and what to do if one occurs?	+
If contact with a line results in a release of oil and or produced water contact Chevron Representative at Emergency Phone # listed below immediately.	21
Special Precaution: If work is to be performed within a 3 rd party right-of-way, location near a populated area, designated area, or if undergrutilities are in the vicinity then 1-800-545-6005 (TX) or 1-800 321-2537 (NM) (One-Call Notification) MUST be made 48 in advance of any excavation work.	iours
1. Has One-Call Notification been called? YES Date of call: 6-17-02 Time of call: 1/1434	m
2. Permitted start date and time: 6-19-02 21:45 p. Estimated duration of job: 6-19-02	
3. One-Call Notification confirmation # 2002 3544 250565	
THIS PERMIT MUST BE COMPLETED PRIOR TO MECHANICAL DIGGING AND AVAILABLE FOR REVIEW AT THE WORKSITE. If contact is made with an underground line or cable, this permit will be attached to the accident report, otherwise, it should be attached to the work ticket.	
Rodry Bailey Chevroid Representative / Emergency Phone # Contractor Date Contractor	02
Chevron Representative / Emergency Phone # Contractor Date	- 12
REVISED 02/05/01	

CHEVRON U.S.A. INC.	Chevron
WEST ASSET TEAM / DIGGING PERMIT	
PERMIT FOR DIGGING, TRENCHING, OR EXCAVATING WITH ANY TYPE (OF POWEREI
TOOL OR MECHANIZED EQUIPMENT	
Supervisor: Rating Bartey Eddie 5 Harper Date Authorized: 6-17-03	
Field Location: Vacuum unit well 103 Type Work: Back dragging + Exchunting Continuing Isl 507	
Sacrific Barrier Contaminated Son	· <
Specific Restrictions:Other:	1000
Machanical discission	
Mechanical digging equipment should not be used within 12" of an underground line.	
PERMIT REQUIREMENTS:	
Basic Precautions: 1. Has an underground line map been reviewed? Yes	No N/A
Piping plan must be used when work is performed within a facility.	2.9
2. Has the person operating the digging equipment isolated the energy source	
and performed LOTO? If electrical energy source cannot be accurately located, miles already.	4
annue electrical contractor with electric line locating equipment	-
3. Have digging operations been discussed w/ an employee familiar with the area?	
4. Has a metal detecting line finder been used in the area to be excavated?	
5. Are there any line markers near the excavation area?	
6. Is there a visible right-of-way where the digging will be done?	
7. Are there excelled a service and while the digging will be done?	
7. Are there special concerns with any equipment, i.e., tank batteries, satellites, wells, buildings, power poles, etc., within 150' of the excavation area?	
3. Are there special concerns with overhead power lines within 100' of the excavation?	
9. Will digging exceed 16" in depth?	
If yes, see Special Precaution below.	
0. Have you discussed the importance of not creating a spill and what to do if one occurs?	X
f contact with a line results in a release of oil and or produced water contact Chevron Representative at Emergency Phone # listed below	
Special Precaution:	immediately.
f work is to be performed within a 2rd	
tilities are in the vicinity then 1-800-545-6005 (TX) or 1-800 321-2537 (NM) (One-Call Notification) MUST	or if undergroun
advance of any excavation work.	be made 48 hour
Has One-Call Notification been called? Yss Date of call: 6-17-02 Time of call:	. /
Permitted start date and time: / - 19	11.45 Am
Permitted start date and time: 6-19-02 //: 45 am Estimated duration of job:	
One-Call Notification confirmation # 2002 250 416	
HIS PERMIT MUST BE COMPLETED PRIOR TO MECHANICAL DIGGING AND AVAILABLE FOR EVIEW AT THE WORKSITE.	
EVIEW AT THE WORKSITE.	
contact is made with an underground line or cable, this permit will be attached to the accident report, otherwise, should be attached to the work ticket.	
Roder Bailer Devror Representative / Emergency Phone # Contractor	
Contractor	Date



APPENDIX 7.A, Annual Inspection Certification Form

Sequence of Applying Energy Controls:

Indicate if the sequence of applying energy controls was followed by checking the appropriate line.

1. Energy isolation was applied only by an authorized employee.

2. All affected employees were notified.

Equipment was prepared for shut down (types and level/quantity of energy and hazards involved).

4. Equipment was properly shut down using correct operating controls.

Equipment was isolated (operate all energy devices to assure that the equipment is isolated from the energy source).

6. Lockout and tagout devices were applied.

Provision was made for control of stored energy (stop all moving parts, install ground wires, relieve trapped pressure, release tension springs, block hydraulic parts, bleed lines down, blind or blank flanges, watch for stored energy to reaccumulate).

8. Isolation of equipment was verified (clear of personnel, unnecessary tools and equipment).

Y 9. Work was performed while watching for any work operations that could reactivate the equipment.

Y 10. When work was finished, lockout/tagout device was removed.

	lace for	Signature of Inspector	Mark Harb
	control procedures in p.s.	Comments	10 11 II
APPENDIX 7.B (cont.) Annual Inspection Log Book Example	ie Annual Inspection Performance of the energy control procedures in place for equipment involved in lockout/tagout operations.	Name of Inspector	Kallus Stratos
APPE Annual Inspe	sord of the Annual Inspectio yees and equipment involve	Equipment on which Energy Control Applied	Chaler Ve wall 103 Chaler Ve wall 103 Chaler Ve wall 103
72	The following is a record of the authorized employees and	Authorized Employee(s)	Church Makes
15		Date of Inspection	20/31/2

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 2040 South Pacheco Santa Fe, NM 87505 Form C-141 Revised March 17, 1999

Submit 2 Copies to appropriate District Office in accordance with Rule 116 on back side of form

Releas	e Notification a	and Correcti	ve Action			
	OPER	RATOR	Ġ	Initial Repo	ort 🔲 Final	Report
Name of Company Cheurow Texaco		Contact	Podwey &	0 %		
Address 15 Smith Rd. Midland tx 75	9702	Telephone No.	5-687-	72		
Facility Name CONTRAL VACUUM UNIT # 18	(* 1) () * 600 () () () ()	Facility Type	Producia	19		
Surface Owner	Mineral Owner	AP1#300	25030916	Lease	No.	
	LOCATION	OF RELEASE	1			
Unit Letter Section Township Range 1				West Line	County	
	NATIDEO	F RELEASE				
Type of Release Roduce water & Crude		Volume of Releas	40iL	7 was	Recovered 3 01	
Source of Release Stuffing Box Was Immediate Notice Given?		Date and Hour of	2		d Hour of Discov	ery
	No Not Required		i: Transjuljukaro	1. 1. 751 1.14		
By Whom?		Date and Hour			2324252	6273
Was a Watercourse Reached?	No	If YES, Volume I	mpacting the Wa	tercourse./		A
If a Watercourse was Impacted, Describe Fully.*				18.17.978	Hobbs E	0
Describe Cause of Problem and Remedial Action One fort of Soil was R Describe Area Affected and Cleanup Action Take	eplaced. Rep	howled	to Texaco	lamp	Follow-	8135
AFFERTED AROA 16.612	U. Go	wald while	896	1		
I hereby certify that the information given above and regulations all operators are required to repor- endanger public health or the environment. The a of liability should their operations have failed to a water, human health or the environment. In addit compliance with any other federal, state, or local	is true and complete to the tand/or file certain releast complete to the tand/or file certain releast complete to the tand/or file certain certai	ne best of my knowlese notifications and port by the NMOCE of the contains of the contains the best of	edge and understand perform corrective of marked as "Fination that pose	re actions for al Report" do a threat to gr	releases which n es not relieve the ound water, surfa	operator ce
Signature: Rodwey Bailey Printed Name:	ed motor	Approved by District Supervis	CONSERV	ATION I	DIVISION	
Title: HE.S Chroman		Approval Date:	Jr.	Expiration	on Date:	
Date: 6-24-02 Phone:		Conditions of Ap	oproval:	Expusue	Attached	
* Attach Additional Sheets If Necessary						

District I
1625 N. French Dr., Hobbs, NM 88240
Phone: (575) 393-6161 Fax: (575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. **Santa Fe, NM 87505**

CONDITIONS

Action 37189

CONDITIONS

Operator:	OGRID:
CHEVRON U S A INC	4323
6301 Deauville Blvd	Action Number:
Midland, TX 79706	37189
	Action Type:
	[C-141] Release Corrective Action (C-141)

CONDITIONS

Created By	Condition	Condition Date
bbillings	None	8/26/2021