

**PANTECHS LABORATORIES, INC.**

*Leaders in Petroleum Analytical Services*  
*www.pantechs.com*

# Analytical Report

3/24/2022

|                     |                         |                         |                 |
|---------------------|-------------------------|-------------------------|-----------------|
| <b>Customer:</b>    | Occidental Permian Ltd. | <b>Order:</b>           | 300-3024        |
| <b>Location:</b>    | North Hobbs RCF         | <b>Received:</b>        | 3/21/2022       |
| <b>Description:</b> | Monthly Collection      | <b>Primary Contact:</b> | Richard Sanders |

**REPORT DISTRIBUTION:**

Brian Carlisle , Casey Morris , Chauncia Farayola , Chip Mitchell , Chris Frei , Dillon Hart , Erica Zuniga , Greg Vencil , James King , Jason Sisson , Jimmy Dobson , John Dorow , Judy Rich , Justin Saxon , Kenley Powell , Kevin Mulkern , Richard Sanders

All data reported in this Analytical Report is in compliance with the test method(s) performed as of the date noted above. The validity and integrity of this report will remain intact as long as it is accompanied by this page and reproduced in full. Any datafile (e.g. txt, csv, etc.) produced which is associated with the results in this report shall be considered for convenience only and does not supersede this report as the official test results. We reserve the right to return to you any unused samples received if we consider so necessary (e.g. samples identified as hazardous waste).

We appreciate you choosing Pantechs Laboratories. If you have any questions concerning this report, please feel free to contact us at any time.

**Pantechs Laboratories, Inc.****Order: 300-3024 Order Date: 3/21/2022****Order Description: North Hobbs RCF, Monthly Collection****Sample List**

| Fluid  | Operator                | Location        | Site              | Sample Point          | Date      | Time     |
|--------|-------------------------|-----------------|-------------------|-----------------------|-----------|----------|
| CO2    | Occidental Permian Ltd. | North Hobbs RCF | 2098              | CO2 Discharge         | 3/21/2022 | 12:58 PM |
| CO2    | Occidental Permian Ltd. | North Hobbs RCF | 2099              | CO2 Discharge         | 3/21/2022 | 12:48 PM |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | 1013              | #1 Slug Catcher Inlet | 3/21/2022 | 1:30 PM  |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | 10002             | NGL Plant Inlet       | 3/21/2022 | 1:13 PM  |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | 21013             | #2 Slug Catcher Inlet |           |          |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | 21023             | #3 Slug Catcher Inlet | 3/21/2022 | 1:34 PM  |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | DEX PRO           | Inlet                 | 3/21/2022 | 1:23 PM  |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | DEX PRO           | Outlet                |           |          |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | Reflux Stabilizer | Sample Valve          | 3/21/2022 | 1:07 PM  |
| Gas    | Occidental Permian Ltd. | North Hobbs RCF | Surge Tank        | Propane Vapor         | 3/21/2022 | 1:38 PM  |
| Liquid | Occidental Permian Ltd. | North Hobbs RCF | DEX PRO           | Gasoline              |           |          |
| Liquid | Occidental Permian Ltd. | North Hobbs RCF | NGL Storage       | NGL                   | 3/21/2022 | 1:03 PM  |
| Liquid | Occidental Permian Ltd. | North Hobbs RCF | Stabilizer        | Bottoms               | 3/21/2022 | 1:09 PM  |
| Liquid | Occidental Permian Ltd. | North Hobbs RCF | Surge Tank        | Propane Liquid        | 3/21/2022 | 1:42 PM  |

**No Sample List**

| Operator                | Location        | Site    | Sample Point          | Comment                   |
|-------------------------|-----------------|---------|-----------------------|---------------------------|
| Occidental Permian Ltd. | North Hobbs RCF | 21013   | #2 Slug Catcher Inlet | No Flow at Sample Point   |
| Occidental Permian Ltd. | North Hobbs RCF | DEX PRO | Gasoline              | Sample Point All Water    |
| Occidental Permian Ltd. | North Hobbs RCF | DEX PRO | Outlet                | Sample Point Inaccessible |

Pantechs Laboratories, Inc. - Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 1623 psig   |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | 2098                    | Atm Temp         | 62 F        |
| Site Type    | Meter                   | Collection Date  | 03/21/2022  |
| Sample Point | CO2 Discharge           | Collection Time  | 12:58 PM    |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     | 2098                    | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | CO2                     | Container(s)     | YZ28194     |

## GPA 2177 CO2 Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | VOL%    | WT%     |
|------------------|---------|---------|---------|---------|
| NITROGEN         | N2      | 1.897   | 1.205   | 1.262   |
| CARBON DIOXIDE   | CO2     | 88.646  | 87.500  | 92.676  |
| HYDROGEN SULFIDE | H2S     | 0.662   | 0.516   | 0.536   |
| METHANE          | C1      | 5.873   | 5.765   | 2.238   |
| ETHANE           | C2      | 0.868   | 1.344   | 0.620   |
| PROPANE          | C3      | 1.114   | 1.778   | 1.167   |
| I-BUTANE         | iC4     | 0.174   | 0.330   | 0.240   |
| N-BUTANE         | nC4     | 0.365   | 0.666   | 0.504   |
| I-PENTANE        | iC5     | 0.132   | 0.280   | 0.226   |
| N-PENTANE        | nC5     | 0.109   | 0.229   | 0.187   |
| HEXANES PLUS     | C6+     | 0.160   | 0.388   | 0.344   |
| TOTALS:          |         | 100.000 | 100.000 | 100.000 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

## Liquid Phase Properties

| SCF/Gal (Ideal) | SCF/Gal (Real) | Mol Weight | Relative Density (60/60) | Vapor Pressure 100F, psia |
|-----------------|----------------|------------|--------------------------|---------------------------|
| 58.229          | 57.904         | 42.096     | 0.772                    | 1,463.1                   |

## Vapor Phase Properties

| ITEM            | BTU/CF | Specific Gr. | Z Factor |
|-----------------|--------|--------------|----------|
| DRY             | 142.42 | 1.461        | 0.994    |
| WATER SATURATED | 140.88 | 1.447        | 0.994    |

## Onsite Testing by Stain Tube

| METHOD  | TYPE | MOL%   | GRAINS/100 | PPMV    |
|---------|------|--------|------------|---------|
| GPA2377 | H2S  | 0.6621 | 420.42     | 6,684.7 |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 1627 psig   |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | 2099                    | Atm Temp         | 63 F        |
| Site Type    | Meter                   | Collection Date  | 03/21/2022  |
| Sample Point | CO2 Discharge           | Collection Time  | 12:48 PM    |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     | 2099                    | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | CO2                     | Container(s)     | YZ12639     |

## GPA 2177 CO2 Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | VOL%    | WT%     |
|------------------|---------|---------|---------|---------|
| NITROGEN         | N2      | 1.678   | 1.073   | 1.129   |
| CARBON DIOXIDE   | CO2     | 87.219  | 86.668  | 92.210  |
| HYDROGEN SULFIDE | H2S     | 1.880   | 1.477   | 1.539   |
| METHANE          | C1      | 6.693   | 6.614   | 2.579   |
| ETHANE           | C2      | 1.001   | 1.561   | 0.723   |
| PROPANE          | C3      | 1.132   | 1.819   | 1.199   |
| I-BUTANE         | iC4     | 0.106   | 0.202   | 0.148   |
| N-BUTANE         | nC4     | 0.164   | 0.301   | 0.229   |
| I-PENTANE        | iC5     | 0.041   | 0.088   | 0.071   |
| N-PENTANE        | nC5     | 0.033   | 0.070   | 0.057   |
| HEXANES PLUS     | C6+     | 0.053   | 0.129   | 0.116   |
| TOTALS:          |         | 100.000 | 100.000 | 100.000 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

## Liquid Phase Properties

| SCF/Gal (Ideal) | SCF/Gal (Real) | Mol Weight | Relative Density (60/60) | Vapor Pressure 100F, psia |
|-----------------|----------------|------------|--------------------------|---------------------------|
| 58.620          | 58.298         | 41.628     | 0.769                    | 1,481.5                   |

## Vapor Phase Properties

| ITEM            | BTU/CF | Specific Gr. | Z Factor |
|-----------------|--------|--------------|----------|
| DRY             | 140.51 | 1.445        | 0.995    |
| WATER SATURATED | 138.99 | 1.431        | 0.994    |

## Onsite Testing by Stain Tube

| METHOD  | TYPE | MOL%   | GRAINS/100 | PPMV     |
|---------|------|--------|------------|----------|
| GPA2377 | H2S  | 1.8795 | 1,193.48   | 18,976.3 |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 299 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | 1013                    | Atm Temp         | 62 F        |
| Site Type    | Meter                   | Collection Date  | 03/21/2022  |
| Sample Point | #1 Slug Catcher Inlet   | Collection Time  | 1:30 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     | 1013                    | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Gas                     | Container(s)     | PL1954      |

## GPA 2261 Gas Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | WT%     | GPM    |
|------------------|---------|---------|---------|--------|
| NITROGEN         | N2      | 1.576   | 1.049   | 0.173  |
| CARBON DIOXIDE   | CO2     | 87.314  | 91.310  | 14.886 |
| HYDROGEN SULFIDE | H2S     | 0.784   | 0.635   | 0.106  |
| METHANE          | C1      | 6.495   | 2.476   | 1.101  |
| ETHANE           | C2      | 1.005   | 0.718   | 0.269  |
| PROPANE          | C3      | 1.443   | 1.512   | 0.398  |
| I-BUTANE         | iC4     | 0.227   | 0.314   | 0.074  |
| N-BUTANE         | nC4     | 0.494   | 0.682   | 0.156  |
| I-PENTANE        | iC5     | 0.196   | 0.336   | 0.072  |
| N-PENTANE        | nC5     | 0.165   | 0.283   | 0.060  |
| HEXANES PLUS     | C6+     | 0.301   | 0.685   | 0.129  |
| TOTALS:          |         | 100.000 | 100.000 | 17.424 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

| LIQUID YIELD   | C2+   | C3+   | C4+   | C5+   | 26# Liquid | 10# Liquid |
|----------------|-------|-------|-------|-------|------------|------------|
| GAL/MSCF (GPM) | 1.158 | 0.889 | 0.491 | 0.261 | 0.401      | 0.245      |

| CALCULATED PROPERTIES | BTU/CF | Specific Gr. | Z Factor | Mol Weight | Wobbe IDX |
|-----------------------|--------|--------------|----------|------------|-----------|
| DRY                   | 178.86 | 1.461        | 0.994    | 42.084     | 147.98    |
| WATER SATURATED       | 176.70 | 1.447        | 0.994    | 41.349     |           |

## Onsite Testing by Stain Tube

| METHOD  | TYPE | MOL%   | GRAINS/100 | PPMV    |
|---------|------|--------|------------|---------|
| GPA2377 | H2S  | 0.7835 | 497.50     | 7,910.3 |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 293 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | 10002                   | Atm Temp         | 62 F        |
| Site Type    | Meter                   | Collection Date  | 03/21/2022  |
| Sample Point | NGL Plant Inlet         | Collection Time  | 1:13 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     | 10002                   | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Gas                     | Container(s)     | PL1904      |

## GPA 2261 Gas Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | WT%     | GPM    |
|------------------|---------|---------|---------|--------|
| NITROGEN         | N2      | 1.752   | 1.167   | 0.192  |
| CARBON DIOXIDE   | CO2     | 87.424  | 91.518  | 14.904 |
| HYDROGEN SULFIDE | H2S     | 0.662   | 0.537   | 0.089  |
| METHANE          | C1      | 6.581   | 2.511   | 1.116  |
| ETHANE           | C2      | 0.944   | 0.675   | 0.253  |
| PROPANE          | C3      | 1.277   | 1.339   | 0.352  |
| I-BUTANE         | iC4     | 0.227   | 0.314   | 0.074  |
| N-BUTANE         | nC4     | 0.492   | 0.680   | 0.155  |
| I-PENTANE        | iC5     | 0.194   | 0.333   | 0.071  |
| N-PENTANE        | nC5     | 0.164   | 0.281   | 0.059  |
| HEXANES PLUS     | C6+     | 0.283   | 0.645   | 0.122  |
| TOTALS:          |         | 100.000 | 100.000 | 17.387 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

| LIQUID YIELD   | C2+   | C3+   | C4+   | C5+   | 26# Liquid | 10# Liquid |
|----------------|-------|-------|-------|-------|------------|------------|
| GAL/MSCF (GPM) | 1.086 | 0.833 | 0.481 | 0.252 | 0.386      | 0.232      |

| CALCULATED PROPERTIES | BTU/CF | Specific Gr. | Z Factor | Mol Weight | Wobbe IDX |
|-----------------------|--------|--------------|----------|------------|-----------|
| DRY                   | 172.55 | 1.459        | 0.994    | 42.042     | 142.83    |
| WATER SATURATED       | 170.49 | 1.445        | 0.994    | 41.307     |           |

## Onsite Testing by Stain Tube

| METHOD  | TYPE | MOL%   | GRAINS/100 | PPMV    |
|---------|------|--------|------------|---------|
| GPA2377 | H2S  | 0.6621 | 420.42     | 6,684.7 |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |            |
|--------------|-------------------------|------------------|------------|
| Operator     | Occidental Permian Ltd. | Pressure         | N/A        |
| Location     | North Hobbs RCF         | Sample Temp      | N/A        |
| Site         | 21013                   | Atm Temp         | N/A        |
| Site Type    | Meter                   | Collection Date  |            |
| Sample Point | #2 Slug Catcher Inlet   | Collection Time  |            |
| Spot/Comp    | Spot                    | Collection By    |            |
| Meter ID     | 21013                   | Pressure Base    | 14.650 psi |
| Purchaser    |                         | Temperature Base | 60 F       |
| Fluid        | Gas                     | Container(s)     |            |

## No Sample

| Employee    | Comment                 |
|-------------|-------------------------|
| Cody Carson | No Flow at Sample Point |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 299 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | 21023                   | Atm Temp         | 62 F        |
| Site Type    | Meter                   | Collection Date  | 03/21/2022  |
| Sample Point | #3 Slug Catcher Inlet   | Collection Time  | 1:34 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     | 21023                   | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Gas                     | Container(s)     | PL1037      |

## GPA 2261 Gas Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | WT%     | GPM    |
|------------------|---------|---------|---------|--------|
| NITROGEN         | N2      | 1.772   | 1.164   | 0.194  |
| CARBON DIOXIDE   | CO2     | 90.387  | 93.241  | 15.410 |
| HYDROGEN SULFIDE | H2S     | 0.552   | 0.441   | 0.074  |
| METHANE          | C1      | 4.411   | 1.659   | 0.748  |
| ETHANE           | C2      | 0.692   | 0.488   | 0.185  |
| PROPANE          | C3      | 0.984   | 1.017   | 0.271  |
| I-BUTANE         | iC4     | 0.194   | 0.264   | 0.063  |
| N-BUTANE         | nC4     | 0.424   | 0.578   | 0.134  |
| I-PENTANE        | iC5     | 0.160   | 0.271   | 0.059  |
| N-PENTANE        | nC5     | 0.136   | 0.230   | 0.049  |
| HEXANES PLUS     | C6+     | 0.288   | 0.647   | 0.124  |
| TOTALS:          |         | 100.000 | 100.000 | 17.311 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

| LIQUID YIELD   | C2+   | C3+   | C4+   | C5+   | 26# Liquid | 10# Liquid |
|----------------|-------|-------|-------|-------|------------|------------|
| GAL/MSCF (GPM) | 0.885 | 0.700 | 0.429 | 0.232 | 0.360      | 0.231      |

| CALCULATED PROPERTIES | BTU/CF | Specific Gr. | Z Factor | Mol Weight | Wobbe IDX |
|-----------------------|--------|--------------|----------|------------|-----------|
| DRY                   | 132.49 | 1.481        | 0.994    | 42.662     | 108.87    |
| WATER SATURATED       | 131.11 | 1.467        | 0.994    | 41.917     |           |

## Onsite Testing by Stain Tube

| METHOD  | TYPE | MOL%   | GRAINS/100 | PPMV    |
|---------|------|--------|------------|---------|
| GPA2377 | H2S  | 0.5517 | 350.35     | 5,570.6 |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 296 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | DEX PRO                 | Atm Temp         | 62 F        |
| Site Type    | Station                 | Collection Date  | 03/21/2022  |
| Sample Point | Inlet                   | Collection Time  | 1:23 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     |                         | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Gas                     | Container(s)     | PL2106      |

## GPA 2261 Gas Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | WT%     | GPM    |
|------------------|---------|---------|---------|--------|
| NITROGEN         | N2      | 1.596   | 1.051   | 0.175  |
| CARBON DIOXIDE   | CO2     | 89.906  | 93.000  | 15.328 |
| HYDROGEN SULFIDE | H2S     | 0.552   | 0.442   | 0.074  |
| METHANE          | C1      | 4.900   | 1.848   | 0.831  |
| ETHANE           | C2      | 0.751   | 0.531   | 0.201  |
| PROPANE          | C3      | 1.058   | 1.097   | 0.292  |
| I-BUTANE         | iC4     | 0.204   | 0.279   | 0.067  |
| N-BUTANE         | nC4     | 0.447   | 0.611   | 0.141  |
| I-PENTANE        | iC5     | 0.173   | 0.293   | 0.063  |
| N-PENTANE        | nC5     | 0.147   | 0.249   | 0.053  |
| HEXANES PLUS     | C6+     | 0.266   | 0.599   | 0.114  |
| TOTALS:          |         | 100.000 | 100.000 | 17.339 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

| LIQUID YIELD   | C2+   | C3+   | C4+   | C5+   | 26# Liquid | 10# Liquid |
|----------------|-------|-------|-------|-------|------------|------------|
| GAL/MSCF (GPM) | 0.931 | 0.730 | 0.438 | 0.230 | 0.354      | 0.216      |

| CALCULATED PROPERTIES | BTU/CF | Specific Gr. | Z Factor | Mol Weight | Wobbe IDX |
|-----------------------|--------|--------------|----------|------------|-----------|
| DRY                   | 141.24 | 1.477        | 0.994    | 42.546     | 116.22    |
| WATER SATURATED       | 139.71 | 1.463        | 0.994    | 41.802     |           |

## Onsite Testing by Stain Tube

| METHOD  | TYPE | MOL%   | GRAINS/100 | PPMV    |
|---------|------|--------|------------|---------|
| GPA2377 | H2S  | 0.5517 | 350.35     | 5,570.6 |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |            |
|--------------|-------------------------|------------------|------------|
| Operator     | Occidental Permian Ltd. | Pressure         | N/A        |
| Location     | North Hobbs RCF         | Sample Temp      | N/A        |
| Site         | DEX PRO                 | Atm Temp         | N/A        |
| Site Type    | Station                 | Collection Date  |            |
| Sample Point | Outlet                  | Collection Time  |            |
| Spot/Comp    | Spot                    | Collection By    |            |
| Meter ID     |                         | Pressure Base    | 14.650 psi |
| Purchaser    |                         | Temperature Base | 60 F       |
| Fluid        | Gas                     | Container(s)     |            |

## No Sample

| Employee    | Comment                   |
|-------------|---------------------------|
| Cody Carson | Sample Point Inaccessible |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 238 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | Reflux Stabilizer       | Atm Temp         | 64 F        |
| Site Type    | Station                 | Collection Date  | 03/21/2022  |
| Sample Point | Sample Valve            | Collection Time  | 1:07 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     |                         | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Gas                     | Container(s)     | PL1921      |

## GPA 2261 Gas Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | WT%     | GPM    |
|------------------|---------|---------|---------|--------|
| NITROGEN         | N2      | 1.773   | 1.191   | 0.194  |
| CARBON DIOXIDE   | CO2     | 89.236  | 94.144  | 15.208 |
| HYDROGEN SULFIDE | H2S     | 0.000   | 0.000   | 0.000  |
| METHANE          | C1      | 6.797   | 2.614   | 1.152  |
| ETHANE           | C2      | 0.974   | 0.702   | 0.260  |
| PROPANE          | C3      | 1.051   | 1.111   | 0.290  |
| I-BUTANE         | iC4     | 0.085   | 0.118   | 0.028  |
| N-BUTANE         | nC4     | 0.080   | 0.111   | 0.025  |
| I-PENTANE        | iC5     | 0.000   | 0.000   | 0.000  |
| N-PENTANE        | nC5     | 0.000   | 0.000   | 0.000  |
| HEXANES PLUS     | C6+     | 0.004   | 0.009   | 0.002  |
| TOTALS:          |         | 100.000 | 100.000 | 17.159 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

| LIQUID YIELD   | C2+   | C3+   | C4+   | C5+   | 26# Liquid | 10# Liquid |
|----------------|-------|-------|-------|-------|------------|------------|
| GAL/MSCF (GPM) | 0.605 | 0.345 | 0.055 | 0.002 | 0.003      | 0.002      |

| CALCULATED PROPERTIES | BTU/CF | Specific Gr. | Z Factor | Mol Weight | Wobbe IDX |
|-----------------------|--------|--------------|----------|------------|-----------|
| DRY                   | 118.18 | 1.448        | 0.995    | 41.716     | 98.22     |
| WATER SATURATED       | 117.05 | 1.434        | 0.994    | 40.987     |           |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 175 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | Surge Tank              | Atm Temp         | 62 F        |
| Site Type    | Tank                    | Collection Date  | 03/21/2022  |
| Sample Point | Propane Vapor           | Collection Time  | 1:38 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     |                         | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Gas                     | Container(s)     | PL2227      |

## GPA 2261 Gas Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | WT%     | GPM    |
|------------------|---------|---------|---------|--------|
| NITROGEN         | N2      | 9.123   | 6.641   | 1.007  |
| CARBON DIOXIDE   | CO2     | 0.804   | 0.919   | 0.138  |
| HYDROGEN SULFIDE | H2S     | 0.000   | 0.000   | 0.000  |
| METHANE          | C1      | 1.253   | 0.522   | 0.214  |
| ETHANE           | C2      | 27.084  | 21.164  | 7.291  |
| PROPANE          | C3      | 61.716  | 70.722  | 17.116 |
| I-BUTANE         | iC4     | 0.016   | 0.024   | 0.005  |
| N-BUTANE         | nC4     | 0.002   | 0.003   | 0.001  |
| I-PENTANE        | iC5     | 0.000   | 0.000   | 0.000  |
| N-PENTANE        | nC5     | 0.000   | 0.000   | 0.000  |
| HEXANES PLUS     | C6+     | 0.002   | 0.005   | 0.001  |
| TOTALS:          |         | 100.000 | 100.000 | 25.773 |

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

| LIQUID YIELD   | C2+    | C3+    | C4+   | C5+   | 26# Liquid | 10# Liquid |
|----------------|--------|--------|-------|-------|------------|------------|
| GAL/MSCF (GPM) | 24.414 | 17.123 | 0.007 | 0.001 | 0.002      | 0.001      |

| CALCULATED PROPERTIES | BTU/CF   | Specific Gr. | Z Factor | Mol Weight | Wobbe IDX |
|-----------------------|----------|--------------|----------|------------|-----------|
| DRY                   | 2,063.47 | 1.344        | 0.988    | 38.482     | 1,779.84  |
| WATER SATURATED       | 2,029.28 | 1.332        | 0.988    | 37.810     |           |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |            |
|--------------|-------------------------|------------------|------------|
| Operator     | Occidental Permian Ltd. | Pressure         | N/A        |
| Location     | North Hobbs RCF         | Sample Temp      | N/A        |
| Site         | DEX PRO                 | Atm Temp         | N/A        |
| Site Type    | Station                 | Collection Date  |            |
| Sample Point | Gasoline                | Collection Time  |            |
| Spot/Comp    | Spot                    | Collection By    |            |
| Meter ID     |                         | Pressure Base    | 14.650 psi |
| Purchaser    |                         | Temperature Base | 60 F       |
| Fluid        | Liquid                  | Container(s)     |            |

## No Sample

| Employee    | Comment                |
|-------------|------------------------|
| Cody Carson | Sample Point All Water |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 30 psig     |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | NGL Storage             | Atm Temp         | 62 F        |
| Site Type    | Vessel                  | Collection Date  | 03/21/2022  |
| Sample Point | NGL                     | Collection Time  | 1:03 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     |                         | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Liquid                  | Container(s)     | PL2506      |

## GPA 2177 Liquid Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | VOL%    | WT%     |
|------------------|---------|---------|---------|---------|
| NITROGEN         | N2      | 0.022   | 0.007   | 0.009   |
| CARBON DIOXIDE   | CO2     | 0.010   | 0.005   | 0.007   |
| HYDROGEN SULFIDE | H2S     | 0.000   | 0.000   | 0.000   |
| METHANE          | C1      | 0.000   | 0.000   | 0.000   |
| ETHANE           | C2      | 0.000   | 0.000   | 0.000   |
| PROPANE          | C3      | 16.966  | 13.632  | 11.353  |
| I-BUTANE         | iC4     | 10.216  | 9.745   | 9.010   |
| N-BUTANE         | nC4     | 27.876  | 25.626  | 24.585  |
| I-PENTANE        | iC5     | 13.225  | 14.116  | 14.479  |
| N-PENTANE        | nC5     | 11.196  | 11.824  | 12.258  |
| HEXANES PLUS     | C6+     | 20.489  | 25.045  | 28.299  |
| TOTALS:          |         | 100.000 | 100.000 | 100.000 |

Value of "0.000" in fractional interpreted as below detectable limit.

## Calculated Properties

| SCF/Gal (Ideal) | SCF/Gal (Real) | Mol Weight | Relative Density (60/60) | Vapor Pressure 100F, psia | Reid VP Equivalent, psi |
|-----------------|----------------|------------|--------------------------|---------------------------|-------------------------|
| 29.321          | 27.986         | 65.901     | 0.609                    | 60.5                      | 57.4                    |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 280 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | Stabilizer              | Atm Temp         | 64 F        |
| Site Type    | Vessel                  | Collection Date  | 03/21/2022  |
| Sample Point | Bottoms                 | Collection Time  | 1:09 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     |                         | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Liquid                  | Container(s)     | PL2290      |

## GPA 2177 Liquid Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | VOL%    | WT%     |
|------------------|---------|---------|---------|---------|
| NITROGEN         | N2      | 0.011   | 0.004   | 0.005   |
| CARBON DIOXIDE   | CO2     | 0.002   | 0.001   | 0.002   |
| HYDROGEN SULFIDE | H2S     | 0.000   | 0.000   | 0.000   |
| METHANE          | C1      | 0.000   | 0.000   | 0.000   |
| ETHANE           | C2      | 0.000   | 0.000   | 0.000   |
| PROPANE          | C3      | 41.764  | 36.579  | 32.516  |
| I-BUTANE         | iC4     | 11.666  | 12.131  | 11.972  |
| N-BUTANE         | nC4     | 25.162  | 25.216  | 25.822  |
| I-PENTANE        | iC5     | 7.761   | 9.031   | 9.887   |
| N-PENTANE        | nC5     | 6.022   | 6.933   | 7.671   |
| HEXANES PLUS     | C6+     | 7.612   | 10.105  | 12.125  |
| TOTALS:          |         | 100.000 | 100.000 | 100.000 |

Value of "0.000" in fractional interpreted as below detectable limit.

## Calculated Properties

| SCF/Gal (Ideal) | SCF/Gal (Real) | Mol Weight | Relative Density (60/60) | Vapor Pressure 100F, psia | Reid VP Equivalent, psi |
|-----------------|----------------|------------|--------------------------|---------------------------|-------------------------|
| 31.961          | 30.955         | 56.638     | 0.570                    | 103.7                     | 98.9                    |

Pantechs Laboratories, Inc. Order: 300-3024 - Order Date: 3/21/2022

## Order Description: North Hobbs RCF, Monthly Collection

| SAMPLE ID    |                         | COLLECTION DATA  |             |
|--------------|-------------------------|------------------|-------------|
| Operator     | Occidental Permian Ltd. | Pressure         | 175 psig    |
| Location     | North Hobbs RCF         | Sample Temp      | N/A         |
| Site         | Surge Tank              | Atm Temp         | 62 F        |
| Site Type    | Tank                    | Collection Date  | 03/21/2022  |
| Sample Point | Propane Liquid          | Collection Time  | 1:42 PM     |
| Spot/Comp    | Spot                    | Collection By    | Cody Carson |
| Meter ID     |                         | Pressure Base    | 14.650 psi  |
| Purchaser    |                         | Temperature Base | 60 F        |
| Fluid        | Liquid                  | Container(s)     | PL1629      |

## GPA 2177 Liquid Fractional Analysis

| COMPOUND         | FORMULA | MOL%    | VOL%    | WT%     |
|------------------|---------|---------|---------|---------|
| NITROGEN         | N2      | 0.025   | 0.010   | 0.016   |
| CARBON DIOXIDE   | CO2     | 0.003   | 0.002   | 0.003   |
| HYDROGEN SULFIDE | H2S     | 0.000   | 0.000   | 0.000   |
| METHANE          | C1      | 0.003   | 0.002   | 0.001   |
| ETHANE           | C2      | 0.739   | 0.717   | 0.504   |
| PROPANE          | C3      | 98.582  | 98.490  | 98.595  |
| I-BUTANE         | iC4     | 0.596   | 0.707   | 0.786   |
| N-BUTANE         | nC4     | 0.017   | 0.019   | 0.022   |
| I-PENTANE        | iC5     | 0.004   | 0.005   | 0.007   |
| N-PENTANE        | nC5     | 0.003   | 0.004   | 0.005   |
| HEXANES PLUS     | C6+     | 0.028   | 0.044   | 0.061   |
| TOTALS:          |         | 100.000 | 100.000 | 100.000 |

Value of "0.000" in fractional interpreted as below detectable limit.

## Calculated Properties

| SCF/Gal (Ideal) | SCF/Gal (Real) | Mol Weight | Relative Density (60/60) | Vapor Pressure 100F, psia | Reid VP Equivalent, psi |
|-----------------|----------------|------------|--------------------------|---------------------------|-------------------------|
| 36.455          | 35.823         | 44.091     | 0.506                    | 192.7                     | 184.1                   |

THIS PAGE IS INTENTIONALLY LEFT BLANK

**EVENT SPECIFIC JUSTIFICATIONS FORM****Facility:** North Hobbs Plant**Start Date:** 12/05/2022 @ 02:55 PM**End Date:** 12/05/2022 @ 03:07 PM**Cause:** THE NORTH PLANT FLARED WHEN "A, B, C, AND D" TRAINS SHUT DOWN DUE TO LOW INLET RATES FROM THE FIELD.**Duration of event:** 0:12 hours

Flared MCF: 164

**Method of Flared Gas Measurement:** Flare Meter

---

**1. Reason why this event was beyond Operator's control:**

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to ensure flame is lit and meeting opacity requirements.

This event was a sudden and unforeseeable gas release to the flare due to the shutdown of the compressor unit. Oxy operators shut down "A, B, C, and D" train compressors due to low inlet rates and the compressor were not needed. OXY operators assisted with shutting down the units, and this shut down of the compressor units triggered a flaring event. The compressors will be shut down until inlet gas rates are higher and the need for the compressors is available.

Notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. OXY made every effort to control and minimize emissions as much as possible during this event.

**2. Steps Taken to limit duration and magnitude of venting or flaring:**

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to ensure flame is lit and meeting opacity requirements.

In this case, the steps taken to limit duration and magnitude of flaring was for Oxy operators to quickly respond to the compression equipment and get it blown down, OXY routed all the stranded sales gas to a flare with a 98% combustion efficiency in order to lessen emissions as much as possible. The flare is regularly monitored to ensure the flame is lit and meeting opacity requirements. After thoroughly inspecting the compressor units that were taken down, they will later be brought back to normal working service when inlet gas rates are higher.

Notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. OXY made every effort to control and minimize emissions as much as possible during this event.

**3. Corrective Actions taken to eliminate the cause and reoccurrence of venting or flaring:**

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to ensure the flame is lit and meeting opacity requirements.

Oxy cannot take any corrective actions to eliminate the cause and potential reoccurrence of compressor malfunctions as notwithstanding proper gas compressor design and operation, various forms of mechanical or technical issues can be sudden, reasonably unforeseeable and unexpected which can cause compressor unit malfunctions to occur without warning or advance notice. Oxy continually strives to maintain and operate its facility equipment in a manner consistent with good practices for minimizing emissions and reducing the number of emission events. "A, B, C, and D" trains was working as designed and operated normally prior to the sudden and without warning send of gas to the flare from the compressor units. Oxy has a strong and positive compression equipment preventative maintenance program in place. This incident was completely out of OXY's control to prevent from happening as it was determined the flaring was due to blowing down the compressors and sending gas to the flare due to low inlet rates and the compressors not being needed. OXY made every effort to control and minimize emissions as much as possible during this event. The only actions that Oxy can take and handle that is within its control, is to keep continue with its compression equipment preventative maintenance program for these units.

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

DEFINITIONS  
  
Action 167826

DEFINITIONS

|                                                                               |                                                        |
|-------------------------------------------------------------------------------|--------------------------------------------------------|
| Operator:<br>OCCIDENTAL PERMIAN LTD<br>P.O. Box 4294<br>Houston, TX 772104294 | OGRID:<br>157984                                       |
|                                                                               | Action Number:<br>167826                               |
|                                                                               | Action Type:<br>[C-129] Venting and/or Flaring (C-129) |

DEFINITIONS

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For the sake of brevity and completeness, please allow for the following in all groups of questions and for the rest of this application: <ul style="list-style-type: none"><li>• this application's operator, hereinafter "this operator";</li><li>• venting and/or flaring, hereinafter "vent or flare";</li><li>• any notification or report(s) of the C-129 form family, hereinafter "any C-129 forms";</li><li>• the statements in (and/or attached to) this, hereinafter "the statements in this";</li><li>• and the past tense will be used in lieu of mixed past/present tense questions and statements.</li></ul> |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

QUESTIONS

Action 167826

**QUESTIONS**

|                                                                               |                                                        |
|-------------------------------------------------------------------------------|--------------------------------------------------------|
| Operator:<br>OCCIDENTAL PERMIAN LTD<br>P.O. Box 4294<br>Houston, TX 772104294 | OGRID:<br>157984                                       |
|                                                                               | Action Number:<br>167826                               |
|                                                                               | Action Type:<br>[C-129] Venting and/or Flaring (C-129) |

**QUESTIONS****Prerequisites**

Any messages presented in this section, will prevent submission of this application. Please resolve these issues before continuing with the rest of the questions.

|                   |                                          |
|-------------------|------------------------------------------|
| Incident Well     | Unavailable.                             |
| Incident Facility | [fKJ1517634129] NORTH HOBBS UNIT RCF/WIB |

**Determination of Reporting Requirements**

Answer all questions that apply. The Reason(s) statements are calculated based on your answers and may provide additional guidance.

|                                                                                                            |                                                   |
|------------------------------------------------------------------------------------------------------------|---------------------------------------------------|
| Was this vent or flare caused by an emergency or malfunction                                               | Yes                                               |
| Did this vent or flare last eight hours or more cumulatively within any 24-hour period from a single event | No                                                |
| Is this considered a submission for a vent or flare event                                                  | Yes, minor venting and/or flaring of natural gas. |

An operator shall file a form C-141 instead of a form C-129 for a release that, includes liquid during venting and/or flaring that is or may be a major or minor release under 19.15.29.7 NMAC.

|                                                                                                                                                                                                                                                                                            |     |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|
| Was there at least 50 MCF of natural gas vented and/or flared during this event                                                                                                                                                                                                            | Yes |
| Did this vent or flare result in the release of <b>ANY</b> liquids (not fully and/or completely flared) that reached (or has a chance of reaching) the ground, a surface, a watercourse, or otherwise, with reasonable probability, endanger public health, the environment or fresh water | No  |
| Was the vent or flare within an incorporated municipal boundary or within 300 feet from an occupied permanent residence, school, hospital, institution or church in existence                                                                                                              | No  |

**Equipment Involved**

|                                                           |                                                     |
|-----------------------------------------------------------|-----------------------------------------------------|
| Primary Equipment Involved                                | Other (Specify)                                     |
| Additional details for Equipment Involved. Please specify | Emergency Flare>Compressor Shutdown>Low Inlet Rates |

**Representative Compositional Analysis of Vented or Flared Natural Gas**

Please provide the mole percent for the percentage questions in this group.

|                                                              |       |
|--------------------------------------------------------------|-------|
| Methane (CH4) percentage                                     | 6     |
| Nitrogen (N2) percentage, if greater than one percent        | 2     |
| Hydrogen Sulfide (H2S) PPM, rounded up                       | 7,840 |
| Carbon Dioxide (CO2) percentage, if greater than one percent | 87    |
| Oxygen (O2) percentage, if greater than one percent          | 0     |

If you are venting and/or flaring because of Pipeline Specification, please provide the required specifications for each gas.

|                                                     |               |
|-----------------------------------------------------|---------------|
| Methane (CH4) percentage quality requirement        | Not answered. |
| Nitrogen (N2) percentage quality requirement        | Not answered. |
| Hydrogen Sulfide (H2S) PPM quality requirement      | Not answered. |
| Carbon Dioxide (CO2) percentage quality requirement | Not answered. |
| Oxygen (O2) percentage quality requirement          | Not answered. |

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico  
Energy, Minerals and Natural Resources  
Oil Conservation Division  
1220 S. St Francis Dr.  
Santa Fe, NM 87505

QUESTIONS, Page 2

Action 167826

QUESTIONS (continued)

|                                                                               |                                                        |
|-------------------------------------------------------------------------------|--------------------------------------------------------|
| Operator:<br>OCCIDENTAL PERMIAN LTD<br>P.O. Box 4294<br>Houston, TX 772104294 | OGRID:<br>157984                                       |
|                                                                               | Action Number:<br>167826                               |
|                                                                               | Action Type:<br>[C-129] Venting and/or Flaring (C-129) |

QUESTIONS

| Date(s) and Time(s)                            |            |
|------------------------------------------------|------------|
| Date vent or flare was discovered or commenced | 12/05/2022 |
| Time vent or flare was discovered or commenced | 02:55 PM   |
| Time vent or flare was terminated              | 03:07 PM   |
| Cumulative hours during this event             | 1          |

| Measured or Estimated Volume of Vented or Flared Natural Gas              |                                                                                                             |
|---------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Natural Gas Vented (Mcf) Details                                          | Not answered.                                                                                               |
| Natural Gas Flared (Mcf) Details                                          | Cause: Other   Other (Specify)   Natural Gas Flared   Released: 164 Mcf   Recovered: 0 Mcf   Lost: 164 Mcf. |
| Other Released Details                                                    | Not answered.                                                                                               |
| Additional details for Measured or Estimated Volume(s). Please specify    | Not answered.                                                                                               |
| Is this a gas only submission (i.e. only significant Mcf values reported) | Yes, according to supplied volumes this appears to be a "gas only" report.                                  |

| Venting or Flaring Resulting from Downstream Activity             |               |
|-------------------------------------------------------------------|---------------|
| Was this vent or flare a result of downstream activity            | No            |
| Was notification of downstream activity received by this operator | Not answered. |
| Downstream OGRID that should have notified this operator          | Not answered. |
| Date notified of downstream activity requiring this vent or flare | Not answered. |
| Time notified of downstream activity requiring this vent or flare | Not answered. |

| Steps and Actions to Prevent Waste                                                                                               |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| For this event, this operator could not have reasonably anticipated the current event and it was beyond this operator's control. | True                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Please explain reason for why this event was beyond this operator's control                                                      | The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to the ensure flame is lit and meeting opacity requirements. |
| Steps taken to limit the duration and magnitude of vent or flare                                                                 | The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to the ensure flame is lit and meeting opacity requirements. |
| Corrective actions taken to eliminate the cause and reoccurrence of vent or flare                                                | The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. It is OXY's policy to route all stranded sales gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. The flare is regularly monitored to the ensure flame is lit and meeting opacity requirements. |

**District I**

1625 N. French Dr., Hobbs, NM 88240  
 Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
 Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
 Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
 Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

ACKNOWLEDGMENTS

Action 167826

**ACKNOWLEDGMENTS**

|                                                                               |                                                        |
|-------------------------------------------------------------------------------|--------------------------------------------------------|
| Operator:<br>OCCIDENTAL PERMIAN LTD<br>P.O. Box 4294<br>Houston, TX 772104294 | OGRID:<br>157984                                       |
|                                                                               | Action Number:<br>167826                               |
|                                                                               | Action Type:<br>[C-129] Venting and/or Flaring (C-129) |
|                                                                               |                                                        |

**ACKNOWLEDGMENTS**

|                                     |                                                                                                                                                                                                                                                                                                                           |
|-------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input checked="" type="checkbox"/> | I acknowledge that I am authorized to submit a <i>Venting and/or Flaring</i> (C-129) report on behalf of this operator and understand that this report can be a <b>complete</b> C-129 submission per 19.15.27.8 and 19.15.28.8 NMAC.                                                                                      |
| <input checked="" type="checkbox"/> | I acknowledge that upon submitting this application, I will be creating a new incident file (assigned to this operator) to track any C-129 forms, pursuant to 19.15.27.7 and 19.15.28.8 NMAC and understand that this submission meets the notification requirements of Paragraph (1) of Subsection G and F respectively. |
| <input checked="" type="checkbox"/> | I hereby certify the statements in this report are true and correct to the best of my knowledge and acknowledge that any false statement may be subject to civil and criminal penalties under the Oil and Gas Act.                                                                                                        |
| <input checked="" type="checkbox"/> | I acknowledge that the acceptance of any C-129 forms by the OCD does not relieve this operator of liability should their operations have failed to adequately investigate, report, and remediate contamination that poses a threat to groundwater, surface water, human health, or the environment.                       |
| <input checked="" type="checkbox"/> | I acknowledge that OCD acceptance of any C-129 forms does not relieve this operator of responsibility for compliance with any other applicable federal, state, or local laws and/or regulations.                                                                                                                          |

**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS  
  
Action 167826

CONDITIONS

|                                                                               |                                                        |
|-------------------------------------------------------------------------------|--------------------------------------------------------|
| Operator:<br>OCCIDENTAL PERMIAN LTD<br>P.O. Box 4294<br>Houston, TX 772104294 | OGRID:<br>157984                                       |
|                                                                               | Action Number:<br>167826                               |
|                                                                               | Action Type:<br>[C-129] Venting and/or Flaring (C-129) |

CONDITIONS

| Created By | Condition                                                                                                                                                                          | Condition Date |
|------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|
| ralvarado  | If the information provided in this report requires an amendment, submit a [C-129] Amend Venting and/or Flaring Incident (C-129A), utilizing your incident number from this event. | 12/16/2022     |