

**PANTECHS LABORATORIES, INC.**

Leaders in Petroleum Analytical Services
www.pantechs.com

Analytical Report

2/10/2023

Customer:	Occidental Permian Ltd.	Order:	503-4218
Location:	North Hobbs Unit	Received:	2/9/2023
Description:	Samples from Central Tank, North, and West Batteries for Hydrocarbon Analyses	Primary Contact:	Chris Poe

REPORT DISTRIBUTION:

Chris Poe , Richard Sanders

All data reported in this Analytical Report is in compliance with the test method(s) performed as of the date noted above. The validity and integrity of this report will remain intact as long as it is accompanied by this page and reproduced in full. Any datafile (e.g. txt, csv, etc.) produced which is associated with the results in this report shall be considered for convenience only and does not supersede this report as the official test results. We reserve the right to return to you any unused samples received if we consider so necessary (e.g. samples identified as hazardous waste).

We appreciate you choosing Pantechs Laboratories. If you have any questions concerning this report, please feel free to contact us at any time.

Pantechs Laboratories, Inc.
Order: 503-4218 Order Date: 2/9/2023
Order Description: North Hobbs Unit, Samples from Central Tank, North, and West Batteries for Hydrocarbon Analyses

Sample List						
Fluid	Operator	Location	Site	Sample Point	Date	Time
Gas	Occidental Permian Ltd.	North Hobbs Unit	Central Tank Battery	Gas Leg of Production Separator	2/9/2023	3:41 PM
Gas	Occidental Permian Ltd.	North Hobbs Unit	North Injection Battery	Gas Leg of Production Separator	2/9/2023	3:31 PM
Gas	Occidental Permian Ltd.	North Hobbs Unit	West Injection Battery	Gas Leg of Production Separator	2/9/2023	4:04 PM
Gas	Occidental Permian Ltd.	South Hobbs Unit	Central Tank Battery	Gas Leg of Production Separator	2/9/2023	3:11 PM

No Sample List				
Operator	Location	Site	Sample Point	Comment

Pantechs Laboratories, Inc. - Order: 503-4218 - Order Date: 2/9/2023

Order Description: North Hobbs Unit, Samples from Central Tank, North, and West Batteries for Hydrocarbon Analyses

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	26 psig
Location	North Hobbs Unit	Sample Temp	N/A
Site	Central Tank Battery	Atm Temp	45 F
Site Type	Battery	Collection Date	02/09/2023
Sample Point	Gas Leg of Production Separator	Collection Time	3:41 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL2344

GPA 2261 Gas Fractional Analysis with Water Vapor

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	0.056	0.033	0.006
CARBON DIOXIDE	CO2	80.489	74.605	13.780
HYDROGEN SULFIDE	H2S	1.281	0.919	0.173
WATER VAPOR	H2O	0.555	0.211	0.032
METHANE	C1	0.484	0.164	0.082
ETHANE	C2	0.391	0.248	0.105
PROPANE	C3	2.653	2.464	0.734
I-BUTANE	iC4	1.657	2.028	0.545
N-BUTANE	nC4	4.715	5.772	1.493
I-PENTANE	iC5	2.289	3.478	0.842
N-PENTANE	nC5	1.769	2.688	0.644
HEXANES PLUS	C6+	3.661	7.390	1.579
TOTALS:		100.000	100.000	20.015

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

GPA 2172/ASTM D3588 CALCULATED PROPERTIES

WATER CONTENT	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	652.96	1.652	0.990	47.381	508.07
MEASURED WATER	653.42	1.656	0.990	47.481	

Water Vapor

GPM	PPMM	LBS/MMSCF	SAMPLE SATURATED
0.032	5,550.000	264.286	No

Onsite Testing by Stain Tube

METHOD	TYPE	MEAS VALUE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	1.20 vol%	1.2810	813.46	12,934.0

Mol%, Grains/100, PPMV are pressure and temperature corrected to base conditions.

Pantechs Laboratories, Inc. Order: 503-4218 - Order Date: 2/9/2023

Order Description: North Hobbs Unit, Samples from Central Tank, North, and West Batteries for Hydrocarbon Analyses

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	34 psig
Location	North Hobbs Unit	Sample Temp	N/A
Site	North Injection Battery	Atm Temp	45 F
Site Type	Battery	Collection Date	02/09/2023
Sample Point	Gas Leg of Production Separator	Collection Time	3:31 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL1003

GPA 2261 Gas Fractional Analysis with Water Vapor

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	0.065	0.041	0.007
CARBON DIOXIDE	CO2	94.461	92.516	16.121
HYDROGEN SULFIDE	H2S	0.214	0.162	0.029
WATER VAPOR	H2O	0.540	0.216	0.031
METHANE	C1	0.083	0.030	0.014
ETHANE	C2	0.132	0.088	0.035
PROPANE	C3	0.839	0.823	0.231
I-BUTANE	iC4	0.397	0.514	0.130
N-BUTANE	nC4	1.096	1.418	0.346
I-PENTANE	iC5	0.452	0.726	0.166
N-PENTANE	nC5	0.388	0.623	0.141
HEXANES PLUS	C6+	1.333	2.843	0.573
TOTALS:		100.000	100.000	17.824

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

GPA 2172/ASTM D3588 CALCULATED PROPERTIES

WATER CONTENT	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	178.36	1.558	0.993	44.838	142.89
MEASURED WATER	178.67	1.562	0.993	44.935	

Water Vapor

GPM	PPMM	LBS/MMSCF	SAMPLE SATURATED
0.031	5,400.000	257.143	No

Onsite Testing by Stain Tube

METHOD	TYPE	MEAS VALUE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	0.20 vol%	0.2135	135.58	2,155.7

Mol%, Grains/100, PPMV are pressure and temperature corrected to base conditions.

Pantechs Laboratories, Inc. Order: 503-4218 - Order Date: 2/9/2023

Order Description: North Hobbs Unit, Samples from Central Tank, North, and West Batteries for Hydrocarbon Analyses

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	28 psig
Location	North Hobbs Unit	Sample Temp	N/A
Site	West Injection Battery	Atm Temp	40 F
Site Type	Battery	Collection Date	02/09/2023
Sample Point	Gas Leg of Production Separator	Collection Time	4:04 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL0245

GPA 2261 Gas Fractional Analysis with Water Vapor

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	0.048	0.030	0.005
CARBON DIOXIDE	CO2	93.595	92.306	15.972
HYDROGEN SULFIDE	H2S	1.480	1.130	0.200
WATER VAPOR	H2O	0.511	0.206	0.029
METHANE	C1	0.487	0.175	0.083
ETHANE	C2	0.185	0.125	0.050
PROPANE	C3	0.623	0.616	0.172
I-BUTANE	iC4	0.219	0.285	0.072
N-BUTANE	nC4	0.645	0.840	0.204
I-PENTANE	iC5	0.435	0.703	0.159
N-PENTANE	nC5	0.417	0.674	0.151
HEXANES PLUS	C6+	1.355	2.910	0.582
TOTALS:		100.000	100.000	17.679

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

GPA 2172/ASTM D3588 CALCULATED PROPERTIES

WATER CONTENT	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	167.09	1.547	0.993	44.533	134.32
MEASURED WATER	167.38	1.551	0.993	44.625	

Water Vapor

GPM	PPMM	LBS/MMSCF	SAMPLE SATURATED
0.029	5,110.000	243.333	No

Onsite Testing by Stain Tube

METHOD	TYPE	MEAS VALUE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	1.40 vol%	1.4797	939.64	14,940.3

Mol%, Grains/100, PPMV are pressure and temperature corrected to base conditions.

Pantechs Laboratories, Inc. Order: 503-4218 - Order Date: 2/9/2023

Order Description: North Hobbs Unit, Samples from Central Tank, North, and West Batteries for Hydrocarbon Analyses

SAMPLE ID		COLLECTION DATA	
Operator	Occidental Permian Ltd.	Pressure	27 psig
Location	South Hobbs Unit	Sample Temp	N/A
Site	Central Tank Battery	Atm Temp	50 F
Site Type	Battery	Collection Date	02/09/2023
Sample Point	Gas Leg of Production Separator	Collection Time	3:11 PM
Spot/Comp	Spot	Collection By	Cody Carson
Meter ID		Pressure Base	14.650 psi
Purchaser		Temperature Base	60 F
Fluid	Gas	Container(s)	PL2332

GPA 2261 Gas Fractional Analysis with Water Vapor

COMPOUND	FORMULA	MOL%	WT%	GPM
NITROGEN	N2	0.056	0.033	0.006
CARBON DIOXIDE	CO2	80.302	74.480	13.748
HYDROGEN SULFIDE	H2S	1.509	1.084	0.204
WATER VAPOR	H2O	0.553	0.210	0.032
METHANE	C1	0.483	0.163	0.082
ETHANE	C2	0.390	0.247	0.105
PROPANE	C3	2.647	2.460	0.733
I-BUTANE	iC4	1.653	2.025	0.543
N-BUTANE	nC4	4.705	5.763	1.490
I-PENTANE	iC5	2.284	3.473	0.840
N-PENTANE	nC5	1.765	2.684	0.642
HEXANES PLUS	C6+	3.653	7.378	1.575
TOTALS:		100.000	100.000	20.000

Value of "0.000" in fractional interpreted as below detectable limit.

If Onsite H2S testing is performed, its resulting value is used in fractional table

GPA 2172/ASTM D3588 CALCULATED PROPERTIES

WATER CONTENT	BTU/CF	Specific Gr.	Z Factor	Mol Weight	Wobbe IDX
DRY	653.00	1.651	0.990	47.351	508.26
MEASURED WATER	653.46	1.655	0.990	47.450	

Water Vapor

GPM	PPMM	LBS/MMSCF	SAMPLE SATURATED
0.032	5,530.000	263.333	No

Onsite Testing by Stain Tube

METHOD	TYPE	MEAS VALUE	MOL%	GRAINS/100	PPMV
GPA2377	H2S	1.40 vol%	1.5093	958.43	15,239.0

Mol%, Grains/100, PPMV are pressure and temperature corrected to base conditions.

THIS PAGE IS INTENTIONALLY LEFT BLANK

UPSET FLARING EVENT SPECIFIC JUSTIFICATIONS FORM**Facility:** South Hobbs CTB**Flare Date:** 1/29/2024**Duration of event:** 1 hour and 25 minutes**MCF Flared:** 61**Start Time:** 10:10 AM**End Time:** 11:35 AM**Cause:** Compression Equipment Malfunction > Oil filters change**Method of Flared Gas Measurement:** Gas Flare Meter**Comments:** This upset event was not caused by any wells associated with the facility

1. Reason why this event was beyond Operator's control:

The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. In this case, compressor LP 4500 unit's malfunction occurred due to High discharge pressure alarm. The Oxy's operator immediately diagnose clogged oil filters. Then began the procedure to change the filters and restart the unit as quickly as possible. The facility and all its equipment were working as designed and operated normally prior to the sudden and without warning malfunction.

2. Steps Taken to limit duration and magnitude of venting or flaring:

The steps taken to limit duration and magnitude of flaring was for an Oxy production tech to quickly respond to the compressor malfunction alarm and begin inspecting the unit, diagnose the issue, and make the necessary adjustments to restart the unit back to normal working service. It is OXY's policy to route all stranded gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. Internal procedures ensure that upon compressor unit shutdown, OXY production techs are promptly notified, and are instructed to assess the issue as soon as possible in order to take prompt corrective action and minimize emissions. Upon arrival, an Oxy production tech must assess whether compressor shutdown is due to damage and repair is needed, or whether there are other reasons. In this case, the Oxy production tech arrived from another facility rather quickly, as this an unmanned facility and performed a visual inspection of the malfunctioned compressor unit and finding that the oil filters were clogged.

3. Corrective Actions taken to eliminate the cause and reoccurrence of venting or flaring:

Oxy is limited in the corrective actions available to them to eliminate the cause and potential reoccurrence of compressor malfunctions as notwithstanding compressor engine design and operation, compressors are inherently dynamic and even the smallest alarms, false or true, can be sudden, reasonably unforeseeable and unexpected which can cause compression malfunctions to occur, thereby, triggering the unit's sensors to automatically shut down the unit to avoid catastrophic damage to the internal engine components. Oxy continually strives to maintain and operate its facility and its equipment in a manner consistent with good practices for minimizing emissions and reducing the number of emission events. The only actions that Oxy

can take and handle that is within its control, is to continue with its preventative maintenance program for this facility and its compression equipment.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

DEFINITIONS

Action 313210

DEFINITIONS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 313210
	Action Type: [C-129] Venting and/or Flaring (C-129)

DEFINITIONS

For the sake of brevity and completeness, please allow for the following in all groups of questions and for the rest of this application: • this application's operator, hereinafter "this operator"; • venting and/or flaring, hereinafter "vent or flare"; • any notification or report(s) of the C-129 form family, hereinafter "any C-129 forms"; • the statements in (and/or attached to) this, hereinafter "the statements in this"; • and the past tense will be used in lieu of mixed past/present tense questions and statements.
--

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

QUESTIONS

Action 313210

QUESTIONS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 313210
	Action Type: [C-129] Venting and/or Flaring (C-129)

QUESTIONS

Prerequisites Any messages presented in this section, will prevent submission of this application. Please resolve these issues before continuing with the rest of the questions.	
Incident Well	Unavailable.
Incident Facility	[fJXK1520829861] South Hobbs Unit CTB

Determination of Reporting Requirements Answer all questions that apply. The Reason(s) statements are calculated based on your answers and may provide additional guidance.	
Was this vent or flare caused by an emergency or malfunction	Yes
Did this vent or flare last eight hours or more cumulatively within any 24-hour period from a single event	No
Is this considered a submission for a vent or flare event	Yes, minor venting and/or flaring of natural gas.
An operator shall file a form C-141 instead of a form C-129 for a release that, includes liquid during venting and/or flaring that is or may be a major or minor release under 19.15.29.7 NMAC.	
Was there at least 50 MCF of natural gas vented and/or flared during this event	Yes
Did this vent or flare result in the release of ANY liquids (not fully and/or completely flared) that reached (or has a chance of reaching) the ground, a surface, a watercourse, or otherwise, with reasonable probability, endanger public health, the environment or fresh water	No
Was the vent or flare within an incorporated municipal boundary or withing 300 feet from an occupied permanent residence, school, hospital, institution or church in existence	No

Equipment Involved	
Primary Equipment Involved	Other (Specify)
Additional details for Equipment Involved. Please specify	Compression Equipment Malfunction > Oil filters change

Representative Compositional Analysis of Vented or Flared Natural Gas Please provide the mole percent for the percentage questions in this group.	
Methane (CH4) percentage	0
Nitrogen (N2) percentage, if greater than one percent	0
Hydrogen Sulfide (H2S) PPM, rounded up	15,090
Carbon Dioxide (C02) percentage, if greater than one percent	80
Oxygen (O2) percentage, if greater than one percent	0
If you are venting and/or flaring because of Pipeline Specification, please provide the required specifications for each gas.	
Methane (CH4) percentage quality requirement	Not answered.
Nitrogen (N2) percentage quality requirement	Not answered.
Hydrogen Sufide (H2S) PPM quality requirement	Not answered.
Carbon Dioxide (C02) percentage quality requirement	Not answered.
Oxygen (O2) percentage quality requirement	Not answered.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

QUESTIONS, Page 2

Action 313210

QUESTIONS (continued)

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 313210
	Action Type: [C-129] Venting and/or Flaring (C-129)

QUESTIONS

Date(s) and Time(s)	
Date vent or flare was discovered or commenced	01/29/2024
Time vent or flare was discovered or commenced	10:10 AM
Time vent or flare was terminated	11:35 AM
Cumulative hours during this event	1

Measured or Estimated Volume of Vented or Flared Natural Gas	
Natural Gas Vented (Mcf) Details	Not answered.
Natural Gas Flared (Mcf) Details	Cause: Other Other (Specify) Natural Gas Flared Released: 61 Mcf Recovered: 0 Mcf Lost: 61 Mcf.
Other Released Details	Not answered.
Additional details for Measured or Estimated Volume(s). Please specify	Gas Flare Meter
Is this a gas only submission (i.e. only significant Mcf values reported)	Yes, according to supplied volumes this appears to be a "gas only" report.

Venting or Flaring Resulting from Downstream Activity	
Was this vent or flare a result of downstream activity	No
Was notification of downstream activity received by this operator	Not answered.
Downstream OGRID that should have notified this operator	Not answered.
Date notified of downstream activity requiring this vent or flare	Not answered.
Time notified of downstream activity requiring this vent or flare	Not answered.

Steps and Actions to Prevent Waste	
For this event, this operator could not have reasonably anticipated the current event and it was beyond this operator's control.	True
Please explain reason for why this event was beyond this operator's control	The emissions event was caused by the unforeseen, unexpected, sudden, and unavoidable breakdown of equipment or process that was beyond the owner/operator's control, and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and preventative maintenance practices. In this case, compressor LP 4500 unit's malfunction occurred due to High discharge pressure alarm. The Oxy's operator immediately diagnose clogged oil filters. Then began the procedure to change the filters and restart the unit as quickly as possible The facility and all its equipment were working as designed and operated normally prior to the sudden and without warning malfunction.
Steps taken to limit the duration and magnitude of vent or flare	The steps taken to limit duration and magnitude of flaring was for an Oxy production tech to quickly respond to the compressor malfunction alarm and begin inspecting the unit, diagnose the issue, and make the necessary adjustments to restart the unit back to normal working service. It is OXY's policy to route all stranded gas to a flare during an unforeseen and unavoidable emergency or malfunction, in order to minimize emissions as much as possible. Internal procedures ensure that upon compressor unit shutdown, OXY production techs are promptly notified, and are instructed to assess the issue as soon as possible in order to take prompt corrective action and minimize emissions. Upon arrival, an Oxy production tech must assess whether compressor shutdown is due to damage and repair is needed, or whether there are other reasons. In this case, the Oxy production tech arrived from another facility rather quickly, as this an unmanned facility and performed a visual inspection

	of the malfunctioned compressor unit and finding that the oil filters were clogged.
Corrective actions taken to eliminate the cause and reoccurrence of vent or flare	Oxy is limited in the corrective actions available to them to eliminate the cause and potential reoccurrence of compressor malfunctions as notwithstanding compressor engine design and operation, compressors are inherently dynamic and even the smallest alarms, false or true, can be sudden, reasonably unforeseeable and unexpected which can cause compression malfunctions to occur, thereby, triggering the unit's sensors to automatically shut down the unit to avoid catastrophic damage to the internal engine components. Oxy continually strives to maintain and operate its facility and its equipment in a manner consistent with good practices for minimizing emissions and reducing the number of emission events. The only actions that Oxy Page 2 of 2 can take and handle that is within its control, is to continue with its preventative maintenance program for this facility and its compression equipment.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 313210

ACKNOWLEDGMENTS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 313210
	Action Type: [C-129] Venting and/or Flaring (C-129)

ACKNOWLEDGMENTS

☒	I acknowledge that I am authorized to submit a <i>Venting and/or Flaring</i> (C-129) report on behalf of this operator and understand that this report can be a complete C-129 submission per 19.15.27.8 and 19.15.28.8 NMAC.
☒	I acknowledge that upon submitting this application, I will be creating a new incident file (assigned to this operator) to track any C-129 forms, pursuant to 19.15.27.7 and 19.15.28.8 NMAC and understand that this submission meets the notification requirements of Paragraph (1) of Subsection G and F respectively.
☒	I hereby certify the statements in this report are true and correct to the best of my knowledge and acknowledge that any false statement may be subject to civil and criminal penalties under the Oil and Gas Act.
☒	I acknowledge that the acceptance of any C-129 forms by the OCD does not relieve this operator of liability should their operations have failed to adequately investigate, report, and remediate contamination that poses a threat to groundwater, surface water, human health, or the environment.
☒	I acknowledge that OCD acceptance of any C-129 forms does not relieve this operator of responsibility for compliance with any other applicable federal, state, or local laws and/or regulations.

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS

Action 313210

CONDITIONS

Operator: OCCIDENTAL PERMIAN LTD P.O. Box 4294 Houston, TX 772104294	OGRID: 157984
	Action Number: 313210
	Action Type: [C-129] Venting and/or Flaring (C-129)

CONDITIONS

Created By	Condition	Condition Date
shelbyschoepf	If the information provided in this report requires an amendment, submit a [C-129] Amend Venting and/or Flaring Incident (C-129A), utilizing your incident number from this event.	2/9/2024