## AKM MEASUREMENT SERVICES,LLC. Natural Gas Analysis Report GPA 2172-09/API 14.5 Report with GPA 2145-16 Physical Properties

	Sample Information
Sample Name	LOST TANK 18 FACILITY PROD 2
Technician	ANTHONY DOMINGUEZ
Analyzer Make & Model	INFICON MICRO GC
Last Calibration/Validation Date	12-15-2023
Meter Number	16412P
Air temperature	59
Flow Rate (MCF/Day)	19315
Heat Tracing	HEATED HOSE & GASIFIER
Sample description/mtr name	LOST TANK 18 FACILITY PROD 2
Sampling Method	FILL & EMPTY
Operator	OCCIDENTAL PETROLEUM, OXY USA INC
State	NEW MEXICO
Region Name	PERMIAN_RESOURCES
Asset	NEW MEXICO
System	LOST TANK
FLOC	OP-DELNE-BT010
Sample Sub Type	СТВ
Sample Name Type	METER
Vendor	AKM MEASUREMENT
Cylinder #	38967
Sampled by	SCOTT
Sample date	12-11-2023
Analyzed date	12-19-2023
Method Name	C9
Injection Date	2023-12-19 17:22:49
Report Date	2023-12-19 17:24:34
EZReporter Configuration File	1-16-2023 OXY GPA C9+ H2S #2.cfgx
Source Data File	c9df624d-557a-4940-b08e-304ec2186c4a
NGA Phys. Property Data Source	GPA Standard 2145-16 (FPS)
Data Source	INFICON Fusion Connector

## **Component Results**

Component Name	Peak Area	Raw Amount	Response Factor	Norm Mole%	Gross HV (Dry) (BTU / Ideal cu.ft.)	Relative Gas Density (Dry)	GPM (Dry) (Gal. / 1000 cu.ft.)	
Nitrogen	33914.5	1.9299	0.00005691	1.9234	0.0	0.01860	0.212	
Methane	970996.0	70.7503	0.00007286	70.5121	713.8	0.39057	12.003	
CO2	27471.0	1.3080	0.00004761	1.3036	0.0	0.01981	0.223	
Ethane	291718.9	13.4465	0.00004609	13.4012	237.7	0.13913	3.599	
H2S	0.0	0.0000	0.00000000	0.0000	0.0	0.00000	0.000	
Propane	234132.9	7.6719	0.00003277	7.6461	192.8	0.11641	2.115	
iso-butane	91468.0	1.0116	0.00001106	1.0082	32.9	0.02023	0.331	
n-Butane	233710.5	2.5698	0.00001100	2.5611	83.7	0.05140	0.811	
iso-pentane	50142.9	0.4900	0.00000977	0.4883	19.6	0.01216	0.179	
n-Pentane	56869.7	0.5337	0.00000938	0.5319	21.4	0.01325	0.194	
hexanes	36640.0	0.3612	0.00000986	0.3600	17.2	0.01071	0.149	
heptanes	31543.0	0.1905	0.00000604	0.1899	10.5	0.00657	0.088	
octanes	12956.0	0.0696	0.00000537	0.0694	4.3	0.00274	0.036	
nonanes+	1475.0	0.0048	0.00000326	0.0048	0.3	0.00021	0.003	
Total:		100.3379		100.0000	1334.2	0.80179	19.943	

## **Results Summary**

	Result	Dry	Sat.
Total Un-Normalize	d Mole%	100.3379	
Pressure Base (psi	a)	14.730	
Temperature Base	(Deg. F)	60.00	
Releasted to Tampeinty	:e2/ <b>De</b> G/F25 5:55:21 PM	83.3	

Received by OCD: 2/2/2025 5:18:40 PM	Dry	Sat.	Page
Flowing Pressure (psia)	100.2		
Gross Heating Value (BTU / Ideal cu.ft.)	1334.2	1311.0	
Gross Heating Value (BTU / Real cu.ft.)	1340.0	1317.3	
Relative Density (G), Real	0.8049	0.8022	

## **Monitored Parameter Report**

	Parameter	Value	Lower Limit	Upper Limit	Status	
T	Total un-normalized amount	100.3379	97.0000	103.0000	Pass	

### **UPSET FLARING EVENT SPECIFIC JUSTIFICATIONS FORM**

Facility: Lost Tank 18 CPF Flare Date: 01/18/2025

**Duration of Event:** 50 Minutes **MCF Flared:** 65

Start Time: 01:00 PM End Time: 02:00 PM

Cause: Emergency Flare > Equipment Malfunctions > Production Separator & Tester > Dump Stick

Method of Flared Gas Measurement: Gas Flare Meter

### 1. Reason why this event was beyond Operator's control:

The emissions were caused by the sudden, unavoidable breakdown of equipment or process that was beyond the owner/operator's control and did not stem from activity that could have been foreseen and avoided, and could not have been avoided by good design, operation, and maintenance practices. Internal Oxy procedures ensure that upon a sudden and unexpected flaring event, production techs are promptly notified and are instructed to assess the issue as soon as possible to take prompt corrective action and minimize emissions. In this situation, the dump stick was open on 1011 production separator and the tester due to the flowrate transmitter was showing an abnormal rate when it was gas, which in turn, caused the valve didn't shut itself close. During this time, the facility low pressure side was flaring and kept pressuring up as result of the equipment malfunction with the production separator and the tester, which then tripped the Hihi pressure on the VRT, and triggered a COC of the facility itself and a flaring event to occur. Oxy operators consistently monitor the facility for any deviations from normal operating parameters; however, this was an abnormal failure that would be difficult to predict. Prior to the flaring incident occurring, all OXY operations and equipment were operating at peak optimization levels. This flaring situation was beyond OXY's control, but Oxy took all possible measures to reduce emissions effectively during this circumstance.

### 2. Steps Taken to limit duration and magnitude of venting or flaring:

It is OXY's policy to route all stranded gas to a flare during an unforeseen and unavoidable emergency or malfunction, that is beyond Oxy's control to avoid, prevent or foresee, to minimize emissions as much as possible as part of the overall steps taken to limit duration and magnitude of flaring. The flare at this facility has a 98% combustion efficiency to lessen emissions as much as possible. In this situation, the dump stick was open on 1011 production separator and the tester due to the flowrate transmitter was showing an abnormal rate when it was gas, which in turn, caused the valve didn't shut itself close. During this time, the facility low pressure side was flaring and kept pressuring up as result of the equipment malfunction with the production separator and the tester, which then tripped the Hihi pressure on the VRT, and triggered a COC of the facility itself and a flaring event to occur. Steps were immediately taken to reduce and mitigate the volume of gas being sent to flare by choking back several wells and reduce the amount of gas being sent to the flare. Prior to the flaring incident occurring, all OXY operations and equipment were operating at peak optimization levels. This flaring situation was beyond OXY's control, but Oxy took all possible measures to reduce emissions effectively during this circumstance.

### 3. Corrective Actions taken to eliminate the cause and reoccurrence of venting or flaring:

Oxy's ability to take corrective action to prevent and address malfunctions in this type of circumstance is limited. Despite proper design and operation of the production separator and testers, unexpected mechanical or technical issues can arise without warning and are often unforeseeable, leading to unforeseen equipment malfunctions.

General Information Phone: (505) 629-6116

Online Phone Directory <a href="https://www.emnrd.nm.gov/ocd/contact-us">https://www.emnrd.nm.gov/ocd/contact-us</a>

## State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

DEFINITIONS

Action 427350

### **DEFINITIONS**

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	427350
	Action Type:
	[C-129] Venting and/or Flaring (C-129)

### **DEFINITIONS**

For the sake of brevity and completeness, please allow for the following in all groups of questions and for the rest of this application:

- this application's operator, hereinafter "this operator";
- venting and/or flaring, hereinafter "vent or flare";
- any notification or report(s) of the C-129 form family, hereinafter "any C-129 forms";
- the statements in (and/or attached to) this, hereinafter "the statements in this";
- and the past tense will be used in lieu of mixed past/present tense questions and statements.

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

## **State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division** 1220 S. St Francis Dr. **Santa Fe, NM 87505**

QUESTIONS

Action 427350

QI	JESTIONS		
Operator: OXY USA INC		OGRID: 16696	
P.O. Box 4294 Houston, TX 772104294		Action Number: 427350	
		Action Type: [C-129] Venting and/or Flaring (C-129)	
QUESTIONS			
Prerequisites			
Any messages presented in this section, will prevent submission of this application. Please resolve t	hese issues before continuing with	h the rest of the questions.	
Incident Well	Unavailable.		
Incident Facility	[fAPP2226965761] Lost Ta	ink 18 CPF	
Determination of Depositing Deposition Deposition			
Determination of Reporting Requirements			
Answer all questions that apply. The Reason(s) statements are calculated based on your answers an Was this vent or flare caused by an emergency or malfunction	Yes		
Did this vent or flare last eight hours or more cumulatively within any 24-hour period from a single event	No		
Is this considered a submission for a vent or flare event	Yes, minor venting and/or f	flaring of natural gas.	
An operator shall file a form C-141 instead of a form C-129 for a release that, includes liquid during v			
Was there at least 50 MCF of natural gas vented and/or flared during this event	Yes		
Did this vent or flare result in the release of <b>ANY</b> liquids (not fully and/or completely flared) that reached (or has a chance of reaching) the ground, a surface, a watercourse, or otherwise, with reasonable probability, endanger public health, the environment or fresh water	No		
Was the vent or flare within an incorporated municipal boundary or withing 300 feet from an occupied permanent residence, school, hospital, institution or church in existence	No		
Equipment Involved			
Primary Equipment Involved	Other (Specify)		
Additional details for Equipment Involved. Please specify	Emergency Flare > Equipme	ent Malfunctions > Production Separator & Tester > Dump Stick	
Representative Compositional Analysis of Vented or Flared Natural Gas			
Please provide the mole percent for the percentage questions in this group.			
Methane (CH4) percentage	71		
Nitrogen (N2) percentage, if greater than one percent	2		
Hydrogen Sulfide (H2S) PPM, rounded up	0		
Carbon Dioxide (C02) percentage, if greater than one percent	1		
Oxygen (02) percentage, if greater than one percent	0		
If you are venting and/or flaring because of Pipeline Specification, please provide the required spec	ifications for each gas		
Methane (CH4) percentage quality requirement	Not answered.		
Nitrogen (N2) percentage quality requirement	Not answered.		
Hydrogen Sufide (H2S) PPM quality requirement			
	Not answered.		
Carbon Dioxide (C02) percentage quality requirement	Not answered.  Not answered.		

Sante Fe Main Office Phone: (505) 476-3441 General Information

Phone: (505) 629-6116

Online Phone Directory
<a href="https://www.emnrd.nm.gov/ocd/contact-us">https://www.emnrd.nm.gov/ocd/contact-us</a>

## State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe. NM 87505

QUESTIONS, Page 2

Action 427350

	Santa	e, INIVI 67 303	
	QUESTI	ONS (continued)	
ı	Operator:	OGRID:	
	OXY USA INC P.O. Box 4294	166 Action Number:	
	Houston, TX 772104294	427	
		Action Type:	29] Venting and/or Flaring (C-129)
	QUESTIONS		3 3 3 3 3 3 7
	Date(s) and Time(s)		
	Date vent or flare was discovered or commenced	01/18/2025	
	Time vent or flare was discovered or commenced	01:10 PM	
	Time vent or flare was terminated	02:00 PM	
	Cumulative hours during this event	1	
1			
	Measured or Estimated Volume of Vented or Flared Natural Gas		
	Natural Gas Vented (Mcf) Details	Not answered.	
	Natural Gas Flared (Mcf) Details	Cause: Other   Other (Specify)   Natural Ga Lost: 65 Mcf.	as Flared   Released: 65 Mcf   Recovered: 0 Mcf
	Other Released Details	Not answered.	
	Additional details for Measured or Estimated Volume(s). Please specify	Gas Flare Meter	
	Is this a gas only submission (i.e. only significant Mcf values reported)	Yes, according to supplied volumes this	appears to be a "gas only" report.
1			
	Venting or Flaring Resulting from Downstream Activity		
	Was this vent or flare a result of downstream activity	No	
	Was notification of downstream activity received by this operator	Not answered.	
	Downstream OGRID that should have notified this operator	Not answered.	
	Date notified of downstream activity requiring this vent or flare	Not answered.	
	Time notified of downstream activity requiring this vent or flare	Not answered.	
	Steps and Actions to Prevent Waste		
	For this event, this operator could not have reasonably anticipated the current event and it was beyond this operator's control.	True	
	Please explain reason for why this event was beyond this operator's control	process that was beyond the owner/opera could have been foreseen and avoided, at operation, and maintenance practices. Into and unexpected flaring event, production to emissions. In this situation, the dump stict tester due to the flowrate transmitter was in turn, caused the valve didn't shut itself was flaring and kept pressuring up as resiproduction separator and the tester, which triggered a COC of the facility itself and a finonitor the facility for any deviations from an abnormal failure that would be difficult to OXY operations and equipment were open	en, unavoidable breakdown of equipment or tor's control and did not stem from activity that and could not have been avoided by good design, ernal Oxy procedures ensure that upon a sudden techs are promptly notified and are instructed to take prompt corrective action and minimize k was open on 1011 production separator and the showing an abnormal rate when it was gas, which close. During this time, the facility low pressure side ult of the equipment malfunction with the then tripped the Hihi pressure on the VRT, and laring event to occur. Oxy operators consistently normal operating parameters; however, this was to predict. Prior to the flaring incident occurring, all rating at peak optimization levels. This flaring Dxy took all possible measures to reduce emissions

effectively during this circumstance.

It is OXY's policy to route all stranded gas to a flare during an unforeseen and unavoidable emergency or malfunction, that is beyond Oxy's control to avoid, prevent or foresee, to minimize emissions as much as possible as part of the overall steps taken to limit duration

Steps taken to limit the duration and magnitude of vent or flare	and magnitude of flaring. The flare at this facility has a 98% combustion efficiency to lessen emissions as much as possible. In this situation, the dump stick was open on 1011 production separator and the tester due to the flowrate transmitter was showing an abnormal rate when it was gas, which in turn, caused the valve didn't shut itself close. During this time, the facility low pressure side was flaring and kept pressuring up as result of the equipment malfunction with the production separator and the tester, which then tripped the Hihi pressure on the VRT, and triggered a COC of the facility itself and a flaring event to occur. Steps were immediately taken to reduce and mitigate the volume of gas being sent to flare by choking back several wells and reduce the amount of gas being sent to the flare. Prior to the flaring incident occurring, all OXY operations and equipment were operating at peak optimization levels. This flaring situation was beyond OXY's control, but Oxy took all possible measures to reduce emissions effectively during this circumstance.
Corrective actions taken to eliminate the cause and reoccurrence of vent or flare	Oxy's ability to take corrective action to prevent and address malfunctions in this type of circumstance is limited. Despite proper design and operation of the production separator and testers, unexpected mechanical or technical issues can arise without warning and are often unforeseeable, leading to unforeseen equipment malfunctions.

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

## State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

ACKNOWLEDGMENTS

Action 427350

### **ACKNOWLEDGMENTS**

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	427350
	Action Type:
	[C-129] Venting and/or Flaring (C-129)

### ACKNOWLEDGMENTS

V	I acknowledge that I am authorized to submit a Venting and/or Flaring (C-129) report on behalf of this operator and understand that this report can be a complete C-129 submission per 19.15.27.8 and 19.15.28.8 NMAC.
V	I acknowledge that upon submitting this application, I will be creating a new incident file (assigned to this operator) to track any C-129 forms, pursuant to 19.15.27.7 and 19.15.28.8 NMAC and understand that this submission meets the notification requirements of Paragraph (1) of Subsection G and F respectively.
V	I hereby certify the statements in this report are true and correct to the best of my knowledge and acknowledge that any false statement may be subject to civil and criminal penalties under the Oil and Gas Act.
V	I acknowledge that the acceptance of any C-129 forms by the OCD does not relieve this operator of liability should their operations have failed to adequately investigate, report, and remediate contamination that poses a threat to groundwater, surface water, human health, or the environment.
V	I acknowledge that OCD acceptance of any C-129 forms does not relieve this operator of responsibility for compliance with any other applicable federal, state, or local laws and/or regulations.

General Information Phone: (505) 629-6116

Online Phone Directory https://www.emnrd.nm.gov/ocd/contact-us

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

CONDITIONS

Action 427350

### **CONDITIONS**

Operator:	OGRID:
OXY USA INC	16696
P.O. Box 4294	Action Number:
Houston, TX 772104294	427350
	Action Type:
	[C-129] Venting and/or Flaring (C-129)

### CONDITIONS

Created By		Condition Date
marialuna2	If the information provided in this report requires an amendment, submit a [C-129] Amend Venting and/or Flaring Incident (C-129A), utilizing your incident number from this event.	2/2/2025