

Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

JUN 03 2004
OIL WELL APPLICATION

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

DIVISION	30-007-20506
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name:	VPR D
8. Well No.	161
9. Pool name or Wildcat	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☐ Other ☒ Coalbed Methane

2. Name of Operator
EL PASO ENERGY RATON, L.L.C.

3. Address of Operator
P.O. Box 190, Raton, NM 87740

4. Well Location
Unit Letter I : 1467 feet from the South line and 1013 feet from the East line
Section 16 Township 30N Range 17E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)
9087' (GL)

Fl. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

05/24/04 Spud @ 14:15. Drill 11" surface hole to 350'. Run 8 jts. of 8 5/8", J-55, 23 ppf ST&C casing to 344'. Halliburton mixed and pumped 37 bbls water, 100 sks Midcon II, 14 ppg, yield 1.66 at 4 bpm with 70 psi with 6 % salt, 5#/sx gilsonite, .3% versaset, .25 #/sk flocele. Circulated 6 bbls of cement to surface. WOC 8 hrs. Test surface casing to 500 psi for 30 minutes.
05/25/04 Drill 7 7/8" hole from 350' - 2935'. Reached TD 2935' at 1:30 a.m. MIRU Schlumberger & log well. Loggers TD at 2884'. Ran 70 jts. of 5 1/2", M-50, 15.5 ppf LT&C casing to 2859'. Halliburton mix and pump 70 bbls water, 40 bbls gel pre flush. Pumped 410 sks Midcon II PP, 13 ppg, yield 2.04 at 4 bpm. with 6 % salt, 2 lb/sx Granulite, 5 lb/sx Gilsonite, .3% Versaset, and .1% Super CBL. Bumped plug with 1200 psi. Float held. Circulated 15 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 05/28/04
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 6/7/04
Conditions of approval, if any: