

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO. 30-007-20445
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER _____		7. Lease Name or Unit Agreement Name VPR A	
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> OTHER _____		8. Well No. 138	
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		9. Pool name or Wildcat Stubblefield Canyon Raton - Vermejo Gas	
3. Address of Operator PO BOX 190 RATON, NEW MEXICO 87740			
4. Well Location Unit Letter F : 1530 Feet From The North Line and 1742 Feet From The West Line Section 26 Township 32N Range 19E NMPM Colfax County			
10. Date Spudded 02/18/04	11. Date T.D. Reached 02/19/04	12. Date Compl. (Ready to Prod.) 05/20/04	13. Elevations (DF& R(B. RT, GR, etc.) 8255' (GL)
14. Elev. Casinghead 8255'			
15. Total Depth 2755'	16. Plug Back T.D. 2700'	17. If Multiple Compl. How Many Zones? _____	18. Intervals Drilled By 0 - TD
19. Producing Interval(s), of this completion - Top, Bottom, Name 802' - 2442' Vermejo - Raton Coals			20. Was Directional Survey Made NO
21. Type Electric and Other Logs Run Mud Log, Epithermal Neutron Litho Density, Array Induction Linear Correlation, and Acoustic Cement Bond Log			22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	364'	11"	100 sks	None
5 1/2"	15.5	2711'	7 7/8"	411 sks	
24. LINER RECORD					
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	
25. TUBING RECORD					
SIZE	DEPTH SET	PACKER SET			
2 7/8"	2519'	No			
26. Perforation record (interval, size, and number) 2407' - 2412', 2439' - 2442' 32 Holes 1432' - 1434', 1476' - 1478', 1510' - 1514' 32 Holes 1209' - 1212', 1222' - 1225', 1245' - 1247', 1281' - 1284' 44 Holes 802' - 804', 895' - 898' 1031' - 1033', 1074' - 1079' 20 Holes					
27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
DEPTH INTERVAL			AMOUNT AND KIND MATERIAL USED		
802' - 2442'			174,417 lbs 16/30 Brady Sand		

28. PRODUCTION							
Date First Production 05/21/04		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 PC Pump. Flowing gas up 5 1/2" Casing.			Well Status (Prod. or Shut-in) Prod.		
Date of Test 05/21/04	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period N/A	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl. 447	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 0	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 0	Water - Bbl. 447	Oil Gravity - API - (Corr.) N/A	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.						Test Witnessed By: Jerry Colburn	

30. List Attachments	
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.	

Signature: Shirley Mitchell Printed Shirley A. Mitchell Title Regulatory Analyst Date: 06/09/04

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy _____
T. Salt _____
B. Salt _____
T. Yates _____
T. 7 Rivers _____
T. Queen _____
T. Grayburg _____
T. San Andres _____
T. Glorieta _____
T. Paddock _____
T. Blinberry _____

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian _____
T. Montoya _____
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____

Northwestern New Mexico

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. Raton Top 395'
T. Vermejo 2,205'
Trinidad 2,480'

T. Tubb
T. Drinkard
T. Abo
T. Wolfcamp
T. Penn
T. Cisco (Bough C)

T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology