

District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South Pacheco, Santa Fe, NM 87505

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

WELL API NO.	30-007-20479
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>	
State Oil & Gas Lease No.	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER _____			7. Lease Name or Unit Agreement Name VPR A		
b. Type of Completion: NEW WELL <input checked="" type="checkbox"/> WORK OVER <input type="checkbox"/> DEEPEN <input type="checkbox"/> PLUG BACK <input type="checkbox"/> DIFF. RESVR. <input type="checkbox"/> OTHER _____			8. Well No. 123		
2. Name of Operator EL PASO ENERGY RATON, L.L.C.			9. Pool name or Wildcat Stubblefield Canyon Raton - Vermejo Gas		
3. Address of Operator PO BOX 190 RATON, NEW MEXICO 87740					
4. Well Location Unit Letter P : 1097 Feet From The South Line and 810 Feet From The East Line Section 20 Township 32N Range 19E NMPM Colfax County					
10. Date Spudded 01/29/04	11. Date T.D. Reached 01/30/04	12. Date Compl. (Ready to Prod.) 04/10/04	13. Elevations (DF& R(B. RT, GR, etc.) 8595' (GL)	14. Elev. Casinghead 8595'	
15. Total Depth 2905'	16. Plug Back T.D. 2837'	17. If Multiple Compl. How Many Zones? 	18. Intervals Drilled By 0 - TD	Rotary Tools Cable Tools NONE	
19. Producing Interval(s), of this completion - Top, Bottom, Name 1292'-2544' Vermejo - Raton Coals				20. Was Directional Survey Made NO	
21. Type Electric and Other Logs Run Mud Log. Epithermal Neutron Litho Density, Array Induction Linear Correlation, and Acoustic Cement Bond Log				22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8 5/8"	23	360'	11"	100 sx	None
5 1/2"	15.5	2847'	7 7/8"	399 sx	

24. LINER RECORD					25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2615'	No

26. Perforation record (interval, size, and number) 2540'-2544' 12 Holes 2315'-2317', 2385'-2388' 15 Holes 2086'-2089' 9 Holes 1396'-1401' 24 Holes 1292'-1296', 1327'-1330', 1342'-1345' 30 Holes		27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 1292'-2544' AMOUNT AND KIND MATERIAL USED 172,740 lbs 16/30 brady sand	

28. PRODUCTION							
Date First Production 05/27/04		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 PC Pump. Flowing gas up 5 1/2" Casing.			Well Status (Prod. or Shut-in) Prod.		
Date of Test 05/27/04	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period N/A	Oil - Bbl N/A	Gas - MCF 1	Water - Bbl. 202	Gas - Oil Ratio N/A
Flow Tubing Press.	Casing Pressure 3	Calculated 24-Hour Rate	Oil - Bbl. N/A	Gas - MCF 1	Water - Bbl. 202	Oil Gravity - API - (Corr.) N/A	

29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.	Test Witnessed By: Jerry Colburn
--	-------------------------------------

30. List Attachments
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.

Signature: <i>Shirley Mitchell</i>	Printed Shirley A. Mitchell	Title Regulatory Analyst	Date: 06/08/04
------------------------------------	-----------------------------	--------------------------	----------------

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen	T. Silurian
T. Grayburg	T. Montoya
T. San Andres	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinberry	T. Gr. Wash

T. Tubb _____	T. Delaware Sand _____
T. Drinkard _____	T. Bone Springs _____
T. Abo _____	T. _____
T. Wolfcamp _____	T. _____
T. Penn _____	T. _____
T. Cisco (Bough C) _____	T. _____

Northwestern New Mexico

T. Ojo Alamo _____	T. Penn. "B" _____
T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Pictured Cliffs _____	T. Penn. "D" _____
T. Cliff House _____	T. Leadville _____
T. Menefee _____	T. Madison _____
T. Point Lookout _____	T. Elbert _____
T. Mancos _____	T. McCracken _____
T. Gallup _____	T. Ignacio Otzte _____
Base Greenhorn _____	T. Granite _____
T. Dakota _____	T. Raton Top <u>470'</u>
T. Morrison _____	T. Vermejo <u>2,301'</u>
	Trinidad <u>2,626'</u>

T. Todilto	T. _____
T. Entrada	T. _____
T. Wingate	T. _____
T. Chinle	T. _____
T. Permian	T. _____
T. Penn "A"	T. _____

OIL OR GAS SANDS
OR ZONES

No. 1, from.....to.....
No. 2, from.....to.....

No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology