Submit 3 Copies To Appropriate District Office Energy, Minerals and Natural Resources				Form C-103 Revised March 25, 1999
1625 N. French Dr., Hobbs, NM 87240         District II         811 South First, Artesia, NM 87210         District III         1220 South St. Frances			5. Indicate Type	<b>30-007-20538</b>
1000 Rio Brazos Rd., Aztec, NM 87410     Santa Fe, NM 87505       District IV     Santa Fe, NM 87505       1220 South St. Frances, Santa Fe, NM 87505     87505			STATE 6. State Oil & G	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:			7. Lease Name or Unit Agreement Name: VPR B	
Oil Well Gas Well Other X Coalbed Methane				
2. Name of Operator EL PASO ENERGY RATON, L.L.C.			8. Well No.	53X
3. Address of Operator         P.O. Box 190, Raton, NM 87740         4. Well Location			9. Pool name or V	Vildcat
Unit Letter <u>J: 1429</u> feet from the <u>South</u> line and <u>1693</u> feet from the <u>East</u> line				
Section 19 Township 30N Range 18E NMPM COLFAX County				
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8512' (GL)				
11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING D				
	CHANGE PLANS	COMMENCE DRI	LLING OPNS. 🞆	
		CASING TEST AN CEMENT JOB	ID 🗌	
OTHER:		OTHER:		
<ol> <li>Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.</li> </ol>				
<ul> <li>06/16/04 Spud @ 6:30 a.m. Drill 11" surface hole to 350'. Run 8 jts. of 8 5/8", 24#, J55 ST&amp;C casing to 346'. Halliburton mixed and pumped 100 sks Midcon II PP, 14 ppg, yield 1.66 at 4 bpm with 100 psi with 6% salt, 5#/sx gilsonite, .3% versaset and .25 #/sk flocele. Circulate 9 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.</li> <li>06/17/04 Drill 7 7/8" hole from 350' - 2875'. Reached TD 2875' at 1:30 p.m. MIRU Schlumberger &amp; log well. Logger's TD at 961'. Ran 66 jts of 5 ½", 17#, J55 LT&amp;C casing at 2695'. MIRU Halliburton. Pumped 10 bbls water and 60 bbls gel pre flush. Pumped 578 sks Midcon II PP, 13 ppg, Yield 2.04 at 4 bpm with 350 psi, 6% salt, 5 lb/sx Gilsonite, .3% Versaset, .1% Super CBL and ¼ #/sk flocele. Plug down with 1400 psi. Float held. Circulated 62 bbls of cement to surface. Well shut in.</li> </ul>				
I hereby certify that the information above is true and complete to the best of my knowledge and belief.				
SIGNATURE Shirly nitchell TITLE Regulatory Analyst DATE 06/18/04				
Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785				
(This space for State use) APPPROVED BY				