

Submit to Appropriate District Office  
State Lease - 6 copies  
Fee Lease - 5 copies  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St Francis  
Santa Fe, NM 87505

Form O-100  
Revised March 25, 1999

WELL API NO.	30-007-20436
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
State Oil & Gas Lease No.	

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well: OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> DRY <input type="checkbox"/> OTHER _____	7. Lease Name or Unit Agreement Name  VPR A				
b. Type of Completion NEW <input checked="" type="checkbox"/> WORK <input type="checkbox"/> PLUG <input type="checkbox"/> DIFF. WELL OVER DEEPEN BACK RESVR. OTHER	8. Well No  126				
2. Name of Operator  EL PASO ENERGY RATON, L.L.C.	9. Pool name or Wildcat  Stubblefield Canyon Raton - Vermejo Gas				
3. Address of Operator  PO BOX 190 RATON, NEW MEXICO 87740					
4. Well Location  Unit Letter M : 217 Feet From The South Line and 244 Feet From The West Line Section 22 Township 32N Range 19E NMPM Colfax County					
10. Date Spudded 02/05/04	11. Date T.D. Reached 02/06/04	12. Date Compl. (Ready to Prod.) 06/08/04	13. Elevations (DF& R(B. RT. GR. etc.) 8553' (GL)	14. Elev. Casinghead 8553'	
15. Total Depth 3040'	16. Plug Back T.D. 2968'	17. If Multiple Compl. How Many Zones?	18. Intervals Drilled By 0 - TD	Rotary Tools NONE	Cable Tools NONE
19. Producing Interval(s). of this completion - Top. Bottom. Name 1471' - 2724' Vermejo - Raton Coals				20. Was Directional Survey Made NO	
21. Type Electric and Other Logs Run Mud Log. Epithermal Neutron Litho Density. Array Induction Linear Correlation. and Acoustic Cement Bond Log				22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)							
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED		
8 5/8"	23	364'	11"	100 sks	None		
5 1/2"	15.5	2978'	7 7/8"	481 sks			
24. LINER RECORD			25. TUBING RECORD				
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2 7/8"	2795'	No
26. Perforation record (interval, size, and number) 2718' - 2724' 24 Holes 2690' - 2693' 12 Holes 2673' - 2676 12 Holes 2593' - 2598' 20 Holes 2436' - 2440' 16 Holes 1564' - 1572' 32 Holes 1504' - 1506', 1510' - 1513' 20 Holes 1471' - 1474' 12 Holes				27. ACID. SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. DEPTH INTERVAL 1471' - 2724'			AMOUNT AND KIND MATERIAL USED 156,960 lbs 16/30 brown sand

28. PRODUCTION							
Date First Production 06/14/04		Production Method (Flowing, gas lift, pumping - Size and type pump) Pumping water up 2 7/8" tubing w/30-N-95 PC Pump. Flowing gas up 5 1/2" Casing			Well Status (Prod. or Shut-in) Prod.		
Date of Test 06/14/04	Hours Tested 24 hrs.	Choke Size Full 2"	Prod'n For Test Period	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl. 293	Gas - Oil Ratio N/A
Flow Tubing Press	Casing Pressure 0	Calculated 24- Hour Rate	Oil - Bbl N/A	Gas - MCF 0	Water - Bbl 293	Oil Gravity - API - (Corr.) N/A	
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold, used for fuel.						Test Witnessed By: Jerry Colburn	
30. List Attachments							
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief.							
Signature: Shirley Mitchell Printed Shirley A. Mitchell Title Regulatory Analyst Date 06/28/04							

## INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T. Raton Top <u>644'</u>
T. Blinebry	T. Gr. Wash	T. Morrison	T. Vermejo <u>2,440'</u>
			Trinidad <u>2,770'</u>
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS  
OR ZONES

No. 1, from.....to.....  
No. 2, from.....to.....  
No. 3, from.....to.....  
No. 4, from.....to.....

## IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....  
 No. 2, from.....to.....feet.....  
 No. 3, from.....to.....feet.....

## LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology

From	To	Thickness In Feet	Lithology