

Office  
District I  
1625 N. French Dr., Hobbs, NM 87240  
District II  
811 South First, Artesia, NM 87210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 South Pacheco, Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION  
1220 South St. Francis  
Santa Fe, NM 87505

Form C-103  
Revised March 25, 1999

WELL API NO. 30-007-20447	
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>	
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name:  VPR A	
8. Well No. 140	
9. Pool name or Wildcat	
4. Well Location Unit Letter H : 1368 feet from the North line and 1148 feet from the East line Section 25 Township 32N Range 19E NMPM COLFAX County	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8120' (GR)	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/> PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPLETION <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: COMPLETION <input checked="" type="checkbox"/>

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).  
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

03/09/04 Patterson ran cement bond log. Cement Top estimated at 129'.  
07/01/04 Patterson perf'd 1<sup>st</sup> stage: 2328'-2340' 48 Holes  
HES frac'd 1<sup>st</sup> stage: Pumped 901 mscf 70 quality nitrogen foam with 67,488 lbs of 16/30 brown sand at 11.1 bpm, ATP 1332 psi, Final 502 psi.  
Patterson perf'd 2<sup>nd</sup> stage: 2140'-2144' 16 Holes  
HES frac'd 2<sup>nd</sup> stage: Pumped 339 mscf 70 quality nitrogen foam with 25,260 lbs of 16/30 brown sand at 7.1 bpm, ATP 888 psi, Final ISIP 621 psi.  
07/05/04 Installed rods, tubing, and pump. Well is ready to be tested and placed on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley A. Mitchell TITLE Regulatory Analyst DATE 07/30/04  
Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)  
APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 8/9/04  
Conditions of approval, if any: