

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St Francis, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St Francis
Santa Fe, NM 87505

AUG 30 2004

Form C-103
Revised March 25, 1999

WELL API NO.

30-007-20506

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

VPR D

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other COALBED METHANE

2. Name of Operator

EL PASO ENERGY RATON, L.L.C.

3. Address of Operator

P.O. BOX 190 RATON, NM 87740

8. Well No. 161

9. Pool name or Wildcat

4. Well Location

Unit Letter I : 1467 feet from the South line and 1013 feet from the East line

Section 16 Township 30N Range 17E NMPM COLFAX County

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

9087' (GR)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐ COMPLETION ☒

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

06/12/04 Patterson ran Cement Bond Log. Estimated Cement Top at surface. ✓

06/16/04 Patterson perf'd 1st stage: 2695'-2702' 28 Holes

HES frac'd 1st stage: Pumped fracture treatment with 48,618 lbs of 16/30 sand, Avg Pres 2314 psi, Avg Rate 19.6 bpm, ISIP 2545 psi.

Patterson perf'd 2nd stage: 2562'-2565', 2631'-2634' 24 Holes

HES frac'd 2nd stage: Pumped fracture treatment with 3,753. lbs of 16/30 sand. Screened Out.

Patterson perf'd 3rd stage: 2468'-2475' 28 Holes

HES frac'd 3rd stage: Pumped fracture treatment with 54,832 lbs of 16/30 sand, Avg Pres 2805 psi, Avg Rate 18.0 bpm, ISIP 2876 psi.

06/18/04 Installed rods, tubing, and pump. Well is ready to be tested and put on production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 08/23/04

Type or print name: Shirley A. Mitchell Telephone No.: (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 9/1/04

Conditions of approval, if any: