Submit 3 Copies To Appropriate District Office	State of New Mexico	Form C-103
District I	Energy, Minerals and Natural Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240 District II	LECENT	WELL API NO.
1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVATION DIVISION	30-007-20551 7. Indicate Type of Lease
District III 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr. 1 4. 2	STATE FEE S
District IV	Sania Fe, NIVI 8/303	7 State Oil & Gas Lease No
1220 S. St. Francis Dr., Santa Fe, NM 87505	CIL CONSERV	ATION
	ICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
	OSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A ICATION FOR PERMIT" (FORM C-101) FOR SUCH	
PROPOSALS.)		8. Well Number 64
1. Type of Well: Oil Well	Gas Well  Other Coalbed Methane	
2. Name of Operator EL PASO	D ENERGY RATON, L.L.C.	9. OGRID Number
3. Address of Operator		10. Pool name or Wildcat
P.O. BO	X 190, RATON, NM 87740	
4. Well Location		
Unit Letter J:	1710 feet from the South line and	1725 feet from the <u>East</u> line
Section 6		NMPM Colfax County
	11. Elevation (Show whether DR, RKB, RT, GR, 8,013' (GL)	etc.)
Pit or Below-grade Tank Application ☐  Pit type Depth to Groundy		Distance from wagnest supplier
		Distance from nearest surface water
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF IN	NTENTION TO: S	UBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON   REMEDIAL V	
TEMPORARILY ABANDON		DRILLING OPNS.⊠ PAND A □
PULL OR ALTER CASING	MULTIPLE COMPL CASING/CEN	ENT JOB
OTHER:	☐ OTHER:	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion		
or recompletion.		
02/10/05 Spud @ 6:15 a.m., D	orill 11" surface hole to 346'. Run 8 jts. of 8 5/8'	. 24#, J55 ST&C casing to 336'.
Halliburton mixed and pumped 100 sx Midcon II, 14 ppg, yield 1.66. Circulate 5 bbls of cement to surface.		
WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.		
02/11/05 Drill 7 7/8" hole from 346' - 2,665'. Reached TD 2,665' at 6:30 p.m.		
MIRU Patterson and log well. Logger's TD at 2,644'.  Ran 62 jts of 5 ½", 15.5#, J55 LT&C casing to 2,572'.		
MIRU Halliburton. Pumped water and gel spacer at 4 bpm, with 80 psi. Pumped 443 sks Midcon II		
at 13 ppg, 2.04 yield. Bumped plug with 1489 psi. Circulated 19 bbls of cement to surface. Well shut in.		
	above is true and complete to the best of my know closed according to NMOCD guidelines , a general perm	
SIGNATURE Shifty A Tritchell TITLE Regulatory Malyst DATE 02/11/05		
Type or print name Shirley A. Mychell E-mail address: shirley.mitchell@elpaso.com Telephone No. (505) 445-6785		
For State Use Only	NA / / Z man address. Shirtey mintenent	, /
16/	11 Som	2/14/25
APPROVED BY: 4	TITLE	DATE 2/14/05
Conditions of Approval (if apy):	/	
•		