| Office State of New Mexico   | Form C-103   |
|--|--|
| District I Energy, Minerals and Natural Resources  | May 27, 2004   |
| 1625 N. French Dr., Hobbs, NM 88240  | WELL APINO.  |
| District II 1301 W Grand Ave Artesia NM 88210 OIL CONSERVATION DIVISION  | 30-007-20549   |
| 1301 W. Grand Ave., Artesia, NM 88210  District III  1000 Rio Brazos Rd. Aztec, NM 87410  1220 South St. Francis Dr.   | Indicate Type of Lease   |
| 1000 Rio Brazos Rd., Aztec, NM 87410   |  |
| District IV Santa Fe, NM 87505   | 7. State Oil & Gas Lease No.   |
|  | ervation Division  |
| SUNDRY NOTICES AND REPORTS ON WELLS  | int Francis Drive  |
| SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  | Fe, NM 37505 Name of Offic Agreement Name  |
| DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH  | VPR CH   |
| PROPOSALS.)  |  |
| 1. Type of Well: Oil Well Gas Well Other STRAT TEST  | 8. Well Number 39  |
| 2. Name of Operator  | 9. OGRID Number  |
| EL PASO ENERGY RATON, L.L.C.   | 180514   |
| 3. Address of Operator   | 10. Pool name or Wildcat   |
| P.O. BOX 190, RATON, NM 87740  |  |
| 4. Well Location   | 10000  |
| Unit Letter <u>D</u> : <u>1310</u> feet from the <u>North</u> line and   | 712 feet from the West line  |
|  |  |
| Section Township bitt  | NMPM Colfax County   |
| 11. Elevation (Show whether DR, RKB, RT, GR,   | etc.)  |
| 7,905' (GL)  | The second secon |
|  |  |
| Pit typeDepth to GroundwaterDistance from nearest fresh water well   | _ Distance from nearest surface water  |
| Pit Liner Thickness: mil Below-Grade Tank: Volume bbls   | Construction Material  |
|  |  |
| 12. Check Appropriate Box to Indicate Nature of Notice, Report or Oth  | er Data  |
| NOTICE OF INTENTION TO   | IDSECTIONS DEDOCT OF   |
|  | JBSEQUENT REPORT OF:   |
| PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WO   | ORK ALTERING CASING  |
|  |  |
| TEMPORARILY ABANDON I I CHANGE PLANS I I I COMMENCE D  | RILLING OPNS. TIP AND A 🔻  |
|  | RILLING OPNS. P AND A  |
| PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEME  | , —  |
|  | , —  |
| PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEME  | , —  |
| PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEME OTHER:   OTHER:  | ENT JOB  |
| PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEME  OTHER:   OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail   | S, and give pertinent dates, including estimated date  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER: OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions   | S, and give pertinent dates, including estimated date  |
| PULL OR ALTER CASING   MULTIPLE COMPL   CASING/CEME  OTHER:   OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail   | S, and give pertinent dates, including estimated date  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER: OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER: OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Rar  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'. To 02/18/05 Continuous core to TD at 1,950'.   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion 14 1/2" surface casing to 228'.  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion a 4 ½" surface casing to 228'.   |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD 02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950'.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD  02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950'.  Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plugger.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER: OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD  02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950' Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plug to Total cement used was 140 sks Class G.   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD  02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950'.  Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plugger.  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'.   |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER: OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD  02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950' Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plug to Total cement used was 140 sks Class G.   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  |
| PULL OR ALTER CASING MULTIPLE COMPL CASING/CEME  OTHER: OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'.  To  02/18/05 Continuous core to TD at 1,950'.  Schlumberger ran Induction and Neutron Density Logs. Logger's TD  02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950' Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plug to Total cement used was 140 sks Class G.   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  |
| OTHER:  CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  CASING/CEME  OTHER:  OTHER:  OTHER:  CASING/CEME  OTHER:  OTHER:  OTHER:  OTHER:  CASING/CEME  OTHER:  OT | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  |
| PULL OR ALTER CASING   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  |
| OTHER:    OTHER:   OTHER:  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  |
| PULL OR ALTER CASING   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  |
| OTHER:    OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  ledge and belief. I further certify that any pit or belowit  or an (attached) alternative OCD-approved plan  y Analyst DATE 02-25-05  |
| OTHER:    OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  |
| OTHER:    OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER:   OTHER:     OTHER  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  ledge and belief. I further certify that any pit or belowit  or an (attached) alternative OCD-approved plan  y Analyst DATE 02-25-05  |
| OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'. To 02/18/05 Continuous core to TD at 1,950'. Schlumberger ran Induction and Neutron Density Logs. Logger's TD 02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950' Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plugger Total cement used was 140 sks Class G.  02/21/05 Clean location., close pit, and restore location to original condition.  I hereby certify that the information above is true and complete to the best of my know grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general perm SIGNATURE Shirley Mitchell E-mail address: shirley.mitchell@e  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228.  at 1,948'. to 1,450'. well to surface.  ledge and belief. I further certify that any pit or belowit or an (attached) alternative OCD-approved plan .  y Analyst DATE 02-25-05  lipaso.com Telephone No. (505) 445-6785   |
| OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 1/2" hole to 330'. Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330'. To 02/18/05 Continuous core to TD at 1,950'. Schlumberger ran Induction and Neutron Density Logs. Logger's TD 02/19/05 TiH with DP to bottom. Mix and pump cement. Pumped from 1,950' Pull up to 1,200'. Tripped back to 1,450', tag cement, and stage plug to Total cement used was 140 sks Class G.  02/21/05 Clean location., close pit, and restore location to original condition.  I hereby certify that the information above is true and complete to the best of my know grade tank has been/will be constructed or closed according to NMOCD guidelines , a general perm SIGNATURE  Shirley Mitchell E-mail address: shirley.mitchell@c  | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228'.  at 1,948'. to 1,450'. well to surface.  ledge and belief. I further certify that any pit or belowit  or an (attached) alternative OCD-approved plan .  y Analyst DATE 02-25-05  |
| OTHER:  13. Describe proposed or completed operations. (Clearly state all pertinent detail of starting any proposed work). SEE RULE 1103. For Multiple Completions or recompletion.  12/07/04 Mack Drilling spudded the core hole. Drilled a 6 ½" hole to 330". Ran Mixed and pumped 32 sks class G cement to surface.  01/29/05 MIRU Boart Longyear Core Rig. Drilled cement out to 330". To 02/18/05 Continuous core to TD at 1,950". Schlumberger ran Induction and Neutron Density Logs. Logger's TD 02/19/05 TIH with DP to bottom. Mix and pump cement. Pumped from 1,950" Pull up to 1,200". Tripped back to 1,450", tag cement, and stage plug to 1,200". Tripped back to 1,450", tag cement, and stage plug to 1,200". Clean location., close pit, and restore location to original condition.  I hereby certify that the information above is true and complete to the best of my know grade tank has been/will be constructed or closed according to NMOCD guidelines , a general perm SIGNATURE  Shirley Mitchell E-mail address: shirley.mitchell@e   | s, and give pertinent dates, including estimated date: Attach wellbore diagram of proposed completion at 4 ½" surface casing to 228.  at 1,948'. to 1,450'. well to surface.  ledge and belief. I further certify that any pit or belowit or an (attached) alternative OCD-approved plan .  y Analyst DATE 02-25-05  lipaso.com Telephone No. (505) 445-6785   |