

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 South St. Frances, Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Frances
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-007-20591
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Coalbed Methane		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
2. Name of Operator EL PASO ENERGY RATON, L.L.C.		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 190, Raton, NM 87740		7. Lease Name or Unit Agreement Name: VPR B
4. Well Location Unit Letter D : 1299 feet from the North line and 1257 feet from the West line Section 27 Township 30N Range 18E NMPM COLFAX County		8. Well No. 90
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 8,232' GL		9. Pool name or Wildcat

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work).
SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

03/06/05 Spud @ 1:00 p.m. Drill 11" surface hole to 324'. Run 7 jts. of 8 5/8", 24#, J55 ST&C casing to 314'. Halliburton mixed and pumped 100 sks Midcon II PP, 14 ppg, yield 1.66 at 4 bpm with 100 psi with 6% salt, 5#/sx gilsonite, .3% versaset and .25 #/sk flocele. Circulate 5 bbls of cement to surface. WOC 8 hrs. Test surface 8 5/8" csg to 500 psi for 30 minutes.

03/07/05 Drill 7 7/8" hole from 324' - 2,755'. Reached TD 2,755' at 1:00 p.m. MIRU Patterson & log well. Logger's TD at 2,688'. Ran 64 jts of 5 1/2", 15.5#, J55 LT&C casing at 2,645'. MIRU Halliburton. Pumped 462 sks Midcon II PP, 13 ppg, Yield 2.04 at 4 bpm. Plug down with 1339 psi. Float held. Circulated 33 bbls of cement to surface. Well shut in.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Shirley Mitchell TITLE Regulatory Analyst DATE 03/21/05

Type or print name Shirley A. Mitchell Telephone No. (505) 445-6785

(This space for State use)

APPROVED BY [Signature] TITLE DISTRICT SUPERVISOR DATE 3/24/05
Conditions of approval, if any: