

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(505) 393-6161 Fax:(505) 393-0720
District II
1301 W. Grand Ave., Artesia, NM 88210
Phone:(505) 748-1283 Fax:(505) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-103
Permit 24628

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVIOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well:G 2. Name of Operator BOLD ENERGY, L.P. 3. Address of Operator 415 WEST WALL , , SUITE 500 MIDLAND , TX 79701 4. Well Location Unit Letter J : 1980 feet from the S line and 1980 feet from the E line Section 11 Township 09S Range 32E NMPM Lea County 11. Elevation (Show whether DR, KB, BT, GR, etc.) 4414 GR		WELL API NUMBER 30-025-37515
		5. Indicate Type of Lease S
		6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name JOSHUA STATE		
8. Well Number 001		
9. OGRID Number 233545		
10. Pool name or Wildcat		
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ TEMPORARILY ABANDON ☐ CHANGE OF PLANS ☐ PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐ Other: SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTER CASING ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDON ☐ CASING/CEMENT JOB ☐ Other: Drilling/Cement ☒		
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.		

Reached 11,075' TD on 2/6/06. Schlumberger log tools stopped @ 10,186', bridge. Pulled Platform Express from 10,186' to 8 5/8" shoe @ 3643'. Made bit trip, CO bridge and circ clean @ TD. Ran 276 jts - 5 1/2" 17# L-80 LTC csg & set @ 11,046' w/ FC @ 11,003'. Schlumberger pumped 150 bbls mud w/ 200 SCF nitrogen per bbl & cmt'd csg w/ 1150 sx 50:50 POZ-"H" w/ 10% bentonite, 5% salt, 0.4% D112, 0.2% D46 and 1/4 pps cello-flake followed by 600 sx "H" w/ 2% bentonite, 5% salt & 0.2% D46. BP w/ 1250 psi, floats held. Good circ but no cmt to surface. Install WH equip & CWI. RR 2/10/06.

Casing and Cement Program

Date	String	Fluid Type	Hole Size	Csg Size	Weight lb/ft	Grade	Est TOC	Dpth Set	Sacks	Yield	Class	1" Dpth	Pres Held	Pres Drop	Open Hole
01/03/06	Surf	FreshWater	17.5	13.375	48	H-40	0	425	450	1.34	C		1250	0	
01/08/06	Int1	Brine	12.25	8.625	32	J-55	410	3643	1350		POZ & C		1500	0	
02/09/06	Prod	Mud	7.875	5.5	17	L-80	200	11046	1750		POZ-"H"		1250	0	Y

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Electronically Signed TITLE Vice President DATE 3/8/2006
Type or print name Peggy Kerr E-mail address peggy.kern@boldenergy.com Telephone No. 432-686-1100

For State Use Only:

APPROVED BY: Paul Kautz TITLE Geologist DATE 3/9/2006 6:56:50 AM