

District II

1301 W. Grand Ave., Artesia, NM 88210
Phone:(505) 748-1283 Fax:(505) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

WELL API NUMBER

30-015-34639

5. Indicate Type of Lease

S

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

FREY BIR

8. Well Number

001

9. OGRID Number

25575

10. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVIOR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:G

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 S 4TH ST , ARTESIA , NM 88210

4. Well Location

Unit Letter P : 660 feet from the S line and 710 feet from the E line
Section 13 Township 17S Range 25E NMPM Eddy County

11. Elevation (Show whether DR, KB, BT, GR, etc.)

3441 GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit Type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐TEMPORARILY ABANDON ☐ CHANGE OF PLANS ☐PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

Other:

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTER CASING ☐COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDON ☐CASING/CEMENT JOB ☐Other: **Drilling/Cement** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/6/06 Set 9-5/8" 36# J-55 casing at 1246'. Cemented with 180 sx Thixotropic (yld 1.52, wt 14.6) and 210 sx 35-65-6 Poz "C" + .25#/sx Cellophane flakes + 5#/sx LCM-1 + 2% CaCl2 (yld 1.98, wt 12.5). Tailed in with 200 sx Class "C" + 1% CaCl2 (yld 1.34, wt 14.8). Cement did not circulate. Ran 1" cement to surface with 550 sx Class "C". Tested casing to 1500 psi for 30 min. WOC 53 hrs 15 min. Reduced hole to 8-3/4" and resumed drilling. **2/27/2006** Spudded well.

Casing and Cement Program

Date	String	Fluid Type	Hole Size	Csg Size	Weight lb/ft	Grade	Est TOC	Dpth Set	Sacks	Yield	Class	1" Dpth	Pres Held	Pres Drop	Open Hole
	Surf		17.5	13.375	48		0	377	400		C				
	Int1		12.25	9.625	36		0	1246	1140						

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Electronically Signed

TITLE Regulatory Agent

DATE 3/16/2006

Type or print name Debbie CaffallE-mail address debbiec@ypcnm.comTelephone No. 505-748-4376

For State Use Only:

APPROVED BY: Bryan ArrantTITLE GeologistDATE 3/16/2006 11:24:34 AM