

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP 20 N Broadway Oklahoma City, OK 73102		2. OGRID Number 6137
		3. API Number 30-015-39104
4. Property Code 38600	5. Property Name SNAPPING 2 STATE	6. Well No. 001Y

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	2	26S	31E	N	330	S	1710	W	EDDY

8. Pool Information

WILDCAT:BONE SPRING	96403
---------------------	-------

Additional Well Information

9. Work Type New Well	10. Well Type OIL	11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3240
14. Multiple N	15. Proposed Depth 13443	16. Formation 1st Bone Spring Sand	17. Contractor	18. Spud Date 6/2/2011
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water
Pit: ☐ Linear Synthetic ☐ Closed Loop System	☐ mils thick	☐ Clay	Pit Volume:	bbls Drilling Method: Fresh Water ☒ Brine ☐ Diesel/Oil-based ☐ Gas/Air ☐

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	925	900	0
Int1	12.25	9.625	40	4150	1400	0
Prod	8.75	5.5	17	13443	475	0
Prod	8.75	5.5	17	8300	1950	3650

Casing/Cement Program: Additional Comments

13-3/8" Surface Lead w/650 sx Cl C + 2% bwoc Calcium Chloride + 0.125#/sx CF + 4% bwoc Bentonite + 81.4% FW 13.5 ppg. Yld: 1.75 cf/sx. TOC @ surface. Tail w/ 250 sx Cl C + 2% bwoc Calcium Chloride + 0.125#/sx CF + 56.3% FW 14.8 ppg Yld: 1.35 cf/sx. 9-5/8" Intermediate Lead: 1100 sx (35:65) Poz (Fly Ash):Cl C + 5% bwow Sodium Chloride + 0.125#/sx CF + 6% bwoc Bentonite + 107.8% FW 12.5 ppg Yld: 1.96 cf/sx. TOC @ surface. Tail w/300 sx Cl C + 5% bwow Sodium Chloride + 0.125#/sx CF + 0.4% bwoc Sodium Metasilicate + 4% bwoc MPA-5 + 52.7% Wtr.14.8 ppg Yld: 1.34 cf/sx. 5-1/2" Production 1st Stage Lead: 450 sx (35:65) Poz (Fly Ash):Cl H + 5% bwow Sodium Chloride + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 2% bwoc Bentonite + 0.6% bwoc Sodium Metasilicate + 0.5% bwoc FL-52A + 102.5% FW, 12.5 ppg Yld: 2.00 cf/sk Tail: 1400 sx (50:50) Poz (Fly Ash):Cl H + 1% bwow Sodium Chloride + 0.2% bwoc R-3 + 0.125#/sx CF + 0.5% bwoc BA-10A + 4% bwoc MPA-5 + 58.3% FW 14.2 ppg. Yld: 1.2

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	
Annular	3000	3000	

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify that the drilling pit will be constructed according to NMOCD guidelines ☐ a general permit ☐ , or an (attached) alternative OCD-approved plan ☐ .	OIL CONSERVATION DIVISION	
Printed Name: Electronically filed by Randy Bolles	Approved By: Randy Dade	
Title: Manager, Regulatory Affairs	Title: District Supervisor	
Email Address: randy.bolles@dv.com	Approved Date: 6/2/2011 Expiration Date: 6/2/2013	
Date: 6/2/2011 Phone: 405-228-8588	Conditions of Approval Attached	

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(505) 393-6161 Fax:(505) 393-0720

District II
1301 W. Grand Ave., Artesia, NM 88210
Phone:(505) 748-1283 Fax:(505) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-102
Permit 132486

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-39104	2. Pool Code 96403	3. Pool Name WILDCAT;BONE SPRING
4. Property Code 38600	5. Property Name SNAPPING 2 STATE	6. Well No. 001Y
7. OGRID No. 6137	8. Operator Name DEVON ENERGY PRODUCTION COMPANY, LP	9. Elevation 3240


10. Surface Location

UL - Lot N	Section 2	Township 26S	Range 31E	Lot Idn	Feet From 330	N/S Line S	Feet From 1710	E/W Line W	County EDDY
---------------	--------------	-----------------	--------------	---------	------------------	---------------	-------------------	---------------	----------------

11. Bottom Hole Location If Different From Surface

UL - Lot C	Section 2	Township 26S	Range 31E	Lot Idn C	Feet From 330	N/S Line N	Feet From 1660	E/W Line W	County EDDY
12. Dedicated Acres 160.00		13. Joint or Infill		14. Consolidation Code			15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles
Title: Manager, Regulatory Affairs
Date: 6/2/2011

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Frank Jaramillo
Date of Survey: 3/22/2011
Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: SNAPPING 2 STATE #001Y

API: 30-015-39104

Created By	Comment	Comment Date
barnettj	Pressure Control Equipment: The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe. The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in t	6/2/2011
Artesia	Land S/S	6/2/2011

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: SNAPPING 2 STATE #001Y

API: 30-015-39104

OCD Reviewer	Condition
Artesia	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string