District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-101 August 1, 2011

Permit 144684

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

Operator DEVON ENERGY PR	2. OGRID Number 6137		
20 N Broadway		3. API Number	
Oklahoma City, OK 73102		30-015-40036	
4. Property Code	5. Property Name	6. Well No.	
38433	DIAMOND PWU 22	004H	

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	21	198	29E	P	650	S	880	E	EDDY

8. Pool Information

PARKWAY:BONE SPRING	49622

Additional Well Information

9. Work Type New Well	10. Weti		11. Cable/Rotary	12. Lesse Type State	13. Ground Level Elevation 3339	
14. Multiple	15. Proposed Depth		16. Formation	17. Contractor	18. Spud Date	
N 13512		512	Bone Spring	200	3/30/2012	
Depth to Ground	water	•	Distance from nearest fresh water	r well	Distance to nearest surface water	

19. Proposed Casing and Cement Program

Туре	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	370	360	0
Int1	12.25	9.625	40	3600	1500	0
Prod	8.75	5.5	17	13512	1575	3100
Prod	8.75	5.5	17	8100	955	0

Casing/Cement Program: Additional Comments

13 3/8 w/360 sx Cl C + 2% CaCl + 1/4 lb/sx Cello flake, 9 5/8 w/1500 sx Cl C + 2% CaCl + 1/4 lb/sx Cello flake, 5 1/2 w/2530 sx Cl C + 2% CaCl + 1/4 lb/sx Cello flake. All cement volumes based on at least 25% excesses. Actual cement volumes will be adjusted based on fluid caliper and caliper log data. Positive standoff centralizers will be utilized for the production string every joint of casing from 100' MD above KOP or at the legal footage setback, whichever is deeper MD, up to TOC. Mud: 0-370' fresh, 8.4-9.0, 30-34 visc, N/C water loss. 370-3600' brine, 9.8-10.0, 28-32 visc, N/C water loss. 3600-13512' fresh, 8.6-9.0, 28-32 visc, N/C water loss. Necessary mud products for weight addition and fluid loss control will be on location at all times.

Proposed Blowout Prevention Program

Туре	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
Pipe	3000	3000	
DoubleRam	3000	3000	

I hereby certify that the information given of my knowledge and belief. I further certify that the drilling pit w		OIL CONSERVATION DIVISION		
NMOCD guidelines , a general pern OCD-approved plan .		Approved By: Randy Dade		
Printed Name: Electronically filed	by Randy Bolles	Title: District Supervisor		
Title: Manager, Regulatory Affair	S	Approved Date: 3/12/2012	Expiration Date: 3/12/2014	
Email Address: randy.bolles@dvr	ı.com			
Date: 3/8/2012	Phone: 405-228-8588	Conditions of Approval Attached		

District I 1625 N. French Dr., Hobbs, NM 88240

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u> 811 S. First St., Artesia, NM 88210

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-102 August 1, 2011

Permit 144684

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-40036	2. Pool Code 3. Pool 49622 PARKWAY;B		BONE SPRING
4. Property Code	5. Property N	6. Well No.	
38433	DIAMOND P	004H	
7. OGRID No.	8. Operator N	9. Elevation	
6137	DEVON ENERGY PRODUCT	3339	


10. Surface Location

- [ō	- 3			0-	3		5 9
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	P	21	198	29E		650	S	880	E	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	22	198	29E	P	650	S	330	E	EDDY
	cated Acres	13. J	oint or Infill	14	. Consolidation (Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 3/8/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 2/20/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: DIAMOND PWU 22 #004H

API: 30-015-40036

Created By	Comment	Comment Date
YSASAS	No H2S expected to be encountered.	2/22/2012
YSASAS	C-102 to be mailed next day via Fed-Ex.	2/22/2012
YSASAS	Depth to groundwater is 50' or more, but less than 100', distance to surface water is approximately 1000'; well is not in a wellhead protection area.	2/22/2012
YSASAS	The BOP system used to drill the intermediate hole will consist of a 13-3/8" 5M Double Ram & Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-3/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 5M system prior to drilling out the intermediate casing shoe. Pipe rams will be operated and checked each 24 hour period and blind rams tested each time the dri	3/8/2012
CSHAPARD	Land s/S	3/9/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: DIAMOND PWU 22 #004H

API: 30-015-40036

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string