

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-101
August 1, 2011
Permit 146957

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator Name and Address DEVON ENERGY PRODUCTION COMPANY, LP 20 N Broadway Oklahoma City, OK 73102		2. OGRID Number 6137
		3. API Number 30-015-40216
4. Property Code 38434	5. Property Name TURQUOISE PWU 27	6. Well No. 004H

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	27	19S	29E	M	340	S	340	W	EDDY

8. Pool Information

PARKWAY;BONE SPRING	49622
---------------------	-------

Additional Well Information

9. Work Type New Well	10. Well Type OIL	11. Cable/Rotary	12. Lease Type State	13. Ground Level Elevation 3300
14. Multiple N	15. Proposed Depth 12765	16. Formation 2nd Bone Spring Sand	17. Contractor	18. Spud Date
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

19. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	300	340	0
Int1	12.25	9.625	40	3500	1130	0
Int3	8.75	5.5	17	12765	1820	2850
Prod	8.75	5.5	17	7400	585	0

Casing/Cement Program: Additional Comments

13 3/8" Lead w/340 sx C1 C + 2% bwoc CaCl2 + 0.125 #/sx CF + 4% bwoc Bent, 14.8 ppg, 1.35 cf/sk; TOC sfc. 9 5/8" Lead w/830 sx C1 C + 5% bwow NaCL + 0.125 #/sx CF + 5% bwoc Bent, 12.7 ppg, 1.73 cf/sk; Tail w/300 sx C1 C + 5% bwow NaCL + 0.125 #/sx CF + 0.4% bwoc Na Metasilicate + 4% bwoc MPA,, 14.8 ppg, 1.33 cf/sk; TOC sfc. 5 1/2" 1st Lead w/585 sx C1 H + 5% bwow NaCL + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 2% bwoc Bent + 0.6% bwoc Na Metasilicate + 0.5% bwoc FL-52A, 11.8 ppg, 2.52 cf/sk; 2nd Lead w/375 sx C1 H + 1% bwow NaCL + 0.2% bwoc R-3 + 0.125 #/sx CF + 0.5% bwoc BA-10A + 4% bwoc MPA-5, 12.5 ppg, 1.95 cf/sk; Tail w/1,445 sx C1 H + 5% bwow NaCL + 0.3% bwoc CD-32 + 0.5% bwoc FL-25 + 2% bwoc Bent + 0.6% bwoc Na Metasilicate + 0.5% bwoc FL-52A, 14.8 ppg, 1.22 cf/sk; TOC 2850'.

Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	
Annular	3000	3000	

I hereby certify that the information given above is true and complete to the best of my knowledge and belief. I further certify that the drilling pit will be constructed according to NMOCD guidelines <input type="checkbox"/> , a general permit <input type="checkbox"/> , or an (attached) alternative OCD-approved plan <input type="checkbox"/> .	OIL CONSERVATION DIVISION
Printed Name: Electronically filed by Randy Bolles	Approved By: Randy Dade
Title: Manager, Regulatory Affairs	Title: District Supervisor
Email Address: randy.bolles@dvn.com	Approved Date: 4/30/2012 Expiration Date: 4/30/2014
Date: 4/26/2012 Phone: 405-228-8588	Conditions of Approval Attached

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Francis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

Form C-102
August 1, 2011
Permit 146957

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-015-40216	2. Pool Code 49622	3. Pool Name PARKWAY;BONE SPRING
4. Property Code 38434	5. Property Name TURQUOISE PWU 27	6. Well No. 004H
7. OGRID No. 6137	8. Operator Name DEVON ENERGY PRODUCTION COMPANY, LP	9. Elevation 3300

10. Surface Location

UL - Lot M	Section 27	Township 19S	Range 29E	Lot Idn	Feet From 340	N/S Line S	Feet From 340	E/W Line W	County EDDY
---------------	---------------	-----------------	--------------	---------	------------------	---------------	------------------	---------------	----------------

11. Bottom Hole Location If Different From Surface

11. Bottom Hole Location If Different From Surface									
UL - Lot P	Section 27	Township 19S	Range 29E	Lot Idn P	Feet From 990	N/S Line S	Feet From 340	E/W Line E	County EDDY
12. Dedicated Acres 160.00		13. Joint or Infill		14. Consolidation Code			15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

	<p align="center">OPERATOR CERTIFICATION</p> <p><i>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.</i></p> <p>E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs Date: 4/26/2012</p>		
	<p align="center">SURVEYOR CERTIFICATION</p> <p><i>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.</i></p> <p>Surveyed By: Filimon Jaramillo Date of Survey: 2/23/2012 Certificate Number: 12797</p>		

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: TURQUOISE PWU 27 #004H

API: 30-015-40216

Created By	Comment	Comment Date
dcook	The BOP system used to drill the intermediate and production holes will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the prior casing shoe. The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accesso	4/26/2012
CSHAPARD	Land s/S	4/27/2012
CSHAPARD	Land s/S	4/27/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137

Well: TURQUOISE PWU 27 #004H

API: 30-015-40216

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string