District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II

811 S. First St., Artesia, NM 88210

Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico

Form C-101 August 1, 2011

Permit 148924

Energy, Minerals and Natural Resources Oil Conservation Division

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

	DEVO	1. Ope ON ENERGY 333 V Oklaho		OGRID Nu 6137 API Numbe 30-015-40	r				
4. Property Code 39356				5. Property Name PERIDOT 13 STATE				6. Well No. 006H	
-			61	7. S	urface Loc	ation			
UL - Lot K	Section 12	Township 198	Range 29E	Lot Idn K	Feet From 2085	N/S Line S	Feet From 1470	E/W Line W	County EDDY
			8.	Proposed	Bottom H	ole Locat	ion		\$
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
				9. P	ool Inform	ation			
URKEY T	RACK;BO	NE SPRING		10000					60660
				Addition	al Well Inf	formation	I.	38	
11. Work Type New Well		12. Well Ty OIL	pe	13. Cable/Rotary			14. Lease Type State	R0(333073)	3379

11. Work Type 12. Well Type New Well OIL			13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3379
		osed Depth 18. Formation 3986 2nd Bone Spring Sand		19. Contractor	20. Spud Date
Depth to Ground	water		Distance from nearest fresh water w	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	310	345	0
Int1	12.25	9.625	40	3740	1185	0
Prod	8.75	5.5	17	13986	1915	0
Prod	8.75	5.5	17	6502	575	3240

Casing/Cement Program: Additional Comments

13 3/8" - Tail: 345 sx C+ 2% bwoc Calcium Chloride + 0.125#/sx Poly-E-Flake + 63.1% FW, 14.8 ppg Yield: 1.35 cf/sk TOC @ surf. 9 5/8" - Lead: 860 sx (65:35) Cla CPoz (Fly Ash): + 5% bwow Sodium Chloride + 0.125#/sx Poly-E-Flake + 6% bwoc Bentonite + 70.9% FW, 12.9 ppg Yield: 1.85 cf/sk TOC @ surf. Tail: 325 sx C + 0.125#/sx Poly-E-Flake + 63.5% Wtr, 14.8 ppg . Yield: 1.33 cf/sk. 5 1/2" - 1st Lead: 185 sx (50:50) C1 H Poz (Fly Ash) + 10% bwoc Bentonite + 8#/sx Sodium Chloride + 0.125#/sx Poly-E-Flake + 0.3% bwoc HR-601 + 0.3% bwoc Econolite + 77.2% FW, 11.8 ppg. Yield: 2.52 cf/sk 2nd Lead: 390 sx (65:35) Cl H Poz (Fly Ash) + 6% bwoc Bentonite + 0.125#/sx Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg Yield: 1.95 cf/sk Tail: 1915 sx (50:50) Cl H Poz (Fly Ash) + 1 lb/sk Sodium Chloride + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bentonite + 58.8% FW, 14.5 ppg Yield: 1.22 cf/sk.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

best of my knowledge and belief.	given above is true and complete to the	OIL CONSERVATION DIVISION			
I further certify I have complied wit 19.15.14.9 (B) NMAC , if applica		Approved By: Randy Dade			
Signature:					
Printed Name: Electronically file	ed by Randy Bolles	Title: District Supervisor			
Title: Manager, Regulatory Affa	iirs	Approved Date: 10/10/2012	Expiration Date: 10/10/2014		
Email Address: randy.bolles@d	vn.com				
Date: 9/13/2012	Phone: 405-228-8588	Conditions of Approval Attached			

District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

District IV

State of New Mexico

Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 148924

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code		ol Name
30-015-40780	60660		K;BONE SPRING
4. Property Code	5. Property	6. Well No.	
39356	PERIDOT 1:	006H	
7. OGRID No. 6137	8. Operator DEVON ENERGY PRODU	9. Elevation 3379	

10. Surface Location

5	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
5	K	12	198	29E		2085	S	1470	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	13	198	29E	N	330	S	1980	W	EDDY
12. Dedicated Acres 160.00		13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 9/13/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 5/5/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: PERIDOT 13 STATE #006H

API: 30-015-40780

Created By	Comment	Comment Date
barnettj	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe. In addition to the rams and annular preventer, additional BOP accessories include a kelly codk, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	7/25/2012
CSHAPARD	Reject; drilling restricted due to potash	9/7/2012
CSHAPARD	Intrepid approved waiver letter. Land s/S	10/10/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: PERIDOT 13 STATE #006H

API: 30-015-40780

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string