<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN	, PLUGDACK, OK ADD A ZONE
Operator Name and Address	2. OGRID Number
DEVON ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue	6137
Oklahoma City, OK 73102	3. API Number
Oklaholia City, Ok 73102	30-025-40898

4. Property Code 5. Property Name 6. Well No. THISTLE UNIT 30884 043H

7 Surface Location

2 194		194	194	7. 3	urrace Loc	ation	NI 33	0 (0.00)		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	l
M	33	238	33E	M	200	S	500	W	LEA	l

8. Proposed Bottom Hole Location

1					- Dottom II	ore motures	-	9	
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	33	238	33E	D	330	N	500	W	Lea

9. Pool Information

TRIPLE X;BONE SPRING	59900

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3656
16. Multiple 17. Proposed Depth N 15799				20. Spud Date
Depth to Ground	water	Distance from nearest fresh water w	velt	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1350	1170	0
Int1	12.25	9.625	40	5200	1535	0
Prod	8.75	5.5	17	15799	300	4700
Prod	8.75	5.5	17	10500	2145	0

Casing/Cement Program: Additional Comments

13-3/8" Surface Lead: 835 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 4% bwoc Bent + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sk; TOC @ surface. Tail: 335 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg Yld: 1.35 cf/sx. 9-5/8" Intermediate Lead: 1110 sx (65:35) C1 C Cmt:Poz (Fly Ash): + 5% bwow NaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx; TOC @ surface. Tail: 425 sx Cl C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% W, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production 1st Stage Lead: 820 sx (65:35) Cl H Cmt:Poz (Fly Ash) + 6% bwoc Bent + 0.2% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx; Tail:1325 sx (50:50) C1 H Cmt:Poz (Fly Ash) + 1 #/sx NaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx; DV TOOL @ 6500'. Note: See Permit Comments for 2nd Stage Lead Details.

22. Proposed Blowout Prevention Program

	22. Proposed Diowout Prevention Program								
Type	Working Pressure	Test Pressure	Manufacturer						
Annular	3000	3000							
DaublaDam	2000	2000							

best of my knowledge and belie		OIL CONSERVATION DIVISION				
I further certify I have comp 19.15.14.9 (B) NMAC ⊠, if a	lied with 19.15.14.9 (A) NMAC 🛮 and/or applicable.	Approved By: Paul Kautz				
Signature:		1400				
Printed Name: Electronic	ally filed by Randy Bolles	Title: Geologist				
Title: Manager, Regulator	y Affairs	Approved Date: 12/26/2012	Expiration Date: 12/26/2014			
Email Address: randy.bol	les@dvn.com					
Date: 12/19/2012	Phone: 405-228-8588	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

1220 S. St Francis Dr. Santa Fe, NM 87505

August 1, 2011

Form C-102

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name	
30-025-40898	59900	TRIPLE X;BONE SPRING	
4. Property Code	5. Property		6. Well No.
30884	THISTLE		043H
7. OGRID No. 6137	8. Operator DEVON ENERGY PRODU		9. Elevation 3656


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	33	238	33E		200	S	500	W	LEA

11. Bottom Hole Location If Different From Surface

						The care and			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	33	238	33E	D	200	S	500	W	LEA
	cated Acres	13. Ј	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 12/19/2012

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filiman Jaramillo Date of Survey: 11/8/2012 Certificate Number: 1397

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: THISTLE UNIT #043H

API: 30-025-40898

Created By	Comment	Comment Date
doook	Pressure Control Equipment: The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the surface casing shoe.	12/19/2012
doook	The BOP system used to drill the production hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 as a 3M system prior to drilling out the intermediate casing shoe.	12/19/2012
d∞ok	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 5,000 psi WP.	12/19/2012
dcook	2nd Stage Lead: 155 sx CI C Cmt + 3% bwoc Econolite + 0.125 #/sx Poly-E-Flake + 82.4% FW, 11.4 ppg, Yld: 2.87 cf/sk; Tail:145 sx CI C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% FW, 14.8 ppg Yld:1.33cf/sx; TOC @ 4700°.	12/19/2012
pkautz	Land s/S	12/20/2012
DMULL	OCD Hobbs has received form C-144CLEZ. OCD Permit # P1-05548.	12/26/2012
DMULL	Correcting OCD Permit # P1-05547	12/26/2012

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: THISTLE UNIT #043H

API: 30-025-40898

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string