<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

August 1, 2011

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, I	PLUGBACK, OK ADD A ZONE
Operator Name and Address	OGRID Number

DEVON ENERGY F	rtor Name and Address RODUCTION COMPANY, LP	3. API Number 30-015-41007 Property Name 6. Well No.	
	. Sheridan Avenue ma City, OK 73102		
4. Property Code	5. Property Name	6. Well No.	
38433	DIAMOND PWU 22	007H	

7. Surface Location

W 195	7. Surface Escation									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	1
I	21	198	29E	I	1970	S	170	E	EDDY	l

8. Proposed Bottom Hole Location

	or a control and								
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
I	22	198	29E	I	1750	S	330	E	Eddy

9. Pool Information

TURKEY TRACK:BONE SPRING	60660

Additional Well Information

11. Work Type 12. Well Type New Well OIL		13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3331	
16. Multiple 17. Proposed Depth N 11963		h 18. Formation 19. Contra 1st Bone Spring Sand		20. Spud Date	
Depth to Ground	water	Distance from nearest fresh water w	vell	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	200	210	
Int1	12.25	9.625	40	3550	1005	
Prod	8.75	5.5	17	11963	1630	
Prod	8.75	5.5	17	6320	460	3000

Casing/Cement Program: Additional Comments

13-3/8" Lead w/210 sx Cl C Cmt + 2% bwoc CalChl + 0.125#/sx Poly-EF + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx. 9-5/8" Lead w/650 sx (65:35) Cl C Cmt:Poz (Fly Ash): +5% bwow Sod Chl + 0.125#/sx Poly-EF +6% bwoc Bentonite + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx. Tail w/355 sx Cl C Cmt + 0.125#/sx Poly-EF + 63.5% Wtr, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" 1st Lead w/185 sx (50:50) Cl H Cmt:Poz (Fly Ash) + 10% bwoc Bentonite + 8#/sx Sod Chl + 0.125#/sx Poly-EF + 0.3% bwoc HR-601 + 0.3% bwoc Econolite + 77.2% FW, 11.8 ppg, Yld: 2.52 cf/sx. 2nd Lead w/ 275 sx(65:35) Cl H Cmt:Poz (Fly Ash) + 6% bwoc Bentonite + 0.125 #/sx Poly-EF # 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx. Tail w/ 1630 sx(50:50) Cl H Cmt:Poz (Fty Ash) + 1#/sx Sod Chl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bentonite + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx. TVD: 7127'

22. Proposed Blowout Prevention Program

-23		22. Proposed Diowout	rrevention rrogram	
Γ	Type	Working Pressure	Test Pressure	Manufacturer
	DoubleRam	3000	3000	
Г	Annulae	2000	2000	

best of my knowledge and belief.	ation given above is true and complete to the	OIL CONSERVATION DIVISION Approved By: Randy Dade				
I further certify I have complied 19.15.14.9 (B) NMAC ⊠, if app	d with 19.15.14.9 (A) NMAC And/or olicable.					
Signature:	M.Challe					
Printed Name: Electronically	y filed by Randy Bolles	Title: District Supervisor				
Title: Manager, Regulatory	Affairs	Approved Date: 1/23/2013	Expiration Date: 1/23/2015			
Email Address: randy.bolles	@dvn.com					
Date: 1/22/2013	Phone: 405-228-8588	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II

Phone:(575) 393-6161 Fax:(575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Poo	ol Name
30-015-41007	60660 TURKEY TRACK		K;BONE SPRING
4. Property Code	5. Property	Name	6. Well No.
38433	DIAMOND	PWU 22	007H
7. OGRID No.	8. Operator	Name	9. Elevation
6137	DEVON ENERGY PRODUC	CTION COMPANY, LP	3331


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
I	21	198	29E		1970	S	170	E	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Id	n Feet From	N/S Line	Feet From	E/W Line	County
7.5%	cated Acres	13. J	oint or Infill		14. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 1/22/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 9/6/2012 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: DIAMOND PWU 22 #007H

API: 30-015-41007

Created By	Comment	Comment Date
morawford	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Triple Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe.	1/22/2013
mcrawford	In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	1/22/2013
morawford	No H2S is anticipated to be encountered.	1/22/2013
mcrawford	Mud: 0-200' FW, 8.4-9.0, 30-34,N/C; 200'-3550' Brine, 9.6-10, 28-32, N/C; 3550'-11963' FW, 8.6-9.0, 28-32, N/C-12	1/22/2013
CSHAPARD	land s/S	1/22/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: DIAMOND PWU 22 #007H

API: 30-015-41007

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string