District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 <u>District II</u> 811 S. First St., Artesia, NM 88210 Phone: (575) 748-1283 Fax: (575) 748-9720

Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

<u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 161736

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

COGC	tor Name and Address PERATING LLC	OGRID Number 229137
	Concho Center land, TX 79701	3. API Number 30-025-40968
4. Property Code	5. Property Name	6. Well No.
39678	OSPREY 20 STATE COM	001H

7. Surface Location

7. Surface Location										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
I	20	218	34E	I	2450	S	330	E	LEA	l

8. Proposed Bottom Hole Location

	C. I Toposca Bottom Hote Escation								
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	29	218	34E	P	330	S	380	E	Lea

9. Pool Information

WC-025 G-07 S213430M;BONE SPRING	97962
----------------------------------	-------

Additional Well Information

11. Work Type 12. Weil Ty New Weil OIL		12. Well Type 13. Cable/Rotary OIL		15. Ground Level Elevation 3724	
16. Multiple N	17. Proposed Depth 19158	18. Formation Bone Spring	19. Contractor	20. Spud Date 5/5/2013	
Depth to Ground water		Distance from nearest fresh water	r well	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1980	1155	
Int1	12.25	9.625	36	5800	610	
Prod	7.875	5.5	17	19158	2330	5500

Casing/Cement Program: Additional Comments

Drill 17-1/2" hole to ~1980' w/ fresh water spud mud. Run 13-3/8" 54.5# J55 STC casing to TD and cement to surface in one stage. Will use 1" tubing and Class C w/ 2% CaCl2 to cement to surface, if necessary. Drill 12-1/4" hole to ~5800' with saturated brine water If losses occur in the Reef, will switch to fresh water to interval TD. Run 9-5/8" 36# J55 & 40# N80 BTC casing to TD with a DV tool placed ~ 100' above the Reef. Plan to circulate cement on both stages. Drill 7-7/8" vertical hole, curve, and lateral to 19158' with cut brine. Run 5-1/2" 17# P110 LTC casing to TD and cement to 5500' (300' overlap) surface in one stage.

22. Proposed Blowout Prevention Program

22. Troposed Blowdet Trevention Trogram									
Type	Working Pressure	Test Pressure	Manufacturer						
DoubleRam	3000	3000	Cameron						

best of my knowledge and belie		OIL CONSERVATION DIVISION				
I further certify I have comp 19.15.14.9 (B) NMAC ⊠, if a	lied with 19.15.14.9 (A) NMAC 🛮 and/or applicable.	Approved By: Paul Kautz				
Signature:						
Printed Name: Electronic	ally filed by Diane Kuykendall	Title: Geologist				
Title: Production Reporti	ng Mgr	Approved Date: 2/1/2013	Expiration Date: 2/1/2015			
Email Address: dkuykend	dall@conchoresources.com					
Date: 1/31/2013	Phone: 432-683-7443	Conditions of Approval Attached				

District I
1625 N. French Dr., Hobbs, NM 88240
Phones(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phones(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones(505) 334-6178 Fax:(505) 334-6170

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

District IV

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 161736

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	WC-025 G-07	3. Pool Name
30-025-40968	97962		\$213430M;BONE SPRING
4. Property Code	5. Proper		6. Well No.
39678	OSPREY 20 S		001H
7. OGRID No.	8. Operat		9. Elevation
229137	COG OPER		3724

10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
I	20	218	34E		2450	S	330	E	LEA

11. Bottom Hole Location If Different From Surface

			Dottom						
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	29	218	34E	P	330	S	380	E	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall Title: Production Reporting Mgr

Date: 1/31/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: chad harcrow Date of Survey: 12/20/2012 Certificate Number: 17777

Permit Comments

Operator: COG OPERATING LLC , 229137 Well: OSPREY 20 STATE COM #001H

API: 30-025-40968

Created By	Comment	Comment Date
pkautz	Land s/S	2/1/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-05701	2/1/2013

Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137 Well: OSPREY 20 STATE COM #001H API: 30-025-40968

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string