<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources

Santa Fe, NM 87505

Oil Conservation Division 1220 S. St Francis Dr.

August 1, 2011

Form C-101

	APPLICATION FOR PERMIT TO DRILL	L, RE-ENTER, DEEPEN	, PLUGBACK, OR ADD A ZONE
--	---------------------------------	---------------------	---------------------------

1. Operat	or Name and Address	2. OGRID Number		
	DEVON ENERGY PRODUCTION COMPANY, LP			
	333 W. Sheridan Avenue Oklahoma City, OK 73102			
Oklanon	a ory, or 75102	30-025-40986		
4. Property Code	5. Property Name	6. Well No.		
39699	MONK 21 STATE COM	001H		

7 Surface Location

12		2 194	19	7.0	di lace Loc	ution	20	7.00	
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	21	218	34E	D	330	N	460	W	LEA

8. Proposed Bottom Hole Location

	OT A TOPOGOG DOTTOM AND DOCUMENT									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
M	21	21S	34E	M	330	S	660	W	Lea	

9. Pool Information

BERRY:BONE SPRING, SOUTH	96660

Additional Well Information

11. Work Type New Well	12. Wett Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3734	
16. Multiple 17. Proposed Depth N 15348		18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date	
Depth to Ground	water	Distance from nearest fresh water w	rel1	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1900	1630	0
Int1	12.25	9.625	40	4200	1175	0
Prod	8.75	5.5	17	15348	350	3700
Prod	8.75	5.5	17	10200	2060	0

Casing/Cement Program: Additional Comments

13-3/8" Surface Lead: 1115 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 4% bwoc Bent + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sk, TOC @ surface. Tail: 515 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sk. 9-5/8" Intermediate Lead: 815 sx (65:35) Cl C Cmt:Poz (Fly Ash): +5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sk, TOC @ surface. Tail: 360 sx Cl C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% W, 14.8 ppg, Yld: 1.33 cf/sk. 5-1/2" Production 1st Stage Lead: 630 sx(65:35) Cl H Cmt:Poz(Fly Ash) + 6% bwoc Bent + 0.2% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sk, Tail: 1430 sx(50:50) Cl H Cmt:Poz(Fly Ash) + 1 #/sx CaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sk. DV TOOL at 6000ft See 2nd Stage Production Cmt in Comments section.

22. Proposed Blowout Prevention Program

		22. Proposed Dionout	rrevention rrogram	
ſ	Type	Working Pressure	Test Pressure	Manufacturer
	Annular	3000	3000	
1	DoublePam	2000	3000	

 I hereby certify that the information best of my knowledge and belief. 	n given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complied w 19.15.14.9 (B) NMAC ⊠, if applic	ith 19.15.14.9 (A) NMAC 🛮 and/or able.	Approved By: Paul Kautz				
Signature:		Talkii 14				
Printed Name: Electronically fr	led by Randy Bolles	Title: Geologist				
Title: Manager, Regulatory Af	fairs	Approved Date: 2/7/2013	Expiration Date: 2/7/2015			
Email Address: randy.bolles@	ivn.com					
Date: 2/5/2013	Phone: 405-228-8588	Conditions of Approval Attached				

<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

Shit S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 161957

WELL LOCATION AND ACREACE DEDICATION PLAT

	VELL LOCATION AND ACK	EAGE DEDICATION FL	AI	
1. API Number	2. Pool Code	3. Poo	ol Name	
30-025-40986	96660 BERRY;BONE SP		BERRY;BONE SPRING, SOUTH	
4. Property Code	5. Property	y Name	6. Well No.	
39699	MONK 21 ST	ATE COM	001H	
7. OGRID No.	8. Operato	r Name	9. Elevation	
6137	DEVON ENERGY PRODU	CTION COMPANY I.P.	3734	


10 Surface Location

- /-		Tot but the Location									
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
	D	21	21S	34E		330	N	460	W	LEA	

11. Bottom Hole Location If Different From Surface

	The power and power at particular at the particu										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
M	21	218	34E	M	330	S	660	W	LEA		
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 2/5/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 1/22/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: MONK 21 STATE COM #001H

API: 30-025-40986

Created By	Comment	Comment Date
doook	2nd Stage Lead: 200 sx CI C Cmt + 3% bwoc Econolite + 0.125 #/sx Poly-E-Flake + 82.4% FW, 11.4 ppg, Yld: 2.87 cf/sk, Tail: 150 sx CI C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% FW, 14.8 ppg, Yld: 1.33cf/sk, TOC @ 3700 ft	2/5/2013
dcook	The BOP system used to drill the intermediate hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the surface casing shoe. The BOP system used to drill the production hole will consist of a 13-5/8" 3M Double Ram and Annular preventer. The BOP system will be tested as a 3M system prior to drilling out the intermediate casing shoe.	
dcook	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	2/5/2013
pkautz	Land s/S	2/6/2013
CHERRERA	OCD RECEIVED FORM 144 CLEZ. OCD PERMIT # P1-05745	2/7/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: MONK 21 STATE COM #001H

API: 30-025-40986

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string