District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesis, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505

Type

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

Form C-101 August 1, 2011

Permit 162975

oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

1. Opera	or Name and Address	OGRID Number	
	PERATING LLC	229137	
One Concho Center Midland, TX 79701		3. API Number	
14110	and, 171 / / / / /	30-025-41025	
4. Property Code	5. Property Name	6. Well No.	
39499	002H		

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	20	18S	35E	C	60	N	2180	W	
-	20	100		Proposed	Bottom H	ole Locatio			LLA

8. Proposed Bottom Hole Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	20	188	35E	N	330	S	2180	W	Lea

97930

		Additional Well Inform	nation	
11. Work Type	12. Weil Type	13. Cable/Rotary	14. Lesse Type	15. Ground Level Elevation
New Well	OIL		State	3945
16. Multiple	17. Proposed Depth	18. Formation	19. Contractor	20. Spud Date
N	13964	Bone Spring		3/4/2013
Depth to Ground	water	Distance from nearest fresh water	r well	Distance to nearest surface water

	21. Proposed Casing and Cement Program									
Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC				
Surf	17.5	13.375	54.5	1730	1100					
Int1	12.25	9.625	36	3300	800					
Prod	7.875	5.5	17	13964	1600	2800				

Casing/Cement Program: Additional Comments Plan to drill a 17-1/2" hole to 1730' with Fresh Water. Run 13-3/8", 54.5#, J-55 csg and cmt to surface. Drill 12-1/4" hole to 3300' with Brine, and run 9-5/8", 36#, J55 csg and cement to surface. Drill 7-7/8" curve and lateral with cut brine to approx 13,964'MD. Run

with Brine, and run 9-3/8", 30#, 305 esg and cement to surface. Drill 7-7/8" curve and lateral with cut orine to approx 15,964 MD. Run 5-1/2", 17#, P-110 esg and cement to 2800' in 1 stage.

22. Proposed Blowout Prevention Program

Test Pressure

Manufacturer

Working Pressure

DoubleRam	3000	3000	Cameron		
best of my knowledge and belief		OIL CONSERV	VATION DIVISION		
I further certify I have compli 19.15.14.9 (B) NMAC ⊠, if a Signature:	ied with 19.15.14.9 (A) NMAC 🔀 and/or pplicable.	Approved By: Paul Kautz			
Printed Name: Electronica	lly filed by Diane Kuykendall	Title: Geologist			
Title: Production Reporting	ıg Mgr	Approved Date: 2/26/2013	Expiration Date: 2/26/2015		
Email Address: dkuykend	all@conchoresources.com				
Date: 2/25/2013	Phone: 432-683-7443	Conditions of Approval Atta	ched		

<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phones(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

<u>District II</u> 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Darmit 162075

WELL LOCATION AND ACREAGE DEDICATION PLAT

***	LLE LOCATION MED MC	date bedication that	
1. API Number	2. Pool Code	3. Pool Name	
30-025-41025	97930	WC-025 G-06 \$183518A;BON	E SPRING
1. Property Code	5. Proper	y Name 6. W	eti No.
39499	CONDO	STATE 00	02H
7. OGRID No.	8. Operat	or Name 9. Et	evation
229137	COG OPERA	ATING LLC 39	945


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	20	188	35E		60	N	2180	W	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	20	188	35E	N	330	S	2180	W	LEA
	cated Acres	13. J	oint or Infill	14	14. Consolidation Code			15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall Title: Production Reporting Mgr

Date: 2/25/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: CHad Harcrow Date of Survey: 10/26/2012 Certificate Number: 17777

Permit Comments

Operator: COG OPERATING LLC , 229137 Well: CONDOR STATE #002H

API: 30-025-41025

Created By	Comment	Comment Date
mreyes1	Plan to drill a 17-1/2" hole to 1730" with Fresh Water. Run 13-3/8", 54.5#, J-55 csg and cmt to surface. Drill 12-1/4" hole to 3300" with Brine, and run 9-5/8", 36#, J55 csg and cement to surface. Drill 7-7/8" curve and lateral with cut brine to approx 13,964"MD. Run 6-1/2", 17#, P-110 csg and cement to 2800" in 1 stage.	2/25/2013
pkautz	Land s/S	2/25/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-05816	2/26/2013

Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137 Well: CONDOR STATE #002H API: 30-025-41025

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	In order to seal off protectable water, the surface casing must be set 25' below top of Rustler Formation