District I 1625 N. French Dr., Hobbs, NM 88240 Phone: (575) 393-6161 Fax: (575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170

<u>District IV</u>

1220 S. St Francis Dr., Santa Fe, NM 87505

Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Form C-101

August 1, 2011

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operator	Name and Address	<ol><li>OGRID Number</li></ol>		
	RATING LLC encho Center	229137		
	d. TX 79701	3. API Number		
iviidan	a, 1A /9/01	30-025-41026		
4. Property Code	5. Property Name	6. Well No.		
39748 TYRELL FEE		001H		

7. Surface Location

		170		7.0	diffact Loc	ution	N .	9	
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	14	24S	33E	A	190	N	660	E	LEA

8. Proposed Bottom Hole Location

15 51	8. Proposed Bottom Hole Location										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
P	14	24S	33E	P	330	S	660	E	Lea		

#### 9. Pool Information

RED HILLS;BONE SPRING, NORTH	96434
------------------------------	-------

Additional Well Information

11. Work Type	12. Well Type	13. Cable/Rotary	14. Lesse Type	15. Ground Level Elevation
New Well	OIL		State	3607
16. Multiple	17. Proposed D	pth 18. Formation	19. Contractor	20. Spud Date
N	15648	Bone Spring		3/4/2013
Depth to Ground	water	Distance from nearest fresh wat	er well	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1375	900	
Int1	12.25	9.625	36	5200	1200	
Prod	7.875	5.5	17	15648	2300	4900

### Casing/Cement Program: Additional Comments

Plan to drill a 17-1/2" hole to 1375' with Fresh Water. Run 13-3/8", 54.5#, J-55 csg and cmt to surface. Drill 12-1/4" hole to 5200' with Brine, and run 9-5/8", 36#/40#, J55 and cement to surface. Drill 7-7/8" pilot hole to 12,600' to run OH logs, then plug back to kick off and drill a 7-7/8" curve and lateral with cut brine to approx 15,648' MD. Run 5-1/2", 17#, P-110 csg and cement to 4900' in 1

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	Cameron

best of my knowledge and beli		OIL CONSERVATION DIVISION			
I further certify I have comp 19.15.14.9 (B) NMAC ⊠, if	olied with 19.15.14.9 (A) NMAC 🛮 and/or applicable.	Approved By: Paul Kautz			
Signature:					
Printed Name: Electronic	ally filed by Diane Kuykendall	Title: Geologist	2		
Title: Production Report	ing Mgr	Approved Date: 2/26/2013	Expiration Date: 2/26/2015		
Email Address: dkuyken	dall@conchoresources.com				
Date: 2/25/2013	Phone: 432-683-7443	Conditions of Approval Attached			

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name	
30-025-41026	96434	RED HILLS;BONE SPRING, NORTH	
4. Property Code	5. Propert	y Name 6. Well No.	
39748	TYREL	L FEE 001H	
7. OGRID No.	8. Operato	r Name 9. Elevation	
229137	COG OPERA	TING LLC 3607	


#### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	14	24S	33E		190	N	660	E	LEA

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section 14	Township 24S	Range 33E	Lot Idn P	Feet From 330	N/S Line S	Feet From 660	E/W Line	County LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

#### NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



#### OPERATOR CERTIFICATION

Form C-102

August 1, 2011

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall Title: Production Reporting Mgr

## Date: 2/25/2013

#### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Chad Harcrow Date of Survey: 11/16/2012 Certificate Number: 17777

# **Permit Comments**

Operator: COG OPERATING LLC , 229137 Well: TYRELL FEE #001H

API: 30-025-41026

Created By	Comment	Comment Date
mreyes1	OIL: COG Operating has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that an H2S Contingency Plan would be necessary.	2/25/2013
pkautz	Land p/P	2/25/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-05817	2/26/2013

# Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137 Well: TYRELL FEE #001H API: 30-025-41026

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Inorder to seal off protectable water, the surface casing must be set 25' below the top of the Rustler Anhydrite.