District I 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170

<u>District IV</u>

1220 S. St Francis Dr., Santa Fe, NM 87505

Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Form C-101 August 1, 2011

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT	TO DRILL, RE-ENTER	DEEPEN, PLUGBACK	OR ADD A ZONE

	or Name and Address	OGRID Number		
	COG PRODUCTION, LLC 600 W. Illinois Ave			
	and, TX 79701	3. API Number		
171102	mo, 111 / 5/01	30-025-41048		
4. Property Code	5. Property Name	6. Well No.		
39209	EATA FAJITA STATE	004H		

7. Surface Location

12		2 194	19	7.0	diffice Loc	ution	20	0 /0	1
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	8	24S	33E	P	190	S	380	E	LEA

8. Proposed Bottom Hole Location

	OF A TOPOGCU DOTTOM ALVIE DOCUTON												
UL - La	ot Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County				
A	8	24S	33E	A	330	N	380	E	Lea				

9. Pool Information

TRIPLE X:BONE SPRING, WEST	96674

Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3601	
16. Multiple 17. Proposed Depth N 16134		18. Formation Bone Spring	19. Contractor	20. Spud Date 3/13/2013	
Depth to Ground	water	Distance from nearest fresh water	r well	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1300	850	
Int1	12.25	9.625	40	5150	1050	
Prod	7.875	5.5	17	16134	1650	4950

Casing/Cement Program: Additional Comments

Plan to drill a 17-1/2" hole to 1300' with Fresh Water. Run 13-3/8", 54.5#, J-55 csg and cmt to surface. Drill 12-1/4" hole to 5150' with Brine, and run 9-5/8", 40#, J55/N-80 and cement to surface. Drill 7-7/8" curve and lateral with cut brine to approx 16,134"MD. Run 5-1/2", 17#, P-110 csg and cement to 4950' in 1 stage.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	Cameron

 I hereby certify that the information post of my knowledge and belief. 	•	OIL CONSERVATION DIVISION Approved By: Paul Kautz				
I further certify I have complied with 19.15.14.9 (B) NMAC ⊠, if applicable	19.15.14.9 (A) NMAC 🛮 and/or e.					
Signature:						
Printed Name: Electronically filed	by DIANE KUYKENDALL	Title: Geologist				
Title: Production Reporting Man	ager	Approved Date: 3/6/2013	Expiration Date: 3/6/2015			
Email Address: dkuykendall@con	ncho.com					
Date: 3/6/2013	Phone: 432-685-4372	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

Form C-102 August 1, 2011

1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

	EEE EGCHIION IE D HON	Elion Debicilitor (Lein	
1. API Number	2. Pool Code	3. Pool Name	
30-025-41048	96674	TRIPLE X;BONE SPRING, WEST	
4. Property Code	5. Property	Name 6. Well No.	
39209	EATA FAJIT	A STATE 004H	
7. OGRID No.	8. Operator	Name 9. Elevation	
217955	COG PRODUC	TION, LLC 3601	


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
P	8	24S	33E		190	S	380	E	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County			
P	8	24S	33E	P	330	N	380	E	LEA			
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.				

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: DIANE KUYKENDALL Title: Production Reporting Manager Date: 3/6/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Chad Harcrow Date of Survey: 12/14/2012 Certificate Number: 17777

Permit Comments

Operator: COG PRODUCTION, LLC , 217955 Well: EATA FAJITA STATE #004H

API: 30-025-41048

Created By	Comment	Comment Date
matyereyes		3/6/2013
matyereyes	OIL: COG Operating has conducted a review to determine if an H2S contingency plan is required for the above referenced well. We were able to conclude that any potential hazardous volume would be minimal. H2S concentrations of wells in this area from surface to TD are low enough; therefore we do not believe that an H2S Contingency Plan would be necessary.	3/6/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-05835	3/6/2013
pkautz	Land s/S	3/6/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-05835	3/6/2013

Permit Conditions of Approval

Operator: COG PRODUCTION, LLC , 217955 Well: EATA FAJITA STATE #004H API: 30-025-41048

OCD Reviewer Condition		
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
pkautz	Inorder to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite	