District I 1625 N. French Dr., Hobbs, NM 88240 Phone;(575) 393-6161 Fax:(575) 393-0720 District II 811 S. First St., Artesia, NM 88210 Phone;(575) 748-1283 Fax:(575) 748-9720

Phone:(3/3) /48-1283 Fax:(3/3) /48-9/20 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources**

Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 163772

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE
--

1. Operati	or Name and Address	2. OGRID Number	
	LEUM CORPORATION	25575	
105 S 4TH ST ARTESIA , NM 88210		3. API Number	
		30-025-41054	
4. Property Code	5. Property Name	6. Well No.	
35240	YARROW BHY STATE	004H	

7. Surface Location

				7.0	urrace Loc	ution			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	32	238	33E	В	475	N	2043	E	LEA

8. Proposed Bottom Hole Location

	OTTO DO COM DO COM LIVE DO COM									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
0	32	238	33E	0	330	S	1980	E	Lea	

9. Pool Information

TRIPLE X;BONE SPRING	59900

Additional Well Information

11. Work Type 12. Wetl Type New Well OIL		13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3667	
16. Multiple 17. Proposed Depth N 15448		18. Formation 19. Contractor 2nd Bone Spring Sand		20. Spud Date	
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1315	515	0
Int1	12.25	9.625	40	5200	1680	0
Prod	8.5	5.5	17	15448	1645	7000
Prod	8.75	5.5	17	7500	540	4700

Casing/Cement Program: Additional Comments

22 Dranged Blowaut Drawntion Dragger

3.15		22. Proposed Dionout	r revention r rogram	3.
Γ	Type	Working Pressure	Test Pressure	Manufacturer
	DoubleRam	3000	3000	10172
	DoublePam	5000	5000	(c)

best of my knowledge and be	plied with 19.15.14.9 (A) NMAC and/or	OIL CONSERVATION DIVISION Approved By: Paul Kautz			
Signature:	аррисане.	Manager Committee of the Committee of th			
Printed Name: Electroni	cally filed by LORI FLORES	Title: Geologist			
Title: Land Regulatory	lechnician lechnician	Approved Date: 3/12/2013	Expiration Date: 3/12/2015		
Email Address: lorif@y	atespetroleum.com	(1)			
Date: 3/8/2013	Phone: 575-748-4448	Conditions of Approval Attached			

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

Form C-102 August 1, 2011

1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number			Pool Name
30-025-41054	59900 TRIPLE X;E		BONE SPRING
4. Property Code	5. Property 1	ame	6. Well No.
35240	YARROW BHY	YARROW BHY STATE	
7. OGRID No.	8. Operator 1	fame -	9. Elevation
25575	YATES PETROLEUM	CORPORATION	3667


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	32	238	33E		475	N	2043	E	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	32	238	33E	В	330	S	1980	E	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: LORI FLORES Title: Land Regulatory Technician

Date: 3/8/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Gary Jones Date of Survey: 12/3/2012 Certificate Number: 7977

Permit Comments

Operator: YATES PETROLEUM CORPORATION , 25575 Well: YARROW BHY STATE #004H

API: 30-025-41054

Created By	Comment	Comment Date
THAHN	C-144, C-102 and directional drilling plan to follow by mail.	3/8/2013
THAHN	H2S is not anticipated.	3/8/2013
THAHN	Samples will be taken every 30' to 5200' and then every 10' from 5200' to TD.	3/8/2013
THAHN	Maximum anticipated BHP (Depths are TVD): 0'-850' is 311 PSI, 650'-5200' is 2758 PSI, 5200'- 11208' is 5245 PSI.	3/8/2013
THAHN	Well will be drilled vertically to 10699' and then kicked off and drilled directionally at 12 degrees per 100' with an 8.75" hole to 11445' MD (11177' TVD). Hole will then be reduced to 8.5" and drilled to 15448' MD (11208' TVD) where 5.5" casing will be ran and cemented from TD to 4700' with a DV tool at approximately 7500'. Penetration point of the producing zone will be encountered at 674' FNL & 1976' FEL, Section 32 of T23S-R33E. Deepest TVD in the well is 11208' in the lateral.	3/8/2013
pkautz	Land s/S	3/8/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT # P1-05883	3/12/2013

Permit Conditions of Approval Operator: YATES PETROLEUM CORPORATION , 25575 Well: YARROW BHY STATE #004H

API: 30-025-41054

OCD Reviewer	Condition	
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
pkautz	In order to seal off protectable water, the surface casing must be set 25' below the top of the Rustler Anhydrite.	