<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

SITS. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division

il Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505 Form C-101

August 1, 2011

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operat	or Name and Address	2. OGRID Number		
	COG OPERATING LLC One Concho Center			
15.00	and, TX 79701	3. API Number 30-025-41110		
11101	and, 11177701			
4. Property Code	5. Property Name	6. Well No.		
39012	WILD COBRA 1 STATE	001H		

7. Surface Location

				7.0	difface Loc	ution			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	1	198	34E	4	500	N	330	W	LEA

8. Proposed Bottom Hole Location

55	8. Proposed Bottom Hole Location								
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	1	198	34E	1	500	N	330	E	Lea

#### 9. Pool Information

SCHARB;BONE SPRING	55610
--------------------	-------

Additional Well Information

OIL	11.5 1000.00	State	3967
7. Proposed Depth	18. Formation	19. Contractor	20. Spud Date
15084	Bone Spring		8/15/2013
	7. Proposed Depth	7. Proposed Depth 18. Formation	7. Proposed Depth 18. Formation 19. Contractor

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	54.5	1940	1275	
Int1	12.25	9.625	36	3570	1050	
Prod	7.875	5.5	17	15084	1935	3300

## Casing/Cement Program: Additional Comments

Drill 17-1/2" hole to ~1940' w/ fresh water spud mud. Run 13-3/8" 54.5# J55 STC casing to TD and cement to surface in one stage. Will use 1" tubing and Class C w/ 2% CaCl2 to cement to surface, if necessary. Drill 12-1/4" hole to ~3570' with saturated brine water Run 9-5/8" 36# J55 LTC casing to TD and cement to surface in one stage. Drill 7-7/8" vertical hole, curve, and lateral to 15084' with cut brine. Run 5-1/2" 17# P110 LTC casing to TD with DV tool @ ~6500'. Circulate cement on 1st stage with 1450 sx and bring TOC to 3300' on 2nd stage with 485 sx.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
DoubleRam	3000	3000	Camerons

best of my knowledge and belief.	nation given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complie 19.15.14.9 (B) NMAC ⊠, if ap	d with 19.15.14.9 (A) NMAC 🛮 and/or plicable.	Approved By: Paul Kautz				
Signature:						
Printed Name: Electronicall	y filed by Diane Kuykendall	Title: Geologist				
Title: Production Reporting	g Mgr	Approved Date: 4/12/2013	Expiration Date: 4/12/2015			
Email Address: dkuykendal	ll@conchoresources.com	- C	to the first of the second of			
Date: 4/9/2013	Phone: 432-683-7443	Conditions of Approval Attached				

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 District II

Phone:(575) 393-6161 Fax:(575) 393-0720 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

1220 S. St Francis Dr.

Santa Fe, NM 87505

August 1, 2011

Form C-102

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

***	LLE LOCATION AND ACKL	AGE DEDICATION TEAT
1. API Number	2. Pool Code	3. Pool Name
30-025-41110	55610	SCHARB;BONE SPRING
4. Property Code	5. Property N	ame 6. Well No.
39012	WILD COBRA 1	STATE 001H
7. OGRID No.	8. Operator N	ame 9. Elevation
229137	COG OPERATI	NG LLC 3967

10 Surface Location

					Jul Ince Doc	m.v.v.			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	1	198	34E	4	500	N	330	W	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	1	198	34E	1	500	N	330	E	LEA
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

#### NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

0		

### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Diane Kuykendall Title: Production Reporting Mgr

Date: 4/9/2013

#### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Chad Harcrow Date of Survey: 2/20/2013 Certificate Number: 17777

# **Permit Comments**

Operator: COG OPERATING LLC , 229137 Well: WILD COBRA 1 STATE #001H

API: 30-025-41110

Created By	Comment	Comment Date
mreyes1	Drill 17-1/2" hole to ~1940' w/ fresh water spud mud. Run 13-3/8" 54.5# J55 STC casing to TD and cement to surface in one stage. Will use 1" tubing and Class C w/ 2% CaCl2 to cement to surface, if necessary. Drill 12-1/4" hole to ~3570' with saturated brine water. Run 9-5/8" 36# J55 LTC casing to TD and cement to surface in one stage. Drill 7-7/8" vertical hole, curve, and lateral to 15084' with cut brine. Run 5-1/2" 17# P110 LTC casing to TD with DV tool @ ~ 6500'. Circulate cement on 1st stage with 1450 sx and bring TOC to 3300' on 2nd stage with 485 sx.	4/9/2013
pkautz	Land s/S	4/10/2013
CHERRERA	OCD RECEIVED FORM C144 CLEZ. OCD PERMIT #P1-08043	4/12/2013

# Permit Conditions of Approval

Operator: COG OPERATING LLC , 229137 Well: WILD COBRA 1 STATE #001H API: 30-025-41110

OCD Reviewer	Condition	
Once the well is spud, to prevent ground water contamination through whole or partia pksutz surface, the operator shall drill without interruption through the fresh water zone or zo immediately set in cement the water protection string		
pkautz	In order to seal off protectable water, Surface casing must be set 25' below top of Rustler Anhydrite.	