<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

August 1, 2011

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT TO	DRILL RE-ENTER	DEEPEN PLUGBACK	OR ADD A ZONE

CONTRACTOR	Operator Name and Address     DEVON ENERGY PRODUCTION COMPANY, LP			
Water Street	. Sheridan Avenue ma City, OK 73102	6137 3. API Number 30-025-41144		
4. Property Code	5. Property Name	6. Wett No.		
39429	TAIPAN 10 STATE COM	003H		

### 7. Surface Location

97	100	2		7.0	diffact Loc	ution	300	0	
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	15	238	33E	В	200	N	2370	E	LEA

### 8. Proposed Bottom Hole Location

	OF A TOPOGCU DOTTOM ALOTE MOUNTAIN									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
В	10	238	33E	В	330	N	1980	E	Lea	

### 9. Pool Information

BRINNINSTOOL:BONE SPRING	7320

### Additional Well Information

11. Work Type New Well	12. Wei		13. Cable/Rotary	14. Lease Type State	15. Ground Level Elevation 3705	
The second secon		osed Depth	18. Formation 2nd Bone Spring Sand	19. Contractor	20. Spud Date	
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water	

### 21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1400	1210	0
Int1	12.25	9.625	40	5200	1540	0
Prod	8.75	5.5	17	10450	780	0
Prod	8.75	5.5	17	16053	1345	4700

### Casing/Cement Program: Additional Comments

13-3/8" Surface Lead: 875 sx C1 C Cmt + 2% bwoc CaCt2 + 0.125 #/sx Poly-E-Flake + 4% bwoc Bent + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sx. TOC @ surface. Tail: 335 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sk. 9-5/8" Intermediate Lead:1115 sx(65:35) C1 C Cmt:Poz(Fly Ash): + 5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx, TOC @ surface. Tail: 425 sx Cl C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% Water, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production 1st Lead: 455 sx(50:50) Cl H Cmt:Poz (Fly Ash) + 10% bwoc Bent + 8 #/sx CaCL + 0.125 #/sx Poly-E-Flake + 0.3% bwoc HR-601 + 0.3% bwoc Econolite + 77.2% FW, 11.8 ppg, Yld: 2.52 cf/sx; 2nd Lead: 325 sx(65:35) Cl H Cmt:Poz (Fly Ash) + 6% bwoc Bent + 0.125 #/sx Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx. See Comments section for 5 1/2" production cement Tail.

### 22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer				
Annular	3000	3000					
DoubleRam	3000	3000					

23. I hereby certify that the information best of my knowledge and belief.	given above is true and complete to the	OIL CONSERVATION DIVISION			
I further certify I have complied with 19.15.14.9 (B) NMAC , if applicab		Approved By: Paul Kautz			
Signature:					
Printed Name: Electronically file	d by Randy Bolles	Title: Geologist			
Title: Manager, Regulatory Affa	irs	Approved Date: 4/26/2013	Expiration Date: 4/26/2015		
Email Address: randy.bolles@dv	n.com				
Date: 4/25/2013	Phone: 405-228-8588	Conditions of Approval Attached			

District I
1625 N. French Dr., Hobbs, NM 88240
Phones(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phones(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones(505) 334-6178 Fax:(505) 334-6170

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 165847

<u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-025-41144	2. Pool Code 7320	3. Pool Name BRINNINSTOOL;BONE SPRING		
4. Property Code 39429	5. Property TAIPAN 10 ST		6. Well No. 003H	
7. OGRID No. 6137	8. Operator DEVON ENERGY PRODU		9. Elevation 3705	

10	Corref	aco I	acat	ion

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	15	238	33E		200	N	2370	E	LEA

11. Bottom Hole Location If Different From Surface

	The second state second state of the second									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
В	10	238	33E	В	330	N	1980	W	LEA	
12. Dedicated Acres 160.00		13. J	13. Joint or Infill		14. Consolidation Code		e 15. Order No.			

## NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 4/25/2013

### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 3/21/2013 Certificate Number: 12797

### **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: TAIPAN 10 STATE COM #003H

API: 30-025-41144

Created By	Comment	Comment Date	
doook	5 1/2" Production Tail: 1345 sx (50:50) CI H Cmt:Poz (Fly Ash) + 1 #/sx CaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx. TOC @ 4700	4/25/2013	
pkautz	Land s/S	4/25/2013	
CHERRERA	OCD RECEIVED FORM 144 CLEZ. OCD PERMIT # P1-06115	4/26/2013	

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: TAIPAN 10 STATE COM #003H

API: 30-025-41144

OCD Reviewer	Condition
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite.