<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>

<u>District II</u> 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

## State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

Permit 1658

August 1, 2011 Permit 165848

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

DEVON ENERGY I	ator Name and Address PRODUCTION COMPANY, LP	OGRID Number     6137	
9 Page 15	7. Sheridan Avenue ma City, OK 73102	3. API Number 30-025-41145	
4. Property Code	5. Property Name	6. Well No.	
39429	TAIPAN 10 STATE COM	004H	

### 7. Surface Location

55				7.0	diffice Loc	ution	300	0		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	1
В	15	238	33E	В	200	N	2320	E	LEA	l

### 8. Proposed Bottom Hole Location

					L DOTTOIL AL	ore motures	-		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
A	10	238	33E	A	330	N	660	E	Lea

### 9. Pool Information

BRINNINSTOOL:BONE SPRING	7320

### Additional Well Information

11. Work Type 12. Well Type New Well OIL				14. Lease Type State	15. Ground Level Elevation 3704
16. Multiple 17. Proposed Depth N 16354		18. Formation 19. Contractor 2nd Bone Spring Sand		20. Spud Date	
Depth to Ground	water		Distance from nearest fresh water w	rel1	Distance to nearest surface water

### 21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1400	1210	0
Int1	12.25	9.625	40	5200	1540	0
Prod	8.75	5.5	17	16354	1345	4700
Prod	8.75	5.5	17	10450	780	0

### Casing/Cement Program: Additional Comments

13-3/8" Surface Lead: 875 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 4% bwoc Bent + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sx. TOC @ surface. Tail: 335 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sk. 9-5/8" Intermediate Lead:1115 sx(65:35) Cl C Cmt:Poz(Fly Ash): + 5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx, TOC @ surface. Tail: 425 sx Cl C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% Water, 14.8 ppg, Yld: 1.33 cf/sx. 5-1/2" Production 1st Lead:455 sx(50:50) Cl H Cmt:Poz (Fly Ash) + 10% bwoc Bent + 8 #/sx CaCL + 0.125 #/sx Poly-E-Flake + 0.3% bwoc Bent + 8 #/sx CaCL + 0.125 #/sx Poly-E-Flake + 0.3% bwoc Bent + 0.125 #/sx Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx. See Comments Section for 5 1/2" Production Tail details.

### 22. Proposed Blowout Prevention Program

		22. Proposed Diowout	rievention riogiam	
Γ	Type	Working Pressure	Test Pressure	Manufacturer
	Annular	3000	3000	
	DoubleDam	2000	2000	

23. I hereby certify that the information best of my knowledge and belief.	given above is true and complete to the	OIL CONSERVATION DIVISION				
I further certify I have complied with 19.15.14.9 (B) NMAC , if applicab		Approved By: Paul Kautz				
Signature:		(2004) (1-2)				
Printed Name: Electronically file	d by Randy Bolles	Title: Geologist	02			
Title: Manager, Regulatory Affa	irs	Approved Date: 4/26/2013	Expiration Date: 4/26/2015			
Email Address: randy.bolles@dv	n.com					
Date: 4/25/2013	Phone: 405-228-8588	Conditions of Approval Attached				

District I
1625 N. French Dr., Hobbs, NM 88240
Phones(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phones(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones(505) 334-6178 Fax:(505) 334-6170

# State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Permit 165848

<u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number 30-025-41145	TO AND THE PERSON NAMED IN CONTROL OF THE PERSON NAMED IN CONT		3. Pool Name BRINNINSTOOL;BONE SPRING	
4. Property Code 39429	5. Property Name TAIPAN 10 STATE COM		6. Well No. 004H	
7. OGRID No. 6137		8. Operator Name DEVON ENERGY PRODUCTION COMPANY. LP		

10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	15	238	33E		200	N	2320	E	LEA

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
A	10	238	33E	A	330	N	660	E	LEA		
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.			

## NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 4/25/2013

### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 3/21/2013 Certificate Number: 12797

### **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: TAIPAN 10 STATE COM #004H

API: 30-025-41145

Created By	Comment	Comment Date
doook	5 1/2" Production Tail: 1345 sx(50:50) CI H Cmt:Poz (Fly Ash) + 1 #/sx CaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, YId: 1.22 d/sx. TOC @ 4700	4/25/2013
dœok	A 3M 13-5/8" BOP system (Double Ram and Annular preventer) will be installed and tested prior to drilling out the surface casing shoe. The BOP system used to drill the intermediate hole will be tested per BLM Onshore Oil and Gas Order 2. A 3M 13-5/8" BOP system (Double Ram and Annular preventer) will be installed and tested prior to drilling out the intermediate casing shoe. The BOP system used to drill the production hole will be tested per BLM Onshore Oil and Gas Order 2.	4/25/2013
dœok	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	4/25/2013
pkautz	Land s/S	4/25/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: TAIPAN 10 STATE COM #004H

API: 30-025-41145

OCD Reviewer Condition		
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite.	