<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410

Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

APPLICATION FOR PERMIT	TO DRILL, RE-ENTER	, DEEPEN, PLUGBACK,	OR ADD A ZONE

	or Name and Address	OGRID Number	
	DEVON ENERGY PRODUCTION COMPANY, LP 333 W. Sheridan Avenue		
	Oklahoma City, OK 73102	3. API Number 30-015-41296	
Oklanoni	a ony, one 75102		
4. Property Code	5. Property Name	6. Well No.	
39862 TRANQUIL 13 STATE		004H	

7. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	13	25S	27E	D	330	N	660	W	EDDY

8. Proposed Bottom Hole Location

	o. Troposca Bottom Hote Escation												
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County				
M	13	25S	27E	M	330	S	660	W	Eddy				

9. Pool Information

HAY HOLLOW;BONE SPRING, NORTH	30216
-------------------------------	-------

Additional Well Information

11. Work Type 12. Well Type New Well OIL		13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3095
16. Multiple 17. Proposed Depth N 12285		18. Formation Bone Spring	19. Contractor	20. Spud Date
Depth to Ground	water	Distance from nearest fresh water	r well	Distance to nearest surface water

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	650	670	0
Int1	12.25	9.625	36	2320	690	0
Prod	8.75	5.5	17	12285	1300	0
Prod	8.75	5.5	17	7235	875	1820

Casing/Cement Program: Additional Comments

13-3/8" Surf: Tail: 670 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 lbs/sack Poly-E-Flake + 63.1% Fresh Water, 14.8 ppg, Yld: 1.35 cf/sk, TOC @ 0. 9-5/8" Inter:Lead:330 sx(65:35)Cl C Cmt:Poz(Fly Ash): + 5% bwow NaCl + 0.125 lbs/sk Poly-E-Flake + 6% bwoc Bent 10.9% FW, 12.9 ppg, Yld: 1.85 cfsk, Taii:360 sx C1 C Cmt + 0.125 lbs/sk Poly-E-Flake + 63.5% Wtr, 14.8 ppg, Yld: 1.33 cfsk, TOC @ 0.5-1/2" Prod:Lead: 875 sx(65:35)C1 H Cmt:Poz(Fly Ash) + 6% bwoc Bent + 0.125 lbs/sk Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sk, Taii:1300 sx(50:50)C1 H Cmt:Poz(Fly Ash) + 1 lb/sk NaCl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sk, TOC @ 1820'.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

 I hereby certify that the informat best of my knowledge and belief. 	ion given above is true and complete to the	OIL CONSERVATION DIVISION Approved By: Randy Dade			
I further certify I have complied to 19.15.14.9 (B) NMAC , if appli	with 19.15.14.9 (A) NMAC 🛮 and/or cable.				
Signature:		4411117			
Printed Name: Electronically	filed by Randy Bolles	Title: District Supervisor			
Title: Manager, Regulatory A	ffairs	Approved Date: 4/30/2013	Expiration Date: 4/30/2015		
Email Address: randy.bolles@	dvn.com		7.		
Date: 4/25/2013	Phone: 405-228-8588	Conditions of Approval Attached			

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720

District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

1220 S. St Francis Dr. Santa Fe, NM 87505

WELL LOCATION AND ACREAGE DEDICATION PLAT

	VLLE LOCATION AND AC	MAGE DEDICATION II	
1. API Number	2. Pool Code	3. Pool Name	
30-015-41296	30216	HAY HOLLOW;BONE SPRING, NORT	
4. Property Code	5. Prope	5. Property Name	
39862	TRANQUII	L 13 STATE	004H
7. OGRID No.	8. Opera	8. Operator Name	
6137	DEVON ENERGY PROD	UCTION COMPANY, LP	3095


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	13	25S	27E		330	N	660	W	EDDY

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	13	25S	27E	M	330	S	660	W	EDDY
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

Form C-102

August 1, 2011

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 4/25/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 3/26/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: TRANQUIL 13 STATE #004H API: 30-015-41296

Created By	Comment	Comment Date
priechers	The BOP system used to drill the intermediate hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order 2. A 3M system will be installed and tested prior to drilling out the surface casing shoe.	4/25/2013
priechers	The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order 2. A 3M system will be installed prior to drilling out the intermediate casing shoe.	4/25/2013
priechers	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	
priechers	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line); The line will be kept as straight as possible with minimal turns.	4/25/2013
CSHAPARD	Land s/S	4/30/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: TRANQUIL 13 STATE #004H

API: 30-015-41296

OCD Reviewer	Condition
CSHAPARD	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string