<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

SITS. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u> 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u> 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-101 August 1, 2011

Permit 16704

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

1. Operat	1. Operator Name and Address				
DEVON ENERGY PI	6137 3. API Number				
333 W. Sheridan Avenue Oklahoma City, OK 73102					
Oklanon	a City, OK 75102	30-015-41363			
4. Property Code	5. Property Name	6. Well No.			
300635 COTTON DRAW UNIT		219H			

7. Surface Location

77	7. Surface Location									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
P	2	25S	31E	P	200	S	1110	E	EDDY	

8. Proposed Bottom Hole Location

55	Of Proposed Bottom Profe Bottation									
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	1
В	2	25S	31E	2	330	N	1980	E	Eddy	l

9. Pool Information

PADUCA; BONE SPRING (O)	ATTACAM STATE AND TO BE USE	96641

Additional Well Information

11. Work Type 12. Wel New Well OI			13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3453	
16. Multiple 17. Proposed Depth N 15647		200 A 100	18. Formation Bone Spring	19. Contractor	20. Spud Date	
Depth to Ground	water	•	Distance from nearest fresh water	r well	Distance to nearest surface water	

21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	875	815	0
Int1	12.25	9.625	40	4200	1260	0
Prod	8.75	5.5	17	15647	1475	0
Prod	8.75	5.5	17	9000	755	3700

Casing/Cement Program: Additional Comments

13-3/8" Surf: Lead: 300 sx C1 C Cmt + 2% bwoc CACl2 + 0.125 lbs/sk Poly-E-Flake + 4% bwoc Bentonite + 70.1% FW, 13.5 ppg, Yld: 1.75 cf/sk, Tail: 515 sx C1 C Cmt + 2% bwoc CACl2 + 0.125 lbs/sk Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sk. TOC @ surface 9-5/8" Inter: Lead: 900 sx(65:35)C1 C Cmt:Poz(Fly Ash): + 5% bwow NACl + 0.125 lbs/sk Poly-E-Flake + 6% bwoc Bentonite + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sk. Tail:360 sx C1 C Cmt + 0.125 lbs/sk Poly-E-Flake + 63.5% Wtr, 14.8 ppg, Yld: 1.33 cf/sk. TOC @ 0'. 5-1/2" Prod: 1st Lead: 380 sx(50:50)C1 H Cmt:Poz(Fly Ash) + 10% bwoc Bentonite + 8 lb/sk NACl + 0.125 lbs/sk Poly-E-Flake + 0.3% bwoc HR-601 + 0.125 lbs/sk Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sk, Tail: 1475 sx(50:50)C1 H Cmt:Poz(Fly Ash) + 1 lb/sk NACl + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Be

22. Proposed Blowout Prevention Program

zz. rroposcu ziowode rrevention rrogram								
Type	Working Pressure	Test Pressure	Manufacturer					
Annular	3000	3000						
DoubleRam	3000	3000						

best of my knowledge and be		OIL CONSERVATION DIVISION Approved By: Randy Dade			
I further certify I have com 19.15.14.9 (B) NMAC ⊠, if	plied with 19.15.14.9 (A) NMAC 🛮 and/or applicable.				
Signature:					
Printed Name: Electroni	cally filed by Randy Bolles	Title: District Supervisor			
Title: Manager, Regulate	ory Affairs	Approved Date: 5/15/2013	Expiration Date: 5/15/2015		
Email Address: randy.b	olles@dvn.com				
Date: 5/14/2013	Phone: 405-228-8588	Conditions of Approval Attached			

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>

Phone:(5/5) 748-1283 Fax:(5/5) 748-9720

Phone:(5/5) 748-1283 Fax:(5/5) 748-9720

District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phones(505) 334-6178 Fax.(505) 334-6170
District IV
1220 S. St Francis Dr., Sants Fe, NM 87505
Phones(505) 476-3470 Fax.(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.

Santa Fe, NM 87505

Form C-102 August 1, 2011

Donnit 16704

WELL LOCATION AND ACREAGE DEDICATION PLAT

	TELE LOCATION AND ACK	LAGE DEDICATION IL	11
1. API Number	2. Pool Code	3. Poo	Name
30-015-41363	96641	PADUCA; BOX	NE SPRING (O)
4. Property Code	5. Property 1	Name	6. Well No.
300635	COTTON DRA	AW UNIT	219H
7. OGRID No.	8. Operator 1	Name	9. Elevation
6137	DEVON ENERGY PRODUC	CTION COMPANY, LP	3453


10 Surface Location

	Tot Duringe Doubles										
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County		
P	2	25S	31E		200	S	1110	E	EDDY		

11. Bottom Hole Location If Different From Surface

			Down		THE PARTY OF THE P		Jan Surance		
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
В	2	25S	31E	2	330	N	1980	E	EDDY
	cated Acres	13. J	oint or Infill	14	. Consolidation	Code		15. Order No.	

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 5/14/2013

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Frank Jaramillo Date of Survey: 5/3/2013 Certificate Number: 12797

Permit Comments

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: COTTON DRAW UNIT #219H

API: 30-015-41363

Created By	Comment	Comment Date
priechers	The BOP system used to drill the intermediate hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2, a 3M system will be installed and tested prior to drilling out the surface casing shoe.	5/13/2013
priechers	The BOP system used to drill the production hole will consist of a 13-5/8" Double Ram and Annular preventer. The BOP system will be tested as per BLM Onshore Oil and Gas Order No. 2 a 3M system will be installed prior to drilling out the intermediate casing shoe.	5/13/2013
priechers	The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2* kill line and 3* choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	5/13/2013
priechers	Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke lineThe line will be kept as straight as possible with minimal turns.	5/13/2013
Artesia	Land s/S	5/15/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137

Well: COTTON DRAW UNIT #219H

API: 30-015-41363

OCD Reviewer	Condition
Artesia	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string