<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 District II

811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III 1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division

August 1, 2011

Form C-101

1220 S. St Francis Dr. Santa Fe, NM 87505

APPLICATION FOR PERMIT	TO DRILL, RE	-ENTER, DEEPEN	, PLUGBACK,	OR ADD A ZONE	

DEVON ENERGY	: Name and Address 2. OGRID Number ODUCTION COMPANY, LP 6137	
	W. Sheridan Avenue oma City, OK 73102	3. API Number 30-025-41245
4. Property Code	5. Property Name	6. Well No.
39319	IRONHOUSE 19 STATE COM	004H

#### 7. Surface Location

1	V	200	1		7.0	urrace Loc	utivii	909 99	0 (0)	7
	UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
	M	19	188	35E	4	150	S	1215	W	LEA

#### 8. Proposed Bottom Hole Location

				Troposed	Dottom II	ore motures			
UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
D	19	18S	35E	1	330	N	660	W	Lea

#### 9. Pool Information

WC-025 G-06 \$183518A;BONE SPRING	97930
-----------------------------------	-------

#### Additional Well Information

11. Work Type New Well	12. Well Type OIL	13. Cable/Rotary	14. Lesse Type State	15. Ground Level Elevation 3958 20. Spud Date	
16. Multiple N	17. Proposed De 14577	oth 18. Formation 2nd Bone Spring Sand	19. Contractor		
Depth to Ground	water	Distance from nearest fresh water	well	Distance to nearest surface water	

#### 21. Proposed Casing and Cement Program

Type	Hole Size	Casing Type	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1825	1475	0
Int1	12.25	9.625	40	5400	1570	0
Prod	8.75	5.5	17	14577	2560	4900
Prod	8.75	5.5	17	9100	585	0

### Casing/Cement Program: Additional Comments

13-3/8" Surface: 1475 sx Cl C Cmt + 2% bwoc CaCl2 + 0.125 #/sx Poly-E-Flake + 63.1% FW, 14.8 ppg, Yld: 1.35 cf/sx. TOC @ surface 9 5/8" Intermediate: Lead w/1140 sx(65:35) Cl C Cmt:Poz (Fly Ash): + 5% bwow CaCL + 0.125 #/sx Poly-E-Flake + 6% bwoc Bent + 70.9% FW, 12.9 ppg, Yld: 1.85 cf/sx; Tail w/430 sx Cl C Cmt + 0.125 #/sx Poly-E-Flake + 63.5% W, 14.8 ppg, Yld: 1.33 cf/sx. TOC @ surface. 5-1/2" Production: Lead w/585 sx(65:35) Cl H Cmt:Poz (Fly Ash) + 6% bwoc Bent + 0.125 #/sx Poly-E-Flake + 0.1% bwoc HR-601 + 74.1% FW, 12.5 ppg, Yld: 1.95 cf/sx; Tail w/2560 sx(50:50) Cl H Cmt:Poz (Fly Ash) + 1 #/sx CaCL + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.1% bwoc HR-601 + 2% bwoc Bent + 58.8% FW, 14.5 ppg, Yld: 1.22 cf/sx. TOC @ 4900 ft.

#### 22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Annular	3000	3000	
DoubleRam	3000	3000	

best of my knowledge and belief.	given above is true and complete to the	OIL CONSERVATION DIVISION  Approved By: ELIDIO GONZALES				
I further certify I have complied with 19.15.14.9 (B) NMAC ⊠, if applicat	n 19.15.14.9 (A) NMAC 🛮 and/or ole.					
Signature:						
Printed Name: Electronically file	d by Randy Bolles	Title: HOBBS STAFF MANAGER				
Title: Manager, Regulatory Affa	irs	Approved Date: 6/26/2013	Expiration Date: 6/26/2015			
Email Address: randy.bolles@dv	n.com	No. L. p.				
Date: 6/24/2013	Phone: 405-228-8588	Conditions of Approval Attached				

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
<u>District II</u>
811 S. First St., Artesia, NM 88210

### Sill S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720

\*\*District III\*\*

1000 Rio Brazos Rd., Aztec, NM 87410

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

### State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division

il Conservation Division 1220 S. St Francis Dr.

Santa Fe, NM 87505

August 1, 2011 Permit 169120

Form C-102

#### WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	ol Name
30-025-41245	97930	518A;BONE SPRING
4. Property Code	5. Property	6. Well No.
39319	IRONHOUSE 19	004H
7. OGRID No.	8. Operator	9. Elevation
6137	DEVON ENERGY PRODUC	3958


#### 10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
M	19	188	35E	4	150	S	1215	W	LEA

#### 11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County	
D	19	188	35E	1	330	N	660	W	LEA	
	cated Acres	13. J	oint or Infill	14.	. Consolidation	Code		15. Order No.		

# NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



#### OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Randy Bolles Title: Manager, Regulatory Affairs

Date: 6/24/2013

#### SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Surveyed By: Filimon Jaramillo Date of Survey: 2/27/2013 Certificate Number: 12797

## **Permit Comments**

Operator: DEVON ENERGY PRODUCTION COMPANY, LP , 6137 Well: IRONHOUSE 19 STATE COM #004H

API: 30-025-41245

Created By	Comment	Comment Date
doook	A 3M 13-5/8" BOP system (Double Ram and Annular preventer) will be installed and tested prior to drilling out the surface casing shoe. The BOP system used to drill the intermediate hole will be tested per BLM Onshore Oil and Gas Order 2.	6/24/2013
doook	A 3M 13-5/8" BOP system (Double Ram and Annular preventer) will be installed and tested prior to drilling out the intermediate casing shoe. The BOP system used to drill the production hole will be tested per BLM Onshore Oil and Gas Order 2. The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly co	6/24/2013
doook	In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP.	6/24/2013
pkautz	Land s/SP	6/25/2013
CHERRERA	OCD RECIEVED FORM C144 DLEZ. OCD PERMIT # P1-08443	6/26/2013

Permit Conditions of Approval

Operator: DEVON ENERGY PRODUCTION COMPANY, LP, 6137
Well: IRONHOUSE 19 STATE COM #004H

API: 30-025-41245

OCD Reviewer	Condition	
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	
pkautz	In order to seal off protectable water, surface casing must be set 25' below top of Rustler Anhydrite	
CHERRERA	24 HOURS CALL IN FOR SPUD, CASING, CEMENT AND ALL OTHER 24 HOUR NOTICES TO BE REPORTED TO THE OFFICE PHONE 575-393-6161 EXT 102,120,OR 107 LEAVE MESSAGE IF NO ONE ANSWERS EMERGENCY ONLY PHONE 575-370-3186	