Submit 3 Copies To Appropriate District	State of Ne	ew Mex	rico	Form C-103
Office District I	Energy, Minerals an	id Natur	al Resources	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240				WELL API NO. 30-021-20575
District II 1301 W. Grand Ave., Artesia, NM 88210	OIL CONSERVA	TION !	DIVISION	5. Indicate Type of Lease
District III	1220 South S	it. Franc	cis Dr.	STATE FEE S
1000 Rio Brazos Rd., Aztec, NM 87410 District IV	Santa Fe, 1	NM 875	505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM				
SUNDRY NOT (DO NOT USE THIS FORM FOR PROPO	TICES AND REPORTS ON V		G BACK TO A	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPLI				Libby Minerals LLC 2032
PROPOSALS.) 1. Type of Well: Oil Well	Gas Well Other CO2	Wall		8. Well Number 12-1-J
2. Name of Operator	Gas well Ouler CO2	WEII		9. OGRID Number
Reliant Exploration & Production	, LLC.			251905
3. Address of Operator				10. Pool name or Wildcat
10817 West County Road 60 Mid	and, TX 79707			Bravo Dome 96010
4. Well Location				
Unit LetterJ:_	1655feet from the\$	South	line and	1655feet from theEastline
Section 12			Range 32 I	
	11. Elevation (Show wheth	her DR,	RKB, RT, GR, etc.)	
Pit or Below-grade Tank Application	4972.5			
Pit type Depth to Grounds		et frach we	nter well Nist	ance from nearest surface water
Pit Liner Thickness: mi				nstruction Material
12. Check	Appropriate Box to Indi	cate Na	iture of Notice,	Report of Other Data
NOTICE OF I	NTENTION TO:		SUB	SEQUENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON [REMEDIAL WOR	
TEMPORARILY ABANDON	-		COMMENCE DRI	
PULL OR ALTER CASING	MULTIPLE COMPL [CASING/CEMENT	L JOB
OTHER:			OTHER:	П
	pleted operations. (Clearly st	tate all p		give pertinent dates, including estimated date
of starting any proposed w				tach wellbore diagram of proposed completion
or recompletion.				
See Attachment				
Lhereby certify that the information	above is true and complete t	to the be	st of my knowledge	e and belief. I further certify that any pit or below-
				or an (attached) alternative OCD-approved plan .
arayyamma //				7 1.15
SIGNATURE		TLE	_Manager	DATE <u> </u>
Type or print name Vance Van	derburg E-mail addre	ess: van	ce@reliantgases.co	om Telephone No.432-559-7085
For State Use Only	.0		,	
CIHIO	ma	T) - TT	5.00 - 2/9/2
APPROVED BY:	Tr	TLE	15/m 1x	DATE 1/1/15
Conditions of Approval (if any):				1

SERVICE TOOL JOB DETAIL SHEET

Page __1 __ of __1

								12.		MOACHES	DED	7	DE IOP			
CUSTOME	2			DATE		HUDSON PACKER REP					TYPE JOB					
Reliant LEASE & WELL NAME-OCSG				1-29-15 Brad Euing						uing	production packer COUNTY-PARISH-BLOCK					
		-ocsG	-	-	LOCATION								LOCK			
Libby Minerals LLC えのえ ユーーゴ				Logan, NM						Harding,						
DISTRICT			DI	RILLING OF	WELL SER	VICE CON	TACTOR I	IG NO			OPERATO	R				
Hobbs			B	orderline												
EQUIPMEN	T USED:															
5 1/2 X 2	7/8 Wirei	ine set A	S-1X plas	tic coated	packer											
2 7/8 Pla	stic coate	d T2 on/o	ff tool													
2.31X Sta																
			прри				 									
2 7/8 Pur	npoutpiug	2 pins					ļ									
										2010			0	- 4-4		
HOLE				DRILLPIPE	OFRTU	CHE	T 14		TYPE	DEPTH	SIZE	Upe W	n Hok	GRADE		
SIZE	EXCESS	DEPTH	SIZE	WGT.	TYPE	DEPTH	SIZE		VGT,			SIZE	- 770	<i>71.</i>	GRADE	
			2 7/8	1.7	FG		5 1/	4 1	5.5	J-55						
			L							L	1	Тор		Btm		
			- BR PLUG-	LINER			PERF-DEI				CONNECTION			ELL F		
	Ві	RAND & TY	PE		DEPTH	TO		BTM	_	SIZE	THREA	U	TYPE	+	WGT	
							2344		\perp	2 7/8			fresh	\perp		
ı																
	********	-04700	П							OR.						
pare.	TOOL OP		TCOST							ÓB FAUS						
DATE	NAI	HE ES	T COST	الله الله الله		5.1/2 V) 7/9 AC	17.	DE	AILS	Y Staintos	e staal	profile	ninn!	and 2.7/8	
DATE 01/29/1	NAI		F	RIH with w	rireline set	5 1/2 X 2	2 7/8 AS	-1X pa	DE1 acker	AILS	T X Stainles	s steel	profile i	nipple	e and 2 7/8	
01/29/1	5 NAI	Brad	F.	umpout p	rireline set olug. Set pa	acker rub	ber at 2	303.7	⊅€1 acker 5	rails with 2.31						
	5 NAI	HE ES	R P R	umpout p IH with 2	rireline set lug. Set pa 7/8 Plastic	cker rub coated	ber at 2 T2 on/o	303.75 f tool	DE1 acker 5 and 7	rAILS with 2.312 O jts fiber	glass tbg	and 6')	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set lug. Set pa 7/8 Plastic	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plastion onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			
01/29/1	5 NAI	Brad	F P F L	umpout p IH with 2 atched or	rireline set olug. Set pa 7/8 Plasti onto packer	acker rub c coated and nipp	ber at 2 T2 on/oi le up we	303.75 f tool Ilhead	pen acker 5 and 7 d. Tes	With 2.312 With 2.312 O jts fiber Sted casin	glass tbg g to 500#	and 6' 2 Test C	C 2 7/8			

CO. REP. Vance Vanderburg

TOOL OPERATOR Brad Euing