## District I State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 August 1, 2011 **Energy, Minerals and Natural Resources** Permit 183036 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 WELL API NUMBER Oil Conservation Division 30-025-41487 District III 1000 Rio Brazos Rd., Aztec, NM 87410 5. Indicate Type of Lease 1220 S. St Francis Dr. Phone:(505) 334-6178 Fax:(505) 334-6170 District IV Santa Fe, NM 87505 6. State Oil & Gas Lease No. 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS THISTLE UNIT (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 061H 9. OGRID Numbe DEVON ENERGY PRODUCTION COMPANY, LP 6137 3. Address of Operato 10. Pool name or Wildcat 333 W. Sheridan Avenue, Oklahoma City, OK 73102 4. Well Location Unit Letter $\underline{M}$ : $\underline{200}$ feet from the $\underline{S}$ line and feet 660 from the W Township 23S Range 33E NMPM County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3701 GR Pit or Below-grade Tank Application or Closure \_\_\_ Depth to Groundwater\_\_\_ Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTER CASING ☐ PLUG AND ABANDON ☐ CHANGE OF PLANS TEMPORARILY ABANDON COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING ☐ MULTIPLE COMPL CASING/CEMENT JOB X Other: Other: Spud 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 2/23/2014 Soudded well. Additional drilling information listed under comments. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines $\square$ , a general permit $\square$ or an (attached) alternative OCD-approved plan $\square$ . SIGNATURE Electronically Signed Manager, Regulatory Affairs 3/13/2014

randy.bolles@dvn.com

Geologist

Telephone No.

DATE

405-228-8588

3/13/2014

E-mail address

TITLE

Type or print name

For State Use Only: APPROVED BY: Randy Bolles

Paul Kautz

Comments

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
311 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 183036

## NOTICE SPUD COMMENTS

State of New Mexico **Energy, Minerals and Natural Resources** 

Oil Conservation Division

Operator:	OGRID:
DEVON ENERGY PRODUCTION COMPANY, LP	6137
333 W. Sheridan Avenue	Permit Number:
Oklahoma City, OK 73102	183036
	Permit Type:
	NoticeSpud

## Comments

Created By	Comment	Comment Date
The Street Street	(2/23/14-2/25/14) Spud @ 07:00. TD 17-1/2" hole @ 1420'. RIH w/ 34 jts 13-3/8" 48# H40 STC csg, set @ 1420'. First stage cmt: Lead w/ 390 sx Halcem-C, yld 1.72 cu ft/sk. Tail w/ 400 sx Halcem-C, yld 1.33 cu ft/sk. Disp w/ 216 bbl FW. Drop DV opening plug, had immediate circ due to filling up backside before inflating pkr. Circ 20 bbls cmt to surf. 2nd stage cmt: Lead w/ 400 sx Halcem-C, yld 1.33 cu ft/sk. Disp w/ 43.6 bbls FW. Circ 163 sx cmt to surf.	3/13/2014
	(3/2/14-3/4/14) TD 12-1/4" hole @ 5250'. RIH w/ 128 jts 9-5/8" 40# HCK55 csg, set @ 5250'. Lead w/ 1140 sx Econocem-HLC, yld 1.85 cu ft/sk. Tail w/ 430 sx Premium Plus C, yld 1.33 cu ft/sk. Disp w/ 392 bbls FW. Circ 168 sx cmt to surf.	3/13/2014
mmoravec	Production casing to follow.	3/13/2014