District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

Depth to Ground water

District II

811 S. First St., Artesia, NM 88210

Phone:(575) 748-1283 Fax:(575) 748-9720

District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-101 August 1, 2011

Distance to nearest surface water

			APPLICA	ATION FO	R PERMIT	TO DRILL	L, RE-	ENTER, DEEPE	N, PL	UGBAC	K, OR ADD	AZO	NE			
Y	YATE		M CORPORATI	ON				,				2. OGRI	D Number 25575			
		4TH ST SIA , NM 8821	10									3. API N	30-025-427	791		
4. Property Code 5. Property Nan TAN			ame ANGO BTP S	STATE COM	1					6. Well N	No. 006H					
							7. Surf	ace Location								
UL - Lot	0	Section 36	Township 2	0S Rar	ige 33E	Lot Idn	С	Feet From 200	N/S	Line N	Feet From 2	2010	E/W Line		unty	Lea
						8. Prop	osed B	ottom Hole Locati	on							
UL - Lot	V	Section 36	Township 2	0S Rar	ige 33E	Lot Idn	N	Feet From 330	N/S	Line S	Feet From 2	010	E/W Line W		unty	Lea
							9. Poo	Information								
WC-025 G	3-08	3213304D;BO	NE SPRING					and the state of the					97	7895		
						Add	litional	Well Information								
11. Work Type 12. Well Type OIL			13. Cable/F	13. Cable/Rotary			1	14. Lease Type State		15. Ground Level Elevation 3675						
16. Multiple 17. Proposed Depth N 15175			18. Formation 2nd Bone Spring Sand			1	9. Contracto	or .	20. Spuc	Date						

☐ We will be using a closed-loop system in lieu of lined pits

21 Droposed Casing and Coment Drogram

Distance from nearest fresh water well

0.74	Zit i roposca casing and coment i rogiam					
Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
Surf	17.5	13.375	48	1525	1125	0
Int1	12.25	9.625	36	5700	1925	0
Prod	8.5	5.5	17	15175	1515	10898
Prod	8.75	5.5	17	10898	790	10150

Casing/Cement Program: Additional Comments

Well will be drilled to 10150'. Well will then be kicked off at approx. 10150' and directionally drilled at 12 degrees per 100' with a 8 3/4" hole to 10898' MD (10628' TVD). Hole size will then be reduced to 8 1/2" and drilled to 15175' MD (10650' TVD) where 5 1/2" casing will be set and cemented. Production cement will tie back 500' into previous casing string in a single stage. If intermediate cement is done in 2 stages, production cement will be brought 200' above intermediate DV/Packer stage tool. Penetration point of producing zone will be encountered at 675' FNL and 2010' FWL, 36-20S-33E. Deepest TVD is 10650' in lateral.

22. Proposed Blowout Prevention Program

Type	Working Pressure	Test Pressure	Manufacturer
Double Ram	3000	3000	
Double Ram	5000	5000	

knowledge and bel	lief. nave complied with 19.15.14.9 (A)	rue and complete to the best of my NMAC 🛭 and/or 19.15.14.9 (B)		OIL CONSERVATIO	N DIVISION
Signature:					
Printed Name:	Electronically filed by Travis Hahn		Approved By:	Paul Kautz	
Title:	ritle: Land Regulatory Agent			Geologist	20 July 100 100 100 100 100 100 100 100 100 10
Email Address:	nsil Address: thahn@yatespetroleum.com			9/16/2015	Expiration Date: 9/16/2017
Date:	9/4/2015	Phone: 575-748-4120	Conditions of Approval Attached		

District I

1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 District III

1000 Rio Brazos Rd., Aztec, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 District IV

1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Form C-102 August 1, 2011

WELL LOCATION AND ACREAGE DEDICATION PLAT

1. API Number	2. Pool Code	3. Pool Name
30-025-42791	97895	WC-025 G-08 S213304D;BONE SPRING
4. Property Code	5. Property Name	6. Well No.
40238	TANGO BTP STATE COM	006H
7. OGRID No. 25575	8. Operator Name YATES PETROLEUM CORPORATION	9. Elevation 3675


10. Surface Location

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
C	36	20S	33E	C	200	N	2010	W	Lea

11. Bottom Hole Location If Different From Surface

UL - Lot	Section	Township	Range	Lot Idn	Feet From	N/S Line	Feet From	E/W Line	County
N	36	208	33E	N	330	S	2010	W	Lea
12. Dedicated Acres 160.00			13. Joint or Infill		14. Consolidation Cod	e	15. Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location(s) or has a right to drill this well at this location pursuant to a contract with an owner of such a mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

E-Signed By: Travis Hahn

Land Regulatory Agent

9/4/2015

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

Gary Jones Surveyed By:

8/5/2015 Date of Survey: Certificate Number: 7977

Form APD Comments

<u>District I</u> 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720

Phone:(575) 393-6161 Fax:(575) 393-0720 <u>District II</u>:
311 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 <u>District III</u>:
1000 Rio Brazos Rd., Azteo, NM 87410 Phone:(505) 334-6178 Fax:(505) 334-6170 <u>District IV</u>:
1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 209472

PERMIT COMMENTS

Operator Name and Address:	API Number:
YATES PETROLEUM CORPORATION [25575]	30-025-42791
105 S 4TH ST	Well:
ARTESIA , NM 88210	TANGO BTP STATE COM #006H

Created By		Comment Date
CHRISG	Samples:; 30' samples to 4500'. 10' samples 4500'-TD; Logging:; NO OPEN HOLE LOGS; Mudlogging:; On after surface casing. MAXIMUM ANTICIPATED BHP: DEPTHS ARE TVD 0'-1525' 730 PSI 1525'-5700' 3023 PSI 5700'-10650' 5095 PSI; H2S is not anticipated. C102 and Horizontal Drilling Diagram to follow	9/4/2015
plmartinez	POTASH AREA	9/15/2015

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
811 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
1220 S. St Frencis Dr., Santa Fe, NM 87505
Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

Permit 209472

PERMIT CONDITIONS OF APPROVAL

Operator Name and Address:	API Number:
YATES PETROLEUM CORPORATION [25575]	30-025-42791
105 S 4TH ST	Well:
ARTESIA , NM 88210	TANGO BTP STATE COM #006H

OCD Reviewer	Condition
pkautz	Will require a directional survey with the C-104
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
pkautz	Pit construction and closure must satisfy all requirements of your approved plan.
pkautz	If using a pit for drilling and completion operations, must have an approved pit from prior to spudding the well.
pkautz	1) SURFACE & INTERNEMIATE CASING - Cement must circulate to surface 2) PRODUCTION CASING - Cement must tie back into intermediate casing
pkautz	If cement does not circulate to surface, must run temperature survey or other log to determine top of cement
pkautz	Surface casing must be set 25' below top of Rustler Anhydrite in order to seal off protectable water
pkautz	Must notify OCD Hobbs Office if lost circulation is encountered at 575-370-3186
pkautz	1) Must notify OCD Hobbs Office prior to running Stage Tool at 575-370-3186 2) If using Stage Tool on Surface casing, Stage Tool must be set greater than 350' from surface and a minimum of 200 feet above surface shoe. 3) When using a Stage Tool on Intermediate or Production Casing Stage must be a minimum of 50 feet below previous casing shoe.