District I State of New Mexico 1625 N. French Dr., Hobbs, NM 88240 Phone:(575) 393-6161 Fax:(575) 393-0720 August 1, 2011 Energy, Minerals and Natural Resources Permit 215992 District II 811 S. First St., Artesia, NM 88210 Phone:(575) 748-1283 Fax:(575) 748-9720 WELL API NUMBER Oil Conservation Division 30-025-42455 District III 1000 Rio Brazos Rd., Aztec, NM 87410 5. Indicate Type of Lease 1220 S. St Francis Dr. Phone:(505) 334-6178 Fax:(505) 334-6170 District IV Santa Fe, NM 87505 6. State Oil & Gas Lease No 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS CHILES 28 STATE (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: 8. Well Number 001H 2. Name of Operator 9. OGRID Number DEVON ENERGY PRODUCTION COMPANY, LP 6137 3. Address of Operato 10. Pool name or Wildcat 333 W. Sheridan Avenue, Oklahoma City, OK 73102 Unit Letter D : 350 feet from the N line and feet 350 from the W Township 21S Range 34E NMPM County Lea 11. Elevation (Show whether DR, KB, BT, GR, etc.) 3712 GR Pit or Below-grade Tank Application Or Closure ___ Depth to Groundwater____ Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: ____ mil Below-Grade Tank: Volume ____ bbls; Construction Material _ 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON☐ CHANGE OF PLANS REMEDIAL WORK ALTER CASING TEMPORARILY ABANDON COMMENCE DRILLING OPNS. PLUG AND ABANDON PULL OR ALTER CASING MULTIPLE COMPL CASING/CEMENT JOB Other: Drilling/Cement Other: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work.) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. Drilling, Casing & Cement Operations.5/21/2015 Spudded well. Casing and Cement Program String Weight Grade Yield Open Hole Csg TOC Dpth Size Size lb/ft Set 05/23/15 Surf 17.5 13.375 54.5 J55 0 1905 785 1.87 **ECONOCEMHL** Υ Y 13 375 545 J55 1905 05/23/15 Surf 17.5 0 425 1 34 Halcem C 05/26/15 Int1 12.25 9.625 36 J55 0 3919 860 1.87 C Y 05/26/15 Int2 12.25 9.625 40 J55 3919 395 1.33 I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines \square , a general permit \square or an (attached) alternative OCD-approved plan \square . Electronically Signed Manager, Regulatory Affairs 2/1/2016 Type or print name Randy Bolles E-mail address randy.bolles@dvn.com Telephone No. 405-228-8588

Geologist

2/15/2016 10:24:37 AM

For State Use Only: APPROVED BY:

Paul Kautz

Comments

Permit 215992

District I
1625 N. French Dr., Hobbs, NM 88240
Phone:(575) 393-6161 Fax:(575) 393-0720
District II
311 S. First St., Artesia, NM 88210
Phone:(575) 748-1283 Fax:(575) 748-9720
District III
1000 Rio Brazos Rd., Aztec, NM 87410
Phone:(505) 334-6178 Fax:(505) 334-6170
District IV

District IV 1220 S. St Francis Dr., Santa Fe, NM 87505 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico **Energy, Minerals and Natural Resources** Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505

DRILLING COMMENTS

Operator:	OGRID:
DEVON ENERGY PRODUCTION COMPANY, LP	6137
333 W. Sheridan Avenue	Permit Number:
Oklahoma City, OK 73102	215992
	Permit Type:
	Drilling

Comments

Created By	Comment	Comment Date
Imorris	Surface Casing: Cement Circulated Reported in bbls (102). Intermediate Casing: Cement Circulated Reported in bbls (99). Cast Iron Bridge Plug: Lead w/ 580 sx Halchem cmt, yld 1.33 cu ft/sk. Disp w/ 45 bbls FW. Tail w/ 775 sx CIC cmt, disp with 20 bbls sugar water and 58 bbls FW. M/U Cast Iron Bridge Plug & TIH to 3810'.	2/1/2016
Imorris	Cement Plugs: Stage #1 - Tail w/ 50 sx CIC cmt, yld 1.33 cu fl/sk. ETOC @ 3644', Btm @ 3800'. Stage #2 - Tail w/ 50 sx CIC cmt, yld 1.33 cu fl/sk. ETOC @ 1802', Btm @ 1958'. Stage #3 - Tail w/ 50 sx CIC cmt, yld 1.33 cu fl/sk. ETOC @ surface, Btm @ 100'. No Returns.	2/1/2016