

Submit within 45 days of well completion	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 S. St Francis Dr. Santa Fe, NM 87505	Revised November 6, 2013				
		1. WELL API NO: 30-025-40926				
		2. Well Name: DRAGON 36 STATE #004H				
		3. Well Number: 004H				
HYDRAULIC FRACTURING FLUID DISCLOSURE ☒ Original ☐ Amendment		4. Surface Hole Location: Unit:N Lot:N Section:36 Township:24S Range:33E Feet from:220 N/S Line:S Feet from:1995 E/W Line:W				
		5. Bottom Hole Location: Unit:N Lot:N Section:36 Township:24S Range:33E Feet from:220 N/S Line:S Feet from:1995 E/W Line:W				
		6. latitude: longitude: 32.1674042 -103.5280991				
		7. County: Lea				
8. Operator Name and Address: EOG RESOURCES INC P.O. Box 2267 Midland 79702		9. OGRID: 7377	10. Phone Number: 432-686-3689			
11. Last Fracture Date: 9/21/2016 Frac Performed by: Keane		12. Production Type: O				
13. Pool Code(s): 97900		14. Gross Fractured Interval: 9,729 ft to 14,094 ft				
15. True Vertical Depth (TVD): 9,729 ft		16. Total Volume of Fluid Pumped: 9,968,079 gals				
17. Total Volume of Re-Use Water Pumped: N/A		18. Percent of Re-Use Water in Fluid Pumped: Not Disclosed				
19. HYDRAULIC FLUID COMPOSITION AND CONCENTRATION:						
Trade Name	Supplier	Purpose	Ingredients	(CAS #) Chemical Abstract Service #	Maximum Ingredient Concentration in Additive (% by mass)	Maximum Ingredient Concentration in HF Fluid (% by mass)
Water	EOG	Carrier/Base Fluid	Water	7732-18-5	100%	86.36738%
Sand	EOG	Proppant	Crystalline Silica	14808-60-7	100%	13.33257%
Hydrochloric Acid	EOG	Acid	Hydrochloric Acid	7647-01-0	7.5%	0.0151%
			Water	7732-18-5	100%	0.20127%
Ecopol-NE 601	Keane	Surfactant	Methyl Alcohol	67-56-1	50%	4E-05%
			Coconut Diethanolamide	68603-42-9	20%	2E-05%
			Proprietary	Proprietary	30%	3E-05%
KFEAC-30	Keane	Iron Control	Acetic Acid	64-19-7	60%	0.00037%
			Citric Acid	77-92-9	30%	0.00018%
			Water	7732-18-5	60%	0.00037%
Econo-CI200	Keane	Corrosion Inhibitor	Methanol	67-56-1	80%	0.00024%
			Fatty Acids	Proprietary	20%	6E-05%
HiRate 600W	Innospec	Friction Reducer	Hydrotreated light petroleum distillates	64742-47-8	30%	0.0053%
			Ammonium Chloride	12125-02-9	20%	0.00353%
			Ethoxylated Alcohol Surfactant Blend	68439-50-9	4.9%	0.00087%
			Ethoxylated Alcohol Surfactant Blend	68551-12-2	4.9%	0.00087%
			Ethoxylated Alcohol Surfactant Blend	68002-97-1	4.9%	0.00087%
ScaleCease 7029	Innospec	Phosphonate Scale Inhibitor	Ammonium Chloride	12125-02-9	2.6%	0.00058%
			Aminophosponate Salt	Proprietary	14%	0.00312%
MBC-516	Keane	Biocide	Proprietary	Proprietary	56.72%	0.0103%
			Glutaral	111-30-8	26.7%	0.00485%
			Didecyldimethylammonium Chloride	7173-51-5	7.97%	0.00145%
			Quaternary ammonium compounds, bezyl-C-12-16-alkyldimethyl, chlorides	68424-85-1	5.31%	0.00096%
			Ethanol	64-17-5	2.8%	0.00051%
HiRate 680	Innospec	Anionic Friction Reducer	Aliphatic Hydrocarbon	Trade Secret	30%	0.0119%
			Alcohols, C12-16, ethoxylated	68551-12-2	5%	0.00198%
20. I, as Operator, hereby certify that the information shown on this disclosure form is true and complete to the best of my knowledge and belief.						
Signature: Signed Electronically		Printed Name: Kiera Staples		Environmental Title: Associate		
Date: 10/21/2016						
E-mail Address: kiera_staples@eogresources.com						

NMOCD does not require the reporting of information beyond MSDS data as described in 29 CFR 1910.1200. NMOCD does not require the reporting or disclosure of proprietary, trade secret or confidential business information.