

Form 3160-3  
(June 2015)FORM APPROVED  
OMB No. 1004-0137  
Expires: January 31, 2018

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
**APPLICATION FOR PERMIT TO DRILL OR REENTER**

1a. Type of work: <input type="checkbox"/> DRILL <input type="checkbox"/> REENTER 1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other 1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		5. Lease Serial No.  6. If Indian, Allottee or Tribe Name  7. If Unit or CA Agreement, Name and No.  8. Lease Name and Well No.	
2. Name of Operator		9. API Well No. <b>30 015 48175</b> <span style="color: red;">Purple Sage Wolfcamp</span>	
3a. Address		3b. Phone No. (include area code)	
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface At proposed prod. zone		10. Field and Pool, or Exploratory <hr style="border: 1px solid red;"/>	
11. Sec., T. R. M. or Blk. and Survey or Area		12. County or Parish	
13. State		14. Distance in miles and direction from nearest town or post office*	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)		16. No of acres in lease	
17. Spacing Unit dedicated to this well		18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.	
19. Proposed Depth		20. BLM/BIA Bond No. in file	
21. Elevations (Show whether DF, KDB, RT, GL, etc.)		22. Approximate date work will start*	
23. Estimated duration		24. Attachments	
The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)			
1. Well plat certified by a registered surveyor. 2. A Drilling Plan. 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office).		4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). 5. Operator certification. 6. Such other site specific information and/or plans as may be requested by the BLM.	
25. Signature		Name (Printed/Typed)	
Title		Date	
Approved by (Signature)		Name (Printed/Typed)	
Title		Office	
Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon. Conditions of approval, if any, are attached.			
Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.			

(Continued on page 2)

\*(Instructions on page 2)



DISTRICT I  
1625 N. French Dr., Hobbs, NM 88240  
Phone: (575) 393-6161 Fax: (575) 393-0720  
DISTRICT II  
811 S. First St., Artesia, NM 88210  
Phone: (575) 748-1283 Fax: (575) 748-9720  
DISTRICT III  
1000 Rio Brazos Road, Aztec, NM 87410  
Phone: (505) 334-6178 Fax: (505) 334-6170  
DISTRICT IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505  
Phone: (505) 476-3460 Fax: (505) 476-3462

State of New Mexico  
Energy, Minerals & Natural Resources Department  
OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, New Mexico 87505

Form C-102  
Revised August 1, 2011  
Submit one copy to appropriate  
District Office

AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

API Number <b>30 015 48175</b>	Pool Code	Pool Name <b>PURPLE SAGE ; WOLFCAMP</b>
Property Code <b>330658</b>	Property Name <b>OCHOA 8703 FEDERAL COM</b>	Well Number <b>2H</b>
OGRID No. <b>260297</b>	Operator Name <b>BTA OIL PRODUCERS, LLC</b>	Elevation <b>3016'</b>

Surface Location


UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
<b>H</b>	<b>12</b>	<b>23-S</b>	<b>28-E</b>		<b>1647</b>	<b>NORTH</b>	<b>361.7</b>	<b>EAST</b>	<b>EDDY</b>

Bottom Hole Location If Different From Surface

UL or lot No.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
<b>C</b>	<b>8</b>	<b>23-S</b>	<b>29-E</b>		<b>999.8</b>	<b>NORTH</b>	<b>2600</b>	<b>WEST</b>	<b>EDDY</b>

Dedicated Acres	Joint or Infill	Consolidation Code	Order No.
<b>474.11</b>			

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION



OPERATOR CERTIFICATION

I hereby certify that the information herein is true and complete to the best of my knowledge and belief, and that this organization either owns a working interest or unleased mineral interest in the land including the proposed bottom hole location or has a right to drill this well at this location pursuant to a contract with an owner of such mineral or working interest, or to a voluntary pooling agreement or a compulsory pooling order heretofore entered by the division.

Signature: *Sammy Hajar* Date: **6/13/2019**

Printed Name: **Sammy Hajar**

E-mail Address: **SHAJAR@BTAOIL.COM**

SURVEYOR CERTIFICATION

I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief.

**FEBRUARY 27, 2019**

Date of Survey  
Signature & Seal of Professional Surveyor:

*Ronald J. Eidson*  
Certificate Number: **3239**  
LSL: **12641**  
JWSC W.O.: **19.11.0282**

GEODETIC COORDINATES NAD 27 NME	FIRST TAKE POINT NAD 27 NME	DIRECTIONAL BEND NAD 27 NME	LAST TAKE POINT NAD 27 NME	BOTTOM HOLE LOCATION NAD 27 NME
SURFACE LOCATION Y= 481295.8 N X= 592873.7 E LAT.=32.322840° N LONG.=104.032678° W	Y= 481934.0 N X= 593567.0 E LAT.=32.324589° N LONG.=104.030428° W	Y= 481762.4 N X= 598288.0 E LAT.=32.324080° N LONG.=104.015146° W	Y= 481791.2 N X= 600615.9 E LAT.=32.324140° N LONG.=104.007610° W	Y= 481794.6 N X= 600887.2 E LAT.=32.324147° N LONG.=104.006732° W

GEODETIC COORDINATES NAD 83 NME	FIRST TAKE POINT NAD 83 NME	DIRECTIONAL BEND NAD 83 NME	LAST TAKE POINT NAD 83 NME	BOTTOM HOLE LOCATION NAD 83 NME
SURFACE LOCATION Y= 481355.4 N X= 634056.5 E LAT.=32.322961° N LONG.=104.033172° W	Y= 481993.7 N X= 634749.7 E LAT.=32.324710° N LONG.=104.030922° W	Y= 481822.1 N X= 639470.8 E LAT.=32.324201° N LONG.=104.015640° W	Y= 481851.0 N X= 641798.8 E LAT.=32.324261° N LONG.=104.008103° W	Y= 481854.3 N X= 642070.0 E LAT.=32.324268° N LONG.=104.007225° W

CORNER COORDINATES TABLE  
NAD 27 NME

A - Y= 480271.9 N, X= 591890.3 E  
B - Y= 481599.7 N, X= 591894.8 E  
C - Y= 482927.6 N, X= 591899.2 E  
D - Y= 482948.2 N, X= 593239.8 E  
E - Y= 481615.9 N, X= 593236.2 E  
F - Y= 481432.3 N, X= 598292.8 E  
G - Y= 482761.9 N, X= 598273.6 E  
H - Y= 482794.6 N, X= 600921.6 E  
I - Y= 481465.4 N, X= 600953.9 E

CORNER COORDINATES TABLE  
NAD 83 NME

A - Y= 480331.5 N, X= 633073.1 E  
B - Y= 481659.3 N, X= 633077.5 E  
C - Y= 482987.3 N, X= 633081.8 E  
D - Y= 483007.9 N, X= 634422.5 E  
E - Y= 481675.5 N, X= 634418.9 E  
F - Y= 481492.0 N, X= 639475.6 E  
G - Y= 482821.6 N, X= 639456.4 E  
H - Y= 482854.4 N, X= 642104.4 E  
I - Y= 481525.1 N, X= 642136.7 E

## PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

<b>OPERATOR'S NAME:</b>	<b>BTA Oil Producers LLC</b>
<b>LEASE NO.:</b>	<b>NMNM103879</b>
<b>WELL NAME &amp; NO.:</b>	Ochoa 8703 Federal Com 2H
<b>SURFACE HOLE FOOTAGE:</b>	1647'/N & 361'/E
<b>BOTTOM HOLE FOOTAGE:</b>	999'/N & 2600'/W
<b>LOCATION:</b>	Section 12, T.23 S., R.28 E., NMPM
<b>COUNTY:</b>	Eddy County, New Mexico

COA

H2S	<input type="radio"/> Yes	<input checked="" type="radio"/> No	
Potash	<input checked="" type="radio"/> None	<input type="radio"/> Secretary	<input type="radio"/> R-111-P
Cave/Karst Potential	<input type="radio"/> Low	<input checked="" type="radio"/> Medium	<input type="radio"/> High
Cave/Karst Potential	<input type="radio"/> Critical		
Variance	<input type="radio"/> None	<input checked="" type="radio"/> Flex Hose	<input type="radio"/> Other
Wellhead	<input type="radio"/> Conventional	<input type="radio"/> Multibowl	<input checked="" type="radio"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

### A. HYDROGEN SULFIDE

Hydrogen Sulfide (H2S) monitors shall be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the Hydrogen Sulfide area shall meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, provide measured values and formations to the BLM.

### B. CASING

1. The **10-3/4** inch surface casing shall be set at approximately **500 feet** (a minimum of **70 feet (Eddy County)** into the Rustler Anhydrite and above the salt) and cemented to the surface.
  - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
  - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8**

- hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
- c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
  - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

**Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.**

2. The minimum required fill of cement behind the **7-5/8** inch intermediate casing is:

**Option 1 (Single Stage):**

- Cement to surface. If cement does not circulate see B.1.a, c-d above.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**

**Option 2:**

Operator has proposed a DV tool, the depth may be adjusted as long as the cement is changed proportionally. The DV tool may be cancelled if cement circulates to surface on the first stage.

- a. First stage to DV tool: Cement to circulate. If cement does not circulate off the DV tool, contact the appropriate BLM office before proceeding with second stage cement job.
  - b. Second stage above DV tool:
    - Cement to surface. If cement does not circulate, contact the appropriate BLM office.  
**Wait on cement (WOC) time for a primary cement job is to include the lead cement slurry due to cave/karst or potash.**
  - ❖ In Medium Cave/Karst Areas if cement does not circulate to surface on the first two casing strings, the cement on the 3rd casing string must come to surface.
3. The minimum required fill of cement behind the production casing is:
    - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.

### C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
- 2.

#### Option 1:

- a. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **3000 (3M)** psi.
- b. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the intermediate casing shoe shall be **5000 (5M)** psi.

#### Option 2:

1. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M)** psi.
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
  - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

### D. SPECIAL REQUIREMENT (S)

#### Communitization Agreement

- The operator will submit a Communitization Agreement to the Carlsbad Field Office, 620 E Greene St. Carlsbad, New Mexico 88220, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees



of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

## GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

☒ Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,  
(575) 361-2822

☒ Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)  
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
  - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
  - b. When the operator proposes to set surface casing with Spudder Rig
    - Notify the BLM when moving in and removing the Spudder Rig.
    - Notify the BLM when moving in the 2<sup>nd</sup> Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
    - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

## A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

## B. PRESSURE CONTROL



1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
  - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
  - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
  - c. Manufacturer representative shall install the test plug for the initial BOP test.
  - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
  - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
  - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not

hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

#### C. DRILLING MUD

Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

**D. WASTE MATERIAL AND FLUIDS**

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.



U.S. Department of the Interior  
BUREAU OF LAND MANAGEMENT

# Drilling Plan Data Report

04/19/2021

APD ID: 10400043190

Submission Date: 06/26/2019

Highlighted data  
reflects the most  
recent changes

Operator Name: BTA OIL PRODUCERS LLC

Well Name: OCHOA 8703 FEDERAL COM

Well Number: 2H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

## Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
487819	QUATERNARY	3016	0	0	ALLUVIUM	NONE	N
487833	RUSTLER	2740	277	277	ANHYDRITE	NONE	N
487822	TOP SALT	1200	1817	1817		NONE	N
487824	BASE OF SALT	505	2512	2512		NONE	N
487823	DELAWARE	255	2762	2762		NATURAL GAS, OIL	N
487836	BELL CANYON	225	2792	2792		NATURAL GAS, OIL	N
487837	CHERRY CANYON	-750	3767	3767		NATURAL GAS, OIL	N
487829	BRUSHY CANYON	-1760	4777	4777		NATURAL GAS, OIL	N
487834	BONE SPRING LIME	-3325	6342	6342		NATURAL GAS, OIL	N
487830	FIRST BONE SPRING SAND	-4400	7417	7417		NATURAL GAS, OIL	N
487838	BONE SPRING 2ND	-5150	8167	8167		NATURAL GAS, OIL	Y
487839	BONE SPRING 3RD	-6345	9362	9362		NATURAL GAS, OIL	N
487840	WOLFCAMP	-6670	9687	9687		NATURAL GAS, OIL	Y

## Section 2 - Blowout Prevention

**Operator Name:** BTA OIL PRODUCERS LLC**Well Name:** OCHOA 8703 FEDERAL COM**Well Number:** 2H**Pressure Rating (PSI):** 5M**Rating Depth:** 11000

**Equipment:** The blowout preventer equipment (BOP) shown in Exhibit A will consist of a (5M system) double ram type (5,000 psi WP) preventer and a bag-type (Hydril) preventer (5000 psi WP). Both units will be hydraulically operated and the ram type preventer will be equipped with blind rams on top and 5" drill pipe rams on bottom. The BOP's will be installed on the 13-3/8" surface casing and utilized continuously until total depth is reached. A 2" kill line and 3" choke line will be incorporated in the drilling spool below the ram-type BOP. A remote kill line will be used for the 5M system as per onshore order #2. Other accessory BOP equipment will include a Kelly cock, floor safety valve, choke lines, and choke manifold having a 5,000 psi WP rating. The 5M annular will be tested as per BLM drilling Operations Order No. 2.

**Requesting Variance?** NO**Variance request:** n/a

**Testing Procedure:** Pipe rams will be operated and checked each 24-hour period and each time the drill pipe is out of the hole. These functional tests will be documented on the daily driller's log. All BOP's and associated equipment will be tested as per BLM drilling Operations Order No. 2.

**Choke Diagram Attachment:**

Choke\_Hose\_\_\_Test\_Chart\_and\_Specs\_20181129153440.pdf

5M\_choke\_mannifold\_20190211164346.pdf

**BOP Diagram Attachment:**

5M\_BOP\_diagram\_20190211164555.pdf

### Section 3 - Casing

Casing ID	String Type	Hole Size	Csg Size	Condition	Standard	Tapered String	Top Set MD	Bottom Set MD	Top Set TVD	Bottom Set TVD	Top Set MSL	Bottom Set MSL	Calculated casing length MD	Grade	Weight	Joint Type	Collapse SF	Burst SF	Joint SF Type	Joint SF	Body SF Type	Body SF
1	SURFACE	14.75	10.75	NEW	API	N	0	500	0	500			500	J-55	40.5	ST&C	7.3	14.5	DRY	20.7	DRY	31.1
2	PRODUCTION	6.75	5.5	NEW	API	Y	0	9990	0	9962			9990	P-110	20	BUTT	1.5	1.7	DRY	3.3	DRY	3.2
3	INTERMEDIATE	9.875	7.625	NEW	API	N	0	10190	0	10162			10190	P-110	29.7	BUTT	2	1.9	DRY	3.2	DRY	3.1
4	PRODUCTION	6.75	5.0	NEW	API	Y	9990	18532	9962	10693			8542	P-110	18	BUTT	1.7	1.7	DRY	1.8	DRY	1.7

**Casing Attachments**

**Operator Name:** BTA OIL PRODUCERS LLC**Well Name:** OCHOA 8703 FEDERAL COM**Well Number:** 2H**Casing Attachments**

---

**Casing ID:** 1      **String Type:** SURFACE**Inspection Document:****Spec Document:****Tapered String Spec:****Casing Design Assumptions and Worksheet(s):**ochoa\_2h\_casing\_assumption\_20190626152340.JPG

---

**Casing ID:** 2      **String Type:** PRODUCTION**Inspection Document:****Spec Document:****Tapered String Spec:**

5.5\_tapered\_string\_spec\_20190626123411.jpg

**Casing Design Assumptions and Worksheet(s):**ochoa\_2h\_casing\_assumption\_20190626152333.JPG

---

**Casing ID:** 3      **String Type:** INTERMEDIATE**Inspection Document:****Spec Document:****Tapered String Spec:****Casing Design Assumptions and Worksheet(s):**ochoa\_2h\_casing\_assumption\_20190626152327.JPG

---



Operator Name: BTA OIL PRODUCERS LLC

Well Name: OCHOA 8703 FEDERAL COM

Well Number: 2H

## Casing Attachments

Casing ID: 4 String Type: PRODUCTION

Inspection Document:

Spec Document:

Tapered String Spec:

5\_tapered\_string\_spec\_20190626123520.jpg

Casing Design Assumptions and Worksheet(s):

ochoa\_2h\_casing\_assumption\_20190626152320.JPG

## Section 4 - Cement

String Type	Lead/Tail	Stage Tool Depth	Top MD	Bottom MD	Quantity(sx)	Yield	Density	Cu Ft	Excess%	Cement type	Additives
PRODUCTION	Lead		0	0	0	0	0	0		n/a	n/a
PRODUCTION	Tail		8990	9990							none
PRODUCTION	Lead		0	0	0	0	0	0		n/a	n/a
PRODUCTION	Tail		9990	1853 2	905	1.27	14.8	1149. 35	10	Class H	0.1% Fluid Loss
SURFACE	Lead		0	255	160	1.8	13.5	288	100	Class C	2% CaCl2
SURFACE	Tail		255	500	200	1.34	14.8	268	100	Class C	2% CaCl2
INTERMEDIATE	Lead	2762	0	2335	375	2.19	12.7	821.2 5	50	Class C	0.5% CaCl2
INTERMEDIATE	Tail		2335	2762	150	1.33	14.8	199.5	50	Class C	1% CaCl2
INTERMEDIATE	Lead		2762	8305	520	2.64	10.5	1372. 8	15	Class H	0.5% CaCl2
INTERMEDIATE	Tail		8305	1019 0	400	1.19	15.6	476	15	Class H	1% CaCl2

**Operator Name:** BTA OIL PRODUCERS LLC**Well Name:** OCHOA 8703 FEDERAL COM**Well Number:** 2H**Section 5 - Circulating Medium****Mud System Type:** Closed**Will an air or gas system be Used?** NO**Description of the equipment for the circulating system in accordance with Onshore Order #2:****Diagram of the equipment for the circulating system in accordance with Onshore Order #2:****Describe what will be on location to control well or mitigate other conditions:** Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.**Describe the mud monitoring system utilized:** PVT/Pason/Visual Monitoring**Circulating Medium Table**

Top Depth	Bottom Depth	Mud Type	Min Weight (lbs/gal)	Max Weight (lbs/gal)	Density (lbs/cu ft)	Gel Strength (lbs/100 sqft)	PH	Viscosity (CP)	Salinity (ppm)	Filtration (cc)	Additional Characteristics
0	500	OTHER : FW Spud	8.3	8.4							
500	1016 2	OTHER : DBE	9	9.4							
1016 2	1069 3	OIL-BASED MUD	11	13							

**Section 6 - Test, Logging, Coring****List of production tests including testing procedures, equipment and safety measures:**

Drill Stem Tests will be based on geological sample shows.

**List of open and cased hole logs run in the well:**

CBL,GR,MUDLOG

**Coring operation description for the well:**

None planned

**Operator Name:** BTA OIL PRODUCERS LLC**Well Name:** OCHOA 8703 FEDERAL COM**Well Number:** 2H

## Section 7 - Pressure

**Anticipated Bottom Hole Pressure:** 7228**Anticipated Surface Pressure:** 4875.54**Anticipated Bottom Hole Temperature(F):** 166**Anticipated abnormal pressures, temperatures, or potential geologic hazards?** NO**Describe:****Contingency Plans geohazards description:****Contingency Plans geohazards attachment:****Hydrogen Sulfide drilling operations plan required?** YES**Hydrogen sulfide drilling operations plan:**

H2S\_Plan\_20181129153648.pdf

H2S\_Equipment\_Schematic\_20181129153733.pdf

BTA\_Oil\_Producers\_LLC\_\_\_EMERGENCY\_CALL\_LIST\_20190205154800.pdf

## Section 8 - Other Information

**Proposed horizontal/directional/multi-lateral plan submission:**

Ochoa\_8703\_Federal\_\_2H\_directional\_plan\_20190626152952.pdf

Ochoa\_8703\_Federal\_\_2H\_Wall\_Plot\_20190626152952.pdf

Ochoa\_2H\_Gas\_Capture\_Plan\_20190626153003.pdf


**Other proposed operations facets description:**

A variance is requested for a Multi Bowl Wellhead. See the attached schematic and running procedure. \*All strings will be kept 1/3 full while running.

**Other proposed operations facets attachment:****Other Variance attachment:**

Casing\_Head\_Running\_Procedure\_20181129153916.pdf

Multi\_Bowl\_Diagram\_\_3\_STRING\_10\_34\_SOW\_\_20190626131606.pdf




### 5M CHOKES MANIFOLD EQUIPMENT - CONFIGURATION OF CHOKES MAY VARY

Although not required for any of the choke manifold systems, buffer tanks are sometimes installed downstream of the choke assemblies for the purpose of manifold the bleed lines together. When buffer tanks are employed, valves shall be installed upstream to isolate a failure or malfunction without interrupting flow control. Though not shown on 2M, 3M, 10M, OR 15M drawings, it would also be applicable to those situations.

[54 FR 39528, Sept. 27, 1989]

## 13-5/8" 5,000 PSI BOP



**BTA OIL PRODUCERS LLC****HYDROGEN SULFIDE DRILLING OPERATIONS PLAN****1. HYDROGEN SULFIDE TRAINING**

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

- a. The hazards and characteristics of hydrogen sulfide (H<sub>2</sub>S).
- b. The proper use and maintenance of personal protective equipment and life support systems.
- c. The proper use of H<sub>2</sub>S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
- d. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

- a. The effects of H<sub>2</sub>S on metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
- b. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
- c. The contents and requirements of the H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H<sub>2</sub>S zone (within 3 days or 500 feet) and weekly H<sub>2</sub>S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H<sub>2</sub>S Drilling Operations Plan and the Public Protection Plan. This plan shall be available at the well site. All personnel will be required to carry documentation that they have received the proper training.

**2. H<sub>2</sub>S SAFETY EQUIPMENT AND SYSTEMS**

Note: All H<sub>2</sub>S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H<sub>2</sub>S. If H<sub>2</sub>S greater than 100 ppm is encountered in the gas stream we will shut in and install H<sub>2</sub>S equipment.

- a. Well Control Equipment:
  - Flare line.
  - Choke manifold with remotely operated choke.
  - Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit.
  - Auxiliary equipment to include: annular preventer, mud-gas separator, rotating head.
- b. Protective equipment for essential personnel:
  - Mark II Surviveair 30-minute units located in the dog house and at briefing areas.
- c. H<sub>2</sub>S detection and monitoring equipment:



- 2 - portable H2S monitor positioned on location for best coverage and response. These units have warning lights and audible sirens when H2S levels of 20 ppm are reached.
- d. Visual warning systems:  
Caution/Danger signs shall be posted on roads providing direct access to location. Signs will be painted a high visibility yellow with black lettering of sufficient size to be readable at a reasonable distance from the immediate location. Bilingual signs will be used, when appropriate. See example attached.
- e. Mud Program:  
The mud program has been designed to minimize the volume of H2S circulated to the surface.
- f. Metallurgy:  
All drill strings, casings, tubing, wellhead, blowout preventers, drilling spool, kill lines, choke manifold and lines, and valves shall be suitable for H2S service.
- g. Communication:  
Company vehicles equipped with cellular telephone.


# **W A R N I N G**

**YOU ARE ENTERING AN H<sub>2</sub>S AREA  
AUTHORIZED PERSONNEL ONLY**

- 1. BEARDS OR CONTACT LENSES NOT ALLOWED**
- 2. HARD HATS REQUIRED**
- 3. SMOKING IN DESIGNATED AREAS ONLY**
- 4. BE WIND CONSCIOUS AT ALL TIMES**
- 5. CK WITH BTA OIL PRODUCERS LLC FOREMAN AT MAIN OFFICE**

**BTA OIL PRODUCERS LLC**

**1-432-682-3753**



## **EMERGENCY CALL LIST**

	<b><u>OFFICE</u></b>	<b><u>MOBILE</u></b>
BTA Oil Producers LLC OFFICE	432-682-3753	
BEN GRIMES, Operations	432-682-3753	432-559-4309
NICK EATON, Drilling	432-682-3753	432-260-7841
TRACE WOHLFAHRT, Completions	432-682-3753	

## **EMERGENCY RESPONSE NUMBERS**

	<b><u>OFFICE</u></b>
STATE POLICE	575-748-9718
EDDY COUNTY SHERIFF	575-746-2701
EMERGENCY MEDICAL SERVICES (AMBULANCE)	911 or 575-746-2701
EDDY COUNTY EMERGENCY MANAGEMENT (HARRY BURGESS)	575-887-9511
STATE EMERGENCY RESPONSE CENTER (SERC)	575-476-9620
CARLSBAD POLICE DEPARTMENT	575-885-2111
CARLSBAD FIRE DEPARTMENT	575-885-3125
NEW MEXICO OIL CONSERVATION DIVISION	575-748-1283
INDIAN FIRE & SAFETY	800-530-8693
HALLIBURTON SERVICES	800-844-8451

# **BTA Oil Producers, LLC**

**Eddy County, NM (NAD 83)**

**Ochoa**

**Ochoa #02H**

**Wellbore #1**

**Plan: Design #1**

## **Standard Planning Report - Geographic**

**21 June, 2019**

**Microsoft**  
Planning Report - Geographic

<b>Database:</b>	Old	<b>Local Co-ordinate Reference:</b>	Well Ochoa #02H
<b>Company:</b>	BTA Oil Producers, LLC	<b>TVD Reference:</b>	GL @ 3016.0usft
<b>Project:</b>	Eddy County, NM (NAD 83)	<b>MD Reference:</b>	GL @ 3016.0usft
<b>Site:</b>	Ochoa	<b>North Reference:</b>	Grid
<b>Well:</b>	Ochoa #02H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

<b>Project</b>	Eddy County, NM (NAD 83)		
<b>Map System:</b>	US State Plane 1983	<b>System Datum:</b>	Ground Level
<b>Geo Datum:</b>	North American Datum 1983		
<b>Map Zone:</b>	New Mexico Eastern Zone		Using geodetic scale factor

Site	Ochoa					
Site Position:		Northing:	481,307.00 usft	Latitude:	32° 19' 22.181 N	
From:	Map	Easting:	634,083.00 usft	Longitude:	104° 1' 59.112 W	
Position Uncertainty:		0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.16 °

Well	Ochoa #02H					
Well Position	+N/-S	0.0 usft	Northing:	481,355.00 usft	Latitude:	32° 19' 22.657 N
	+E/-W	0.0 usft	Easting:	634,056.00 usft	Longitude:	104° 1' 59.425 W
Position Uncertainty		0.0 usft	Wellhead Elevation:		Ground Level:	3,016.0 usft

<b>Wellbore</b>	Wellbore #1				
<b>Magnetics</b>	<b>Model Name</b>	<b>Sample Date</b>	<b>Declination (°)</b>	<b>Dip Angle (°)</b>	<b>Field Strength (nT)</b>
	IGRF200510	12/31/2009	7.97	60.25	48,803.84606979

Design	Design #1				
Audit Notes:					
Version:	Phase:	PROTOTYPE		Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)	
	0.0	0.0	0.0	86.44	

<b>Plan Survey Tool Program</b>	<b>Date</b>	6/6/2019			
<b>Depth From (usft)</b>	<b>Depth To (usft)</b>	<b>Survey (Wellbore)</b>	<b>Tool Name</b>	<b>Remarks</b>	
1	0.0	18,532.0 Design #1 (Wellbore #1)			

<b>Plan Sections</b>										
<b>Measured Depth (usft)</b>	<b>Inclination (°)</b>	<b>Azimuth (°)</b>	<b>Vertical Depth (usft)</b>	<b>+N/-S (usft)</b>	<b>+E/-W (usft)</b>	<b>Dogleg Rate (°/100usft)</b>	<b>Build Rate (°/100usft)</b>	<b>Turn Rate (°/100usft)</b>	<b>TFO (°)</b>	<b>Target</b>
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,366.0	0.00	0.00	1,366.0	0.0	0.0	0.00	0.00	0.00	0.00	
1,616.0	5.00	0.00	1,615.7	10.9	0.0	2.00	2.00	0.00	0.00	
8,777.9	5.00	0.00	8,750.3	635.1	0.0	0.00	0.00	0.00	0.00	
9,027.9	0.00	0.00	9,000.0	646.0	0.0	2.00	-2.00	0.00	180.00	
10,243.4	0.00	0.00	10,215.5	646.0	0.0	0.00	0.00	0.00	0.00	
10,993.4	90.00	91.05	10,693.0	637.2	477.4	12.00	12.00	0.00	91.05	
18,532.0	90.00	91.05	10,693.0	499.0	8,014.6	0.00	0.00	0.00	0.00	Ochoa #2H BHL

**Microsoft**  
Planning Report - Geographic

<b>Database:</b>	Old	<b>Local Co-ordinate Reference:</b>	Well Ochoa #02H
<b>Company:</b>	BTA Oil Producers, LLC	<b>TVD Reference:</b>	GL @ 3016.0usft
<b>Project:</b>	Eddy County, NM (NAD 83)	<b>MD Reference:</b>	GL @ 3016.0usft
<b>Site:</b>	Ochoa	<b>North Reference:</b>	Grid
<b>Well:</b>	Ochoa #02H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude
0.0	0.00	0.00	0.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
100.0	0.00	0.00	100.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
200.0	0.00	0.00	200.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
300.0	0.00	0.00	300.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
400.0	0.00	0.00	400.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
500.0	0.00	0.00	500.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
600.0	0.00	0.00	600.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
700.0	0.00	0.00	700.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
800.0	0.00	0.00	800.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
900.0	0.00	0.00	900.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
1,000.0	0.00	0.00	1,000.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
1,100.0	0.00	0.00	1,100.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
1,200.0	0.00	0.00	1,200.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
1,300.0	0.00	0.00	1,300.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
1,366.0	0.00	0.00	1,366.0	0.0	0.0	481,355.00	634,056.00	32° 19' 22.657 N	104° 1' 59.425 W
1,400.0	0.68	0.00	1,400.0	0.2	0.0	481,355.20	634,056.00	32° 19' 22.659 N	104° 1' 59.425 W
1,500.0	2.68	0.00	1,500.0	3.1	0.0	481,358.13	634,056.00	32° 19' 22.688 N	104° 1' 59.425 W
1,600.0	4.68	0.00	1,599.7	9.5	0.0	481,364.55	634,056.00	32° 19' 22.751 N	104° 1' 59.425 W
1,616.0	5.00	0.00	1,615.7	10.9	0.0	481,365.90	634,056.00	32° 19' 22.765 N	104° 1' 59.425 W
1,700.0	5.00	0.00	1,699.4	18.2	0.0	481,373.22	634,056.00	32° 19' 22.837 N	104° 1' 59.424 W
1,800.0	5.00	0.00	1,799.0	26.9	0.0	481,381.93	634,056.00	32° 19' 22.923 N	104° 1' 59.424 W
1,900.0	5.00	0.00	1,898.6	35.7	0.0	481,390.65	634,056.00	32° 19' 23.010 N	104° 1' 59.424 W
2,000.0	5.00	0.00	1,998.2	44.4	0.0	481,399.36	634,056.00	32° 19' 23.096 N	104° 1' 59.423 W
2,100.0	5.00	0.00	2,097.8	53.1	0.0	481,408.08	634,056.00	32° 19' 23.182 N	104° 1' 59.423 W
2,200.0	5.00	0.00	2,197.5	61.8	0.0	481,416.79	634,056.00	32° 19' 23.268 N	104° 1' 59.423 W
2,300.0	5.00	0.00	2,297.1	70.5	0.0	481,425.51	634,056.00	32° 19' 23.354 N	104° 1' 59.423 W
2,400.0	5.00	0.00	2,396.7	79.2	0.0	481,434.22	634,056.00	32° 19' 23.441 N	104° 1' 59.422 W
2,500.0	5.00	0.00	2,496.3	87.9	0.0	481,442.94	634,056.00	32° 19' 23.527 N	104° 1' 59.422 W
2,600.0	5.00	0.00	2,595.9	96.7	0.0	481,451.65	634,056.00	32° 19' 23.613 N	104° 1' 59.422 W
2,700.0	5.00	0.00	2,695.6	105.4	0.0	481,460.37	634,056.00	32° 19' 23.699 N	104° 1' 59.421 W
2,800.0	5.00	0.00	2,795.2	114.1	0.0	481,469.08	634,056.00	32° 19' 23.786 N	104° 1' 59.421 W
2,900.0	5.00	0.00	2,894.8	122.8	0.0	481,477.80	634,056.00	32° 19' 23.872 N	104° 1' 59.421 W
3,000.0	5.00	0.00	2,994.4	131.5	0.0	481,486.51	634,056.00	32° 19' 23.958 N	104° 1' 59.421 W
3,100.0	5.00	0.00	3,094.0	140.2	0.0	481,495.23	634,056.00	32° 19' 24.044 N	104° 1' 59.420 W
3,200.0	5.00	0.00	3,193.7	149.0	0.0	481,503.94	634,056.00	32° 19' 24.131 N	104° 1' 59.420 W
3,300.0	5.00	0.00	3,293.3	157.7	0.0	481,512.66	634,056.00	32° 19' 24.217 N	104° 1' 59.420 W
3,400.0	5.00	0.00	3,392.9	166.4	0.0	481,521.37	634,056.00	32° 19' 24.303 N	104° 1' 59.419 W
3,500.0	5.00	0.00	3,492.5	175.1	0.0	481,530.09	634,056.00	32° 19' 24.389 N	104° 1' 59.419 W
3,600.0	5.00	0.00	3,592.1	183.8	0.0	481,538.80	634,056.00	32° 19' 24.476 N	104° 1' 59.419 W
3,700.0	5.00	0.00	3,691.8	192.5	0.0	481,547.52	634,056.00	32° 19' 24.562 N	104° 1' 59.419 W
3,800.0	5.00	0.00	3,791.4	201.2	0.0	481,556.23	634,056.00	32° 19' 24.648 N	104° 1' 59.418 W
3,900.0	5.00	0.00	3,891.0	210.0	0.0	481,564.95	634,056.00	32° 19' 24.734 N	104° 1' 59.418 W
4,000.0	5.00	0.00	3,990.6	218.7	0.0	481,573.66	634,056.00	32° 19' 24.821 N	104° 1' 59.418 W
4,100.0	5.00	0.00	4,090.2	227.4	0.0	481,582.38	634,056.00	32° 19' 24.907 N	104° 1' 59.417 W
4,200.0	5.00	0.00	4,189.8	236.1	0.0	481,591.09	634,056.00	32° 19' 24.993 N	104° 1' 59.417 W
4,300.0	5.00	0.00	4,289.5	244.8	0.0	481,599.81	634,056.00	32° 19' 25.079 N	104° 1' 59.417 W
4,400.0	5.00	0.00	4,389.1	253.5	0.0	481,608.52	634,056.00	32° 19' 25.166 N	104° 1' 59.417 W
4,500.0	5.00	0.00	4,488.7	262.3	0.0	481,617.24	634,056.00	32° 19' 25.252 N	104° 1' 59.416 W
4,600.0	5.00	0.00	4,588.3	271.0	0.0	481,625.95	634,056.00	32° 19' 25.338 N	104° 1' 59.416 W
4,700.0	5.00	0.00	4,687.9	279.7	0.0	481,634.67	634,056.00	32° 19' 25.424 N	104° 1' 59.416 W
4,800.0	5.00	0.00	4,787.6	288.4	0.0	481,643.38	634,056.00	32° 19' 25.510 N	104° 1' 59.415 W
4,900.0	5.00	0.00	4,887.2	297.1	0.0	481,652.10	634,056.00	32° 19' 25.597 N	104° 1' 59.415 W
5,000.0	5.00	0.00	4,986.8	305.8	0.0	481,660.81	634,056.00	32° 19' 25.683 N	104° 1' 59.415 W
5,100.0	5.00	0.00	5,086.4	314.5	0.0	481,669.52	634,056.00	32° 19' 25.769 N	104° 1' 59.415 W
5,200.0	5.00	0.00	5,186.0	323.3	0.0	481,678.24	634,056.00	32° 19' 25.855 N	104° 1' 59.414 W



**Microsoft**  
Planning Report - Geographic

<b>Database:</b>	Old	<b>Local Co-ordinate Reference:</b>	Well Ochoa #02H
<b>Company:</b>	BTA Oil Producers, LLC	<b>TVD Reference:</b>	GL @ 3016.0usft
<b>Project:</b>	Eddy County, NM (NAD 83)	<b>MD Reference:</b>	GL @ 3016.0usft
<b>Site:</b>	Ochoa	<b>North Reference:</b>	Grid
<b>Well:</b>	Ochoa #02H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
5,300.0	5.00	0.00	5,285.7	332.0	0.0	481,686.95	634,056.00	32° 19' 25.942 N	104° 1' 59.414 W	
5,400.0	5.00	0.00	5,385.3	340.7	0.0	481,695.67	634,056.00	32° 19' 26.028 N	104° 1' 59.414 W	
5,500.0	5.00	0.00	5,484.9	349.4	0.0	481,704.38	634,056.00	32° 19' 26.114 N	104° 1' 59.413 W	
5,600.0	5.00	0.00	5,584.5	358.1	0.0	481,713.10	634,056.00	32° 19' 26.200 N	104° 1' 59.413 W	
5,700.0	5.00	0.00	5,684.1	366.8	0.0	481,721.81	634,056.00	32° 19' 26.287 N	104° 1' 59.413 W	
5,800.0	5.00	0.00	5,783.8	375.6	0.0	481,730.53	634,056.00	32° 19' 26.373 N	104° 1' 59.413 W	
5,900.0	5.00	0.00	5,883.4	384.3	0.0	481,739.24	634,056.00	32° 19' 26.459 N	104° 1' 59.412 W	
6,000.0	5.00	0.00	5,983.0	393.0	0.0	481,747.96	634,056.00	32° 19' 26.545 N	104° 1' 59.412 W	
6,100.0	5.00	0.00	6,082.6	401.7	0.0	481,756.67	634,056.00	32° 19' 26.632 N	104° 1' 59.412 W	
6,200.0	5.00	0.00	6,182.2	410.4	0.0	481,765.39	634,056.00	32° 19' 26.718 N	104° 1' 59.411 W	
6,300.0	5.00	0.00	6,281.9	419.1	0.0	481,774.10	634,056.00	32° 19' 26.804 N	104° 1' 59.411 W	
6,400.0	5.00	0.00	6,381.5	427.9	0.0	481,782.82	634,056.00	32° 19' 26.890 N	104° 1' 59.411 W	
6,500.0	5.00	0.00	6,481.1	436.6	0.0	481,791.53	634,056.00	32° 19' 26.977 N	104° 1' 59.411 W	
6,600.0	5.00	0.00	6,580.7	445.3	0.0	481,800.25	634,056.00	32° 19' 27.063 N	104° 1' 59.410 W	
6,700.0	5.00	0.00	6,680.3	454.0	0.0	481,808.96	634,056.00	32° 19' 27.149 N	104° 1' 59.410 W	
6,800.0	5.00	0.00	6,780.0	462.7	0.0	481,817.68	634,056.00	32° 19' 27.235 N	104° 1' 59.410 W	
6,900.0	5.00	0.00	6,879.6	471.4	0.0	481,826.39	634,056.00	32° 19' 27.322 N	104° 1' 59.409 W	
7,000.0	5.00	0.00	6,979.2	480.1	0.0	481,835.11	634,056.00	32° 19' 27.408 N	104° 1' 59.409 W	
7,100.0	5.00	0.00	7,078.8	488.9	0.0	481,843.82	634,056.00	32° 19' 27.494 N	104° 1' 59.409 W	
7,200.0	5.00	0.00	7,178.4	497.6	0.0	481,852.54	634,056.00	32° 19' 27.580 N	104° 1' 59.409 W	
7,300.0	5.00	0.00	7,278.1	506.3	0.0	481,861.25	634,056.00	32° 19' 27.666 N	104° 1' 59.408 W	
7,400.0	5.00	0.00	7,377.7	515.0	0.0	481,869.97	634,056.00	32° 19' 27.753 N	104° 1' 59.408 W	
7,500.0	5.00	0.00	7,477.3	523.7	0.0	481,878.68	634,056.00	32° 19' 27.839 N	104° 1' 59.408 W	
7,600.0	5.00	0.00	7,576.9	532.4	0.0	481,887.40	634,056.00	32° 19' 27.925 N	104° 1' 59.408 W	
7,700.0	5.00	0.00	7,676.5	541.2	0.0	481,896.11	634,056.00	32° 19' 28.011 N	104° 1' 59.407 W	
7,800.0	5.00	0.00	7,776.2	549.9	0.0	481,904.83	634,056.00	32° 19' 28.098 N	104° 1' 59.407 W	
7,900.0	5.00	0.00	7,875.8	558.6	0.0	481,913.54	634,056.00	32° 19' 28.184 N	104° 1' 59.407 W	
8,000.0	5.00	0.00	7,975.4	567.3	0.0	481,922.26	634,056.00	32° 19' 28.270 N	104° 1' 59.406 W	
8,100.0	5.00	0.00	8,075.0	576.0	0.0	481,930.97	634,056.00	32° 19' 28.356 N	104° 1' 59.406 W	
8,200.0	5.00	0.00	8,174.6	584.7	0.0	481,939.69	634,056.00	32° 19' 28.443 N	104° 1' 59.406 W	
8,300.0	5.00	0.00	8,274.2	593.4	0.0	481,948.40	634,056.00	32° 19' 28.529 N	104° 1' 59.406 W	
8,400.0	5.00	0.00	8,373.9	602.2	0.0	481,957.12	634,056.00	32° 19' 28.615 N	104° 1' 59.405 W	
8,500.0	5.00	0.00	8,473.5	610.9	0.0	481,965.83	634,056.00	32° 19' 28.701 N	104° 1' 59.405 W	
8,600.0	5.00	0.00	8,573.1	619.6	0.0	481,974.55	634,056.00	32° 19' 28.788 N	104° 1' 59.405 W	
8,700.0	5.00	0.00	8,672.7	628.3	0.0	481,983.26	634,056.00	32° 19' 28.874 N	104° 1' 59.404 W	
8,777.9	5.00	0.00	8,750.3	635.1	0.0	481,990.05	634,056.00	32° 19' 28.941 N	104° 1' 59.404 W	
8,800.0	4.56	0.00	8,772.4	636.9	0.0	481,991.89	634,056.00	32° 19' 28.959 N	104° 1' 59.404 W	
8,900.0	2.56	0.00	8,872.2	643.1	0.0	481,998.09	634,056.00	32° 19' 29.021 N	104° 1' 59.404 W	
9,000.0	0.56	0.00	8,972.1	645.9	0.0	482,000.81	634,056.00	32° 19' 29.048 N	104° 1' 59.404 W	
9,027.9	0.00	0.00	9,000.0	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,100.0	0.00	0.00	9,072.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,200.0	0.00	0.00	9,172.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,300.0	0.00	0.00	9,272.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,400.0	0.00	0.00	9,372.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,500.0	0.00	0.00	9,472.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,600.0	0.00	0.00	9,572.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,700.0	0.00	0.00	9,672.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,800.0	0.00	0.00	9,772.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
9,900.0	0.00	0.00	9,872.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
10,000.0	0.00	0.00	9,972.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
10,100.0	0.00	0.00	10,072.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
10,200.0	0.00	0.00	10,172.1	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
10,243.4	0.00	0.00	10,215.5	646.0	0.0	482,000.95	634,056.00	32° 19' 29.049 N	104° 1' 59.404 W	
10,300.0	6.79	91.05	10,272.0	645.9	3.3	482,000.89	634,059.35	32° 19' 29.048 N	104° 1' 59.365 W	
10,400.0	18.79	91.05	10,369.3	645.5	25.4	482,000.48	634,081.44	32° 19' 29.044 N	104° 1' 59.107 W	

**Microsoft**  
Planning Report - Geographic

<b>Database:</b>	Old	<b>Local Co-ordinate Reference:</b>	Well Ochoa #02H
<b>Company:</b>	BTA Oil Producers, LLC	<b>TVD Reference:</b>	GL @ 3016.0usft
<b>Project:</b>	Eddy County, NM (NAD 83)	<b>MD Reference:</b>	GL @ 3016.0usft
<b>Site:</b>	Ochoa	<b>North Reference:</b>	Grid
<b>Well:</b>	Ochoa #02H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
10,500.0	30.79	91.05	10,459.9	644.8	67.3	481,999.71	634,123.28	32° 19' 29.035 N	104° 1' 58.620 W	
10,600.0	42.79	91.05	10,539.9	643.7	127.1	481,998.62	634,183.05	32° 19' 29.022 N	104° 1' 57.923 W	
10,700.0	54.79	91.05	10,605.6	642.3	202.1	481,997.24	634,258.12	32° 19' 29.007 N	104° 1' 57.048 W	
10,800.0	66.79	91.05	10,654.4	640.7	289.2	481,995.65	634,345.22	32° 19' 28.988 N	104° 1' 56.033 W	
10,900.0	78.79	91.05	10,683.9	638.9	384.6	481,993.90	634,440.55	32° 19' 28.968 N	104° 1' 54.922 W	
10,993.4	90.00	91.05	10,693.0	637.2	477.4	481,992.20	634,533.35	32° 19' 28.949 N	104° 1' 53.841 W	
11,000.0	90.00	91.05	10,693.0	637.1	484.0	481,992.08	634,539.93	32° 19' 28.948 N	104° 1' 53.764 W	
11,100.0	90.00	91.05	10,693.0	635.3	583.9	481,990.24	634,639.90	32° 19' 28.927 N	104° 1' 52.599 W	
11,200.0	90.00	91.05	10,693.0	633.5	683.9	481,988.41	634,739.88	32° 19' 28.906 N	104° 1' 51.434 W	
11,300.0	90.00	91.05	10,693.0	631.6	783.9	481,986.58	634,839.85	32° 19' 28.885 N	104° 1' 50.269 W	
11,400.0	90.00	91.05	10,693.0	629.8	883.9	481,984.74	634,939.83	32° 19' 28.864 N	104° 1' 49.104 W	
11,500.0	90.00	91.05	10,693.0	628.0	983.9	481,982.91	635,039.80	32° 19' 28.843 N	104° 1' 47.939 W	
11,600.0	90.00	91.05	10,693.0	626.1	1,083.9	481,981.08	635,139.78	32° 19' 28.822 N	104° 1' 46.774 W	
11,700.0	90.00	91.05	10,693.0	624.3	1,183.8	481,979.24	635,239.75	32° 19' 28.801 N	104° 1' 45.609 W	
11,800.0	90.00	91.05	10,693.0	622.5	1,283.8	481,977.41	635,339.73	32° 19' 28.780 N	104° 1' 44.443 W	
11,900.0	90.00	91.05	10,693.0	620.6	1,383.8	481,975.58	635,439.70	32° 19' 28.759 N	104° 1' 43.278 W	
12,000.0	90.00	91.05	10,693.0	618.8	1,483.8	481,973.74	635,539.68	32° 19' 28.738 N	104° 1' 42.113 W	
12,100.0	90.00	91.05	10,693.0	617.0	1,583.8	481,971.91	635,639.65	32° 19' 28.717 N	104° 1' 40.948 W	
12,200.0	90.00	91.05	10,693.0	615.1	1,683.8	481,970.08	635,739.63	32° 19' 28.696 N	104° 1' 39.783 W	
12,300.0	90.00	91.05	10,693.0	613.3	1,783.7	481,968.24	635,839.60	32° 19' 28.675 N	104° 1' 38.618 W	
12,400.0	90.00	91.05	10,693.0	611.5	1,883.7	481,966.41	635,939.58	32° 19' 28.654 N	104° 1' 37.453 W	
12,500.0	90.00	91.05	10,693.0	609.6	1,983.7	481,964.58	636,039.55	32° 19' 28.633 N	104° 1' 36.288 W	
12,600.0	90.00	91.05	10,693.0	607.8	2,083.7	481,962.74	636,139.53	32° 19' 28.612 N	104° 1' 35.123 W	
12,700.0	90.00	91.05	10,693.0	606.0	2,183.7	481,960.91	636,239.50	32° 19' 28.591 N	104° 1' 33.958 W	
12,800.0	90.00	91.05	10,693.0	604.1	2,283.7	481,959.08	636,339.48	32° 19' 28.570 N	104° 1' 32.793 W	
12,900.0	90.00	91.05	10,693.0	602.3	2,383.6	481,957.24	636,439.45	32° 19' 28.549 N	104° 1' 31.627 W	
13,000.0	90.00	91.05	10,693.0	600.5	2,483.6	481,955.41	636,539.43	32° 19' 28.529 N	104° 1' 30.462 W	
13,100.0	90.00	91.05	10,693.0	598.6	2,583.6	481,953.58	636,639.40	32° 19' 28.508 N	104° 1' 29.297 W	
13,200.0	90.00	91.05	10,693.0	596.8	2,683.6	481,951.75	636,739.38	32° 19' 28.487 N	104° 1' 28.132 W	
13,300.0	90.00	91.05	10,693.0	595.0	2,783.6	481,949.91	636,839.35	32° 19' 28.466 N	104° 1' 26.967 W	
13,400.0	90.00	91.05	10,693.0	593.1	2,883.6	481,948.08	636,939.33	32° 19' 28.445 N	104° 1' 25.802 W	
13,500.0	90.00	91.05	10,693.0	591.3	2,983.5	481,946.25	637,039.30	32° 19' 28.424 N	104° 1' 24.637 W	
13,600.0	90.00	91.05	10,693.0	589.5	3,083.5	481,944.41	637,139.28	32° 19' 28.403 N	104° 1' 23.472 W	
13,700.0	90.00	91.05	10,693.0	587.6	3,183.5	481,942.58	637,239.25	32° 19' 28.382 N	104° 1' 22.307 W	
13,800.0	90.00	91.05	10,693.0	585.8	3,283.5	481,940.75	637,339.23	32° 19' 28.361 N	104° 1' 21.142 W	
13,900.0	90.00	91.05	10,693.0	584.0	3,383.5	481,938.91	637,439.20	32° 19' 28.340 N	104° 1' 19.977 W	
14,000.0	90.00	91.05	10,693.0	582.1	3,483.5	481,937.08	637,539.18	32° 19' 28.318 N	104° 1' 18.811 W	
14,100.0	90.00	91.05	10,693.0	580.3	3,583.4	481,935.25	637,639.15	32° 19' 28.297 N	104° 1' 17.646 W	
14,200.0	90.00	91.05	10,693.0	578.5	3,683.4	481,933.41	637,739.13	32° 19' 28.276 N	104° 1' 16.481 W	
14,300.0	90.00	91.05	10,693.0	576.6	3,783.4	481,931.58	637,839.10	32° 19' 28.255 N	104° 1' 15.316 W	
14,400.0	90.00	91.05	10,693.0	574.8	3,883.4	481,929.75	637,939.08	32° 19' 28.234 N	104° 1' 14.151 W	
14,500.0	90.00	91.05	10,693.0	573.0	3,983.4	481,927.91	638,039.05	32° 19' 28.213 N	104° 1' 12.986 W	
14,600.0	90.00	91.05	10,693.0	571.1	4,083.4	481,926.08	638,139.03	32° 19' 28.192 N	104° 1' 11.821 W	
14,700.0	90.00	91.05	10,693.0	569.3	4,183.3	481,924.25	638,239.00	32° 19' 28.171 N	104° 1' 10.656 W	
14,800.0	90.00	91.05	10,693.0	567.5	4,283.3	481,922.41	638,338.98	32° 19' 28.150 N	104° 1' 9.491 W	
14,900.0	90.00	91.05	10,693.0	565.6	4,383.3	481,920.58	638,438.95	32° 19' 28.129 N	104° 1' 8.326 W	
15,000.0	90.00	91.05	10,693.0	563.8	4,483.3	481,918.75	638,538.93	32° 19' 28.108 N	104° 1' 7.161 W	
15,100.0	90.00	91.05	10,693.0	562.0	4,583.3	481,916.91	638,638.90	32° 19' 28.087 N	104° 1' 5.996 W	
15,200.0	90.00	91.05	10,693.0	560.1	4,683.3	481,915.08	638,738.88	32° 19' 28.066 N	104° 1' 4.830 W	
15,300.0	90.00	91.05	10,693.0	558.3	4,783.2	481,913.25	638,838.85	32° 19' 28.045 N	104° 1' 3.665 W	
15,400.0	90.00	91.05	10,693.0	556.5	4,883.2	481,911.42	638,938.83	32° 19' 28.024 N	104° 1' 2.500 W	
15,500.0	90.00	91.05	10,693.0	554.6	4,983.2	481,909.58	639,038.80	32° 19' 28.003 N	104° 1' 1.335 W	
15,600.0	90.00	91.05	10,693.0	552.8	5,083.2	481,907.75	639,138.78	32° 19' 27.982 N	104° 1' 0.170 W	
15,700.0	90.00	91.05	10,693.0	551.0	5,183.2	481,905.92	639,238.76	32° 19' 27.961 N	104° 0' 59.005 W	
15,800.0	90.00	91.05	10,693.0	549.1	5,283.2	481,904.08	639,338.73	32° 19' 27.940 N	104° 0' 57.840 W	


**Microsoft**  
Planning Report - Geographic

<b>Database:</b>	Old	<b>Local Co-ordinate Reference:</b>	Well Ochoa #02H
<b>Company:</b>	BTA Oil Producers, LLC	<b>TVD Reference:</b>	GL @ 3016.0usft
<b>Project:</b>	Eddy County, NM (NAD 83)	<b>MD Reference:</b>	GL @ 3016.0usft
<b>Site:</b>	Ochoa	<b>North Reference:</b>	Grid
<b>Well:</b>	Ochoa #02H	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	Wellbore #1		
<b>Design:</b>	Design #1		

Planned Survey										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Map Northing (usft)	Map Easting (usft)	Latitude	Longitude	
15,900.0	90.00	91.05	10,693.0	547.3	5,383.1	481,902.25	639,438.71	32° 19' 27.919 N	104° 0' 56.675 W	
16,000.0	90.00	91.05	10,693.0	545.5	5,483.1	481,900.42	639,538.68	32° 19' 27.898 N	104° 0' 55.510 W	
16,100.0	90.00	91.05	10,693.0	543.6	5,583.1	481,898.58	639,638.66	32° 19' 27.876 N	104° 0' 54.345 W	
16,200.0	90.00	91.05	10,693.0	541.8	5,683.1	481,896.75	639,738.63	32° 19' 27.855 N	104° 0' 53.180 W	
16,300.0	90.00	91.05	10,693.0	540.0	5,783.1	481,894.92	639,838.61	32° 19' 27.834 N	104° 0' 52.014 W	
16,400.0	90.00	91.05	10,693.0	538.1	5,883.1	481,893.08	639,938.58	32° 19' 27.813 N	104° 0' 50.849 W	
16,500.0	90.00	91.05	10,693.0	536.3	5,983.0	481,891.25	640,038.56	32° 19' 27.792 N	104° 0' 49.684 W	
16,600.0	90.00	91.05	10,693.0	534.5	6,083.0	481,889.42	640,138.53	32° 19' 27.771 N	104° 0' 48.519 W	
16,700.0	90.00	91.05	10,693.0	532.6	6,183.0	481,887.58	640,238.51	32° 19' 27.750 N	104° 0' 47.354 W	
16,800.0	90.00	91.05	10,693.0	530.8	6,283.0	481,885.75	640,338.48	32° 19' 27.729 N	104° 0' 46.189 W	
16,900.0	90.00	91.05	10,693.0	529.0	6,383.0	481,883.92	640,438.46	32° 19' 27.708 N	104° 0' 45.024 W	
17,000.0	90.00	91.05	10,693.0	527.1	6,483.0	481,882.08	640,538.43	32° 19' 27.687 N	104° 0' 43.859 W	
17,100.0	90.00	91.05	10,693.0	525.3	6,582.9	481,880.25	640,638.41	32° 19' 27.666 N	104° 0' 42.694 W	
17,200.0	90.00	91.05	10,693.0	523.5	6,682.9	481,878.42	640,738.38	32° 19' 27.644 N	104° 0' 41.529 W	
17,300.0	90.00	91.05	10,693.0	521.6	6,782.9	481,876.58	640,838.36	32° 19' 27.623 N	104° 0' 40.364 W	
17,400.0	90.00	91.05	10,693.0	519.8	6,882.9	481,874.75	640,938.33	32° 19' 27.602 N	104° 0' 39.199 W	
17,500.0	90.00	91.05	10,693.0	518.0	6,982.9	481,872.92	641,038.31	32° 19' 27.581 N	104° 0' 38.033 W	
17,600.0	90.00	91.05	10,693.0	516.1	7,082.9	481,871.09	641,138.28	32° 19' 27.560 N	104° 0' 36.868 W	
17,700.0	90.00	91.05	10,693.0	514.3	7,182.8	481,869.25	641,238.26	32° 19' 27.539 N	104° 0' 35.703 W	
17,800.0	90.00	91.05	10,693.0	512.5	7,282.8	481,867.42	641,338.23	32° 19' 27.518 N	104° 0' 34.538 W	
17,900.0	90.00	91.05	10,693.0	510.6	7,382.8	481,865.59	641,438.21	32° 19' 27.497 N	104° 0' 33.373 W	
18,000.0	90.00	91.05	10,693.0	508.8	7,482.8	481,863.75	641,538.18	32° 19' 27.475 N	104° 0' 32.208 W	
18,100.0	90.00	91.05	10,693.0	507.0	7,582.8	481,861.92	641,638.16	32° 19' 27.454 N	104° 0' 31.043 W	
18,200.0	90.00	91.05	10,693.0	505.1	7,682.8	481,860.09	641,738.13	32° 19' 27.433 N	104° 0' 29.878 W	
18,300.0	90.00	91.05	10,693.0	503.3	7,782.7	481,858.25	641,838.11	32° 19' 27.412 N	104° 0' 28.713 W	
18,400.0	90.00	91.05	10,693.0	501.5	7,882.7	481,856.42	641,938.08	32° 19' 27.391 N	104° 0' 27.548 W	
18,500.0	90.00	91.05	10,693.0	499.6	7,982.7	481,854.59	642,038.06	32° 19' 27.370 N	104° 0' 26.383 W	
18,532.0	90.00	91.05	10,693.0	499.0	8,014.6	481,854.00	642,070.00	32° 19' 27.363 N	104° 0' 26.010 W	

Design Targets										
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude	
Ochoa #2H BHL	0.00	0.00	10,693.0	499.0	8,014.6	481,854.00	642,070.00	32° 19' 27.363 N	104° 0' 26.010 W	
- hit/miss target										
- Shape										
- plan hits target center										
- Point										

## BTA Oil Producers, LLC



Azimuths to Grid North  
 True North:  $-0.16^\circ$   
 Magnetic North:  $7.81^\circ$   
 Magnetic Field  
 Strength: 48803.8nT  
 Dip Angle:  $60.25^\circ$   
 Date: 12/31/2009  
 Model: IGRF200510

## SITE DETAILS: Ochoa

Site Centre Northing: 481307.00  
 Easting: 634083.00

Positional Uncertainty: 0.0  
 Convergence: 0.16  
 Local North: Grid

## SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg
1	0.0	0.00	0.00	0.0	0.0	0.0	0.00
2	1366.0	0.00	0.00	1366.0	0.0	0.0	0.00
3	1616.0	5.00	0.00	1615.7	10.9	0.0	2.00
4	8777.9	5.00	0.00	8750.3	635.1	0.0	0.00
5	9027.9	0.00	0.00	9000.0	646.0	0.0	2.00
6	10243.4	0.00	0.00	10215.5	646.0	0.0	0.00
7	10993.4	90.00	91.05	10693.0	637.2	477.4	12.00
8	18532.0	90.00	91.05	10693.0	499.0	8014.6	0.00



## PROJECT DETAILS: Eddy County, NM (NAD 83)

Geodetic System: US State Plane 1983  
 Datum: North American Datum 1983  
 Ellipsoid: GRS 1980  
 Zone: New Mexico Eastern Zone

System Datum: Ground Level

## WELL DETAILS: Ochoa #02H

+N/-S	+E/-W	Northing	Easting	Ground Level	3016.0	Latitude	Longitude
0.0	0.0	481355.00	634056.00			32° 19' 22.657 N	104° 1' 59.425 W



District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
811 S. First St., Artesia, NM 88210  
District III  
1000 Rio Brazos Road, Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources Department  
Oil Conservation Division  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

Submit Original  
to Appropriate  
District Office

### GAS CAPTURE PLAN

Date: 5/6/2019

☒ Original

Operator & OGRID No.: 260297

☐ Amended - Reason for Amendment: \_\_\_\_\_

This Gas Capture Plan outlines actions to be taken by the Operator to reduce well/production facility flaring/venting for new completion (new drill, recomple to new zone, re-frac) activity.

*Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).*

#### Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
OCHOA 8703		SEC 12 ; 23S ; 28E	1647 FNL 361.7 FEL	2000	Flared	Battery Connected
FEDERAL 2H						To ETP System

#### Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if gas transporter system is in place. The gas produced from production facility is dedicated to Gas Transporter and will be connected to Gas Transporter low/high pressure gathering system located in EDDY County, New Mexico. It will require 0 ' of pipeline to (ETP) connect the facility to low/high pressure gathering system. Operator provides (periodically) to Gas Transporter a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Operator and Gas Transporter have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at Gas Transporter Processing Plant located in Sec.\_\_\_\_, Twn.\_\_\_\_, Rng.\_\_\_\_, \_\_\_\_\_ County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

#### Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on Gas Transporter system at that time. Based on current information, it is Operator's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.


#### Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.


- Power Generation – On lease
  - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
  - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
  - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines




## WFT Split Bowl (SB) Wellhead System

**WFT-SB Split  
Multi-Bowl/  
Conventional  
Wellhead System**


RP104091

 <b>Weatherford</b> 5-3-GL-GL-WES-00XXX	<b>Field Service Manual</b>	Prepared By:	Reviewed By:	Approved By:	<b>SM-13-1</b>
		<i>Marion Robertson</i>	Brad Franks	Manual Zaragoza	<b>Rev WIP</b>
		Marion Robertson	Brad Franks	Manual Zaragoza	Page 3 of 24
		December 2014	December 2014	December 2014	





10-3/4" x 7-5/8" x 5-1/2" WH

TubingHead

SW-TCM

13-5/8"10M x 7-1/16"15M w/  
5-1/2" PP Seal  
w/ (2) 1-13/16"15M SSO

SW-MB Spool Assembly Upper  
MBH

13-5/8"10Mx 13-5/8"5M w/(2)  
1-13/16" 10MSSO

CasingHead Assembly Lower  
MBH

13-5/8"5Mx 10-3/4"SOW w/(2)  
2-1/16"5MSSO

Casing Hanger C-22,  
13-5/8"x 5-1/2"

Packoff Assembly SW  
MB, 13-5/8" x 7-5/8"

Casing Hanger  
SW MDRL, 13-5/8" x 7-5/8"



**District I**  
1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720  
**District II**  
811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720  
**District III**  
1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170  
**District IV**  
1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

COMMENTS

Action 24470

**COMMENTS**

Operator:			OGRID:	Action Number:	Action Type:
BTA OIL PRODUCERS, LLC 104 S Pecos Midland, TX79701			260297	24470	FORM 3160-3
Created By	Comment	Comment Date			
kpickford	KP GEO Review 4/21/2021	04/21/2021			

**District I**

1625 N. French Dr., Hobbs, NM 88240  
Phone:(575) 393-6161 Fax:(575) 393-0720

**District II**

811 S. First St., Artesia, NM 88210  
Phone:(575) 748-1283 Fax:(575) 748-9720

**District III**

1000 Rio Brazos Rd., Aztec, NM 87410  
Phone:(505) 334-6178 Fax:(505) 334-6170

**District IV**

1220 S. St Francis Dr., Santa Fe, NM 87505  
Phone:(505) 476-3470 Fax:(505) 476-3462

**State of New Mexico**  
**Energy, Minerals and Natural Resources**  
**Oil Conservation Division**  
**1220 S. St Francis Dr.**  
**Santa Fe, NM 87505**

CONDITIONS

Action 24470

**CONDITIONS OF APPROVAL**

Operator:				OGRID:	Action Number:	Action Type:
	BTA OIL PRODUCERS, LLC	104 S Pecos	Midland, TX79701	260297	24470	FORM 3160-3

OCD Reviewer	Condition
kpickford	Notify OCD 24 hours prior to casing & cement
kpickford	Will require a File As Drilled C-102 and a Directional Survey with the C-104
kpickford	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string
kpickford	Cement is required to circulate on both surface and intermediate1 strings of casing
kpickford	Oil base muds are not to be used until fresh water zones are cased and cemented providing isolation from the oil or diesel. This includes synthetic oils. Oil based mud, drilling fluids and solids must be contained in a steel closed loop system