

Form 3160-3
(June 2015)

FORM APPROVED
OMB No. 1004-0137
Expires: January 31, 2018

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No.
1b. Type of Well: <input type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		6. If Indian, Allottee or Tribe Name
1c. Type of Completion: <input type="checkbox"/> Hydraulic Fracturing <input type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		7. If Unit or CA Agreement, Name and No.
2. Name of Operator [6137]		8. Lease Name and Well No. [325998]
3a. Address	3b. Phone No. (include area code)	9. API Well No. 30-025-49021
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface At proposed prod. zone		10. Field and Pool, or Exploratory [98270]
14. Distance in miles and direction from nearest town or post office*		11. Sec., T. R. M. or Blk. and Survey or Area
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any)		12. County or Parish
16. No of acres in lease		13. State
17. Spacing Unit dedicated to this well		
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft.		20. BLM/BIA Bond No. in file
19. Proposed Depth		
21. Elevations (Show whether DF, KDB, RT, GL, etc.)	22. Approximate date work will start*	23. Estimated duration
24. Attachments		

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, and the Hydraulic Fracturing rule per 43 CFR 3162.3-3 (as applicable)

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification. |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be requested by the BLM. |

25. Signature	Name (Printed/Typed)	Date
Title		
Approved by (Signature)	Name (Printed/Typed)	Date
Title		
Office		

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

GCP Rec 04/29/2021

SL

(Continued on page 2)



KZ
06/14/2021

*(Instructions on page 2)

Intent As Drilled

API # **30-025-49021**

Operator Name: DEVON ENERGY PRODUCTION COMPANY, L.P.	Property Name: MARWARI 21-16 STATE FED COM	Well Number 621H
--	--	----------------------------

Kick Off Point (KOP)

UL D	Section 28	Township 25S	Range 32E	Lot	Feet 225	From N/S NORTH	Feet 680	From E/W WEST	County LEA
Latitude 32.107946					Longitude -103.686480				NAD 83

First Take Point (FTP)

UL M	Section 21	Township 25S	Range 32E	Lot	Feet 100	From N/S SOUTH	Feet 680	From E/W WEST	County LEA
Latitude 32.1088677					Longitude 103.6864879				NAD 83

Last Take Point (LTP)

UL D	Section 16	Township 25S	Range 32E	Lot	Feet 100	From N/S NORTH	Feet 680	From E/W WEST	County LEA
Latitude 32.1373711					Longitude 103.6864088				NAD 83

Is this well the defining well for the Horizontal Spacing Unit?

Is this well an infill well? YES

If infill is yes please provide API if available, Operator Name and well number for Defining well for Horizontal Spacing Unit.

API #	Operator Name:	Property Name:	Well Number

KZ 06/29/2018

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Original
to Appropriate
District Office

GAS CAPTURE PLAN

Date: 2/19/2019

Original Operator & OGRID No.: Devon Energy Prod Co., LP (6137)
 Amended - Reason for Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Devon to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Marwari 21-16 State Fed Com 621H	30-025-49021	UNIT D, SEC 28-T25S-R32E	325 FNL 160 FWL			MARWARI 21 CTB 1

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if DCP system is in place. The gas produced from production facility is dedicated to DCP and will be connected to DCP low/high pressure gathering system located in Lea County, New Mexico. It will require 1100' of pipeline to connect the facility to low/high pressure gathering system. Devon provides (periodically) to DCP a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Devon and DCP have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP Processing Plant located in Sec. 19, Twn. 19S, Rng. 32E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP system at that time. Based on current information, it is Devon's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

Devon Energy **APD VARIANCE DATA**

OPERATOR NAME: Devon Energy

1. SUMMARY OF Variance:

Devon Energy respectfully requests approval for the following additions to the drilling plan:

1. Potential utilization of a spudder rig to pre-set surface casing.

2. Description of Operations

1. A spudder rig contractor may move in their rig to drill the surface hole section and pre-set surface casing on this well.
 - a. After drilling the surface hole section, the rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - b. Rig will utilize fresh water based mud to drill surface hole to TD.
2. The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
3. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wingvalves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
4. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
5. Drilling operation will be performed with the big rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The BLM will be contacted / notified 24 hours before the big rig moves back on to the pad with the pre-set surface casing.
6. Devon Energy will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
7. Once the rig is removed, Devon Energy will secure the wellhead area by placing a guard rail around the cellar area.



U.S. Department of the Interior
BUREAU OF LAND MANAGEMENT

Drilling Plan Data Report

04/12/2021

APD ID: 10400039087

Submission Date: 02/21/2019

Highlighted data
reflects the most
recent changes

Operator Name: DEVON ENERGY PRODUCTION COMPANY LP

Well Name: MARWARI 21-16 STATE FED COM

Well Number: 621H

[Show Final Text](#)

Well Type: OIL WELL

Well Work Type: Drill

Section 1 - Geologic Formations

Formation ID	Formation Name	Elevation	True Vertical Depth	Measured Depth	Lithologies	Mineral Resources	Producing Formation
396761	UNKNOWN	3374	0	0	ALLUVIUM	NONE	N
396762	RUSTLER	2545	829	829	ANHYDRITE	NONE	N
396763	SALADO	2182	1192	1192	SALT	NONE	N
396756	DELAWARE	-1198	4572	4572	SANDSTONE	NATURAL GAS, OIL	N
396757	BONE SPRING	-5161	8535	8535	LIMESTONE	NATURAL GAS, OIL	N
396758	BONE SPRING 1ST	-6092	9466	9466	SANDSTONE	NATURAL GAS, OIL	N
396759	BONE SPRING 2ND	-6777	10151	10151	SANDSTONE	NATURAL GAS, OIL	N
1389483	2ND BONE SPRING LIME	-6807	10310	10310	SANDSTONE	NATURAL GAS, OIL	N
396760	BONE SPRING 3RD	-8002	11376	11376	SANDSTONE	OIL	N
396842	WOLFCAMP	-8443	11817	11817	SHALE	NATURAL GAS, OIL	Y

Section 2 - Blowout Prevention

Pressure Rating (PSI): 5M

Rating Depth: 11816

Equipment: BOP/BOPE will be installed per Onshore Oil & Gas Order #2 requirements prior to drilling below surface casing, a BOP/BOPE system with the above minimum rating will be installed on the wellhead system. BOP/BOPE will be tested by an independent service company per Onshore Oil & Gas Order #2 requirements and MASP (Maximum Anticipated Surface Pressure) calculations. If the system is upgraded, all the components installed will be functional and tested.

Requesting Variance? YES

Variance request: A variance is requested for the use of a flexible choke line from the BOP stack to the choke manifold. See attached for specs for hydrostatic test chart.

Testing Procedure: A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Choke Diagram Attachment:

2. Casing Program (Primary Design)

Hole Size	Casing Interval		Csg. Size	Wt (PPF)	Grade	Conn	Min SF Collapse	Min SF Burst	Min SF Tension
	From	To							
17 1/2	0	854 TVD	13 3/8	48.0	H40	STC	1.125	1.25	1.6
9 7/8	0	11376 TVD	7 5/8	29.7	P110	Flushmax III	1.125	1.25	1.6
6 3/4	0	TD	5 1/2	20.0	P110	Vam SG	1.125	1.25	1.6
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- A variance is requested for collapse rating on intermediate casing. Operator will keep pipe full while running casing.
- Int casing shoe will be selected based on drilling data/gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the Intermediate casing and production casing.
- A variance is requested to set intermediate casing in the curve if hole conditions dictate that a higher shoe strength is required.

Casing Program (Alternative Design)

Hole Size	Casing Interval		Csg. Size	Wt (PPF)	Grade	Conn	Min SF Collapse	Min SF Burst	Min SF Tension
	From	To							
17 1/2	0	854 TVD	13 3/8	48.0	H40	STC	1.125	1.25	1.6
9 7/8	0	11376 TVD	8 5/8	32.0	P110	TLW	1.125	1.25	1.6
7 7/8	0	TD	5 1/2	17.0	P110	BTC	1.125	1.25	1.6
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 IILB.1.h Must have table for contingency casing.
- Rustler top will be validated via drilling parameters (i.e. reduction in ROP) and surface casing setting depth revised accordingly if needed.
- A variance is requested for collapse rating on intermediate casing. Operator will keep pipe full while running casing.
- Int casing shoe will be selected based on drilling data/gamma, setting depth with be revised accordingly if needed.
- A variance is requested to wave the centralizer requirement for the Intermediate casing and production casing.
- Variance requested to drill 10.625" hole instead of 9.875" for intermediate 1, the 8.625" connection will change from TLW to BTC.
- A variance is requested to set intermediate casing in the curve if hole conditions dictate that a higher shoe strength is required.

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Capitan Reef	
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
SOPA	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
R-111-P	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
High Cave/Karst	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Critical Cave/Karst	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program (Primary Design)

Casing	# Sks	TOC	Wt. (lb/gal)	Yld (ft3/sack)	Slurry Description
Surface	657	Surf	13.2	1.44	Lead: Class C Cement + additives
Int 1	704	Surf	9	3.27	Lead: Class C Cement + additives
	783	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Int 1 Two Stage w/ DV @ TVD of Delaware	534	200' above DV	9	3.27	1st stage Lead: Class C Cement + additives
	93	500' above shoe	13.2	1.44	1st stage Tail: Class H / C + additives
	412	Surf	9	3.27	2nd stage Lead: Class C Cement + additives
	93	500' above DV	13.2	1.44	2nd stage Tail: Class H / C + additives
Int 1 Intermediate Squeeze	As Needed	Surf	9	1.44	Squeeze Lead: Class C Cement + additives
	704	Surf	9	3.27	Lead: Class C Cement + additives
	783	4000' above shoe	13.2	1.44	Tail: Class H / C + additives
Production	64	9018	9.0	3.3	Lead: Class H / C + additives
	731	11018	13.2	1.4	Tail: Class H / C + additives

If a DV tool is ran the depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. Slurry weights will be adjusted based on estimated fracture gradient of the formation. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. If cement is not returned to surface during the primary cement job on the surface casing string, a planned top job will be conducted immediately after completion of the primary job.

Casing String	% Excess
Surface	50%
Intermediate 1	30%
Intermediate 1 (Two Stage)	25%
Prod	10%

4. Pressure Control Equipment (Three String Design)

BOP installed and tested before drilling which hole?		Size?	Min. Required WP	Type	✓	Tested to:
Int 1	13-58"	5M	Annular	X	50% of rated working pressure	
			Blind Ram	X	5M	
			Pipe Ram			
			Double Ram	X		
			Other*			
Production	13-5/8"	10M	Annular (5M)	X	100% of rated working pressure	
			Blind Ram	X	10M	
			Pipe Ram			
			Double Ram	X		
			Other*			
			Annular (5M)			
			Blind Ram			
			Pipe Ram			
			Double Ram			
			Other*			
N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.					
Y	A variance is requested to run a 5 M annular on a 10M system					

5. Mud Program (Three String Design)

Section	Type	Weight (ppg)
Surface	FW Gel	8.5-9
Intermediate	DBE / Cut Brine	10-10.5
Production	OBM	10-10.5

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well - vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain.
	Coring? If yes, explain.

Additional logs planned	Interval
	Resistivity
	Density
X	CBL
X	Mud log
	PEX

7. Drilling Conditions

Condition	Specify what type and where?
BH pressure at deepest TVD	6511
Abnormal temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered measured values and formations will be provided to the BLM.

N	H2S is present
Y	H2S plan attached.

8. Other facets of operation

Is this a walking operation? Potentially

- 1 If operator elects, drilling rig will batch drill the surface holes and run/cement surface casing; walking the rig to next wells on the pad.
- 2 The drilling rig will then batch drill the intermediate sections and run/cement intermediate casing; the wellbore will be isolated with a blind flange and pressure gauge installed for monitoring the well before walking to the next well.
- 3 The drilling rig will then batch drill the production hole sections on the wells with OBM, run/cement production casing, and install TA caps or tubing heads for completions.

NOTE: During batch operations the drilling rig will be moved from well to well however, it will not be removed from the pad until all wells have production casing run/cemented.

Will be pre-setting casing? Potentially

- 1 Spudder rig will move in and batch drill surface hole.
 - a. Rig will utilize fresh water based mud to drill surface hole to TD. Solids control will be handled entirely on a closed loop basis.,
- 2 After drilling the surface hole section, the spudder rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
- 3 The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
- 4 A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with a pressure gauge installed on the wellhead.
- 5 Spudder rig operations is expected to take 4-5 days per well on a multi-well pa.
- 6 The NMOCD will be contacted and notified 24 hours prior to commencing spudder rig operations.
- 7 Drilling operations will be performed with drilling rig. A that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The NMOCD will be contacted / notified 24 hours before the drilling rig moves back on to the pad with the pre-set surface casing.

Attachments


- X Directional Plan
- Other, describe



Well: Marwari 21-16 State Fed Com 621H
County: Lea
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
2000.00	0.00	55.00	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2500.00	10.00	55.00	2497.47	24.96	35.65	26.50	1.00	Hold Tangent
5628.58	10.00	55.00	5578.52	336.57	480.67	357.32	0.00	Drop to Vertical
6128.58	0.00	55.00	6075.98	361.54	516.33	383.82	2.00	Hold Vertical
11453.71	0.00	359.79	11401.12	361.54	516.33	383.82	0.00	KOP
12362.88	90.92	359.79	11974.00	943.65	514.19	965.29	10.00	Landing Point
22307.43	90.92	359.79	11815.00	10886.87	477.75	10897.34	0.00	BHL



Key Depths	MD (ft)	TVD (ft)
Rustler	0.00	0.00
Salt	1380.00	1380.00
Base of Salt	4660.36	4625.00
Lamar	4660.36	4625.00
Delaware	4660.36	4625.00
Cherry Canyon	5630.09	5580.00
Brushy Canyon	7222.60	7170.00
1st Bone Spring Lime	8732.60	8680.00
Bone Spring 1st	9717.60	9665.00
Bone Spring 2nd	10362.60	10310.00
3rd Bone Spring Lime	10857.60	10805.00
Bone Spring 3rd	11467.60	11415.00
Wolfcamp / Point of Penetration	12080.16	11910.00
EXIT	22227.43	11816.29

	MD (ft)	TVD (ft)	Lat (°)	Long (°)	Section Footages
SHL	0.00	0.00	32.1076	-103.6882	325' FNL, 160' FWL of Sec 28 in T25S, R32E
KOP	11453.71	11401.12	32.1085	-103.6866	29' FSL, 680' FWL of Sec 21 in T25S, R32E
Point of Penetration	12080.16	11910.00	32.1088	-103.6865	100' FSL, 680' FWL of Sec 21 in T25S, R32E
Exit	22227.43	11816.29	32.1374	-103.6864	100' FNL, 680' FWL of Sec 16 in T25S, R32E
BHL	22307.43	11815.00	32.1375	-103.6865	20' FNL, 680' FWL of Sec 16 in T25S, R32E



Well: Marwari 21-16 State Fed Com 621H
County: Lea
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	SHL
100.00	0.00	55.00	100.00	0.00	0.00	0.00	0.00	
200.00	0.00	55.00	200.00	0.00	0.00	0.00	0.00	
300.00	0.00	55.00	300.00	0.00	0.00	0.00	0.00	
400.00	0.00	55.00	400.00	0.00	0.00	0.00	0.00	
500.00	0.00	55.00	500.00	0.00	0.00	0.00	0.00	
600.00	0.00	55.00	600.00	0.00	0.00	0.00	0.00	
700.00	0.00	55.00	700.00	0.00	0.00	0.00	0.00	
800.00	0.00	55.00	800.00	0.00	0.00	0.00	0.00	
900.00	0.00	55.00	900.00	0.00	0.00	0.00	0.00	
995.00	0.00	55.00	995.00	0.00	0.00	0.00	0.00	Rustler
1000.00	0.00	55.00	1000.00	0.00	0.00	0.00	0.00	
1100.00	0.00	55.00	1100.00	0.00	0.00	0.00	0.00	
1200.00	0.00	55.00	1200.00	0.00	0.00	0.00	0.00	
1300.00	0.00	55.00	1300.00	0.00	0.00	0.00	0.00	
1380.00	0.00	55.00	1380.00	0.00	0.00	0.00	0.00	Salt
1400.00	0.00	55.00	1400.00	0.00	0.00	0.00	0.00	
1500.00	0.00	55.00	1500.00	0.00	0.00	0.00	0.00	
1600.00	0.00	55.00	1600.00	0.00	0.00	0.00	0.00	
1700.00	0.00	55.00	1700.00	0.00	0.00	0.00	0.00	
1800.00	0.00	55.00	1800.00	0.00	0.00	0.00	0.00	
1900.00	0.00	55.00	1900.00	0.00	0.00	0.00	0.00	
2000.00	0.00	55.00	2000.00	0.00	0.00	0.00	0.00	Start Tangent
2100.00	2.00	55.00	2099.98	1.00	1.43	1.06	2.00	
2200.00	4.00	55.00	2199.84	4.00	5.72	4.25	2.00	
2300.00	6.00	55.00	2299.45	9.00	12.86	9.56	2.00	
2400.00	8.00	55.00	2398.70	15.99	22.84	16.98	2.00	
2500.00	10.00	55.00	2497.47	24.96	35.65	26.50	1.00	Hold Tangent
2600.00	10.00	55.00	2595.95	34.92	49.88	37.08	0.00	
2700.00	10.00	55.00	2694.43	44.88	64.10	47.65	0.00	
2800.00	10.00	55.00	2792.91	54.84	78.32	58.22	0.00	
2900.00	10.00	55.00	2891.39	64.80	92.55	68.80	0.00	
3000.00	10.00	55.00	2989.87	74.76	106.77	79.37	0.00	
3100.00	10.00	55.00	3088.35	84.72	121.00	89.95	0.00	
3200.00	10.00	55.00	3186.83	94.68	135.22	100.52	0.00	
3300.00	10.00	55.00	3285.31	104.64	149.45	111.10	0.00	
3400.00	10.00	55.00	3383.79	114.60	163.67	121.67	0.00	
3500.00	10.00	55.00	3482.27	124.56	177.90	132.24	0.00	
3600.00	10.00	55.00	3580.75	134.52	192.12	142.82	0.00	
3700.00	10.00	55.00	3679.23	144.48	206.34	153.39	0.00	
3800.00	10.00	55.00	3777.72	154.44	220.57	163.97	0.00	
3900.00	10.00	55.00	3876.20	164.40	234.79	174.54	0.00	
4000.00	10.00	55.00	3974.68	174.36	249.02	185.11	0.00	
4100.00	10.00	55.00	4073.16	184.32	263.24	195.69	0.00	
4200.00	10.00	55.00	4171.64	194.28	277.47	206.26	0.00	
4300.00	10.00	55.00	4270.12	204.24	291.69	216.84	0.00	
4400.00	10.00	55.00	4368.60	214.20	305.92	227.41	0.00	
4500.00	10.00	55.00	4467.08	224.16	320.14	237.98	0.00	
4600.00	10.00	55.00	4565.56	234.12	334.36	248.56	0.00	
4660.36	10.00	55.00	4625.00	240.14	342.95	254.94	0.00	Base of Salt, Lamar, Delaware
4700.00	10.00	55.00	4664.04	244.08	348.59	259.13	0.00	
4800.00	10.00	55.00	4762.52	254.04	362.81	269.71	0.00	
4900.00	10.00	55.00	4861.00	264.00	377.04	280.28	0.00	
5000.00	10.00	55.00	4959.48	273.96	391.26	290.86	0.00	
5100.00	10.00	55.00	5057.97	283.92	405.49	301.43	0.00	
5200.00	10.00	55.00	5156.45	293.88	419.71	312.00	0.00	
5300.00	10.00	55.00	5254.93	303.85	433.93	322.58	0.00	
5400.00	10.00	55.00	5353.41	313.81	448.16	333.15	0.00	
5500.00	10.00	55.00	5451.89	323.77	462.38	343.73	0.00	
5600.00	10.00	55.00	5550.37	333.73	476.61	354.30	0.00	
5628.58	10.00	55.00	5578.52	336.57	480.67	357.32	0.00	Drop to Vertical
5630.09	9.97	55.00	5580.00	336.72	480.89	357.48	2.00	Cherry Canyon
5700.00	8.57	55.00	5649.00	343.18	490.11	364.34	2.00	
5800.00	6.57	55.00	5748.12	350.74	500.91	372.36	2.00	
5900.00	4.57	55.00	5847.64	356.31	508.86	378.27	2.00	
6000.00	2.57	55.00	5947.44	359.88	513.96	382.07	2.00	
6100.00	0.57	55.00	6047.40	361.45	516.21	383.74	2.00	
6128.58	0.00	55.00	6075.98	361.54	516.33	383.82	2.00	Hold Vertical
6200.00	0.00	359.79	6147.40	361.54	516.33	383.82	0.00	
6300.00	0.00	359.79	6247.40	361.54	516.33	383.82	0.00	



Well: Marwari 21-16 State Fed Com 621H
County: Lea
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
6400.00	0.00	359.79	6347.40	361.54	516.33	383.82	0.00	
6500.00	0.00	359.79	6447.40	361.54	516.33	383.82	0.00	
6600.00	0.00	359.79	6547.40	361.54	516.33	383.82	0.00	
6700.00	0.00	359.79	6647.40	361.54	516.33	383.82	0.00	
6800.00	0.00	359.79	6747.40	361.54	516.33	383.82	0.00	
6900.00	0.00	359.79	6847.40	361.54	516.33	383.82	0.00	
7000.00	0.00	359.79	6947.40	361.54	516.33	383.82	0.00	
7100.00	0.00	359.79	7047.40	361.54	516.33	383.82	0.00	
7200.00	0.00	359.79	7147.40	361.54	516.33	383.82	0.00	
7222.60	0.00	359.79	7170.00	361.54	516.33	383.82	0.00	Brushy Canyon
7300.00	0.00	359.79	7247.40	361.54	516.33	383.82	0.00	
7400.00	0.00	359.79	7347.40	361.54	516.33	383.82	0.00	
7500.00	0.00	359.79	7447.40	361.54	516.33	383.82	0.00	
7600.00	0.00	359.79	7547.40	361.54	516.33	383.82	0.00	
7700.00	0.00	359.79	7647.40	361.54	516.33	383.82	0.00	
7800.00	0.00	359.79	7747.40	361.54	516.33	383.82	0.00	
7900.00	0.00	359.79	7847.40	361.54	516.33	383.82	0.00	
8000.00	0.00	359.79	7947.40	361.54	516.33	383.82	0.00	
8100.00	0.00	359.79	8047.40	361.54	516.33	383.82	0.00	
8200.00	0.00	359.79	8147.40	361.54	516.33	383.82	0.00	
8300.00	0.00	359.79	8247.40	361.54	516.33	383.82	0.00	
8400.00	0.00	359.79	8347.40	361.54	516.33	383.82	0.00	
8500.00	0.00	359.79	8447.40	361.54	516.33	383.82	0.00	
8600.00	0.00	359.79	8547.40	361.54	516.33	383.82	0.00	
8700.00	0.00	359.79	8647.40	361.54	516.33	383.82	0.00	
8732.60	0.00	359.79	8680.00	361.54	516.33	383.82	0.00	1st Bone Spring Lime
8800.00	0.00	359.79	8747.40	361.54	516.33	383.82	0.00	
8900.00	0.00	359.79	8847.40	361.54	516.33	383.82	0.00	
9000.00	0.00	359.79	8947.40	361.54	516.33	383.82	0.00	
9100.00	0.00	359.79	9047.40	361.54	516.33	383.82	0.00	
9200.00	0.00	359.79	9147.40	361.54	516.33	383.82	0.00	
9300.00	0.00	359.79	9247.40	361.54	516.33	383.82	0.00	
9400.00	0.00	359.79	9347.40	361.54	516.33	383.82	0.00	
9500.00	0.00	359.79	9447.40	361.54	516.33	383.82	0.00	
9600.00	0.00	359.79	9547.40	361.54	516.33	383.82	0.00	
9700.00	0.00	359.79	9647.40	361.54	516.33	383.82	0.00	
9717.60	0.00	359.79	9665.00	361.54	516.33	383.82	0.00	Bone Spring 1st
9800.00	0.00	359.79	9747.40	361.54	516.33	383.82	0.00	
9900.00	0.00	359.79	9847.40	361.54	516.33	383.82	0.00	
10000.00	0.00	359.79	9947.40	361.54	516.33	383.82	0.00	
10100.00	0.00	359.79	10047.40	361.54	516.33	383.82	0.00	
10200.00	0.00	359.79	10147.40	361.54	516.33	383.82	0.00	
10300.00	0.00	359.79	10247.40	361.54	516.33	383.82	0.00	
10362.60	0.00	359.79	10310.00	361.54	516.33	383.82	0.00	Bone Spring 2nd
10400.00	0.00	359.79	10347.40	361.54	516.33	383.82	0.00	
10500.00	0.00	359.79	10447.40	361.54	516.33	383.82	0.00	
10600.00	0.00	359.79	10547.40	361.54	516.33	383.82	0.00	
10700.00	0.00	359.79	10647.40	361.54	516.33	383.82	0.00	
10800.00	0.00	359.79	10747.40	361.54	516.33	383.82	0.00	
10857.60	0.00	359.79	10805.00	361.54	516.33	383.82	0.00	3rd Bone Spring Lime
10900.00	0.00	359.79	10847.40	361.54	516.33	383.82	0.00	
11000.00	0.00	359.79	10947.40	361.54	516.33	383.82	0.00	
11100.00	0.00	359.79	11047.40	361.54	516.33	383.82	0.00	
11200.00	0.00	359.79	11147.40	361.54	516.33	383.82	0.00	
11300.00	0.00	359.79	11247.40	361.54	516.33	383.82	0.00	
11400.00	0.00	359.79	11347.40	361.54	516.33	383.82	0.00	
11453.71	0.00	359.79	11401.12	361.54	516.33	383.82	0.00	KOP
11467.60	1.39	359.79	11415.00	361.70	516.33	383.99	10.00	Bone Spring 3rd
11500.00	4.63	359.79	11447.35	363.40	516.32	385.69	10.00	
11600.00	14.63	359.79	11545.82	380.11	516.26	402.38	10.00	
11700.00	24.63	359.79	11639.89	413.66	516.13	435.89	10.00	
11800.00	34.63	359.79	11726.70	463.03	515.95	485.21	10.00	
11900.00	44.63	359.79	11803.62	526.73	515.72	548.84	10.00	
12000.00	54.63	359.79	11868.31	602.82	515.44	624.84	10.00	
12080.16	62.64	359.79	11910.00	671.21	515.19	693.15	10.00	Wolfcamp / Point of Penetration
12100.00	64.63	359.79	11918.81	688.99	515.12	710.91	10.00	
12200.00	74.63	359.79	11953.58	782.61	514.78	804.43	10.00	
12300.00	84.63	359.79	11971.56	880.85	514.42	902.56	10.00	
12362.88	90.92	359.79	11974.00	943.65	514.19	965.29	10.00	Landing Point
12400.00	90.92	359.79	11973.41	980.77	514.06	1002.36	0.00	



Well: Marwari 21-16 State Fed Com 621H
County: Lea
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
12500.00	90.92	359.79	11971.81	1080.76	513.69	1102.24	0.00	
12600.00	90.92	359.79	11970.21	1180.74	513.32	1202.11	0.00	
12700.00	90.92	359.79	11968.61	1280.73	512.96	1301.99	0.00	
12800.00	90.92	359.79	11967.01	1380.72	512.59	1401.86	0.00	
12900.00	90.92	359.79	11965.41	1480.70	512.22	1501.74	0.00	
13000.00	90.92	359.79	11963.81	1580.69	511.85	1601.61	0.00	
13100.00	90.92	359.79	11962.22	1680.68	511.49	1701.48	0.00	
13200.00	90.92	359.79	11960.62	1780.66	511.12	1801.36	0.00	
13300.00	90.92	359.79	11959.02	1880.65	510.75	1901.23	0.00	
13400.00	90.92	359.79	11957.42	1980.63	510.39	2001.11	0.00	
13500.00	90.92	359.79	11955.82	2080.62	510.02	2100.98	0.00	
13600.00	90.92	359.79	11954.22	2180.61	509.65	2200.86	0.00	
13700.00	90.92	359.79	11952.62	2280.59	509.29	2300.73	0.00	
13800.00	90.92	359.79	11951.02	2380.58	508.92	2400.60	0.00	
13900.00	90.92	359.79	11949.43	2480.57	508.55	2500.48	0.00	
14000.00	90.92	359.79	11947.83	2580.55	508.18	2600.35	0.00	
14100.00	90.92	359.79	11946.23	2680.54	507.82	2700.23	0.00	
14200.00	90.92	359.79	11944.63	2780.53	507.45	2800.10	0.00	
14300.00	90.92	359.79	11943.03	2880.51	507.08	2899.98	0.00	
14400.00	90.92	359.79	11941.43	2980.50	506.72	2999.85	0.00	
14500.00	90.92	359.79	11939.83	3080.49	506.35	3099.72	0.00	
14600.00	90.92	359.79	11938.23	3180.47	505.98	3199.60	0.00	
14700.00	90.92	359.79	11936.64	3280.46	505.62	3299.47	0.00	
14800.00	90.92	359.79	11935.04	3380.45	505.25	3399.35	0.00	
14900.00	90.92	359.79	11933.44	3480.43	504.88	3499.22	0.00	
15000.00	90.92	359.79	11931.84	3580.42	504.51	3599.10	0.00	
15100.00	90.92	359.79	11930.24	3680.41	504.15	3698.97	0.00	
15200.00	90.92	359.79	11928.64	3780.39	503.78	3798.84	0.00	
15300.00	90.92	359.79	11927.04	3880.38	503.41	3898.72	0.00	
15400.00	90.92	359.79	11925.44	3980.37	503.05	3998.59	0.00	
15500.00	90.92	359.79	11923.85	4080.35	502.68	4098.47	0.00	
15600.00	90.92	359.79	11922.25	4180.34	502.31	4198.34	0.00	
15700.00	90.92	359.79	11920.65	4280.33	501.95	4298.22	0.00	
15800.00	90.92	359.79	11919.05	4380.31	501.58	4398.09	0.00	
15900.00	90.92	359.79	11917.45	4480.30	501.21	4497.96	0.00	
16000.00	90.92	359.79	11915.85	4580.29	500.84	4597.84	0.00	
16100.00	90.92	359.79	11914.25	4680.27	500.48	4697.71	0.00	
16200.00	90.92	359.79	11912.65	4780.26	500.11	4797.59	0.00	
16300.00	90.92	359.79	11911.06	4880.24	499.74	4897.46	0.00	
16400.00	90.92	359.79	11909.46	4980.23	499.38	4997.34	0.00	
16500.00	90.92	359.79	11907.86	5080.22	499.01	5097.21	0.00	
16600.00	90.92	359.79	11906.26	5180.20	498.64	5197.08	0.00	
16700.00	90.92	359.79	11904.66	5280.19	498.28	5296.96	0.00	
16800.00	90.92	359.79	11903.06	5380.18	497.91	5396.83	0.00	
16900.00	90.92	359.79	11901.46	5480.16	497.54	5496.71	0.00	
17000.00	90.92	359.79	11899.86	5580.15	497.17	5596.58	0.00	
17100.00	90.92	359.79	11898.27	5680.14	496.81	5696.46	0.00	
17200.00	90.92	359.79	11896.67	5780.12	496.44	5796.33	0.00	
17300.00	90.92	359.79	11895.07	5880.11	496.07	5896.21	0.00	
17400.00	90.92	359.79	11893.47	5980.10	495.71	5996.08	0.00	
17500.00	90.92	359.79	11891.87	6080.08	495.34	6095.95	0.00	
17600.00	90.92	359.79	11890.27	6180.07	494.97	6195.83	0.00	
17700.00	90.92	359.79	11888.67	6280.06	494.61	6295.70	0.00	
17800.00	90.92	359.79	11887.08	6380.04	494.24	6395.58	0.00	
17900.00	90.92	359.79	11885.48	6480.03	493.87	6495.45	0.00	
18000.00	90.92	359.79	11883.88	6580.02	493.50	6595.33	0.00	
18100.00	90.92	359.79	11882.28	6680.00	493.14	6695.20	0.00	
18200.00	90.92	359.79	11880.68	6779.99	492.77	6795.07	0.00	
18300.00	90.92	359.79	11879.08	6879.98	492.40	6894.95	0.00	
18400.00	90.92	359.79	11877.48	6979.96	492.04	6994.82	0.00	
18500.00	90.92	359.79	11875.88	7079.95	491.67	7094.70	0.00	
18600.00	90.92	359.79	11874.29	7179.94	491.30	7194.57	0.00	
18700.00	90.92	359.79	11872.69	7279.92	490.94	7294.45	0.00	
18800.00	90.92	359.79	11871.09	7379.91	490.57	7394.32	0.00	
18900.00	90.92	359.79	11869.49	7479.89	490.20	7494.19	0.00	
19000.00	90.92	359.79	11867.89	7579.88	489.83	7594.07	0.00	
19100.00	90.92	359.79	11866.29	7679.87	489.47	7693.94	0.00	
19200.00	90.92	359.79	11864.69	7779.85	489.10	7793.82	0.00	
19300.00	90.92	359.79	11863.09	7879.84	488.73	7893.69	0.00	
19400.00	90.92	359.79	11861.50	7979.83	488.37	7993.57	0.00	



Well: Marwari 21-16 State Fed Com 621H
County: Lea
Wellbore: Permit Plan
Design: Permit Plan #1

Geodetic System: US State Plane 1983
Datum: North American Datum 1927
Ellipsoid: Clarke 1866
Zone: 3001 - NM East (NAD83)

MD (ft)	INC (°)	AZI (°)	TVD (ft)	NS (ft)	EW (ft)	VS (ft)	DLS (°/100ft)	Comment
19500.00	90.92	359.79	11859.90	8079.81	488.00	8093.44	0.00	
19600.00	90.92	359.79	11858.30	8179.80	487.63	8193.31	0.00	
19700.00	90.92	359.79	11856.70	8279.79	487.27	8293.19	0.00	
19800.00	90.92	359.79	11855.10	8379.77	486.90	8393.06	0.00	
19900.00	90.92	359.79	11853.50	8479.76	486.53	8492.94	0.00	
20000.00	90.92	359.79	11851.90	8579.75	486.16	8592.81	0.00	
20100.00	90.92	359.79	11850.30	8679.73	485.80	8692.69	0.00	
20200.00	90.92	359.79	11848.71	8779.72	485.43	8792.56	0.00	
20300.00	90.92	359.79	11847.11	8879.71	485.06	8892.43	0.00	
20400.00	90.92	359.79	11845.51	8979.69	484.70	8992.31	0.00	
20500.00	90.92	359.79	11843.91	9079.68	484.33	9092.18	0.00	
20600.00	90.92	359.79	11842.31	9179.67	483.96	9192.06	0.00	
20700.00	90.92	359.79	11840.71	9279.65	483.60	9291.93	0.00	
20800.00	90.92	359.79	11839.11	9379.64	483.23	9391.81	0.00	
20900.00	90.92	359.79	11837.51	9479.63	482.86	9491.68	0.00	
21000.00	90.92	359.79	11835.92	9579.61	482.49	9591.55	0.00	
21100.00	90.92	359.79	11834.32	9679.60	482.13	9691.43	0.00	
21200.00	90.92	359.79	11832.72	9779.59	481.76	9791.30	0.00	
21300.00	90.92	359.79	11831.12	9879.57	481.39	9891.18	0.00	
21400.00	90.92	359.79	11829.52	9979.56	481.03	9991.05	0.00	
21500.00	90.92	359.79	11827.92	10079.55	480.66	10090.93	0.00	
21600.00	90.92	359.79	11826.32	10179.53	480.29	10190.80	0.00	
21700.00	90.92	359.79	11824.72	10279.52	479.93	10290.68	0.00	
21800.00	90.92	359.79	11823.13	10379.50	479.56	10390.55	0.00	
21900.00	90.92	359.79	11821.53	10479.49	479.19	10490.42	0.00	
22000.00	90.92	359.79	11819.93	10579.48	478.82	10590.30	0.00	
22100.00	90.92	359.79	11818.33	10679.46	478.46	10690.17	0.00	
22200.00	90.92	359.79	11816.73	10779.45	478.09	10790.05	0.00	
22227.43	90.92	359.79	11816.29	10806.88	477.99	10817.44	0.00	EXIT
22300.00	90.92	359.79	11815.13	10879.44	477.72	10889.92	0.00	
22307.43	90.92	359.79	11815.00	10886.87	477.75	10897.34	0.00	BHL



**Devon Energy Center
333 West Sheridan Avenue
Oklahoma City, Oklahoma 73102-5015**

Hydrogen Sulfide (H₂S) Contingency Plan

For



Marwari 21-16 State Fed Com 621H

**Sec-28 T-25S R-32E
325' FNL & 160' FWL
LAT. = 32.1076798' N (NAD83)
LONG = 103.6881612' W**

Lea County NM

Marwari 21-16 State Fed Com 621H

This is an open drilling site. H₂S monitoring equipment and emergency response equipment will be used within 500' of zones known to contain H₂S, including warning signs, wind indicators and H₂S monitor.



Assumed 100 ppm ROE = 3000' (Radius of Exposure)
100 ppm H₂S concentration shall trigger activation of this plan.

Escape

Crews shall escape upwind of escaping gas in the event of an emergency release of gas. Escape can be facilitated from the location entrance road. Crews should then block the entrance to the location from the lease road so as not to allow anyone traversing into a hazardous area. The blockade should be at a safe distance outside of the ROE. There are no homes or buildings in or near the ROE.

Assumed 100 ppm ROE = 3000'

100 ppm H₂S concentration shall trigger activation of this plan.

Emergency Procedures

In the event of a release of gas containing H₂S, the first responder(s) must

- Isolate the area and prevent entry by other persons into the 100 ppm ROE.
- Evacuate any public places encompassed by the 100 ppm ROE.
- Be equipped with H₂S monitors and air packs in order to control the release.
- Use the “buddy system” to ensure no injuries occur during the response
- Take precautions to avoid personal injury during this operation.
- Contact operator and/or local officials to aid in operation. See list of phone numbers attached.
- Have received training in the
 - Detection of H₂S, and
 - Measures for protection against the gas,
 - Equipment used for protection and emergency response.

Ignition of Gas Source

Should control of the well be considered lost and ignition considered, take care to protect against exposure to Sulfur Dioxide (SO₂). Intentional ignition must be coordinated with the NMOCD and local officials. Additionally the NM State Police may become involved. NM State Police shall be the Incident Command on scene of any major release. Take care to protect downwind whenever there is an ignition of the gas

Characteristics of H₂S and SO₂

Common Name	Chemical Formula	Specific Gravity	Threshold Limit	Hazardous Limit	Lethal Concentration
Hydrogen Sulfide	H ₂ S	1.189 Air = 1	10 ppm	100 ppm/hr	600 ppm
Sulfur Dioxide	SO ₂	2.21 Air = 1	2 ppm	N/A	1000 ppm

Contacting Authorities

Devon Energy Corp. personnel must liaison with local and state agencies to ensure a proper response to a major release. Additionally, the OCD must be notified of the release as soon as possible but no later than 4 hours. Agencies will ask for information such as type and volume of release, wind direction, location of release, etc. Be prepared with all information available. The following call list of essential and potential responders has been prepared for use during a release. Devon Energy Corp. Company response must be in coordination with the State of New Mexico’s ‘Hazardous Materials Emergency Response Plan’ (HMER)

Hydrogen Sulfide Drilling Operation Plan

I. HYDROGEN SULFIDE (H₂S) TRAINING

All personnel, whether regularly assigned, contracted, or employed on an unscheduled basis, will receive training from a qualified instructor in the following areas prior to commencing drilling operations on this well:

1. The hazards and characteristics of hydrogen sulfide (H₂S)
2. The proper use and maintenance of personal protective equipment and life support systems.
3. The proper use of H₂S detectors, alarms, warning systems, briefing areas, evacuation procedures, and prevailing winds.
4. The proper techniques for first aid and rescue procedures.

In addition, supervisory personnel will be trained in the following areas:

1. The effects of H₂S metal components. If high tensile tubulars are to be used, personnel will be trained in their special maintenance requirements.
2. Corrective action and shut-in procedures when drilling or reworking a well and blowout prevention and well control procedures.
3. The contents and requirements of the H₂S Drilling Operations Plan and Public Protection Plan.

There will be an initial training session just prior to encountering a known or probable H₂S zone (within 3 days or 500 feet) and weekly H₂S and well control drills for all personnel in each crew. The initial training session shall include a review of the site specific H₂S Drilling Operations Plan and the Public Protection Plan.

II. HYDROGEN SULFIDE TRAINING

Note: All H₂S safety equipment and systems will be installed, tested, and operational when drilling reaches a depth of 500 feet above, or three days prior to penetrating the first zone containing or reasonably expected to contain H₂S.

1. Well Control Equipment

- A. Flare line
- B. Choke manifold – Remotely Operated
- C. Blind rams and pipe rams to accommodate all pipe sizes with properly sized closing unit
- D. Auxiliary equipment may include if applicable: annular preventer and rotating head.
- E. Mud/Gas Separator

2. Protective equipment for essential personnel:

30-minute SCBA units located at briefing areas, as indicated on well site diagram, with escape units available in the top doghouse. As it may be difficult to communicate audibly while wearing these units, hand signals shall be utilized.

3. H₂S detection and monitoring equipment:

Portable H₂S monitors positioned on location for best coverage and response. These units have warning lights which activate when H₂S levels reach 10 ppm and audible sirens which activate at 15 ppm. Sensor locations:

- Bell nipple
- Possum Belly/Shale shaker
- Rig floor
- Choke manifold
- Cellar

Visual warning systems:

- A. Wind direction indicators as shown on well site diagram
- B. Caution/ Danger signs shall be posted on roads providing direct access to locations. Signs will be painted a high visibility yellow with black lettering of sufficient size to be reasonable distance from the immediate location. Bilingual signs will be used when appropriate.

4. Mud program:

The mud program has been designed to minimize the volume of H₂S circulated to surface. Proper mud weight, safe drilling practices and the use of H₂S scavengers will minimize hazards when penetrating H₂S bearing zones.

5. Metallurgy:

- A. All drill strings, casings, tubing, wellhead, blowout preventer, drilling spool, kill lines, choke manifold lines, and valves shall be H₂S trim.
- B. All elastomers used for packing and seals shall be H₂S trim.

6. Communication:

- A. Company personnel have/use cellular telephones in the field.
- B. Land line (telephone) communications at Office

7. Well testing:

- A. Drill stem testing will be performed with a minimum number of personnel in the immediate vicinity, which are necessary to safety and adequately conduct the test. The drill stem testing will be conducted during daylight hours and formation fluids will not be flowed to the surface. All drill-stem-testing operations conducted in an H₂S environment will use the closed chamber method of testing.
- B. There will be no drill stem testing.

PECOS DISTRICT DRILLING CONDITIONS OF APPROVAL

OPERATOR'S NAME:	Devon Energy Production Company LP
LEASE NO.:	NMLC0061869
LOCATION:	Section 28, T.25 S., R.32 E., NMPM
COUNTY:	Lea County, New Mexico

WELL NAME & NO.:	Marwari 21-16 State Fed Com 333H
SURFACE HOLE FOOTAGE:	325'/N & 1680'/E
BOTTOM HOLE FOOTAGE:	20'/N & 1600'/E

WELL NAME & NO.:	Marwari 21-16 State Fed Com 624H
SURFACE HOLE FOOTAGE:	325'/N & 715'/E
BOTTOM HOLE FOOTAGE:	20'/N & 1000'/E

WELL NAME & NO.:	Marwari 21-16 State Fed Com 331H
SURFACE HOLE FOOTAGE:	325'/N & 220'/W
BOTTOM HOLE FOOTAGE:	20'/N & 1280'/W

WELL NAME & NO.:	Marwari 21-16 State Fed Com 623H
SURFACE HOLE FOOTAGE:	325'/N & 1740'/E
BOTTOM HOLE FOOTAGE:	20'/N & 2200'/E

WELL NAME & NO.:	Marwari 21-16 State Fed Com 333H
SURFACE HOLE FOOTAGE:	325'/N & 1680'/E
BOTTOM HOLE FOOTAGE:	20'/N & 1600'/E

WELL NAME & NO.:	Marwari 21-16 State Fed Com 621H
SURFACE HOLE FOOTAGE:	325'/N & 160'/W
BOTTOM HOLE FOOTAGE:	20'/N & 680'/W

WELL NAME & NO.:	Marwari 21-16 State Fed Com 712H
SURFACE HOLE FOOTAGE:	325'/N & 190'/W
BOTTOM HOLE FOOTAGE:	20'/N & 980'/W

COA

H2S	<input checked="" type="checkbox"/> Yes	<input checked="" type="checkbox"/> No	
Potash	<input checked="" type="checkbox"/> None	<input checked="" type="checkbox"/> Secretary	<input checked="" type="checkbox"/> R-111-P
Cave/Karst Potential	<input checked="" type="checkbox"/> Low	<input checked="" type="checkbox"/> Medium	<input checked="" type="checkbox"/> High
Cave/Karst Potential	<input checked="" type="checkbox"/> Critical		
Variance	<input checked="" type="checkbox"/> None	<input checked="" type="checkbox"/> Flex Hose	<input checked="" type="checkbox"/> Other
Wellhead	<input checked="" type="checkbox"/> Conventional	<input checked="" type="checkbox"/> Multibowl	<input checked="" type="checkbox"/> Both
Other	<input type="checkbox"/> 4 String Area	<input type="checkbox"/> Capitan Reef	<input type="checkbox"/> WIPP
Other	<input checked="" type="checkbox"/> Fluid Filled	<input checked="" type="checkbox"/> Cement Squeeze	<input type="checkbox"/> Pilot Hole
Special Requirements	<input type="checkbox"/> Water Disposal	<input checked="" type="checkbox"/> COM	<input type="checkbox"/> Unit

A. HYDROGEN SULFIDE

A Hydrogen Sulfide (H2S) Drilling Plan shall be activated 500 feet prior to drilling into the **Jennings Pool**. As a result, the Hydrogen Sulfide area must meet Onshore Order 6 requirements, which includes equipment and personnel/public protection items. If Hydrogen Sulfide is encountered, please provide measured values and formations to the BLM.

B. CASING

1. The **13-3/8** inch surface casing shall be set at approximately **920 feet** (a minimum of **25 feet (Lea County)**) into the Rustler Anhydrite and above the salt) and cemented to the surface.
 - a. If cement does not circulate to the surface, the appropriate BLM office shall be notified and a temperature survey utilizing an electronic type temperature survey with surface log readout will be used or a cement bond log shall be run to verify the top of the cement. Temperature survey will be run a minimum of six hours after pumping cement and ideally between 8-10 hours after completing the cement job.
 - b. Wait on cement (WOC) time for a primary cement job will be a minimum of **8 hours** or 500 pounds compressive strength, whichever is greater. (This is to include the lead cement)
 - c. Wait on cement (WOC) time for a remedial job will be a minimum of 4 hours after bringing cement to surface or 500 pounds compressive strength, whichever is greater.
 - d. If cement falls back, remedial cementing will be done prior to drilling out that string.

Intermediate casing must be kept fluid filled to meet BLM minimum collapse requirement.

2. The minimum required fill of cement behind the **8-5/8** inch intermediate casing is:
 - Cement to surface. If cement does not circulate see B.1.a, c-d above.

Operator has proposed to pump down 13-3/8" X 8-5/8" annulus. Operator must run a CBL from TD of the 8-5/8" casing to surface. Submit results to BLM.

3. The minimum required fill of cement behind the **5-1/2** inch production casing is:
 - Cement should tie-back at least **200 feet** into previous casing string. Operator shall provide method of verification.
Cement excess is less than 25%, more cement might be required.

C. PRESSURE CONTROL

1. Variance approved to use flex line from BOP to choke manifold. Manufacturer's specification to be readily available. No external damage to flex line. Flex line to be installed as straight as possible (no hard bends).'
2. Operator has proposed a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be **5000 (5M) psi**.
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
 - e. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.

D. SPECIAL REQUIREMENT (S)

Communitization Agreement

- The operator will submit a Communitization Agreement to the Santa Fe Office, 301 Dinosaur Trail Santa Fe, New Mexico 87508, at least 90 days before the anticipated date of first production from a well subject to a spacing order issued by the New Mexico Oil Conservation Division. The Communitization Agreement will include the

signatures of all working interest owners in all Federal and Indian leases subject to the Communitization Agreement (i.e., operating rights owners and lessees of record), or certification that the operator has obtained the written signatures of all such owners and will make those signatures available to the BLM immediately upon request.

- If the operator does not comply with this condition of approval, the BLM may take enforcement actions that include, but are not limited to, those specified in 43 CFR 3163.1.
- In addition, the well sign shall include the surface and bottom hole lease numbers. When the Communitization Agreement number is known, it shall also be on the sign.

GENERAL REQUIREMENTS

The BLM is to be notified in advance for a representative to witness:

- a. Spudding well (minimum of 24 hours)
- b. Setting and/or Cementing of all casing strings (minimum of 4 hours)
- c. BOPE tests (minimum of 4 hours)

Eddy County

Call the Carlsbad Field Office, 620 East Greene St., Carlsbad, NM 88220,
(575) 361-2822

Lea County

Call the Hobbs Field Station, 414 West Taylor, Hobbs NM 88240, (575)
393-3612

1. Unless the production casing has been run and cemented or the well has been properly plugged, the drilling rig shall not be removed from over the hole without prior approval.
 - a. In the event the operator has proposed to drill multiple wells utilizing a skid/walking rig. Operator shall secure the wellbore on the current well, after installing and testing the wellhead, by installing a blind flange of like pressure rating to the wellhead and a pressure gauge that can be monitored while drilling is performed on the other well(s).
 - b. When the operator proposes to set surface casing with Spudder Rig
 - Notify the BLM when moving in and removing the Spudder Rig.
 - Notify the BLM when moving in the 2nd Rig. Rig to be moved in within 90 days of notification that Spudder Rig has left the location.
 - BOP/BOPE test to be conducted per Onshore Oil and Gas Order No. 2 as soon as 2nd Rig is rigged up on well.
2. Floor controls are required for 3M or Greater systems. These controls will be on the rig floor, unobstructed, readily accessible to the driller and will be operational at all times during drilling and/or completion activities. Rig floor is defined as the area immediately around the rotary table; the area immediately above the substructure on which the draw works are located, this does not include the dog house or stairway area.
3. The record of the drilling rate along with the GR/N well log run from TD to surface (horizontal well – vertical portion of hole) shall be submitted to the BLM office as well as all other logs run on the borehole 30 days from completion. If available, a digital copy of the logs is to be submitted in addition to the paper copies. The Rustler top and top and bottom of Salt are to be recorded on the Completion Report.

A. CASING

1. Changes to the approved APD casing program need prior approval if the items substituted are of lesser grade or different casing size or are Non-API. The Operator can exchange the components of the proposal with that of superior strength (i.e. changing from J-55 to N-80, or from 36# to 40#). Changes to the approved cement program need prior approval if the altered cement plan has less volume or strength or if the changes are substantial (i.e. Multistage tool, ECP, etc.). The initial wellhead installed on the well will remain on the well with spools used as needed.
2. Wait on cement (WOC) for Potash Areas: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi for all cement blends, 2) until cement has been in place at least 24 hours. WOC time will be recorded in the driller's log. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
3. Wait on cement (WOC) for Water Basin: After cementing but before commencing any tests, the casing string shall stand cemented under pressure until both of the following conditions have been met: 1) cement reaches a minimum compressive strength of 500 psi at the shoe, 2) until cement has been in place at least 8 hours. WOC time will be recorded in the driller's log. See individual casing strings for details regarding lead cement slurry requirements. The casing integrity test can be done (prior to the cement setting up) immediately after bumping the plug.
4. Provide compressive strengths including hours to reach required 500 pounds compressive strength prior to cementing each casing string. Have well specific cement details onsite prior to pumping the cement for each casing string.
5. No pea gravel permitted for remedial or fall back remedial without prior authorization from the BLM engineer.
6. On that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Formation at the shoe shall be tested to a minimum of the mud weight equivalent anticipated to control the formation pressure to the next casing depth or at total depth of the well. This test shall be performed before drilling more than 20 feet of new hole.
7. If hardband drill pipe is rotated inside casing, returns will be monitored for metal. If metal is found in samples, drill pipe will be pulled and rubber protectors which have a larger diameter than the tool joints of the drill pipe will be installed prior to continuing drilling operations.
8. Whenever a casing string is cemented in the R-111-P potash area, the NMOCD requirements shall be followed.

B. PRESSURE CONTROL

1. All blowout preventer (BOP) and related equipment (BOPE) shall comply with well control requirements as described in Onshore Oil and Gas Order No. 2 and API RP 53 Sec. 17.
2. If a variance is approved for a flexible hose to be installed from the BOP to the choke manifold, the following requirements apply: The flex line must meet the requirements of API 16C. Check condition of flexible line from BOP to choke manifold, replace if exterior is damaged or if line fails test. Line to be as straight as possible with no hard bends and is to be anchored according to Manufacturer's requirements. The flexible hose can be exchanged with a hose of equal size and equal or greater pressure rating. Anchor requirements, specification sheet and hydrostatic pressure test certification matching the hose in service, to be onsite for review. These documents shall be posted in the company man's trailer and on the rig floor.
3. 5M or higher system requires an HCR valve, remote kill line and annular to match. The remote kill line is to be installed prior to testing the system and tested to stack pressure.
4. If the operator has proposed a multi-bowl wellhead assembly in the APD. The following requirements must be met:
 - a. Wellhead shall be installed by manufacturer's representatives, submit documentation with subsequent sundry.
 - b. If the welding is performed by a third party, the manufacturer's representative shall monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
 - c. Manufacturer representative shall install the test plug for the initial BOP test.
 - d. Whenever any seal subject to test pressure is broken, all the tests in OOGO2.III.A.2.i must be followed.
 - e. If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head shall be cut off, cementing operations performed and another wellhead installed.
5. The appropriate BLM office shall be notified a minimum of 4 hours in advance for a representative to witness the tests.
 - a. In a water basin, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. The casing cut-off and BOP installation can be initiated four hours after installing the slips, which will be approximately six hours after bumping the plug. For those casing strings not using slips, the minimum wait time before cut-off is eight hours after bumping the plug. BOP/BOPE testing can begin after cut-off or once cement reaches 500 psi compressive strength (including lead when specified), whichever is greater. However, if the float does not

hold, cut-off cannot be initiated until cement reaches 500 psi compressive strength (including lead when specified).

- b. In potash areas, for all casing strings utilizing slips, these are to be set as soon as the crew and rig are ready and any fallback cement remediation has been done. For all casing strings, casing cut-off and BOP installation can be initiated at twelve hours after bumping the plug. However, **no tests** shall commence until the cement has had a minimum of 24 hours setup time, except the casing pressure test can be initiated immediately after bumping the plug (only applies to single stage cement jobs).
- c. The tests shall be done by an independent service company utilizing a test plug not a cup or J-packer. The operator also has the option of utilizing an independent tester to test without a plug (i.e. against the casing) pursuant to Onshore Order 2 with the pressure not to exceed 70% of the burst rating for the casing. Any test against the casing must meet the WOC time for water basin (8 hours) or potash (24 hours) or 500 pounds compressive strength, whichever is greater, prior to initiating the test (see casing segment as lead cement may be critical item).
- d. The test shall be run on a 5000 psi chart for a 2-3M BOP/BOP, on a 10000 psi chart for a 5M BOP/BOPE and on a 15000 psi chart for a 10M BOP/BOPE. If a linear chart is used, it shall be a one hour chart. A circular chart shall have a maximum 2 hour clock. If a twelve hour or twenty-four hour chart is used, tester shall make a notation that it is run with a two hour clock.
- e. The results of the test shall be reported to the appropriate BLM office.
- f. All tests are required to be recorded on a calibrated test chart. A copy of the BOP/BOPE test chart and a copy of independent service company test will be submitted to the appropriate BLM office.
- g. The BOP/BOPE test shall include a low pressure test from 250 to 300 psi. The test will be held for a minimum of 10 minutes if test is done with a test plug and 30 minutes without a test plug. This test shall be performed prior to the test at full stack pressure.
- h. BOP/BOPE must be tested by an independent service company within 500 feet of the top of the Wolfcamp formation if the time between the setting of the intermediate casing and reaching this depth exceeds 20 days. This test does not exclude the test prior to drilling out the casing shoe as per Onshore Order No. 2.

C. DRILLING MUD


Mud system monitoring equipment, with derrick floor indicators and visual and audio alarms, shall be operating before drilling into the Wolfcamp formation, and shall be used until production casing is run and cemented.

D. WASTE MATERIAL AND FLUIDS

All waste (i.e. drilling fluids, trash, salts, chemicals, sewage, gray water, etc.) created as a result of drilling operations and completion operations shall be safely contained and disposed of properly at a waste disposal facility. No waste material or fluid shall be disposed of on the well location or surrounding area.

Porto-johns and trash containers will be on-location during fracturing operations or any other crew-intensive operations.

13-5/8" 5M BOPE & Closed Loop Equipment Schematic



A multibowl wellhead may be used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.

Devon proposes using a multi-bowl wellhead assembly. This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 5000 (5M) psi.

- Wellhead will be installed by wellhead representatives.
- If the welding is performed by a third party, the wellhead representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal.
- Wellhead representative will install the test plug for the initial BOP test.
- Wellhead company will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 5M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time.
- If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted.
- Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating.
- Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2.



After running the surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 5M will be installed on the wellhead system and will undergo a 250 psi low pressure test followed by a 5,000 psi high pressure test. The 5,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2.

After running the intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 5M will already be installed on the wellhead.

The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 5,000 psi WP.

Devon's proposed wellhead manufactures will be FMC Technologies, Cactus Wellhead, or Cameron.

INFORMATION CONTAINED HEREIN IS THE PROPERTY OF CACTUS WELLHEAD, LLC. REPRODUCTION, DISCLOSURE, OR USE THEREOF IS PERMISSIBLE ONLY AS PROVIDED BY CONTRACT OR AS EXPRESSLY AUTHORIZED BY CACTUS WELLHEAD, LLC.



CACTUS WELLHEAD LLC

20" x 13-3/8" x 8-5/8" x 5-1/2" MBU-3T-CFL-R-DBLO Wellhead Sys.
 With Quick Connect Top TA Cap, 5-1/2" Emergency Slip Hanger
 And 13-5/8" 5M x 7-1/16" 10M CTH-DBLHPS Tubing Head

DEVON ENERGY CORPORATION
 DELAWARE BASIN


ALL DIMENSIONS APPROXIMATE

DRAWN DLE 25FEB19

APPRV

DRAWING NO. SDT-1929

13-5/8" 5M BOPE & Closed Loop Equipment Schematic



Casing Assumptions and Load Cases

Surface

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.

Surface Casing Burst Design		
Load Case	External Pressure	Internal Pressure
Pressure Test	Formation Pore Pressure	Max mud weight of next hole-section plus Test psi
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section
Displace to Gas	Formation Pore Pressure	Dry gas from next casing point

Surface Casing Collapse Design		
Load Case	External Pressure	Internal Pressure
Full Evacuation	Water gradient in cement, mud above TOC	None
Cementing	Wet cement weight	Water (8.33ppg)

Surface Casing Tension Design	
Load Case	Assumptions
Overpull	100kips
Runing in hole	3 ft/s
Service Loads	N/A

Casing Assumptions and Load Cases

Intermediate

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.

Intermediate Casing Burst Design		
Load Case	External Pressure	Internal Pressure
Pressure Test	Formation Pore Pressure	Max mud weight of next hole-section plus Test psi
Drill Ahead	Formation Pore Pressure	Max mud weight of next hole section
Fracture @ Shoe	Formation Pore Pressure	Dry gas

Intermediate Casing Collapse Design		
Load Case	External Pressure	Internal Pressure
Full Evacuation	Water gradient in cement, mud above TOC	None
Cementing	Wet cement weight	Water (8.33ppg)

Intermediate Casing Tension Design	
Load Case	Assumptions
Overpull	100kips
Runing in hole	2 ft/s
Service Loads	N/A

Casing Assumptions and Load Cases

Production

All casing design assumptions were ran in Stress Check to determine safety factor which meet or exceed both Devon Energy and BLM minimum requirements. All casing strings will be filled while running in hole in order to not exceed collapse rating of the pipe.

Production Casing Burst Design		
Load Case	External Pressure	Internal Pressure
Pressure Test	Formation Pore Pressure	Fluid in hole (water or produced water) + test psi
Tubing Leak	Formation Pore Pressure	Packer @ KOP, leak below surface 8.6 ppg packer fluid
Stimulation	Formation Pore Pressure	Max frac pressure with heaviest frac fluid

Production Casing Collapse Design		
Load Case	External Pressure	Internal Pressure
Full Evacuation	Water gradient in cement, mud above TOC.	None
Cementing	Wet cement weight	Water (8.33ppg)

Production Casing Tension Design	
Load Case	Assumptions
Overpull	100kips
Runing in hole	2 ft/s
Service Loads	N/A



Commitment Runs Deep



Design Plan
Operation and Maintenance Plan
Closure Plan

SENM - Closed Loop Systems
June 2010

I. Design Plan

Devon uses MI SWACO closed loop system (CLS). The MI SWACO CLS is designed to maintain drill solids at or below 5%. The equipment is arranged to progressively remove solids from the largest to the smallest size. Drilling fluids can thus be reused and savings is realized on mud and disposal costs. Dewatering may be required with the centrifuges to insure removal of ultra fine solids.

The drilling location is constructed to allow storm water to flow to a central sump normally the cellar. This insures no contamination leaves the drilling pad in the event of a spill. Storm water is reused in the mud system or stored in a reserve fluid tank farm until it can be reused. All lubricants, oils, or chemicals are removed immediately from the ground to prevent the contamination of storm water. An oil trap is normally installed on the sump if an oil spill occurs during a storm.

A tank farm is utilized to store drilling fluids including fresh water and brine fluids. The tank farm is constructed on a 20 ml plastic lined, bermed pad to prevent the contamination of the drilling site during a spill. Fluids from other sites may be stored in these tanks for processing by the solids control equipment and reused in the mud system. At the end of the well the fluids are transported from the tank farm to an adjoining well or to the next well for the rig.

Prior to installing a closed-loop system on site, the topsoil, if present, will be stripped and stockpiled for use as the final cover or fill at the time of closure.

Signs will be posted on the fence surrounding the closed-loop system unless the closed-loop system is located on a site where there is an existing well, that is operated by Devon.


II. Operations and Maintenance Plan

Primary Shakers: The primary shakers make the first removal of drill solids from the drilling mud as it leaves the well bore. The shakers are sized to handle maximum drilling rate at optimal screen size. The shakers normally remove solids down to 74 microns.

Mud Cleaner: The Mud Cleaner cleans the fluid after it leaves the shakers. A set of hydrocyclones are sized to handle 1.25 to 1.5 times the maximum circulating rate. This ensures all the fluid is being processed to an average cut point of 25 microns. The wet discharged is dewatered on a shaker equipped with ultra fine mesh screens and generally cut at 40 microns.



Closed Loop Schematic



Mi SWACO

Centrifuges: The centrifuges can be one or two in number depending on the well geometry or depth of well. The centrifuges are sized to maintain low gravity solids at 5% or below. They may or may not need a dewatering system to enhance the removal rates. The centrifuges can make a cut point of 8-10 microns depending on bowl speed, feed rate, solids loading and other factors.

The centrifuge system is designed to work on the active system and be flexible to process incoming fluids from other locations. This set-up is also dependant on well factors.

Dewatering System: The dewatering system is a chemical mixing and dosing system designed to enhance the solids removal of the centrifuge. Not commonly used in shallow wells. It may contain pH adjustment, coagulant mixing and dosing, and polymer mixing and dosing. Chemical flocculation binds ultra fine solids into a mass that is within the centrifuge operating design. The

dewatering system improves the centrifuge cut point to infinity or allows for the return of clear water or brine fluid. This ability allows for the ultimate control of low gravity solids.

Cuttings Boxes: Cuttings boxes are utilized to capture drill solids that are discarded from the solids control equipment. These boxes are set upon a rail system that allows for the removal and replacement of a full box of cuttings with an empty one. They are equipped with a cover that insures no product is spilled into the environment during the transportation phase.

Process Tank: (Optional) The process tank allows for the holding and process of fluids that are being transferred into the mud system. Additionally, during times of lost circulation the process tank may hold active fluids that are removed for additional treatment. It can further be used as a mixing tank during well control conditions.

Sump and Sump Pump: The sump is used to collect storm water and the pump is used to transfer this fluid to the active system or to the tank for to hold in reserve. It can also be used to collect fluids that may escape during spills. The location contains drainage ditches that allow the location fluids to drain to the sump.

Reserve Fluids (Tank Farm): A series of frac tanks are used to replace the reserve pit. These are steel tanks that are equipped with a manifold system and a transfer pump. These tanks can contain any number of fluids used during the drilling process. These can include fresh water, cut brine, and saturated salt fluid. The fluid can be from the active well or reclaimed fluid from other locations. A 20 ml liner and berm system is employed to ensure the fluids do not migrate to the environment during a spill.

If a leak develops, the appropriate division district office will be notified within 48 hours of the discovery and the leak will be addressed. Spill prevention is accomplished by maintaining pump packing, hoses, and pipe fittings to insure no leaks are occurring. During an upset condition the source of the spill is isolated and repaired as soon as it is discovered. Free liquid is removed by a diaphragm pump and returned to the mud system. Loose topsoil may be used to stabilize the spill and the contaminated soil is excavated and placed in the cuttings boxes. After the well is finished and the rig has moved, the entire location is scrapped and testing will be performed to determine if a release has occurred.

All trash is kept in a wire mesh enclosure and removed to an approved landfill when full. All spent motor oils are kept in separate containers and they are removed and sent to an approved recycling center. Any spilled lubricants, pipe

dope, or regulated chemicals are removed from soil and sent to landfills approved for these products.

These operations are monitored by Mi Swaco service technicians. Daily logs are maintained to ensure optimal equipment operation and maintenance. Screen and chemical use is logged to maintain inventory control. Fluid properties are monitored and recorded and drilling mud volumes are accounted for in the mud storage farm. This data is kept for end of well review to insure performance goals are met. Lessons learned are logged and used to help with continuous improvement.

A MI SWACO field supervisor manages from 3-5 wells. They are responsible for training personnel, supervising installations, and inspecting sites for compliance of MI SWACO safety and operational policy.

III. Closure Plan

A maximum 340' X 340' caliche pad is built per well. All of the trucks and steel tanks fit on this pad. All fluid cuttings go to the steel tanks to be hauled by various trucking companies to an agency approved disposal.

District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 S. First St., Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources Department
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Submit Original
to Appropriate
District Office

GAS CAPTURE PLAN

Date: 2/19/2019

Original Operator & OGRID No.: Devon Energy Prod Co., LP (6137)
 Amended - Reason for Amendment: _____

This Gas Capture Plan outlines actions to be taken by the Devon to reduce well/production facility flaring/venting for new completion (new drill, recomplete to new zone, re-frac) activity.

Note: Form C-129 must be submitted and approved prior to exceeding 60 days allowed by Rule (Subsection A of 19.15.18.12 NMAC).

Well(s)/Production Facility – Name of facility

The well(s) that will be located at the production facility are shown in the table below.

Well Name	API	Well Location (ULSTR)	Footages	Expected MCF/D	Flared or Vented	Comments
Marwari 21-16 State Fed Com 621H		UNIT D, SEC 28-T25S-R32E	325 FNL 160 FWL			MARWARI 21 CTB 1

Gathering System and Pipeline Notification

Well(s) will be connected to a production facility after flowback operations are complete, if DCP system is in place. The gas produced from production facility is dedicated to DCP and will be connected to DCP low/high pressure gathering system located in Lea County, New Mexico. It will require 1100' of pipeline to connect the facility to low/high pressure gathering system. Devon provides (periodically) to DCP a drilling, completion and estimated first production date for wells that are scheduled to be drilled in the foreseeable future. In addition, Devon and DCP have periodic conference calls to discuss changes to drilling and completion schedules. Gas from these wells will be processed at DCP Processing Plant located in Sec. 19, Twn. 19S, Rng. 32E, Lea County, New Mexico. The actual flow of the gas will be based on compression operating parameters and gathering system pressures.

Flowback Strategy

After the fracture treatment/completion operations, well(s) will be produced to temporary production tanks and gas will be flared or vented. During flowback, the fluids and sand content will be monitored. When the produced fluids contain minimal sand, the wells will be turned to production facilities. Gas sales should start as soon as the wells start flowing through the production facilities, unless there are operational issues on DCP system at that time. Based on current information, it is Devon's belief the system can take this gas upon completion of the well(s).

Safety requirements during cleanout operations from the use of underbalanced air cleanout systems may necessitate that sand and non-pipeline quality gas be vented and/or flared rather than sold on a temporary basis.

Alternatives to Reduce Flaring

Below are alternatives considered from a conceptual standpoint to reduce the amount of gas flared.

- Power Generation – On lease
 - Only a portion of gas is consumed operating the generator, remainder of gas will be flared
- Compressed Natural Gas – On lease
 - Gas flared would be minimal, but might be uneconomical to operate when gas volume declines
- NGL Removal – On lease
 - Plants are expensive, residue gas is still flared, and uneconomical to operate when gas volume declines

Devon Energy APD VARIANCE DATA

OPERATOR NAME: Devon Energy

1. SUMMARY OF Variance:

Devon Energy respectfully requests approval for the following additions to the drilling plan:

1. Potential utilization of a spudder rig to pre-set surface casing.

2. Description of Operations

1. A spudder rig contractor may move in their rig to drill the surface hole section and pre-set surface casing on this well.
 - a. After drilling the surface hole section, the rig will run casing and cement following all of the applicable rules and regulations (OnShore Order 2, all COAs and NMOCD regulations).
 - b. Rig will utilize fresh water based mud to drill surface hole to TD.
2. The wellhead will be installed and tested once the surface casing is cut off and the WOC time has been reached.
3. A blind flange with the same pressure rating as the wellhead will be installed to seal the wellbore. Pressure will be monitored with needle valves installed on two wingvalves.
 - a. A means for intervention will be maintained while the drilling rig is not over the well.
4. The BLM will be contacted and notified 24 hours prior to commencing spudder rig operations.
5. Drilling operation will be performed with the big rig. At that time an approved BOP stack will be nipped up and tested on the wellhead before drilling operations commences on each well.
 - a. The BLM will be contacted / notified 24 hours before the big rig moves back on to the pad with the pre-set surface casing.
6. Devon Energy will have supervision on the rig to ensure compliance with all BLM and NMOCD regulations and to oversee operations.
7. Once the rig is removed, Devon Energy will secure the wellhead area by placing a guard rail around the cellar area.



Fluid Technology

ContiTech Beattie Corp.
Website: www.contitechbeattie.com

Monday, June 14, 2010

RE: Drilling & Production Hoses
Lifting & Safety Equipment

To Helmerich & Payne,

A Continental ContiTech hose assembly can perform as intended and suitable for the application regardless of whether the hose is secured or unsecured in its configuration. As a manufacturer of High Pressure Hose Assemblies for use in Drilling & Production, we do offer the corresponding lifting and safety equipment, this has the added benefit of easing the lifting and handling of each hose assembly whilst affording hose longevity by ensuring correct handling methods and procedures as well as securing the hose in the unlikely event of a failure; but in no way does the lifting and safety equipment affect the performance of the hoses providing the hoses have been handled and installed correctly. It is good practice to use lifting & safety equipment but not mandatory.


Should you have any questions or require any additional information/clarifications then please do not hesitate to contact us.

ContiTech Beattie is part of the Continental AG Corporation and can offer the full support resources associated with a global organization.

Best regards,

Robin Hodgson
Sales Manager
ContiTech Beattie Corp

ContiTech Beattie Corp,
11535 Brittmoore Park Drive,
Houston, TX 77041
Phone: +1 (832) 327-0141
Fax: +1 (832) 327-0148
www.contitechbeattie.com



RIG 212



QUALITY DOCUMENT

PHOENIX RUBBER INDUSTRIAL LTD.

6728 Szeged, Budapesti út 10. Hungary • H-6701 Szeged, P. O. Box 152
Phone: (3662) 566-737 • Fax: (3662) 566-738

SALES & MARKETING: H-1092 Budapest, Ráday u. 42-44. Hungary • H-1440 Budapest, P. O. Box 26
Phone: (361) 456-4200 • Fax: (361) 217-2972, 456-4273 • www.taurusemerge.hu

QUALITY CONTROL INSPECTION AND TEST CERTIFICATE			CERT. N°: 552	
PURCHASER: Phoenix Beattie Co.			P.O. N°: 1519FA-871	
PHOENIX RUBBER order N°: 170466		HOSE TYPE: 3" ID Choke and Kill Hose		
HOSE SERIAL N°: 34128		NOMINAL / ACTUAL LENGTH: 11,43 m		
W.P. 68,96 MPa	10000 psi	T.P. 103,4 MPa	15000 psi	Duration: 60 min.
Pressure test with water at ambient temperature <p style="text-align: center;">See attachment. (1 page)</p>				
↑ 10 mm = 10 Min. → 10 mm = 25 MPa				
COUPLINGS				
Type	Serial N°	Quality	Heat N°	
3" coupling with 4 1/16" Flange end	720 719	AISI 4130	C7626	
		AISI 4130	47357	
API Spec 16 C Temperature rate: "B"				
All metal parts are flawless				
WE CERTIFY THAT THE ABOVE HOSE HAS BEEN MANUFACTURED IN ACCORDANCE WITH THE TERMS OF THE ORDER AND PRESSURE TESTED AS ABOVE WITH SATISFACTORY RESULT.				
Date: 29. April. 2002.	Inspector	Quality Control PHOENIX RUBBER Industrial Ltd. Hose Inspection and VERIFIED TRUE COPY PHOENIX RUBBER S.C.		

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720
District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720
District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170
District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS
 Action 26364

CONDITIONS

Operator: DEVON ENERGY PRODUCTION COMPANY, LP 333 West Sheridan Ave. Oklahoma City, OK 73102	OGRID: 6137
	Action Number: 26364
	Action Type: [C-101] BLM - Federal/Indian Land Lease (Form 3160-3)

CONDITIONS

Created By	Condition	Condition Date
pkautz	Will require a File As Drilled C-102 and a Directional Survey with the C-104	6/14/2021
pkautz	Once the well is spud, to prevent ground water contamination through whole or partial conduits from the surface, the operator shall drill without interruption through the fresh water zone or zones and shall immediately set in cement the water protection string	6/14/2021