

Well Name: WINTERFELL 5 6 B2PO FED COM	Well Location: T18S / R32E / SEC 5 / TR P / 32.772739 / -103.7814103	County or Parish/State: LEA / NM
Well Number: 1H	Type of Well: OIL WELL	Allottee or Tribe Name:
Lease Number: NMNM0555567	Unit or CA Name:	Unit or CA Number:
US Well Number: 3002547866	Well Status: Approved Application for Permit to Drill	Operator: MEWBOURNE OIL COMPANY

Notice of Intent

Sundry ID: 2631321

Type of Submission: Notice of Intent

Type of Action: Other

Date Sundry Submitted: 08/30/2021

Time Sundry Submitted: 09:42

Date proposed operation will begin: 09/08/2021

Procedure Description: Mewbourne Oil Co. has an approved APD for the referenced well. Mewbourne Oil Co is seeking approval to change the setting depth of the intermediate casing string and change the casing grade that will be used. The new setting depth is is 2,625' using 9.625" 36# J55 LTC casing. Please see attached document for full design change.

Surface Disturbance

Is any additional surface disturbance proposed?: No

NOI Attachments

Procedure Description

Winterfell_5_6_B2PO_Fed_Com_1H_Sundry_20210830094128.pdf

Well Name: WINTERFELL 5 6 B2PO
FED COM

Well Location: T18S / R32E / SEC 5 /
TR P / 32.772739 / -103.7814103

County or Parish/State: LEA /
NM

Well Number: 1H

Type of Well: OIL WELL

Allottee or Tribe Name:

Lease Number: NMNM0555567

Unit or CA Name:

Unit or CA Number:

US Well Number: 3002547866

Well Status: Approved Application for
Permit to Drill

Operator: MEWBOURNE OIL
COMPANY

Conditions of Approval

Specialist Review

WINTERFELL_5_6_B2PO_FED_COM_1H_Drilling_Sundry_2631321_COA_OTA_20210831141641.pdf

Operator Certification

I certify that the foregoing is true and correct. Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction. Electronic submission of Sundry Notices through this system satisfies regulations requiring a submission of Form 3160-5 or a Sundry Notice.

Operator Electronic Signature: BRADLEY BISHOP

Signed on: AUG 30, 2021 09:41 AM

Name: MEWBOURNE OIL COMPANY

Title: Regulatory

Street Address: PO Box 5270

City: Hobbs

State: NM

Phone: (575) 393-5905

Email address: bbishop@mewbourne.com

Field Representative

Representative Name: Landon Stallings

Street Address: PO Box 5270

City: Hobbs

State: NM

Zip: 88260

Phone: (575)393-5905

Email address: lstallings@mewbourne.com

BLM Point of Contact

BLM POC Name: AJIBOLA OLABODE

BLM POC Title: Engineer

BLM POC Phone: 5752342231

BLM POC Email Address: OAJIBOLAEIT@BLM.GOV

Disposition: Approved

Disposition Date: 08/31/2021

Signature: Olabode Thomas Ajibola

Mewbourne Oil Company, Winterfell 5/6 B2PO Fed Com #1H
Sec 5, T18S, R32E
SL: 1240' FSL & 455' FEL (5)
BHL: 500' FSL & 2539' FEL (6)

Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Jt Tension	SF Body Tension
	From	To								
17.5"	0'	1385'	13.375"	48	H40	STC	1.21	2.73	4.84	8.14
12.25"	0'	2625'	9.625"	36	J55	LTC	1.48	2.58	4.79	5.97
8.75"	0'	9078'	7"	26	P110	LTC	1.80	2.30	2.94	3.52
6.125"	8330'	16429'	4.5"	13.5	P110	LTC	1.95	2.27	3.09	3.86
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, Winterfell 5/6 B2PO Fed Com #1H
Sec 5, T18S, R32E
SL: 1240' FSL & 455' FEL (5)
BHL: 500' FSL & 2539' FEL (6)

Cementing Program

Casing	# Sks	Wt. lb/gal	Yld ft3/sack	H ₂ O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	790	12.5	2.12	11	10	Lead: Class C + Salt + Gel + Extender + LCM
	200	14.8	1.34	6.3	8	Tail: Class C + Retarder
Inter.	340	12.5	2.12	11	10	Lead: Class C + Salt + Gel + Extender + LCM
	200	14.8	1.34	6.3	8	Tail: Class C + Retarder
Prod.	370	12.5	2.12	11	9	Lead: Class C + Salt + Gel + Extender + LCM
	400	15.6	1.18	5.2	10	Tail: Class H + Retarder + Fluid Loss + Defoamer
Liner	320	11.2	2.97	18	16	Class H + Salt + Gel + Fluid Loss + Retarder + Dispersant + Defoamer + Anti-Settling Agent

A copy of cement test will be available on location at time of cement job providing pump times & compressive strengths.

Casing String	TOC	% Excess
Surface	0'	100%
Intermediate	0'	25%
Production	2,425'	25%
Liner	8330'	25%

Mud Program

TVD		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0'	1385'	Spud Mud	8.6-8.8	28-34	N/C
1385'	2625'	Brine	10.0	28-34	N/C
2625'	9078'	Cut Brine	8.6-9.5	28-34	N/C
9078'	16429'	OBM	8.6-10	30-40	<10cc

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Pason/PVT/Visual Monitoring
---	-----------------------------

District I
 1625 N. French Dr., Hobbs, NM 88240
 Phone:(575) 393-6161 Fax:(575) 393-0720

District II
 811 S. First St., Artesia, NM 88210
 Phone:(575) 748-1283 Fax:(575) 748-9720

District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 Phone:(505) 334-6178 Fax:(505) 334-6170

District IV
 1220 S. St Francis Dr., Santa Fe, NM 87505
 Phone:(505) 476-3470 Fax:(505) 476-3462

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 S. St Francis Dr.
Santa Fe, NM 87505

CONDITIONS
 Action 47661

CONDITIONS

Operator: MEWBOURNE OIL CO P.O. Box 5270 Hobbs, NM 88241	OGRID: 14744
	Action Number: 47661
	Action Type: [C-103] NOI Change of Plans (C-103A)

CONDITIONS

Created By	Condition	Condition Date
pkautz	None	9/13/2021